

Shared Foundations

The session log, the cloud-run allowance, the Prisma singleton, session ownership and shared types

EdgePilot AI - Team 15

Documentation set, 26 August 2026

6 documents in this volume

src/core/ - cross-cutting concerns

Work package: benchmark and provider layer.

What this folder is

Things used by more than one module and owned by none of them. Exactly one concern lives here now: the session log.

What happened here

Two whole subfolders were removed and one file was replaced.

rate-limit/ and security/ guarded endpoints that have no authentication and no public URL. Security machinery that protects nothing is not neutral - it still has to be read, maintained and reasoned about by everyone who comes after, and it implies a threat model the application does not actually have.

logging/logger.ts was replaced by logging/SessionLog.ts, which is the difference between a logging utility and a logging **policy**: a redaction rule, an export format, and opt-in behaviour.

Subfolders

Subfolder	What it holds
logging/	The session activity log and its store
quota/	cloudRunQuota.ts - a small in-memory, per-session cap on cloud vision runs that spend the SERVER's key; a visitor using their own key is not capped. Best-effort, not a security boundary (per process on a serverless host)

Connected folders

- src/app/api/v1/session-log/ - the endpoints that expose it.
- tests/core/ - the suite.

Referenced from

These folders point here. Each link below resolves in both directions.

- src/

src/lib/ - process-level singletons

Work package: integration and API surface; `sessionOwner.ts` belongs to the benchmark layer.

What this folder is

Two files, both answering a question that has exactly one correct answer per process: which Prisma client, and who owns this row.

What happened here

`sessionOwner.ts` is new, and it closed a real data leak.

Two routes previously attributed every row they created to a single hardcoded user, `local-sandbox@edgepilot.invalid`, with a comment saying session handling did not exist yet. On one laptop that is harmless. The moment the application is hosted it is a leak: GET would hand every visitor every other visitor's workloads, because they would all be the same user.

The replacement **fails closed**. A request with no session id gets a 400. It does not fall back to a shared user - that fallback is exactly the leak, and it fails silently, because the caller gets a 200 and someone else's data.

Files

File	What it is
<code>prisma.ts</code>	33 lines. The single <code>PrismaClient</code> for the process, cached on <code>globalThis</code> . Without the cache, a new client per hot reload exhausts the database connection limit within a few edits
<code>sessionOwner.ts</code>	76 lines. <code>sessionIdOf(request)</code> , <code>resolveOwnerId(sessionId)</code> which upserts a <code>User</code> , and <code>missingSession()</code> which returns the 400

Connected folders

- `src/components/dashboard/` - `session.ts`, the browser half that generates the id.
- `src/app/api/v1/workloads/` - the route that used to attribute everything to one user.
- `prisma/` - the `users.session_id` column and the migration that added it.

Referenced from

These folders point here. Each link below resolves in both directions.

- `docs/benchmark/`
- `src/`
- `src/app/api/v1/`
- `src/modules/benchmark/infrastructure/repositories/`

src/shared/ - types crossing module boundaries

Work package: integration and API surface.

What this folder is

The scaffold's shared type definitions and zod schemas.

What happened here

`types/device.ts` was removed with the device module. The rest is largely unchanged, and its role has narrowed in a way worth understanding: the benchmark module now defines its own richer measurement envelope in `application/dtos/BenchmarkMeasurement.ts`, and the dashboard imports **that** rather than these. These remain the scaffold contract and the shape the original endpoints were written against.

Subfolders

Subfolder	What it holds
types/	Benchmark, provider and workload types with their zod schemas

Connected folders

- `src/modules/benchmark/application/dtos/` - the superset that supersedes these for measurement.
- `src/app/api/v1/` - the routes that validate with them.

Referenced from

These folders point here. Each link below resolves in both directions.

- `src/`

src/core/logging/ - the session activity log

Work package: benchmark and provider layer.

What this folder is

A per-session record of what the application did, exportable as JSON, with no account and no user identity attached.

What happened here

New, replacing a generic `logger.ts`. Two rules are built in rather than configurable, and both are there because the obvious design would have been wrong.

Redaction is not optional. The obvious thing for a benchmark log to record is the prompt. The prompt is also the confidential thing this product exists to warn people about - the egress warning tells a user "this text is about to leave your machine", and a log that then writes the same text into a file they can email around has defeated the warning it just issued. So prompt **content** is never recorded by default. Only a length and a short digest, which is enough to prove two runs used the same prompt without disclosing what it was.

Logging is opt-in by header. A request without `x-edgepilot-session` is not logged anonymously and not logged to a default bucket - it is not logged at all. That keeps the default behaviour "we kept no record of what you ran", which is the only default consistent with the rest of the application.

The store is cached on `globalThis` for the same reason the Prisma client is: Next.js hot-reloads modules in development, and a fresh store per reload would drop every session log mid-use.

Files

File	What it is
<code>SessionLog.ts</code>	407 lines. The log, its event and category vocabulary, <code>redact</code> , <code>digestPrompt</code> , the in-memory store, <code>buildSharePayload</code> and <code>SHARE_CONSENT_STATEMENT</code>
<code>sessionLogStore.ts</code>	56 lines. The process-wide store, the <code>x-edgepilot-session</code> header name, and <code>logForRequest</code>

Connected folders

- `src/app/api/v1/session-log/` and `share/` - the endpoints.
- `src/components/dashboard/` - `session.ts` generates the header value; `api.ts` writes the header name out as a literal rather than importing it, because importing this module from the client would instantiate server state at module scope.
- `src/modules/benchmark/core/services/` - `egress-warning.ts`, the warning this log must not undermine.
- `tests/core/` - `session-log.test.ts`.

Referenced from

These folders point here. Each link below resolves in both directions.

- `src/components/history/`
- `src/core/`

src/core/quota/ - the cloud-run allowance

Work package: shared.

What this folder is

A cap on how much of the server's cloud quota one visitor may spend.

What happened here

New with hosting. A cloud vision run is 21 requests to Gemini or Groq. With the visitor's own key that is their business; with the key the operator configured, an ungated button is an invitation to spend it all evening. So a visitor gets CLOUD_RUNS_PER_HOUR server-key runs an hour, keyed on their session id, and a message that says when to try again and where to add their own key.

It is in-memory and per process. On a serverless host each instance keeps its own count, so it turns "unlimited" into "a handful" rather than into a hard wall. That is stated in the file rather than implied.

Files

File	What it is
cloudRunQuota.ts	takeCloudRun records a run against the session's bucket if there is room and returns a verdict; resetCloudRunQuota for tests

Connected folders

- src/app/vision-benchmark/ - the server action that calls it.
- tests/core/ - its tests.

Referenced from

These folders point here. Each link below resolves in both directions.

- src/core/

src/shared/types/ - the scaffold contract

Work package: integration and API surface.

What this folder is

Four small files pairing a TypeScript type with the zod schema that validates it, so validation and typing cannot disagree.

What happened here

`device.ts` was deleted with the device module, and `index.ts` lost its export of it - a one-line change that is the visible end of a removal touching the UI, the API, the module and the database.

`benchmark.ts` changed by three lines. That small number is deliberate: the benchmark module's own DTO is a **superset** of this shape rather than a replacement, keeping every field it already had, in the same place, with the same name, so the dashboard being written against this contract did not have to be rewritten.

Files

File	What it is
<code>benchmark.ts</code>	46 lines. <code>BenchmarkRequest</code> , <code>BenchmarkResult</code> , <code>ReadinessScore</code> and their schemas
<code>provider.ts</code>	46 lines. <code>Provider</code> , <code>AIPProvider</code> , <code>AIResponse</code> , <code>ProviderBenchmarkResult</code>
<code>workload.ts</code>	17 lines. <code>Workload</code> , <code>CreateWorkloadRequest</code> and their schemas
<code>index.ts</code>	4 lines. Re-exports. Three lines now, where there were four

Connected folders

- `src/modules/benchmark/application/dtos/` - the superset envelope.
- `src/app/api/v1/workloads/` - validates against `CreateWorkloadSchema`.
- `src/shared/` - the parent.