


Whole-genome short-read sequencing

DNA


↓ Random shearing



↓ Illumina adapter ligation
incl. individual index



↓ Size selection




paired-end sequencing

Up to 20 billion read pairs



1. Quality check and trimming raw reads




Fastq file of reads

```
@HWUSI-EAS611:34:6669YAAXX:1:1:5069:1159 1:N:0:
TCGATAATACCGTTTTTTTCCGTTTGATGTTGATACCAT
+
IIHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHHH
```


2. Alignment to the reference genome with bwa

reference


bwa



3. Variant and genotype calling with bcftools



3. Variant and genotype calling with bcftools



vcf file: Genotypes for each individual at genomic sites

```
##FORMAT=<ID=GT,Number=1,Type=String,Description="Genotype"
#CHROM POS ID REF ALT QUAL FILTER INFO FORMAT GEN
chr1 82154 . T C . GT 0/0 1/1 0/0 1/1 0/0 1/1
chr1 752566 . T . . GT 0/0 0/0 0/0 0/0 0/0 0/0
chr1 752721 . T C . GT 1/1 1/1 1/1 1/1 1/1 1/1
chr1 752721 . A . . GT ./.
```


Many tools for variant and genotype calling

- Bcftools – fast, easy and good
- GATK – state of the art but only if the individuals to map are closely related to the reference genome (designed for human data)
- FreeBayes – also widely used
- ANGSD – for low-coverage data (<15x coverage)

Vcf file structure

- For every sequenced position in the genome, there will be a line
- For every individual, there will be a column

```
##FORMAT=<ID=GT,Number=1,Type=String,Description="Genotype"  
#CHROM  POS  ID   REF  ALT  QUAL  FILTER  INFO    FORMAT  GEN  
chr1    82154  .    T    C    .    GT      0/0  1/1  0/0  1/1  0/0  1/1  
chr1    752566  .    T    .    .    GT      0/0  0/0  0/0  0/0  0/0  0/0  
chr1    752721  .    T    C    .    GT      1/1  1/1  1/1  1/1  1/1  1/1  
chr1    752728  .    A    .    .    GT      ./.  0/0  0/0  0/0  0/0  0/0
```