

Log File: cisco\_Tech\_support.txt

Execution Count: 16

## DashBoard

CPU Utilization	%
5 sec utilization	23%
1 min utilization	23%
5 min utilization	23%

Memory Utilization	Total	Used	Free
Memory utilization	6.00 GB	1.59 GB	4.49 GB

Device Summary	
Hostname	BVSB04FRWL001
Device info	Cisco Adaptive Security Appliance Software Version 9.4(1)
Image version	"disk0:/asa941-smp-k8.bin"
Uptime	1 year 139 days
Config Register	0x1
Hardware	ASA5585-SSP-10

## Policy Findings

The total device-wide Access Control List (ACL) count is ACL1 0 2493  
Top ACLs, by size, on this Firewall:

ACL_list	rule
Outside-IN	555
Outside-IN	555
partners_ext-IN	384
partners_int-IN	203
was-IN	200
rp-IN	156

rp-IN	156
ivs-IN	108
smtp-IN	65
vbp-IN	37

#### Low

Filter Drop Rules Were Configured Without Logging. It is recommended to enable logging

#### Medium

access-list partners\_ext-IN extended permit ip any object n-193.222.178.0-24

access-list pbr-acl1 extended permit ip any host 10.158.51.14

access-list pbr-acl2 extended permit ip any host 10.158.51.13

access-list pbr-acl3 extended permit ip any any

#### Medium

access-list partners\_int-IN extended permit tcp host 193.222.178.75 host 189.206.117.134 eq telnet

■ ■access-list partners\_int-IN extended permit tcp host 193.222.178.74 host 189.206.117.134 eq telnet

access-list partners\_int-IN extended permit tcp host 193.222.178.82 host 189.206.117.134 eq telnet

access-list partners\_int-IN extended permit tcp host 193.222.178.83 host 189.206.117.134 eq telnet

access-list partners\_int-IN extended permit tcp host 193.222.178.76 host 189.206.117.134 eq telnet

access-list partners\_int-IN extended permit tcp host 193.222.178.82 host 189.206.86.172 eq telnet

access-list partners\_int-IN extended permit tcp host 193.222.178.83 host 189.206.86.172 eq telnet

#### Critical

access-list pbr-acl3 extended permit ip any any

## Interfaces

Interface_name	Interface_description	Interface_state	Duplex_state
GigabitEthernet0/0		DOWN	Auto-Duplex
GigabitEthernet0/1		DOWN	Auto-Duplex
GigabitEthernet0/2		DOWN	Auto-Duplex
GigabitEthernet0/3		DOWN	Auto-Duplex
GigabitEthernet0/4		DOWN	Auto-Duplex
GigabitEthernet0/5		DOWN	Auto-Duplex
GigabitEthernet0/6		UP	Auto-Duplex(Full-duplex)

GigabitEthernet0/7		UP	Auto-Duplex(Full-duplex)
Management0/0	management	UP	Auto-Duplex(Full-duplex)
Management0/1		DOWN	Auto-Duplex
TenGigabitEthernet0/8		UP	(Full-duplex)
TenGigabitEthernet0/9		UP	(Full-duplex)

## Observation

console\_timeout 0 Console timeout was configured

log\_time\_stamp 0 Logging timestamp was not configured which can make log analysis difficult

not\_monitored

All Interfaces are currently monitored

from_state	to_state	Reason
Active Applying Config	Active Config Applied	HELLO not heard from mate
Active Drain	Active Applying Config	HELLO not heard from mate
Active Config Applied	Active	HELLO not heard from mate
Standby Ready	Just Active	HELLO not heard from mate
Just Active	Active Drain	HELLO not heard from mate

process	run_time
bcmLINK.0	123648116

Interface_name	IP
10.158.134.181	
10.128.3.11	
10.158.134.179	

Interface_name	minute_1_input_rate	minute_5_input_rate	minute_1_output_rate	minute_5_output_rate
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA

[illegible]

Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA
Internal-Data0/3	1.25 Tbps	NA	NA	NA

CPU Utilization is normal

