

NATURAL LANGUAGE PROCESSING


Firenze

November, 25th 2017

Cesare Taronna



AGENDA




INTRODUCTION: NATURAL LANGUAGE PROCESSING

What is Natural Language?

It refers to the language spoken by people, e.g. English, Italian, Spanish. As opposed to artificial languages like Python, Java, etc.

What is Natural Language Processing?


It is the field of study that focuses on the interactions between human language and computers.



INTRODUCTION: TEXT MINING

What is Text Mining?


The **goal of text mining is to discover relevant information in text by transforming the text into data** that can be used for further analysis.



Text mining accomplishes this through the use of a variety of analysis methodologies; natural language processing (NLP) is one of them.



INTRODUCTION: NATURAL LANGUAGE PROCESSING



INTRODUCTION: ACTUAL USE CASE

TV advertising & audience analysis:

TV shows or live televised events are some of the most talked-about topics on Twitter. Marketers and TV producers can benefit from using Text Analytics **getting an understanding of how their audience feels** about certain characters, settings, storylines, featured music.




Spam detection:

To decide if an email is a spam or not, **several hundred rules are applied to each email** that passes Google's data centers. Each rule describes some attributes of a spam and has some numerical value associated with it, based on the likelihood that the attribute is a spam.

Chatting with machines:

SIRI and **Cortana** involve a number of technologies, including natural language processing, question analysis, data mashups, and machine learning.



REAL USE CASE



REAL USE CASE: DATA OVERVIEW

Data description:

Over 20k recipes listed by recipe rating, nutritional information and assigned category (sparse) with information about ingredients and description of how to make it.

Data source: Kaggle

Our goal:

- Retrieve most used ingredients from all recipes
- Find similarity between recipes based on the key ingredients or procedures

Techniques:

- Data pre-processing
- Stemming
- Topic extraction
- Relationship evaluation



DATA PREPROCESSING



DATA PREPROCESSING

Cleaning:

- Clean empty data
- Remove duplicate



Tokenization:

In this phase we divide text into a sequence of tokens, which roughly correspond to "words"

A token is:

- Linguistically significant
- Methodologically useful

The dog is on the table →

- The
- dog
- is
- on
- the
- table



DATA PREPROCESSING

Text Vectorization – Bag of words:

Turn a text into a vector of number, treating text as a Bag of words:

- Count how many times each word occurs
- Do a binary Yes-No for whether each word is contained

the dog is on the table


0	0	1	1	0	1	1	1
are	cat	dog	is	now	on	table	the



DATA PREPROCESSING

Removing Stop words:

- Omit certain common words when doing the analysis



N-Gram:

- Look at n-grams of length n-word instead of looking at just single words

The dog is on the table

The dog dog is is on on the the table

The dog is dog is on is on the on the table

Tokens

Bi-Gram

Tri-Gram

DATA PREPROCESSING

Stemming:

- Replace by a common root, or stem, the entire word.

affect

affect
affectation
affected
affecting
affection
affections
affects

amus

amuse
amused
amusement
amusements
amusing

close

close
closed
closely
closing

grate

grate
grateful
gratefully

Lemming:

- The analog of the stem here is an actual word

WORDS

the
waiter
cleared
the
plates
from
the
table

TAGS

DET
PREP
VERB
NOUN

Part of Speech Tagging:

- Process a sequence of words and attaches a part of speech tag to each word

TERM FREQUENCY — INVERSE DOCUMENT FREQUENCY (TF-IDF)



TF – IDF WEIGHTING

Definition: tf-idf is a numerical statistic that is intended to reflect how important a word is to a document in a collection of documents.

Goal: Word that appears in most of the documents should not have a big impact on the relevance and a word that appears in very few documents make them very relevant when it appears in the query.

Tf:

$$tf(t,d) = \frac{\text{\#occurences of word in document}}{\text{\#words in document}}$$

$$tf(t,d) = tf^{L^2}(t,d) = \frac{tf^{raw}(t,d)}{\sqrt{\sum_t tf^{raw}(t,d)^2}}$$

tf measures how relevant is a word for a specified document

Idf:

$$idf(t,d) = \log \frac{\text{\#documents}}{\text{\#documents containing word}}$$

$$idf^{naive}(t,D) = \log \frac{\#D}{\#\{d \in D : t \in d\}}$$

IDF measures how relevant is word according the full corpus of documents

TF – IDF WEIGHTING

Now we would like to find **words that are common in one document, and not common in all of them.**

Tfidf:

$$tfidf(t, d, D) = tf(t, d)idf(t, D)$$

The tf-idf value increases proportionally to the number of times a word appears in the document, but is often offset by the frequency of the word in the corpus, which helps to adjust for the fact that some words appear more frequently in general



DOCUMENT SIMILARITY METRICS




COSINE SIMILARITY

Goal: find most similar documents to a given one

Issue: A common problem is looking up a document similar to a given snippet, or relatedly comparing two documents for similarity.

Cosine similarity provides a simple method for this.



COSINE SIMILARITY

Cosine similarity using tf-idf weighting

Suppose we want to find the similarity between d_1 and d_2 :

- To each of the two documents d_1, d_2 in a corpus of documents D , assign its tf or tf-idf vector for each possible words


$$(v_i)_j = \text{tfidf}(t_j, d_i, D)$$

where i = indices for documents

j = indices for terms in the vocabulary.

- To compare the two documents, simply find the cosine of the angle between the vectors i and i' associated respectively to d_1 and d_2 :

$$\frac{v_i \cdot v_{i'}}{\|v_i\| \|v_{i'}\|}$$



HANDS-ON



THANK YOU

Cesare Taronna
Data Scientist

Data Reply
Via Robert Koch, 1/4
20152 - Milano - ITALY
phone: +39 02 535761
c.taronna@reply.it