

61A Lecture 5

Friday, January 30

Environments for Higher-Order Functions

Environments Enable Higher-Order Functions

Environments Enable Higher-Order Functions

Functions are first-class: Functions are values in our programming language

Environments Enable Higher-Order Functions

Functions are first-class: Functions are values in our programming language

Higher-order function: A function that takes a function as an argument value **or**
A function that returns a function as a return value

Environments Enable Higher-Order Functions

Functions are first-class: Functions are values in our programming language

Higher-order function: A function that takes a function as an argument value **or**
A function that returns a function as a return value

Environment diagrams describe how higher-order functions work!

Environments Enable Higher-Order Functions

Functions are first-class: Functions are values in our programming language


Higher-order function: A function that takes a function as an argument value **or**
A function that returns a function as a return value

Environment diagrams describe how higher-order functions work!

(Demo)


Names can be Bound to Functional Arguments

```
1 def apply_twice(f, x):  
2     return f(f(x))  
3  
→ 4 def square(x):  
5     return x * x  
6  
→ 7 result = apply_twice(square, 2)
```



Names can be Bound to Functional Arguments

```
1 def apply_twice(f, x):  
2     return f(f(x))  
3  
→ 4 def square(x):  
5     return x * x  
6  
→ 7 result = apply_twice(square, 2)
```



Names can be Bound to Functional Arguments

```
1 def apply_twice(f, x):  
2     return f(f(x))  
3  
→ 4 def square(x):  
5     return x * x  
6  
→ 7 result = apply_twice(square, 2)
```

Global frame
apply_twice
square

func apply_twice(f, x) [parent=Global]


func square(x) [parent=Global]

Applying a user-defined function:

- Create a new frame
- Bind formal parameters (f & x) to arguments
- Execute the body:
return f(f(x))

Names can be Bound to Functional Arguments


```
1 def apply_twice(f, x):  
2     return f(f(x))  
3  
→ 4 def square(x):  
5     return x * x  
6  
→ 7 result = apply_twice(square, 2)
```



Applying a user-defined function:

- Create a new frame
- Bind formal parameters (f & x) to arguments
- Execute the body:
return f(f(x))


```
→ 1 def apply_twice(f, x):  
→ 2     return f(f(x))  
3  
4 def square(x):  
5     return x * x  
6  
7 result = apply_twice(square, 2)
```



Interactive Diagram

Names can be Bound to Functional Arguments

```
1 def apply_twice(f, x):  
2     return f(f(x))  
3  
→ 4 def square(x):  
5     return x * x  
6  
→ 7 result = apply_twice(square, 2)
```




func apply_twice(f, x) [parent=Global]

func square(x) [parent=Global]

Applying a user-defined function:

- Create a new frame
- Bind formal parameters (f & x) to arguments
- Execute the body:
return f(f(x))

```
→ 1 def apply_twice(f, x):  
→ 2     return f(f(x))  
3  
4 def square(x):  
5     return x * x  
6  
7 result = apply_twice(square, 2)
```




func apply_twice(f, x) [parent=Global]

func square(x) [parent=Global]

Interactive Diagram

Names can be Bound to Functional Arguments

```
1 def apply_twice(f, x):  
2     return f(f(x))  
3  
→ 4 def square(x):  
5     return x * x  
6  
→ 7 result = apply_twice(square, 2)
```



func apply_twice(f, x) [parent=Global]

func square(x) [parent=Global]

Applying a user-defined function:

- Create a new frame
- Bind formal parameters (f & x) to arguments
- Execute the body:
return f(f(x))

```
→ 1 def apply_twice(f, x):  
→ 2     return f(f(x))  
3  
4 def square(x):  
5     return x * x  
6  
7 result = apply_twice(square, 2)
```

2 Global frame

1

f1: apply_twice [parent=Global]

apply_twice
square

func apply_twice(f, x) [parent=Global]

func square(x) [parent=Global]

f
x 2


Interactive Diagram

Environments for Nested Definitions

(Demo)

Environment Diagrams for Nested Def Statements

```
1 def make_adder(n):  
2     def adder(k):  
3         return k + n  
4     return adder  
5  
6 add_three = make_adder(3)  
7 add_three(4)
```




Interactive Diagram

Environment Diagrams for Nested Def Statements

Nested def

```
1 def make_adder(n):  
2   def adder(k):  
3       return k + n  
4   return adder  
5  
6 add_three = make_adder(3)  
7 add_three(4)
```




Interactive Diagram

Environment Diagrams for Nested Def Statements

Nested def

```
1 def make_adder(n):  
2   def adder(k):  
3       return k + n  
4   return adder  
5  
6 add_three = make_adder(3)  
7 add_three(4)
```




Interactive Diagram

Environment Diagrams for Nested Def Statements

Nested def

```
1 def make_adder(n):  
2     def adder(k):  
3         return k + n  
4     return adder  
5  
6 add_three = make_adder(3)  
7 add_three(4)
```




Interactive Diagram

Environment Diagrams for Nested Def Statements

Nested def

```
1 def make_adder(n):  
2     def adder(k):  
3         return k + n  
4     return adder  
5  
6 add_three = make_adder(3)  
7 add_three(4)
```




Interactive Diagram

Environment Diagrams for Nested Def Statements

Nested def

```
1 def make_adder(n):  
2     def adder(k):  
3         return k + n  
4     return adder  
5  
6 add_three = make_adder(3)  
7 add_three(4)
```




Interactive Diagram

Environment Diagrams for Nested Def Statements


Nested def

```
1 def make_adder(n):  
2     def adder(k):  
3         return k + n  
4     return adder  
5  
6 add_three = make_adder(3)  
7 add_three(4)
```



Interactive Diagram

Environment Diagrams for Nested Def Statements




Environment Diagrams for Nested Def Statements


Nested def

```
1 def make_adder(n):
2     def adder(k):
3         return k + n
4     return adder
5
6 add_three = make_adder(3)
7 add_three(4)
```


- Every user-defined function has a parent frame (often global)




Environment Diagrams for Nested Def Statements



Environment Diagrams for Nested Def Statements



Environment Diagrams for Nested Def Statements



- Every user-defined function has a parent frame (often global)
- The parent of a function is the frame in which it was defined
- Every local frame has a parent frame (often global)
- The parent of a frame is the parent of the function called

Interactive Diagram

How to Draw an Environment Diagram

How to Draw an Environment Diagram

When a function is defined:

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.



f1: make_adder func adder(k) [parent=f1]

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.

f1: make_adder func adder(k) [parent=f1]

Bind <name> to the function value in the current frame

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.

f1: make_adder func adder(k) [parent=f1]

Bind <name> to the function value in the current frame

When a function is called:

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.



`f1: make_adder` `func adder(k) [parent=f1]`

Bind <name> to the function value in the current frame

When a function is called:


1. Add a local frame, titled with the <name> of the function being called.

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.



f1: make_adder func adder(k) [parent=f1]

Bind <name> to the function value in the current frame

When a function is called:


1. Add a local frame, titled with the <name> of the function being called.
- ★ 2. Copy the parent of the function to the local frame: [parent=<label>]

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.



`f1: make_adder` `func adder(k) [parent=f1]`

Bind <name> to the function value in the current frame

When a function is called:


1. Add a local frame, titled with the <name> of the function being called.
- ★ 2. Copy the parent of the function to the local frame: `[parent=<label>]`
3. Bind the <formal parameters> to the arguments in the local frame.

How to Draw an Environment Diagram

When a function is defined:

Create a function value: `func <name>(<formal parameters>) [parent=<label>]`

Its parent is the current frame.



f1: make_adder func adder(k) [parent=f1]

Bind <name> to the function value in the current frame

When a function is called:


1. Add a local frame, titled with the <name> of the function being called.
- ★ 2. Copy the parent of the function to the local frame: [parent=<label>]
3. Bind the <formal parameters> to the arguments in the local frame.
4. Execute the body of the function in the environment that starts with the local frame.

Local Names


(Demo)

Local Names are not Visible to Other (Non-Nested) Functions


```
1 def f(x, y):  
2     return g(x)  
3  
4 def g(a):  
→ 5     return a + y  
6  
7 result = f(1, 2)
```




Local Names are not Visible to Other (Non-Nested) Functions




Local Names are not Visible to Other (Non-Nested) Functions



Local Names are not Visible to Other (Non-Nested) Functions




Local Names are not Visible to Other (Non-Nested) Functions




Interactive Diagram

Local Names are not Visible to Other (Non-Nested) Functions




Local Names are not Visible to Other (Non-Nested) Functions



- An environment is a sequence of frames.

Local Names are not Visible to Other (Non-Nested) Functions




- An environment is a sequence of frames.
- The environment created by calling a top-level function (no def within def) consists of one local frame, followed by the global frame.

Function Composition

(Demo)

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```




Interactive Diagram

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```


→



Interactive Diagram

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```




Interactive Diagram

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```

→




Interactive Diagram

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```

Return value of make_adder is
an argument to compose1




Interactive Diagram

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```

Return value of make_adder is
an argument to compose1




Interactive Diagram

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```

Return value of make_adder is an argument to compose1




Interactive Diagram

The Environment Diagram for Function Composition



```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```

Return value of make_adder is an argument to compose1





Interactive Diagram

The Environment Diagram for Function Composition



Interactive Diagram

The Environment Diagram for Function Composition




Interactive Diagram

The Environment Diagram for Function Composition

```
1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10     def h(x):
11         return f(g(x))
12     return h
13
14 compose1(square, make_adder(2))(3)
```

Return value of make_adder is
an argument to compose1



Interactive Diagram

Lambda Expressions

(Demo)

Lambda Expressions

Lambda Expressions

```
>>> x = 10
```

Lambda Expressions

```
>>> x = 10
```

```
>>> square = x * x
```

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

```
>>> square = lambda x: x * x
```


Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

A function

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

A function

with formal parameter x

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

A function

with formal parameter x

that returns the value of " $x * x$ "

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

Important: No "return" keyword!

A function

with formal parameter `x`

that returns the value of `"x * x"`

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

Important: No "return" keyword!

A function

with formal parameter *x*

that returns the value of *"x * x"*

Must be a single expression

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

Important: No "return" keyword!

A function

with formal parameter x

that returns the value of "x * x"

```
>>> square(4)  
16
```

Must be a single expression

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

Important: No "return" keyword!

A function

with formal parameter x

that returns the value of "x * x"

```
>>> square(4)  
16
```

Must be a single expression

Lambda expressions are not common in Python, but important in general

Lambda Expressions

```
>>> x = 10
```

An expression: this one evaluates to a number

```
>>> square = x * x
```

Also an expression: evaluates to a function

```
>>> square = lambda x: x * x
```

Important: No "return" keyword!

A function

with formal parameter `x`

that returns the value of `"x * x"`

```
>>> square(4)  
16
```

Must be a single expression

Lambda expressions are not common in Python, but important in general

Lambda expressions in Python cannot contain statements at all!

Lambda Expressions Versus Def Statements

Lambda Expressions Versus Def Statements

VS

Lambda Expressions Versus Def Statements



square = lambda x: x * x

VS

Lambda Expressions Versus Def Statements



```
square = lambda x: x * x
```

VS



```
def square(x):  
    return x * x
```

Lambda Expressions Versus Def Statements



```
square = lambda x: x * x
```

VS

```
def square(x):  
    return x * x
```



- Both create a function with the same domain, range, and behavior.

Lambda Expressions Versus Def Statements



```
square = lambda x: x * x
```

VS

```
def square(x):  
    return x * x
```



- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.

Lambda Expressions Versus Def Statements



```
square = lambda x: x * x
```

VS

```
def square(x):  
    return x * x
```



- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.
- Both bind that function to the name square.

Lambda Expressions Versus Def Statements



```
square = lambda x: x * x
```

VS

```
def square(x):  
    return x * x
```



- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.
- Both bind that function to the name square.
- Only the def statement gives the function an intrinsic name.

Lambda Expressions Versus Def Statements



`square = lambda x: x * x`

VS



`def square(x):
 return x * x`

- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.
- Both bind that function to the name `square`.
- Only the `def` statement gives the function an intrinsic name.

Global frame

`square`

`func λ(x) <line 1> [parent=Global]`

`f1: λ <line 1> [parent=Global]`

<code>x</code>	<code>4</code>
<code>Return value</code>	<code>16</code>

Lambda Expressions Versus Def Statements



`square = lambda x: x * x`

VS



`def square(x):
 return x * x`

- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.
- Both bind that function to the name `square`.
- Only the `def` statement gives the function an intrinsic name.

Global frame

`square`

`func λ(x) <line 1> [parent=Global]`

`f1: λ <line 1> [parent=Global]`

<code>x</code>	<code>4</code>
Return value	<code>16</code>

Lambda Expressions Versus Def Statements




```
square = lambda x: x * x
```

VS



```
def square(x):  
    return x * x
```

- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.
- Both bind that function to the name square.
- Only the def statement gives the function an intrinsic name.



Lambda Expressions Versus Def Statements




```
square = lambda x: x * x
```

VS

```
def square(x):  
    return x * x
```



- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.
- Both bind that function to the name square.
- Only the def statement gives the function an intrinsic name.



Lambda Expressions Versus Def Statements





```
square = lambda x: x * x
```

VS



```
def square(x):  
    return x * x
```

- Both create a function with the same domain, range, and behavior.
- Both functions have as their parent the frame in which they were defined.
- Both bind that function to the name square.
- Only the def statement gives the function an intrinsic name.



Currying

Function Currying

Function Currying

```
def make_adder(n):  
    return lambda k: n + k
```

Function Currying

```
def make_adder(n):  
    return lambda k: n + k
```

```
>>> make_adder(2)(3)  
5  
>>> add(2, 3)  
5
```

Function Currying

```
def make_adder(n):  
    return lambda k: n + k
```

```
>>> make_adder(2)(3)  
5  
>>> add(2, 3)  
5
```

There's a general
relationship between
these functions

Function Currying

```
def make_adder(n):  
    return lambda k: n + k
```

```
>>> make_adder(2)(3)  
5  
>>> add(2, 3)  
5
```

There's a general
relationship between
these functions

(Demo)

Function Currying

```
def make_adder(n):  
    return lambda k: n + k
```

```
>>> make_adder(2)(3)  
5  
>>> add(2, 3)  
5
```

There's a general
relationship between
these functions

(Demo)

Curry: Transform a multi-argument function into a single-argument, higher-order function