



Deploy NVIDIA Triton Inference Server (Automated Deployment)

HCI

NetApp
October 01, 2020

This PDF was generated from https://docs.netapp.com/us-en/hci-solutions/hciaiedge_deploy_nvidia_triton_inference_server_automated_deployment.html on November 04, 2020.
Always check docs.netapp.com for the latest.



Table of Contents

Deploy NVIDIA Triton Inference Server (Automated Deployment) 1

Deploy NVIDIA Triton Inference Server (Automated Deployment)

To set up automated deployment for the Triton Inference Server, complete the following steps:

1. Open a VI editor and create a PVC yaml file `vi pvc-triton-model-repo.yaml`.

```
kind: PersistentVolumeClaim
apiVersion: v1
metadata:
  name: triton-pvc namespace: triton
spec:
  accessModes:
    - ReadWriteMany
  resources:
    requests:
      storage: 10Gi
  storageClassName: ontap-flexvol
```

2. Create the PVC.

```
kubectl create -f pvc-triton-model-repo.yaml
```

3. Open a VI editor, create a deployment for the Triton Inference Server, and call the file `triton_deployment.yaml`.

```
---
apiVersion: v1
kind: Service
metadata:
  labels:
    app: triton-3gpu
    name: triton-3gpu
    namespace: triton
spec:
  ports:
    - name: grpc-trtis-serving
      port: 8001
      targetPort: 8001
    - name: http-trtis-serving
      port: 8000
      targetPort: 8000
    - name: prometheus-metrics
```

```
    port: 8002
    targetPort: 8002
  selector:
    app: triton-3gpu
  type: LoadBalancer
---
apiVersion: v1
kind: Service
metadata:
  labels:
    app: triton-1gpu
  name: triton-1gpu
  namespace: triton
spec:
  ports:
    - name: grpc-trtis-serving
      port: 8001
      targetPort: 8001
    - name: http-trtis-serving
      port: 8000
      targetPort: 8000
    - name: prometheus-metrics
      port: 8002
      targetPort: 8002
  selector:
    app: triton-1gpu
  type: LoadBalancer
---
apiVersion: apps/v1
kind: Deployment
metadata:
  labels:
    app: triton-3gpu
  name: triton-3gpu
  namespace: triton
spec:
  replicas: 1
  selector:
    matchLabels:
      app: triton-3gpu      version: v1
  template:
    metadata:
      labels:
        app: triton-3gpu
        version: v1
    spec:
      containers:
        - image: nvcr.io/nvidia/tritonserver:20.07-v1-py3
```

```

    command: ["/bin/sh", "-c"]
    args: ["trtserver --model-store=/mnt/model-repo"]
    imagePullPolicy: IfNotPresent
    name: triton-3gpu
    ports:
      - containerPort: 8000
      - containerPort: 8001
      - containerPort: 8002
    resources:
      limits:
        cpu: "2"
        memory: 4Gi
        nvidia.com/gpu: 3
      requests:
        cpu: "2"
        memory: 4Gi
        nvidia.com/gpu: 3
    volumeMounts:
      - name: triton-model-repo
        mountPath: /mnt/model-repo
    gpu-count: "3"
    nodeSelector:
      nvidia.com/gpu: 3
  volumes:
    - name: triton-model-repo
      persistentVolumeClaim:
        claimName: triton-pvc---
apiVersion: apps/v1
kind: Deployment
metadata:
  labels:
    app: triton-1gpu
    name: triton-1gpu
    namespace: triton
spec:
  replicas: 3
  selector:
    matchLabels:
      app: triton-1gpu
      version: v1
  template:
    metadata:
      labels:
        app: triton-1gpu
        version: v1
    spec:
      containers:
        - image: nvcr.io/nvidia/tritonserver:20.07-v1-py3
          command: ["/bin/sh", "-c", "sleep 1000"]
          args: ["trtserver --model-store=/mnt/model-repo"]

```

```

imagePullPolicy: IfNotPresent
name: triton-1gpu
ports:
- containerPort: 8000
- containerPort: 8001
- containerPort: 8002
resources:
  limits:
    cpu: "2"
    memory: 4Gi
    nvidia.com/gpu: 1
  requests:
    cpu: "2"
    memory: 4Gi
    nvidia.com/gpu: 1
volumeMounts:
- name: triton-model-repo
  mountPath: /mnt/model-repo
nodeSelector:
  gpu-count: "1"
volumes:
- name: triton-model-repo
  persistentVolumeClaim:
    claimName: triton-pvc

```

Two deployments are created here as an example. The first deployment spins up a pod that uses three GPUs and has replicas set to 1. The other deployment spins up three pods each using one GPU while the replica is set to 3. Depending on your requirements, you can change the GPU allocation and replica counts.

Both of the deployments use the PVC created earlier and this persistent storage is provided to the Triton inference servers as the model repository.

For each deployment, a service of type LoadBalancer is created. The Triton Inference Server can be accessed by using the LoadBalancer IP which is in the application network.

A nodeSelector is used to ensure that both deployments get the required number of GPUs without any issues.

4. Label the K8 worker nodes.

```

kubectl label nodes hci-ai-k8-worker-01 gpu-count=3
kubectl label nodes hci-ai-k8-worker-02 gpu-count=1

```

5. Create the deployment.

```
kubectl apply -f triton_deployment.yaml
```

6. Make a note of the LoadBalancer service external LPS.

```
kubectl get services -n triton
```

The expected sample output is as follows:

```
rarvind@deployment-jump:~/triton-inference-server$ kubectl get services -n triton
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
triton-1gpu-v20-07-v1	LoadBalancer	10.233.21.185	172.21.231.133	8001:31238/TCP,8000:30171/TCP,8002:32348/TCP	10h
triton-3gpu-v20-07-v1	LoadBalancer	10.233.13.17	172.21.231.132	8001:31549/TCP,8000:30220/TCP,8002:31517/TCP	10h

7. Connect to any one of the pods that were created from the deployment.

```
kubectl exec -n triton --stdin --tty triton-1gpu-86c4c8dd64-5451x -- /bin/bash
```

8. Set up the model repository by using the example model repository.

```
git clone
cd triton-inference-server
git checkout r20.07
```

9. Fetch any missing model definition files.

```
cd docs/examples
./fetch_models.sh
```

10. Copy all the models to the model repository location or just a specific model that you wish to use.

```
cp -r model_repository/resnet50_netdef/ /mnt/model-repo/
```

In this solution, only the resnet50_netdef model is copied over to the model repository as an example.

11. Check the status of the Triton Inference Server.

```
curl -v <<LoadBalancer_IP_recorded earlier>>:8000/api/status
```

The expected sample output is as follows:

```
curl -v 172.21.231.132:8000/api/status
* Trying 172.21.231.132...
* TCP_NODELAY set
* Connected to 172.21.231.132 (172.21.231.132) port 8000 (#0)
> GET /api/status HTTP/1.1
> Host: 172.21.231.132:8000
> User-Agent: curl/7.58.0
> Accept: */*
>
< HTTP/1.1 200 OK
< NV-Status: code: SUCCESS server_id: "inference:0" request_id: 9
< Content-Length: 1124
< Content-Type: text/plain
<
id: "inference:0"
version: "1.15.0"
uptime_ns: 377890294368
model_status {
  key: "resnet50_netdef"
  value {
    config {
      name: "resnet50_netdef"
      platform: "caffe2_netdef"
      version_policy {
        latest {
          num_versions: 1
        }
      }
      max_batch_size: 128
      input {
        name: "gpu_0/data"
        data_type: TYPE_FP32
        format: FORMAT_NCHW
        dims: 3
        dims: 224
        dims: 224
      }
      output {
        name: "gpu_0/softmax"
        data_type: TYPE_FP32
        dims: 1000
        label_filename: "resnet50_labels.txt"
      }
    }
    instance_group {
      name: "resnet50_netdef"
      count: 1
      gpus: 0
      gpus: 1
    }
  }
}
```



```
    gpus: 2
    kind: KIND_GPU
  }
  default_model_filename: "model.netdef"
  optimization {
    input_pinned_memory {
      enable: true
    }
    output_pinned_memory {
      enable: true
    }
  }
}
version_status {
  key: 1
  value {
    ready_state: MODEL_READY
    ready_state_reason {
    }
  }
}
}
}
ready_state: SERVER_READY
* Connection #0 to host 172.21.231.132 left intact
```

[Next: Deploy the Client for Triton Inference Server \(Automated Deployment\)](#)

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.