



# Visualization



# Animated D3




# Animated Transitions




- Animated transitions can be applied to selections using the **transition** operator
- Transitions change the **style** and **attr** operators of selections
- Values are interpolate from the current to specified value gradually over time
- The delay and duration of transitions can be specified as functional operators
- Easing can also be set as “**elastic**”, “**cubic-in-out**” and “**linear**”

# Transitions



- Transitions are a form of key frame animation
- Starting frame is the current state of the DOM
- Ending frame is a set of attributes, styles and/or properties you specify
- Use the **transition()** function to make the change

# Transitions Between Datasets



- To transition all the data values at once:
  - Modify the values in your dataset.
  - Rebind the new values to the existing elements
  - Set new attribute values as needed to update the visual display.

# Reacting to an Event

- To initiate the change, we can react to an event
- Add a paragraph to the HTML's body:

```
(<p>Click on this text to update the chart with new data values  
(once).</p>) ↗
```

- Then, add the following:

```
(d3.select("p")  
  .on("click", (function() {  
    //Do something on click  
  }));
```




# Recall our Bar Chart

## ➤ Our 1D data:

```
var dataset = [ 5, 10, 13, 19, 21, 25, 22, 18, 15, 13,  
11, 12, 15, 20, 18, 17, 16, 18, 23, 25 ];
```

## ➤ Color coded, with padding and labels:





# Changing the Data



- We need to bind and use new data values

```
//New values for dataset
```

```
dataset = [ 11, 12, 15, 20, 18, 17, 16, 18, 23, 25,  
            5, 10, 13, 19, 21, 25, 22, 18, 15, 13 ];
```



```

//On click, update with new data
d3.select("p")
  .on("click", function() {
    //New values for dataset
    dataset = [ 11, 12, 15, 20, 18, 17, 16, 18, 23, 25,
                5, 10, 13, 19, 21, 25, 22, 18, 15, 13 ];

    //Update all rects
    svg.selectAll("rect")
      .data(dataset)
      .attr("y", function(d) {
        return h - yScale(d);
      })
      .attr("height", function(d) {
        return yScale(d);
      })
      .attr("fill", function(d) {
        return "rgb(0, 0, " + Math.round(d * 10) + ")";
      });
  });


```





```
svg.selectAll("text")  
  .data(dataset)  
  .text(function(d) {  
    return d;  
  })  
  .attr("y", function(d) {  
    return h - yScale(d) + 14;  
  });  
  
});
```


# Transitions Control



```
//Update all rects
svg.selectAll("rect")
  .data(dataset)
  .transition()    // <-- This is new!

  .attr("y", function(d) {
    return h - yScale(d);
  })
  .attr("height", function(d) {
    return yScale(d);
  })
  .attr("fill", function(d) {
    return "rgb(0, 0, " + Math.round(d * 10) + ")";
  });
```


# Transitions – Duration



- Can override duration with `duration(1000)`



```
svg.selectAll("rect")
  .data(dataset)
  .transition()
  .duration(1000) // <-- Now this is new!
  .attr("y", function(d) {
    return h - yScale(d);
  })
  .attr("height", function(d) {
    return yScale(d);
  })
  .attr("fill", function(d) {
    return "rgb(0, 0, " + Math.round(d * 10) + ")";
  });
```

# Transitions - Ease





- Ease controls the rate of change of the transition
- In addition to the default linear, lots of other easing types are supported:
  - `d3.easeLinear(t)`
  - `d3.easePolyIn(t)`
  - `d3.easePolyOut(t)`
  - `d3.easePoly(t)`
  - `d3.easePolyInOut(t)`
  - `d3.easeQuadIn(t)`
  - Etc, etc, etc

# Transitions – Linear Ease





# Transitions – ExpOut Ease








# Transitions – Expln Ease




# Transitions – ExplnOut Ease





# Transitions – ElasticIn Ease





```
elasticIn(t, 1.20, 0.35)  
elasticIn(t, 1.15, 0.30)  
elasticIn(t, 1.05, 0.25)  
elasticIn(t, 1.00, 0.20)
```





# Transitions – ElasticOut Ease



# Transitions – BounceIn Ease




# Transitions – BounceOut Ease





# Transitions – Ease




- Can set transition style with a call to `Ease()`

```
...    //Selection statement(s)
      .transition()
      .duration(2000)
      .ease(d3.easeLinear)
...

```

# Transitions – Delays



- Can also set a `delay()` timer, before the transition

...


```
.transition()
```

```
.delay(1000)           //1,000 ms or 1 second
```

```
.duration(2000)        //2,000 ms or 2 seconds
```


...

# Transitions – Staggered Delays




- Can also set a delay() timer, before the transition


```
...  
.transition()  
.delay(function(d, i) {  
    return i * 100;  
})  
.duration(500)  
...
```



## More on Interaction




# User Input



- User interaction supported with **event listeners**
- Need to set even listeners with the '.on' method
- Other topics:
  - Mouseover, mouseout, mousedown, mouseup

# User Interface Event Listeners



- To bind a function to a mouse event:

`.on(type, function() { });`

- There are several kinds of events:

- mouseover - mouse is hovering over the object
- mouseout - mouse leaves the object
- mousedown - mouse button is held down
- mouseup - let go of your mouse button
- click - click mouse button





# User Input

- You can bind event listeners when you first create elements

```
//Create bars
svg.selectAll("rect")
  .data(dataset)
  .enter()
  .append("rect")
... //Set attributes (omitted here)
.on("click", function(d) {
  //This will run whenever *any* bar is clicked
});
```


# User Input – selecting bars

- You can bind event listeners when you first create elements

```
//Create bars
svg.selectAll("rect")
  .data(dataset)
  .enter()
  .append("rect")
... //Set attributes (omitted here)

.on("click", function(d) {
  console.log(d);
});
```

# User Input - hovering



```
//Create bars
svg.selectAll("rect")
  .data(dataset)
  .enter()
  .append("rect")
  ... //Set attributes (omitted here)

  .on("mouseover", (function() {
    d3.select(this)
      .attr("fill", "orange");
  }));
```


# User Input – hovering (fixed)


```
//Create bars
svg.selectAll("rect")
  .data(dataset)
  .enter()
  .append("rect")
... //Set attributes (omitted here)
.on("mouseover", function() {
  d3.select(this)
    .attr("fill", "orange");
});
(
.on("mouseout", function(d) {
  d3.select(this)
    .attr("fill", "rgb(0, 0, " + (d * 10) + ")");
});
```

# User Input – hovering (fancy)




```
.on("mouseout", function(d) {  
  d3.select(this)  
    .transition()  
    .duration(250)  
    .attr("fill", "rgb(0, 0, " + (d * 10) + ")");  
});
```






Even More to Learn about






# Layouts & Behaviours




- Layouts supply reusable, flexible visualization techniques, including:
  - partition layout
  - chord layout
  - force layout
  - stack layout
  - squarified treemap layout
  - Etc, etc, etc...
- Common interaction techniques, including:
  - zoom behavior

## Help Hours for D3 assignments and projects




- Lab times (for both 4166 & 6406)
  - Wednesday, 13:35-14:25
  - Friday, 10:35-11:25
  
- TA Office hours (for both 4166 & 6406)
  - Tuesday 11:05 – 11:55
  
- Dipankar Mazumdar is the TA

# More Reference Material



- *Interactive Data Visualization for the Web* by Scott Murray, O'Reilly.
- *Getting Started with D3*, by Mike Dewar, O'Reilly.
- *SVG Essentials*, by J. Eisenberg, O'Reilly.
- The D3 website:
  - <http://d3js.org/>
  - <https://github.com/mbostock/d3/wiki/API-Reference>

# DFA Copyright Information



This lecture and any other materials provided for this course are subject to the copyright of the course instructor and may not be reproduced or copied in whole or in part without the consent of the instructor. Students who are enrolled in the course who have received this lecture or any other material may reproduce it in order to view it at a more convenient time but must destroy the reproduction within 30 days of receiving the final course evaluation.

