Table of Windows Security Event IDs with meaning and when to use each.

Windows Security Event IDs are numerical identifiers associated with audited security activities.

They help reconstruct user activity, authentication attempts, account changes, process execution, and possible evidence tampering.

Event ID	Event Meaning	When It Is Useful
4624	An account was successfully logged on	Identifying successful authentication and suspicious logons
4625	An account failed to log on	Detecting brute-force attempts and authentication failures
4634	An account was logged off	Correlating sessions and tracking logoff activity
4648	A logon was attempted using explicit credentials	Investigating alternate credential use and lateral movement
4672	Special privileges assigned to a new logon	Identifying privileged authentication sessions
4688	A new process was created	Investigating suspicious process execution
4697	A service was installed in the system	Detecting unexpected service installation and persistence
4720	A user account was created	Identifying unauthorized account creation
4722	A user account was enabled	Detecting unexpected account reactivation
4724	An attempt was made to reset an account's password	Investigating password-reset activity
4732	A member was added to a security-enabled local group	Detecting unauthorized local-group membership changes
4768	A Kerberos authentication ticket (TGT) was requested	Investigating Kerberos authentication activity
4769	A Kerberos service ticket was requested	Investigating service-ticket requests and potential Kerberoasting
4776	A computer attempted to validate credentials using NTLM	Investigating NTLM authentication attempts
1102	The Security audit log was cleared	Investigating possible log tampering or evidence destruction

❖ Important Security Event Correlations

- **Repeated Authentication Failures**
  A large number of Event ID 4625 records from the same source may indicate password guessing or a misconfigured application.

- **Failed Logons Followed by Success**
  Multiple 4625 events followed by 4624 may indicate successful authentication after repeated failures.

- **Unauthorized Account Creation**
  Event ID 4720 followed by 4732 may indicate that a newly created account was added to a security-enabled local group.

- **Suspicious Process Execution**
  Event ID 4688 can help identify unauthorized executables, especially when process command-line auditing is configured.

- **Potential Kerberoasting**
  Unusual Event ID 4769 service-ticket requests may indicate Kerberoasting attempts, particularly when combined with other suspicious authentication patterns.

- **Possible Log Tampering**
  Event ID 1102 records that the Security audit log was cleared. This can be legitimate administrative activity or an attempt to remove evidence.

  Event availability depends on audit policy and system configuration. Kerberos ticket events are primarily recorded on domain controllers.