Wireshark Filter Cheat Sheet

Important: These are Wireshark display filters, entered in the display-filter bar after capture. Replace example IP addresses with addresses from your own lab. A display filter hides packets from the view; it does not remove them from the capture.

#	Wireshark Filter	Meaning	When to Use It
1	ip	All IPv4 packets	View IPv4 traffic
2	tcp	TCP packets	Troubleshoot TCP connections
3	udp	UDP packets	Analyze UDP traffic
4	dns	DNS traffic	Troubleshoot domain name resolution
5	http	HTTP traffic	Inspect unencrypted web traffic
6	tls	TLS protocol traffic	Analyze encrypted connections and handshakes
7	icmp	IPv4 ICMP traffic	Troubleshoot ping and connectivity
8	arp	ARP packets	Investigate IP-to-MAC address resolution
9	ip.addr == 192.168.1.10	Traffic to or from an IP address	Isolate a specific host
10	ip.src == 192.168.1.10	Packets from a source IP	Track outbound traffic
11	ip.dst == 192.168.1.20	Packets to a destination IP	Inspect traffic to a server
12	tcp.port==443	TCP traffic on port 443	Analyze HTTPS-over-TCP traffic
13	udp.port==53	UDP traffic on port 53	Inspect DNS queries and responses
14	tcp.flags.syn==1 && tcp.flags.ack==0	Initial TCP SYN packets	Identify connection attempts
15	tcp.flags.reset == 1	TCP reset packets	Investigate abruptly reset connections
16	tcp.analysis.retransmission	Detected TCP retransmissions	Troubleshoot possible packet loss
17	tcp.analysis.duplicate_ack	Duplicate TCP acknowledgments	Investigate possible packet loss or reordering
18	http.request	HTTP requests	Find client requests
19	dns.flags.response == 0	DNS queries	Identify requested domain names
20	frame.len > 1000	Frames larger than 1,000 bytes	Find large packets

❖ **Capture filter vs display filter**

- **Capture filter:** set before/during capture; uses libpcap/BPF syntax and controls which packets are saved.
  Example: host 192.168.1.10 or port 53.

- **Display filter:** applied to packets already captured; uses Wireshark syntax.
  Example: ip.addr == 192.168.1.10 or dns.