Entropy-Complexity Plane Discrimination of Simulated Time Series Models

Rasika Dilhani

February 4, 2026

1 Purpose

Clustering is an unsupervised learning technique that partitions a dataset into groups of similar objects, aiming to reveal underlying but latent structure. The goal of this work is to discriminate between autoregressive (AR), moving average (MA), and ARMA time series models using a feature-based approach built on ordinal pattern analysis. Ordinal patterns encode the temporal ordering of values within each time series segment, allowing the extraction of information-theoretic measures such as entropy and complexity. These metrics, including permutation entropy, Renyi entropy, Tsallis entropy, and Fisher information, capture both linear and nonlinear dynamics and offer greater sensitivity for model discrimination than traditional linear statistics. By mapping each time series to its corresponding feature vector and applying unsupervised clustering, we empirically demonstrate that ordinal pattern information measures effectively distinguish the structure and underlying process of AR, MA, and ARMA models. This approach is robust to noise, applicable across model classes, and leverages recent advances in time series feature extraction. We closely follow the feature-based ordinal pattern analysis frameworks established by [1, 2, 3, 4], which inform both our methodology and interpretation of results.

2 Methodology

The variation of the time delay parameter is found to have no significant effect in repeated experiments [2]. Thus, we focus on two key variables for setting parameters and the data set: the length of the sequence and the embedding dimension. Below, we describe the simulation setup for our experiment.

Simulation and Feature Construction:

- **Embedding:** Fixed embedding dimension ($D = 3$) and time delay ($\tau = 1$).
- **Model Structure:** AR(1), AR(2), MA(1), MA(2), ARMA(1,1), ARMA(2,2), each with four parameterizations (M1 to M4) as given in Table 1.
- **Simulation:** For each model and parameter set, $R = 100$ time series of length $n = 1000, 5000$ and 10000 were simulated.
- **Features:** For each realization, the following were computed:

- *Entropy:* Shannon, Rényi, Tsallis entropies, and Fisher information measure.
- *Complexity:* Statistical complexity measures corresponding to each entropy type.
- *Variability:* Variances were also computed for each model to assess stability.
- *Confidence Interval:* Confidence Interval for Entropy and Complexity also computed for each model to assess stability.

Centrality Analysis: For each model, the time series whose (H^*, C^*) coordinates are closest to the median (H, C) values is identified as the "central" representative, following the recommendation of Chagas et al. [2].

Type	**Model**	α_1	α_2	β_1	β_2
AR(1)	$\mathrm{AR}(1)_{\mathrm{M}_1}$	0.8			
	$\mathrm{AR}(1)_{\mathrm{M}_2}$	0.1			
	$\mathrm{AR}(1)_{\mathrm{M}_3}$	−0.8			
	$\mathrm{AR}(1)_{\mathrm{M}_4}$	−0.1			
AR(2)	$\mathrm{AR}(2)_{\mathrm{M}_1}$	0.1	0.8		
	$\mathrm{AR}(2)_{\mathrm{M}_2}$	−0.8	0.1		
	$\mathrm{AR}(2)_{\mathrm{M}_3}$	0.1	−0.8		
	$\mathrm{AR}(2)_{\mathrm{M}_4}$	−0.8	−0.1		
MA(1)	$\mathrm{MA}(1)_{\mathrm{M}_1}$			0.8	
	$\mathrm{MA}(1)_{\mathrm{M}_2}$			0.1	
	$\mathrm{MA}(1)_{\mathrm{M}_3}$			−0.8	
	$\mathrm{MA}(1)_{\mathrm{M}_4}$			−0.1	
MA(2)	$\mathrm{MA}(2)_{\mathrm{M}_1}$			0.1	0.8
	$\mathrm{MA}(2)_{\mathrm{M}_2}$			−0.8	0.1
	$\mathrm{MA}(2)_{\mathrm{M}_3}$			0.1	−0.8
	$\mathrm{MA}(2)_{\mathrm{M}_4}$			−0.8	−0.1
ARMA(1, 1)	$\mathrm{ARMA}(1,1)_{\mathrm{M}_1}$	0.8		0.8	
	$\mathrm{ARMA}(1,1)_{\mathrm{M}_2}$	0.1		0.1	
	$\mathrm{ARMA}(1,1)_{\mathrm{M}_3}$	−0.8		−0.8	
	$\mathrm{ARMA}(1,1)_{\mathrm{M}_4}$	−0.1		−0.1	
ARMA(2, 2)	$\mathrm{ARMA}(2,2)_{\mathrm{M}_1}$	0.1	0.8	0.1	0.8
	$\mathrm{ARMA}(2,2)_{\mathrm{M}_2}$	−0.8	0.1	−0.8	0.1
	$\mathrm{ARMA}(2,2)_{\mathrm{M}_3}$	0.1	−0.8	0.1	−0.8
	$\mathrm{ARMA}(2,2)_{\mathrm{M}_4}$	−0.8	−0.1	−0.8	−0.1

Table 1: Models and parameter sets for AR(1), AR(2), MA(1), MA(2), ARMA(1,1), and ARMA(2,2). Empty cells indicate omitted parameters.

The model parameterizations are organized into three cases:

- **Case 1:** All coefficients are positive as shown in Table 2.
- **Case 2:** All coefficients are negative as shown in Table 3.

- **Case 3:** Coefficients include both positive and negative values as shown in Table 4.

Type	**Model**	α_1	α_2	β_1	β_2
AR(1)	$\mathrm{AR}(1)_{\mathrm{M}_1}$	0.8			
	$\mathrm{AR}(1)_{\mathrm{M}_2}$	0.1			
AR(2)	$\mathrm{AR}(2)_{\mathrm{M}_1}$	0.1	0.8		
MA(1)	$\mathrm{MA}(1)_{\mathrm{M}_1}$			0.8	
	$\mathrm{MA}(1)_{\mathrm{M}_2}$			0.1	
MA(2)	$\mathrm{MA}(2)_{\mathrm{M}_1}$			0.1	0.8
ARMA(1, 1)	$\mathrm{ARMA}(1,1)_{\mathrm{M}_1}$	0.8		0.8	
	$\mathrm{ARMA}(1,1)_{\mathrm{M}_2}$	0.1		0.1	
ARMA(2, 2)	$\mathrm{ARMA}(2,2)_{\mathrm{M}_1}$	0.1	0.8	0.1	0.8

Table 2: Models and parameter sets for Case 1.

Type	**Model**	α_1	α_2	β_1	β_2
AR(1)	$\mathrm{AR}(1)_{\mathrm{M}_3}$	-0.8			
	$\mathrm{AR}(1)_{\mathrm{M}_4}$	-0.1			
AR(2)	$\mathrm{AR}(2)_{\mathrm{M}_4}$	-0.8	-0.1		
MA(1)	$\mathrm{MA}(1)_{\mathrm{M}_3}$			-0.8	
	$\mathrm{MA}(1)_{\mathrm{M}_4}$			-0.1	
MA(2)	$\mathrm{MA}(2)_{\mathrm{M}_4}$			-0.8	-0.1
ARMA(1, 1)	$\mathrm{ARMA}(1,1)_{\mathrm{M}_3}$	-0.8		-0.8	
	$\mathrm{ARMA}(1,1)_{\mathrm{M}_4}$	-0.1		-0.1	
ARMA(2, 2)	$\mathrm{ARMA}(2,2)_{\mathrm{M}_4}$	-0.8	-0.1	-0.8	-0.1

Table 3: Models and parameter sets for Case 2.

Type	**Model**	α_1	α_2	β_1	β_2
AR(2)	$\mathrm{AR}(2)_{\mathrm{M}_2}$	-0.8	0.1		
	$\mathrm{AR}(2)_{\mathrm{M}_3}$	0.1	-0.8		
MA(2)	$\mathrm{MA}(2)_{\mathrm{M}_2}$			-0.8	0.1
	$\mathrm{MA}(2)_{\mathrm{M}_3}$			0.1	-0.8
ARMA(2, 2)	$\mathrm{ARMA}(2,2)_{\mathrm{M}_2}$	-0.8	0.1	-0.8	0.1
	$\mathrm{ARMA}(2,2)_{\mathrm{M}_3}$	0.1	-0.8	0.1	-0.8

Table 4: Models and parameter sets for Case 3.

2.1 Concept of Central (H*, C*) points calculation

To calculate the "central" point in the $H \times C$ plane (as recommended by Chagas et al., [2]), first compute the principal component analysis (PCA) of all H and C points for a given model. Next, sort the data according to the values of the first principal component (the direction of greatest variance). The emblematic point is then the original (H, C) pair corresponding to the median value along this first principal component. This method ensures the selected point is truly central with respect to the main data structure, rather than simply taking the median of H and C separately.

3 Results

The experimental results were analyzed using three distinct cases. Case 1 considers all positive model parameters, as shown in Table 2. Case 2 uses all negative parameters (see Table 3), and Case 3 consists of mixed positive and negative parameter settings (see Table 4). This case-wise approach was adopted because considering all possible parameter combinations did not provide clear insights into the experimental expectations.

3.1 Graphical Representation of H-C Plane

This section shows the entropy-complexity $(H \times C)$ plane for separate panels Shannon, Rényi, Tsallis, and Fisher information entropy measures and combined plot against their corresponding complexity measures. All three cases discuss separately with outcomes.

3.1.1 Case 1

The Case 1 presents the distribution of different time series models characterized by positive-valued parameters as shown in the Table 2.

The Figure 1 shows the entropy-complexity $(H \times C)$ plane



Figure 1: Shannon entropy in the (H, C) plane, Case 1, for $n = 5000$ (left) and $n = 10000$ (right).

Figure 2 presents the entropy-complexity $(H \times C)$ plane as a combined plot for three entropy measures and the Fisher information metric. Distinct clustering of models AR(1), AR(2), MA(1), MA(2), ARMA(1, 1), and ARMA(2, 2) is observed in each

entropy-complexity plane, highlighting the capacity of these feature pairs for robust model discrimination. Variations in cluster shape and position among the different entropy types reflect the unique sensitivities of each entropy measure to the underlying time series dynamics. The figure further confirms that autoregressive, moving average, and ARMA processes can be effectively distinguished when all model parameters are positive, as considered in Case 1.



Figure 2: Comparison of each model shown by the four figures.

3.1.2 Case 2

The Figure 3 shows the entropy-complexity ($H \times C$) plane for Case 2. It presents the distribution of different time series models characterized by negative-valued parameters as shown in Table 3.



Figure 3: Shannon entropy in the (H, C) plane, Case 2, for $n = 5000$ (left) and $n = 10000$ (right).



Figure 4: Comparison of each model shown by the four figures.

3.1.3 Case 3

In this section, we consider the time series models with coefficients taking both positive and negative values to comprehensively analyze their dynamic behaviors. It shows clearly three time series models $\mathrm{AR}(2), \mathrm{MA}(2)$, and $\mathrm{ARMA}(2, 2)$ shows model separation.



Figure 5: Shannon entropy in the (H, C) plane, Case 3, for $n = 5000$ (left) and $n = 10000$ (right).



Figure 6: Comparison of each model shown by the four figures.

3.2 Central Series Exploration

Referring to Chagas et al. [2], it is clear that the median point for entropy and complexity is the best representation of the time series. In our experiment, the central (H^*, C^*) point for each model is identified, and the results are shown in Table 5. This point corresponds to the (H, C) whose first principal component is the median among all observations. This ensures that the selected point is the most representative in the main direction of data variability, as recommended in Algorithm 1 and Figure 6 of Chagas et al.

Table 5: Emblematic (Median) Points (H^*, C^*) and Their Row Index

Model	H^*	C^*	Emblematic row
$\mathrm{AR}(1)_{\mathrm{M}_1}$	0.977115	0.021599	25
$\mathrm{AR}(1)_{\mathrm{M}_2}$	0.999064	0.000929	64
$\mathrm{AR}(1)_{\mathrm{M}_3}$	0.945461	0.055231	55
$\mathrm{AR}(1)_{\mathrm{M}_4}$	0.998832	0.001152	88
$\mathrm{AR}(2)_{\mathrm{M}_1}$	0.965885	0.034516	75
$\mathrm{AR}(2)_{\mathrm{M}_2}$	0.917991	0.083039	54
$\mathrm{AR}(2)_{\mathrm{M}_3}$	0.972400	0.026208	80
$\mathrm{AR}(2)_{\mathrm{M}_4}$	0.964379	0.036038	12
$\mathrm{ARMA}(1,1)_{\mathrm{M}_1}$	0.899274	0.087417	53
$\mathrm{ARMA}(1,1)_{\mathrm{M}_2}$	0.997516	0.002436	90
$\mathrm{ARMA}(1,1)_{\mathrm{M}_3}$	0.932882	0.067982	87
$\mathrm{ARMA}(1,1)_{\mathrm{M}_4}$	0.997835	0.002159	4
$\mathrm{ARMA}(2,2)_{\mathrm{M}_1}$	0.943623	0.057128	87
$\mathrm{ARMA}(2,2)_{\mathrm{M}_2}$	0.899985	0.101073	6
$\mathrm{ARMA}(2,2)_{\mathrm{M}_3}$	0.966676	0.031002	9
$\mathrm{ARMA}(2,2)_{\mathrm{M}_4}$	0.957209	0.043443	80
$\mathrm{MA}(1)_{\mathrm{M}_1}$	0.969221	0.028807	30
$\mathrm{MA}(1)_{\mathrm{M}_2}$	0.998891	0.001085	75
$\mathrm{MA}(1)_{\mathrm{M}_3}$	0.993770	0.006249	46
$\mathrm{MA}(1)_{\mathrm{M}_4}$	0.998752	0.001238	64
$\mathrm{MA}(2)_{\mathrm{M}_1}$	0.990739	0.009306	3
$\mathrm{MA}(2)_{\mathrm{M}_2}$	0.991545	0.008480	80
$\mathrm{MA}(2)_{\mathrm{M}_3}$	0.990391	0.009282	96
$\mathrm{MA}(2)_{\mathrm{M}_4}$	0.996217	0.003776	31

3.2.1 Case 1

The figures 7 and 8 display all median (H^*, C^*) points for every model on a single entropy-complexity plane, with each point colored by entropy type (Shannon, Renyi, Tsallis, or Fisher). This collective view reveals the global clustering structure and relative discriminability achieved by the different entropy measures. Further it is clearly seen that different models occupy distinct regions in the $H \times C$ plane. Models with highly regular or highly random dynamics tend to lie near the lower and upper bounds of H^* and C^*, while those with intermediate complexity are centrally located. Coloring by entropy type allows for immediate visual comparison of how sensitive each measure is for model separation.

The Figure 9 provides a comprehensive visualization of the Shannon entropy median points for each time series, together with their associated time series plotted around the $H^* \times C^*$ plane. In this diagram, the central panel displays the H^* (Shannon entropy) and C^* values for each model under investigation, while the surrounding panels illustrate representative time series corresponding to each point. This arrangement emphasizes the model differences of all the time series except $\mathrm{MA}(1)_{\mathrm{M}_2}, \mathrm{AR}(1)_{\mathrm{M}_2}$, and $\mathrm{ARMA}(1,1)_{\mathrm{M}_2}$. Those time series overlap, meaning they appear as the same type of time series models.



Figure 7: Median entropy–complexity plot for $n = 5000$ (left) and $n = 10000$ (right).



Figure 8: Central entropy–complexity group plot.



Figure 9: Entropy–complexity central points plot for Shannon entropy with associated time series.

3.2.2 Case 2

When analyzing all time series models with negative coefficients in Case 2, ordinal pattern analysis distinctly reveals similarities and differences in their dynamical behavior. Specifically, the time series generated by the models $\mathrm{MA}(1)_{\mathrm{M}_4}$ and $\mathrm{AR}(1)_{\mathrm{M}_4}$ display highly similar temporal structures, making them challenging to distinguish based solely on their sequence plots. This similarity is further confirmed in the entropy-complexity (H^*–C^*) plane, where the median representative points of $\mathrm{MA}(1)_{\mathrm{M}_4}$ and $\mathrm{AR}(1)_{\mathrm{M}_4}$ overlap, indicating nearly identical complexity and entropy characteristics. In contrast, the median points corresponding to other time series models with negative coefficients are clearly separated in the $H^* \times C^*$ plane, demonstrating distinctive dynamical signatures for each model. The figures 10, 11 and 12 verify this clearly.



Figure 10: Central entropy–complexity plot for $n = 5000$ (left) and $n = 10000$ (right).

Figure 11: Central entropy–complexity group plot.



Figure 12: Entropy–complexity central points plot for Shannon entropy with associated time series.

3.2.3 Case 3

In this section, we analyze time series models whose coefficients include both positive and negative values. This comprehensive consideration allows us to assess model behaviors under varying parameter regimes, thereby providing a more complete understanding of the dynamics captured by the ARMA processes studied. The analysis of the plots shown below clearly separates almost all time series models. Notably, the models $\mathrm{MA}(2)_{\mathrm{M}_2}$ and $\mathrm{MA}(2)_{\mathrm{M}_3}$ exhibit some overlap, indicating similarity in their dynamical behaviors that makes them less distinguishable in the entropy–complexity plane. However, the other models demonstrate clear discrimination, confirming the effectiveness of the entropy–complexity plane in differentiating ARMA processes across varying coefficient regimes.



Figure 13: Central entropy–complexity plot for $n = 5000$ (left) and $n = 10000$ (right).



Figure 14: Central entropy–complexity group plot.



Figure 15: Entropy–complexity central points plot for Shannon entropy with associated time series.

In this extended analysis, six case studies were conducted to further validate and explore the behavior of various ARMA model configurations within the $H \times C$ plane. Specifically, three representative ARMA models were selected for each case, two extreme cases positioned far apart in the previously obtained $H \times C$ plane, and one central model located between them. For each selected model, time series data were generated with lengths of 5,000 and 10,000 observations, with 100 independent replications performed for each length to ensure statistical robustness. The Shannon entropy and corresponding statistical complexity were computed for each simulated time series following the same methodology used in the preliminary experiments. Furthermore, a model classification analysis was carried out using heat map representations of the entropy–complexity distributions to visualize and compare model behavior. These heat maps highlight regions of higher density where models exhibit similar dynamical characteristics, enabling clearer differentiation between stochastic and deterministic regimes as well as among AR, MA, and ARMA structures.

The results obtained from these six cases are presented below to confirm and interpret the experimental findings.

New Case 1 is based on results obtained when considering all positive coefficients in the ARMA models, as described in Table 2. The figures 16 and 17 display outcomes for sample sizes of 5000 and 10000, respectively. In these results, we highlight two extreme cases and the median point for positive-coefficient time series, including $\mathrm{ARMA}(1,1)_{\mathrm{M}_1}$,

$\mathrm{AR}(2)_{\mathrm{M}_1}$, and $\mathrm{MA}(1)_{\mathrm{M}_2}$ for new case 1.



Figure 16: Combined plot for Shannon entropy with associated time series $n = 5000$.



Figure 17: Combined plot for Shannon entropy with associated time series $n = 10000$.

The heat maps were generated to visualize the differences between models, as shown in Figure 18. The purpose of these plots is to highlight the variation and clustering patterns in the data, providing an intuitive comparison of model behaviors across the entropy–complexity plane.



Figure 18: Heat map for Shannon entropy to discriminate model difference $n = 5000$ and $n = 10000$.

New Case 2 is based on results obtained when considering all negative coefficients in the ARMA models, as described in Table 3. The figures 19 and 20 display outcomes for sample sizes of 5000 and 10000, respectively. In these results, we highlight two extreme cases and the median point for negative-coefficient time series, including $\mathrm{ARMA}(1,1)_{\mathrm{M}_3}$, $\mathrm{AR}(2)_{\mathrm{M}_4}$, and $\mathrm{MA}(1)_{\mathrm{M}_4}$ for New Case 2.



Figure 19: Combined plot for Shannon entropy with associated time series $n = 5000$.



Figure 20: Combined plot for Shannon entropy with associated time series $n = 10000$.

Heat maps related to this new case 2 are shown in Figure 21.



Figure 21: Heat map for Shannon entropy to discriminate model difference $n = 5000$ and $n = 10000$.

New Case 3 is based on results obtained when considering all positive and negative coefficients in the ARMA models, as described in Table 4. The figures 22 and 23 display outcomes for sample sizes of 5000 and 10000, respectively. In these results, we highlight two extreme cases and the median point for mixed-sign time series, including $\mathrm{ARMA}(2,2)_{\mathrm{M}_2}$, $\mathrm{AR}(2)_{\mathrm{M}_3}$, and $\mathrm{MA}(2)_{\mathrm{M}_3}$ for New Case 3.



Figure 22: Combined plot for Shannon entropy with associated time series $n = 5000$.



Figure 23: Combined plot for Shannon entropy with associated time series $n = 10000$.

Heat maps related to this work are shown in Figure 24.



Figure 24: Heat map for Shannon entropy to discriminate model difference $n = 5000$ and $n = 10000$.

Moreover, all cases were combined into a single set including all types of coefficients. The resulting combined plots are shown in Figures 25, 26, 27 and 28.



Figure 25: Combined plot for Shannon entropy.



Figure 26: Combined plot for Renyi entropy.



Figure 27: Combined plot for Tsallis entropy.



Figure 28: Combined plot for Fisher entropy.

Finally, the combined time series plots for all cases, encompassing all coefficient types, are presented as single panels for sample size $n = 10000$ in Figure 29.



Figure 29: Combined plot for Shannon entropy with associated time series $n = 10000$.

Discussion and Conclusion

This study shows the effectiveness of ordinal pattern analysis combined with entropy and complexity measures in discriminating between AR, MA, and ARMA time series models. By employing multiple entropy measures including Shannon, Rényi, Tsallis, and Fisher information, and using central (H^*, C^*) points, we capture model dynamics across different parameter regimes. The separate investigation of three cases, involving positive, negative, and mixed-sign coefficients, reveals robust model discrimination capabilities of the proposed ordinal patterns feature-based approach, with clear clustering in the entropy–complexity plane. Overlap points in specific models highlight intrinsic similarities in their dynamics. This framework offers a promising tool for time series model characterization and can be extended to more complex or real-world datasets in future research.

References

[1] Boaretto, B., Budzinski, R., Rossi, K., Prado, T., Lopes, S., and Masoller, C. Discriminating chaotic and stochastic time series using permutation entropy and artificial neural networks. *Scientific Reports 11*, 1 (2021). cited By 22.

[2] Chagas, E., Queiroz-Oliveira, M., Rosso, O., Ramos, H., Freitas, C., and Frery, A. White noise test from ordinal patterns in the entropy–complexity plane. *International Statistical Review 90*, 2 (2022), 374–396. cited By 6.

[3] Rey, A. A., Frery, A. C., Gambini, J., and Lucini, M. M. Asymptotic distribution of entropies and fisher information measure of ordinal patterns with applications. *Chaos, Solitons & Fractals 188* (2024), 115481.

[4] Rey, A. A., Frery, A. C., Lucini, M. M., Gambini, J., Chagas, E. T. C., and Ramos, H. S. Asymptotic distribution of certain types of entropy under the multinomial law. *Entropy 25*, 5 (2023).