

LLM 8-Days Report

Frontier modellar qayda
gilardan foydalanadi?

- Normalization
- Activations
- Position
- Hyperparameters
- Vocabulary (VOCAB)
- Regularization
- Stability
- Inference
- Long context

AutoTokenizer ichiga LLM ichiga
berib o'tamiz
ni (gpt2)

("gwen3.5-0.5")

("Llama3-2")

Bu yerda warning berilishi
mumkin yo'ni Hugging face

dan menggunakan tokenizer
untuk menghasilkan token

Demikian juga dengan cara
token generate dengan cara
sama token b-n menggunakan

Llama - 3.1 - 8B

atau juga 3.1 - 70B

8B era 7 miliar parameter b-n
jumlahnya 7 miliar parameter

Token Size

tokens = 2.480.000.000

bytes_size = tokens * 4

kb = bytes_size / 1024

mb = kb / 1024

gb = mb / 1024

Demikian Dataset size

8.24 GB cukup akan

Vectors Embeddings Practice

Human Text



Tokenizer



Token IDs



Embeddings



Positional Embeddings



Attention



FFN



Output

I love AI
[128, 320, 1256]



Embedding

Yammonarey LLM lar
positional Embeddingdan
foydalanadi

Attention - bu tokenlar bor
bori bilan gaplashib ular
orasidagi boglanishni topish

Transformerdagi Attention
layer Integerlardan foydalan
olmaydi barga vector kirit.

Embeddingni 2 turi bor

wte - word token embedding
(converts token IDs into vectors)

wpe - word position embedding
(gives the model info. -n about
each token's position in the
sequence)

ding.

AutoModel - bu birga Hugging
face ichidagi LLM larni
yuklab olish imkonini beradi

from transformers import AutoModel

print(embeddings[0][0][1:768])

↳ butragami

↳ tokenlar pozitsiya (1 to 768)

Bo'y yuklab olgan LLM

C disk => Users => Rasulbek (ya'ni
user nomi) => .cache => huggingface
=> hub => shu yerdan turaadi

=> hub => model-gpt2 => snapshots =>
=> 607a30d-8 (raganlangan popkai) shuni
ichida fayllar turaadi