Measuring the Measurer: A Scale-Grounded Faithfulness Protocol for Quantitative Vision–Language Metrology

Anonymous submission

Abstract

Recent benchmarks ask whether vision–language models (VLMs) can report physical quantities such as velocity and size from video, and score the predicted *number* against ground truth. We argue this is insufficient: a model can report a plausible number for the wrong reason, anchoring to a learned prior rather than to the visual evidence, and current scoring cannot tell the two apart. We introduce **Scale-Grounded Faithfulness (SGF)**, a label-free evaluation protocol that tests whether a VLM's reported quantity responds to the in-frame scale reference as a faithful measurer's would, rather than staying anchored to a learned prior. SGF is a behavioral test (it probes input-output sensitivity, not internal mechanism). Recent work establishes faithfulness as an axis of VLM capability distinct from accuracy, measured by input perturbation; but those perturbations (counterfactual traces, region edits, cue injection) have no ground-truth correct response and are scored by human raters or model judges. SGF closes this gap in the metrology setting. It applies a *physically calibrated* perturbation, relabeling the in-frame scale so the true millimeters-per-pixel calibration changes by a known factor α while the object's pixel trajectory is untouched, for which a faithful measurer's reported quantity has an *analytically known* target response: it must change by α^d, where d is the quantity's dimension in length (d=1 for velocity and diameter). Because the target response is known in closed form, the faithfulness signal requires no annotation and no judge model, which to our knowledge makes it the first exactly-specified faithfulness target for a VLM probe. SGF reports three quantities: a Scale-Faithfulness Score, a calibration-grounding indicator that separates a correct number from a correctly-read scale, and a hidden-prior hallucination rate using an off-frame, unobservable quantity as a trap. We instantiate the protocol on a controlled droplet-impact dataset with a classical computer-vision oracle and release the protocol, metric code, and a recipe for extending it to any video with an in-frame scale reference. A positive-control experiment confirms the metric and oracle correctly separate a known-faithful measurer from a known prior-driven guesser (SFS $\to 1$ vs. SFS $\to 0.03$, p=7×10^{-15}). Evaluating two independent VLM families (Qwen2.5-VL-7B-Instruct, open-weight; and Gemini-2.5-Flash-Lite, via API) on the instantiated dataset, we find *both* models essentially non-responsive to the scale perturbation (SFS ≈ 0.04–0.19 across models and α) and *both* models' tolerance-band accuracy saturated at exactly zero ($0/36$ items each, $0/72$ pooled), which means the accuracy-vs-faithfulness decoupling question this protocol is designed to answer cannot be meaningfully posed for either model: there is no accuracy variance left to correlate against faithfulness. This is a stronger finding than a single-model result would be: it is not one model's idiosyncrasy but a property that survives across two independently trained model families on this task and this tolerance. We report this as an honest, informative null result rather than force a conclusion the data do not support, and argue it illustrates exactly the failure mode SGF is built to expose: a model can be too ungrounded to even be usefully wrong in a scale-consistent way. The two models diverge sharply at a looser 30% tolerance (2.8% vs. 33.3%), which looked like a lead toward recovering the originally hypothesized decoupled pattern at a different tolerance; sweeping the tolerance from 10% to 100% on the same data shows this does not hold – the accuracy-faithfulness correlation is negative everywhere it is computable, never resembling the hypothesized pattern, and the accuracy gain driving the 30% divergence is itself a session-specific confound, not broader measurement ability. We release the full protocol, perturbation renderer, and evaluation code so the decoupling question can be properly tested on further models.

1 Introduction

A growing line of benchmarks evaluates whether vision–language models (VLMs) can extract *quantitative* physical information from video (the velocity of a moving object, its size, its acceleration) and scores the predicted number against a numerical ground truth [6, 11, 12]. This is a meaningful advance over qualitative visual-question-answering [1, 3]. But scoring the number alone conflates two very different behaviors. A model that genuinely *measures* (locating the object, reading the in-frame scale, converting pixels to physical units) and a model that emits a *plausible prior* (objects in tabletop videos tend to move at order $1\,\mathrm{m/s}$) can receive identical scores whenever the prior happens to land in the tolerance band. The benchmark cannot distinguish a measurer from a guesser.

This distinction is not academic. The promise of VLMs as scientific instruments rests on whether their numbers are *traceable* to visual evidence. An instrument whose reported physical reading does not change when the physical scale of the scene changes is not measuring. We therefore ask a question existing quantitative benchmarks do not: *when a VLM reports a physical quantity from video, does the number respond to the in-frame scale reference as a measurer's would, or does it stay anchored to a learned prior, and does the model know which?*

We answer it with a perturbation that has a property no prior faithfulness probe has exploited: a *known correct response*. Recent work has established that faithfulness is a measurable axis of VLM capability distinct from, and not predicted by, accuracy or scale: step-level visual grounding faithfulness predicts out-of-distribution generalization independently of in-distribution accuracy [15], and cross-modal faithfulness rankings are unstable across perturbation type [4]. We build directly on this consensus. Where it differs is the perturbation: existing probes for language and vision–language models perturb captions, counterfactual reasoning traces, textual cues, or salient image regions and then judge whether the model's *explanation* changes, using human raters or an LLM judge [8, 9, 14–17]. Those perturbations have no ground-truth correct response, so the resulting faithfulness signal is subjective and expensive to obtain. In quantitative metrology the situation is better: if we relabel the in-frame scale so the true calibration changes by a known factor α (millimeters per pixel) while the object's pixel trajectory is untouched, a faithful measurer's reported velocity *must* change by α, because its pixel measurement is unchanged and only the pixel-to-physical conversion has moved. The target response is analytic, so the faithfulness signal needs no annotation and no judge model. This is the core of our protocol and the reason it fits resource-constrained settings.




Figure 1: **The scale-faithfulness probe.** We present the same event with the in-frame scale relabeled so the true calibration changes from c to αc (the object's pixel motion is unchanged). A model that truly measures must report a quantity that scales by α^d (d = the quantity's dimension in length; top, faithful); a model anchored to a learned prior reports nearly the same number (bottom, prior-driven). The target response is known analytically, so no human annotation is needed to score faithfulness.

Contributions.

1. **A reframing.** We show that scoring the predicted number, as current quantitative-physics VLM benchmarks do, cannot separate measurement from prior-driven guessing, and we make this separation the evaluation target.

2. **Scale-Grounded Faithfulness (SGF), a label-free protocol.** A physically calibrated scale perturbation with an analytically known target response yields a Scale-Faithfulness Score that needs no annotation; a calibration-grounding indicator separates a correct number from a correctly-read scale; and a hidden-prior hallucination probe uses an off-frame, unobservable quantity as a trap. Unlike prior perturbation-based faithfulness probes, whose correct response is unknown and scored by raters or judges, ours has a target response known in closed form (Proposition 1); to our knowledge it is the first exactly-specified faithfulness target for a VLM probe, a claim the authors must re-confirm against the literature before submission.

3. **A released artifact and a portable recipe.** We instantiate SGF on a controlled droplet-impact dataset with a classical-CV oracle, release the metric code and protocol, and give the recipe to extend it to any video containing an in-frame scale reference.

4. **A validated instantiation and an honest two-model finding.** A positive-control experiment (E1, Section 5) confirms the metric and oracle separate a known-faithful measurer from a known prior-driven guesser cleanly. Evaluating two independent VLM families (one open-weight, one via API) on the instantiated dataset, we find accuracy saturated at exactly zero for *both*, independently, and faithfulness uniformly low for both, which blocks rather than answers the decoupling question SGF is designed to probe – we report this null result explicitly (Section 6) rather than reframe around a weaker but positive-sounding claim, and argue the failure mode itself (two independently trained models both too ungrounded to be usefully wrong) is worth documenting precisely because it is not one model's quirk.

We confirm novelty by deep, date-aware search of the closest current work (Section 2 and Table 1); authors must re-confirm before submission.

2 Related Work and Positioning

Quantitative physical-reasoning benchmarks. QuantiPhy [12] scores VLM estimates of size, velocity, and acceleration against numerical ground truth, supplying one physical property as a prior. IRIS [6] recovers continuous physical parameters from real monocular video with ground-truth supervision. PhysicsMind [11] evaluates law-consistent quantitative VQA across real and simulated mechanics. All three score the *output number*. None tests whether that number is anchored to the in-frame scale, and none applies a perturbation with a known correct response. Our delta is the evaluation target (anchoring, not magnitude) and the verifiability of the faithfulness signal.

Faithfulness via perturbation. For language and vision–language models, faithfulness is probed by perturbing inputs and observing whether the stated reasoning changes [8, 9, 14, 16, 17]. The closest conceptual precedent is step-level visual grounding faithfulness [15], which establishes faithfulness as an axis orthogonal to accuracy via counterfactual trace perturbations on long-horizon agent tasks, and cross-modal synergy [4], which shows faithfulness rankings are unstable across perturbation type. We adopt their central premise (faithfulness is distinct from accuracy and is probed by perturbation) and change one thing: our perturbation is a physically calibrated quantity with an *analytic* correct response, whereas counterfactual traces, region edits, and cue injection have none and are scored by grounding-verification heuristics, human raters, or LLM judges. The setting also differs: those probes target long-horizon agentic reasoning; we target single-shot quantitative measurement. Our delta is the closed-form verifiability of the faithfulness signal in the metrology setting.

Measurement-grounded representation learning (a distinct line). PRISM-VL [18] uses the term "measurement-grounded" for a different idea: post-ISP RGB rendering can discard raw sensor evidence, so they feed RAW-derived sensor inputs and *train* a model to ground better. That is a representation-and-training contribution about the *input pixel pipeline* (sensor domain versus rendered RGB). SGF is an *evaluation* protocol about whether a frozen model reads the *in-frame scale reference*; it trains nothing and concerns calibration, not the sensor domain. We flag the shared term explicitly to avoid confusion: the two are orthogonal and complementary.

Generative-video physics evaluation. Morpheus [10] and related work score the physical plausibility of *generated* video. We evaluate the *measurement* behavior of VLMs on *real* video, a different task.

Method	Quantitative			Faithful.	
	Real video	Numeric GT	Scale in frame	Known-resp. perturb.	Label free
Quantitative physical-reasoning benchmarks					
QuantiPhy [12]	●	●	○	○	●
IRIS [6]	●	●	○	○	●
PhysicsMind [11]	●	●	○	○	◐
Faithfulness-via-perturbation probes					
Med-VLM faith. [9]	●	○	○	○	○
RL-VLM robust. [14]	●	○	○	○†	●
Step-ground. [15]	●	○	○	○†	◐
PRISM-VL [18]	●	○	○	○	○
SGF (ours)	●	●	●	●	●

Table 1: **SGF is the only method spanning both families.** Quantitative benchmarks score the output number but never test scale grounding; faithfulness probes test grounding but lack a numeric, analytically verifiable signal. "Known-resp. perturbation" = the perturbation has an analytically known correct response, enabling annotation-free faithfulness scoring. ● yes, ◐ partial, ○ no. † perturbs inputs but without a closed-form correct response (scored by raters or judges). Every row verified against the cited source by search; authors must re-confirm at submission. `[UNVERIFIED: confirm no closer scale-grounding metrology paper appears before submission]`

3 The Scale-Grounded Faithfulness Protocol

3.1 Setup and notation

A VLM is shown a video clip of a physical event together with an in-frame scale reference (a ruler) of known true calibration $c^\star$ in millimeters per pixel. The model is asked to report a physical quantity q (e.g. impact velocity). Let $\hat{q}$ denote the model's reported value and $c^\star$ the oracle calibration obtained from the ruler. A classical computer-vision pipeline (blob detection plus optical flow [5]) provides the ground-truth quantity $q^\star$ from the same video; this is the oracle, not a human label.

3.2 Accuracy quantities

We report tolerance-band accuracy $\mathrm{Acc@}\tau = \Pr[\,|\hat{q}-q^\star|/|q^\star| \le \tau\,]$ and the log-accuracy ratio $|\log_{10}(\hat{q}/q^\star)|$, which is robust to order-of-magnitude errors. These mirror existing benchmarks and are *not* our contribution; they are the baseline that SGF augments.

3.3 The scale-faithfulness score

The perturbation must change the *calibration the model must read* while leaving the event's pixel-space dynamics intact, so that the only thing a faithful measurer must update is the pixel-to-physical conversion. We achieve this by *relabeling the in-frame scale*: we present a scale reference whose asserted physical length differs by a known factor, so the true millimeters-per-pixel calibration becomes αc for a known $\alpha \neq 1$, while the object's pixel trajectory is untouched. Operationally this can be done by swapping the displayed ruler for one of a different known length, or by stating a different physical length for the same graduations; the moving content of the frame is unchanged. Under this perturbation a faithful measurer, who reads the scale and converts, must change its reported physical quantity by a known factor, whereas a model that ignores the scale and emits a learned prior does not. Let $\hat{q}$ and $\hat{q}'$ be the model's reports under calibration c and αc.

Why not simply resample the whole frame. Uniformly resampling the frame (rescaling object and ruler pixels together while keeping the ruler's asserted length fixed) does *not* probe grounding: a faithful measurer reads a proportionally finer calibration and recovers the *same* physical quantity, so the ideal response is 1 and the test is inert. The signal comes from changing what the scale *asserts*, not the image resolution.

Assumption 1 (Dimensional homogeneity)**.** *The reported quantity q has a fixed dimension in length: q scales as the d-th power of a physical length (d=1 for velocity and diameter at fixed frame rate, d=2 for area). The model's reported value is obtained by combining a pixel-space measurement with the calibration it reads and is dimensionally consistent with q.*

Proposition 1 (Ideal response under calibration relabeling)**.** *Relabel the in-frame scale so the true calibration changes from c to αc (millimeters per pixel), leaving the object's pixel trajectory unchanged. A faithful measurer recovers a physical length as $L = (\textit{pixels}) \times c$. Since the pixel measurement is unchanged and the calibration is now αc, the recovered length becomes $L' = (\textit{pixels}) \times \alpha c = \alpha L$. Under Assumption 1, where the quantity scales as the d-th power of a length, a faithful measurer's reported quantity satisfies $\hat{q}'/\hat{q} = \alpha^d$.*

Proof. By Assumption 1 write $\hat{q} = \kappa\,(\text{pixel measurement})\,c^d$ for the dimensionless constant κ fixed by the quantity's definition. The pixel measurement is unchanged by relabeling the scale, and the calibration maps $c \mapsto \alpha c$. Hence $\hat{q}' = \kappa\,(\text{pixel measurement})\,(\alpha c)^d = \alpha^d \hat{q}$. □

We fix d per quantity (Assumption 1) and use α^d as the target ratio. The frame rate is held fixed and the time axis is not perturbed, so SGF tests spatial-calibration grounding, not temporal grounding; the latter is out of scope for this version and is noted as a limitation.

Definition 1 (Scale-Faithfulness Score)**.** *For a target ratio α^d and realized ratio $r = \hat{q}'/\hat{q}$,*

$$\mathrm{SFS} = \mathrm{clip}_{[0,1]}\left(1 - \frac{\left|\log r - d\log\alpha\right|}{\left|d\log\alpha\right|}\right),$$

averaged over items. $\mathrm{SFS} = 1$ *iff the response is exactly ideal;* $\mathrm{SFS} = 0$ *when the report does not move with the scale (*$r = 1$*). The log form makes the score symmetric under* $\alpha \leftrightarrow 1/\alpha$*.*

3.4 Calibration grounding

A model can land a correct number with a wrong calibration. We elicit the model's read of the scale, $\hat{c}$, and report the calibration-grounding indicator $\mathrm{CG} = \mathrm{Acc@}\tau(\hat{c}, c^\star)$, which is independent of $\hat{q}$. Low CG with high $\mathrm{Acc@}\tau$ on $\hat{q}$ is the signature of a prior-driven guesser.


3.5 Hidden-prior hallucination

Our dataset has a quantity that is *real but off-frame*: the droplet is released from a fixed height (6.6 cm) that the high-speed camera's field of view does not capture. We ask the model for this height. A faithful model should decline; a prior-driven model asserts a number. The hidden-prior hallucination rate HPH is the fraction of items where the model asserts an off-frame numeric prior instead of declining. This isolates prior injection directly.

3.6 Why droplets, and how to generalize

Droplet impact gives a clean, repeatable event with sub-millimeter features, a natural in-frame ruler, and a well-understood classical-CV oracle for velocity and spreading diameter [7, 13]. The *protocol*, however, depends only on (i) an in-frame scale reference and (ii) a CV oracle for the target quantity. We provide the recipe so any lab with a ruler in frame can instantiate SGF on its own phenomenon; droplets are the first testbed, not the scope of the contribution.

4 Dataset and Oracle



Dataset: 8 conditions (SDS, TX-100, cocoglycinate $\times$ above/below CMC; water; CA-only) $\times \geq 3$ replicates, >2000 fps, in-frame ruler.

Figure 2: **SGF separates measuring from guessing.** A clip of a $4\,\mu$L droplet impact with an in-frame scale (left) is shown with the scale relabeled so the true calibration changes from c to αc while the object's pixel motion is unchanged. *Middle:* a faithful measurer reads the ruler and converts, so its report must scale (blue); an unfaithful model either ignores the ruler and emits a learned prior (red, flat response) or invents an off-frame quantity it cannot see (the 6.6 cm drop height; the hidden-prior trap). *Right:* the reported ratio $\hat{q}'/\hat{q}$ versus α distinguishes the regimes, a faithful α^d slope (d=1 for velocity) versus a flat ≈ 1; SGF scores the gap between them with no annotation. A classical-CV oracle supplies ground truth. CG = cocoglycinate, CA = cellulose acetate.

The raw recording collection comprises high-speed video (2996 fps true capture rate, confirmed against the container metadata's incorrect 60 fps tag) of $4\,\mu$L droplets impacting a superhydrophobic surface across nominally eight chemistry conditions (cellulose-acetate nanoparticle suspensions in three surfactants – SDS, TX-100, cocoglycinate – above and below the critical micelle concentration, plus a water control and a nanoparticle-only control), recorded across five capture sessions. **We report, rather than gloss over, that only three of the five sessions are usable.** Two sessions were excluded after verification: one whose calibration clip is corrupted (unreadable moov atom, confirmed by both OpenCV and ffmpeg, orphaning 8 droplet clips) and one with no calibration clip at all and undocumented provenance (its notes file is a byte-identical duplicate of another session's, describing the wrong dates). Of the three valid sessions, two use a printed-ruler target (1 mm graduation) and one uses a pin-comb target (1/16-inch pitch); calibration values were measured directly per session (104.52, 66.19, and 42.99 px/mm respectively), not assumed from a shared constant. The CV oracle (background-subtraction blob tracking plus a free-fall-plateau velocity fit, described below) yielded a valid pre-impact velocity for 48 of 62 attempted clips (77%; the remainder failed at the motion-detection or track-linking stage, e.g. droplets already too close to impact when they entered frame in the pin-comb session). Of those 48, 34 have a verified deceleration signature at impact and 14 are lower-confidence plain-average velocities from short tracks. Every reported oracle value was cross-checked against free-fall physics ($v = \sqrt{2gh}$) using the (session-specific, independently confirmed) drop height, not merely accepted at face value.

Scope and honesty about scale. This is a single-phenomenon, modest-size dataset, made smaller still by the session-exclusion above, and our model evaluation (Section 5) further restricts to a 12-clip subset drawn from the two ruler-target sessions (the pin-comb session's oracle ground truth is predominantly low-confidence, so we exclude it from model evaluation though it remains usable for future work). We therefore position the dataset as the *instantiation* and the protocol as the artifact: the dataset's value is that it is fully controlled and carries an exact oracle and an in-frame scale, verified end-to-end rather than assumed; the protocol's value is portability to larger and more diverse datasets than this one.

5 Experimental Protocol

We evaluate two independent VLM families under identical prompts across three paraphrased seeds: Qwen2.5-VL-7B-Instruct [2], open-weight, run locally; and Gemini-2.5-Flash-Lite, accessed via API (OpenRouter), added specifically to test whether the single-model gap in an earlier draft of this submission changed the E2/E4 findings. **E2 and E4 are run on both models; E1, E3, and E5 use Qwen2.5-VL-7B-Instruct only** (E1 uses simulated re-measurers rather than a model at all; E3 and E5 were run before API access became available and are not repeated here since neither's conclusion depends on a specific model's accuracy level – Section 8 still flags this as an opportunity for future extension). We report mean and 95% bootstrap CIs over items and prompt seeds throughout.

E1 (positive control, run first). Validate that the CV oracle and the SGF metric separate a *known* faithful pipeline from a *known* prior-driven pipeline, using 48 real oracle velocity measurements (not synthetic data)

fed through two hypothetical re-measurers: (a) the oracle value times α, simulating a perfectly faithful measurer; (b) a fixed $\sim 1\,\mathrm{m/s}$ emitter with 5% noise, simulating a prior-driven guesser that ignores the scale. Confirmed robust across $\alpha \in \{0.5, 2\}$ and 5 random seeds for (b).

E2 (main: scale faithfulness). For each model and $\alpha \in \{0.5, 2\}$, compute SFS, Acc@10%, CG on a 12-clip subset (6 clips each from the two ruler-target sessions) $\times$ 3 conditions (unperturbed, α=0.5, α=2) $\times$ 3 prompt seeds = 108 model calls per model, 216 total.

E3 (hidden-prior trap). Measure HPH on the off-frame drop-height question. **Redesigned mid-study after a validity failure**: an initial version asked only the hidden-prior question and found HPH=0 on all 12 items, which looked like a strong faithfulness result until we tested the exact same prompt with *no video attached at all* and got the identical decline – the model's "I don't know" was a content-independent default, not a video-grounded judgment, so the original HPH=0 was uninterpretable. We fixed this by pairing the hidden-prior question with a control question in the same call ("does the droplet impact the surface?", trivially true and visible in every clip); a decline on the hidden-prior question only counts if the model answers the control correctly, which establishes it engaged with the video at all for that item.

E4 (decoupling analysis). Correlate per-item Acc@10% with per-item SFS across the 36 (clip, seed) items from E2, per model and pooled across both (72 items). The runbook's hypothesized headline was that accuracy and faithfulness are decoupled; as detailed in Section 6, this question turned out not to be answerable as specified for *either* model, which we report rather than substitute a different, more favorable-looking analysis without flagging it.

E5 (robustness). Vary $\alpha \in \{0.25, 0.5, 2, 4\}$, ruler orientation, and prompt phrasing on 2 representative clips (one per ruler-target session), holding the other axes fixed, to check whether the effect in E2 is a single-condition artifact. Ruler orientation required new infrastructure: both valid ruler-target sessions physically photograph a *vertical* ruler rotated in-frame, so we *synthesize* a horizontal-orientation condition by rotating the same real ruler footage $90°$, rather than treating orientation as a naturally-occurring contrast in this dataset.

6 Results and Discussion

E1: metric and oracle validated. The simulated faithful re-measurer scored SFS $= 1.000$ (95% CI $[1.000, 1.000]$); the fixed-prior emitter scored SFS $= 0.032$ (95% CI $[0.018, 0.048]$). A paired sign test across all 48 items found the faithful re-measurer's per-item SFS higher in 48/48 cases ($p = 7.1 \times 10^{-15}$). **E1 passes cleanly**: the metric and oracle correctly separate the two archetypes by construction, clearing the blocking gate before any model result is trusted.

Archetype	SFS	95% CI	n
Faithful re-measurer (simulated)	1.000	[1.000, 1.000]	48
Fixed-prior emitter (simulated)	0.032	[0.018, 0.048]	48

Table 2: **E1 positive control.** Real oracle velocities fed through two hypothetical re-measurement policies. The metric separates them exactly as designed.

E2: both models are essentially non-responsive, in different ways. Qwen2.5-VL-7B-Instruct scored $\mathrm{Acc@10\%} = 0.000$ (95% CI $[0.000, 0.000]$, n=36), $\mathrm{CG} = 0.222$ (95% CI $[0.148, 0.306]$, n=108), and $\mathrm{SFS} = 0.131$ (95% CI $[0.043, 0.238]$) at α=0.5 and $\mathrm{SFS} = 0.107$ (95% CI $[0.053, 0.168]$) at α=2. Gemini-2.5-Flash-Lite scored $\mathrm{Acc@10\%} = 0.000$ as well (identically zero, n=36), $\mathrm{CG} = 0.380$ (better than Qwen but still low), and $\mathrm{SFS} = 0.071$ at α=0.5 and $\mathrm{SFS} = 0.041$ at α=2 (both *lower* than Qwen's). We investigated whether either result was a pipeline bug before trusting it: Qwen's velocity and calibration answers vary only slightly across genuinely different droplet clips within a condition group, drawing from a small set of near-constant values (e.g. 0.5, 1.5, $3.5\,\mathrm{m/s}$) that correlate more with which prompt seed was used than with what the clip shows. Gemini shows a related but distinct failure: on one session it reports the identical calibration ($1.0\,\mathrm{mm}$ per tick) across all three perturbation conditions, and on the other it never once reports the correct relabeled value (2.0) even when we confirmed by direct frame inspection that the on-screen label legibly reads the perturbed number – both models default to a physically plausible prior rather than reading the digits actually in front of them, just with different, model-specific priors. We confirmed both models *can* perceive and describe the two videos correctly when asked to do so directly; neither reliably performs the compositional measurement task (read the scale, track the object, convert) that SGF and the underlying benchmarks it critiques both require.

Metric	**Qwen2.5-VL-7B**	**Gemini-2.5-Flash-Lite**	n
Acc@10%	0.000 [0.000, 0.000]	0.000 [0.000, 0.000]	36
Acc@30% (secondary)	0.028	0.333	36
CG (calibration grounding)	0.222 [0.148, 0.306]	0.380	108
SFS (α=0.5)	0.131 [0.043, 0.238]	0.071 [0.024, 0.128]	36
SFS (α=2)	0.107 [0.053, 0.168]	0.041 [0.015, 0.078]	36

Table 3: **E2 main table, both models.** Low accuracy, low calibration grounding, low faithfulness for both: neither model reliably performs the measurement task, in either sense. Acc@30% (not part of the protocol's primary metric set) is included because it is the one row where the models diverge sharply – see the E4 discussion below.

E3: a genuine but partial faithfulness signal, and a session-specific confound we root-caused rather than papered over. After the control-question redesign, $\mathrm{HPH} = 0$ on the 7 of 12 items where the model answered the control question correctly (i.e. demonstrably engaged with that item's video); the other 5 items (4 from one session, 1 from the other) failed the control and are excluded as uninterpretable rather than counted toward HPH. We investigated the session-level split in engagement rather than accept it as noise. It is **not** explained by a multi-droplet confound: hand-labeling all 12 clips found only 1 genuinely contains a second droplet. It is **not** explained by our video-extraction timing either: we built and validated a per-clip motion-settling detector to replace a fixed extraction margin, re-extracted all 12 clips with genuinely longer, more-settled windows, and reran E3 – the control-answer pattern was unchanged, clip for clip. Direct frame-by-frame comparison then showed the actual cause: the failing session's camera framing compresses the impact surface into a thin, heavily vignette-darkened strip at the extreme bottom of frame, versus the passing session's surface sitting in a well-lit middle region.

Partially recoverable by post-processing. A whole-frame contrast fix (linear stretch, CLAHE) barely helped – the entire frame has low dynamic range (peak pixel value $\approx 90/255$), not just the surface strip, so there is no unused headroom for a global remap to exploit. Cropping tightly to the impact region (located via the same track-linking already used for velocity measurement) and contrast-stretching only that local crop, per frame, made the surface boundary and impact shape clearly legible by eye on all 5 failing clips. Rerunning the control question on the 5 enhanced clips recovered **1 of 5** (HPH coverage improves from 7/12 to 8/12). One of the remaining 4 is the confirmed multi-droplet clip, where the model's wrong answer is plausibly

about *which* droplet is being asked about, not visibility, so contrast enhancement was never expected to fix it. The other 3 still fail despite visibly clear enhanced crops; we did not chase this further; the necessarily small crop size may be downsampled by the model's default video preprocessing in a way that undoes the local contrast gain, but we have not confirmed this and report it as an open question rather than a diagnosed cause. This is a property of that session's camera setup, only partially addressable after the fact, not a fixable pipeline defect, and we report the remaining 4/12 gap as a dataset limitation rather than retry indefinitely.

E4: adding a second, independent model family does not resolve the decoupling question – it strengthens the null result. $\mathrm{Acc@10\%}$ is exactly 0 for Qwen (36/36 items) *and* for Gemini (36/36 items) *and* for the 72-item pool of both – the per-item accuracy indicator the runbook specifies has zero variance in every case; correlating a score against a constant is undefined, not evidence of zero correlation. This is a materially stronger finding than the single-model version in an earlier draft of this submission: it is not one model's idiosyncrasy that happened to saturate, but a property that held independently across two differently-trained model families at this tolerance. Substituting continuous relative error (negated, so higher means more accurate) as the closest computable stand-in gives Pearson $r = -0.481$ (95% CI $[-0.708, -0.029]$, excluding zero) for Qwen alone, $r = -0.218$ (95% CI $[-0.671, 0.063]$, *including* zero – not significant on its own) for Gemini alone, and $r = -0.460$ (95% CI $[-0.664, -0.094]$, excluding zero) pooled. We do not report the pooled correlation as a clean coupling finding: cross-checking against the E2 near-constant-response pattern shows both models' base-condition outputs are driven substantially by which prompt seed or which physically-plausible prior was invoked rather than by clip content, so both the "accuracy" and the "faithfulness" axes being correlated here are downstream of the same non-responsiveness in each model, not independent measurements of two different capabilities. **We therefore report E4 as inconclusive at the** 10% **tolerance for both models tested, not as support for either the "decoupled" or the "coupled" framing**: a number-only benchmark cannot be shown to over-credit prior-driven guessing when neither model tested is accurate under any framing, on any item, at that tolerance. The positive-control result (E1) shows the machinery is capable of detecting real decoupling when it is present; testing whether it exists in a fielded model requires a model whose accuracy is not saturated at zero at the tolerance used.

We checked whether a looser tolerance recovers the hypothesized decoupled pattern; it does not. Table 3's secondary $\mathrm{Acc@30\%}$ row shows Gemini's accuracy rising sharply at a looser tolerance (0.333 vs. Qwen's 0.028), which looked like a plausible lead. We swept τ from 10% to 100% on the same, already-collected E2 responses (no new model calls). The correlation between $\mathrm{Acc@}\tau$ and SFS becomes computable once $\tau \geq$ 15–30% (enough items clear the bar for the indicator to have variance), but it is **negative at every tolerance where it is measurable** – for Gemini, $r = -0.415$ at τ=30% (95% CI $[-0.549, -0.293]$, excluding zero); pooled, r ranges from -0.10 to -0.25 across $\tau \in [15\%, 75\%]$. It never once resembles the originally hypothesized pattern (high accuracy co-occurring with low SFS, $r \approx 0$ or positive). Worse, Gemini's apparent accuracy gain at τ=30% is itself a confound of the same kind documented in E2: all 12 of its hits come from a single session, whose true velocities happen to sit close to Gemini's favorite near-constant output value, not from broader measurement ability. We report this explicitly rather than let the $\mathrm{Acc@30\%}$ row stand as an unexamined lead: loosening the tolerance does not rescue the decoupling analysis on these two models, and the honest conclusion is that decoupling remains untested, not weakly supported, at every tolerance we could compute.

E5: real robustness on two axes, and a third axis's apparent instability is itself an artifact worth naming. SFS is stable across ruler orientation (original 0.209 vs. rotated 0.162, range 0.046) and across the three prompt seeds (range 0.087) – genuine evidence the low SFS in E2 is not an artifact of one ruler orientation or one prompt phrasing. SFS *appears* unstable across α (range 0.331, spiking to 0.396 at α=4), but we traced this to the same fixed-value-palette behavior as E2/E4: at α=4 specifically, every item in the

sweep (both clips, both orientations, all three seeds) happened to report the identical (base, scaled) pair, a content-independent ratio that coincidentally sits near that α's ideal target and scores well by chance. We report this explicitly rather than let the highest number in the table stand uncontextualized.

Axis	**Level**	SFS (mean)	95% CI
Orientation	original	0.209	[0.093, 0.342]
	rotated	0.162	[0.064, 0.279]
Prompt seed	0	0.148	[0.026, 0.297]
	1	0.235	[0.087, 0.397]
	2	0.174	[0.050, 0.323]
α (see caveat)	0.25	0.143	[0.031, 0.276]
	0.5	0.065	[0.000, 0.194]
	2	0.138	[0.035, 0.242]
	4	0.396†	[0.198, 0.594]

Table 4: **E5 robustness sweep.** Orientation and prompt-seed axes show genuine, small spread. †The α=4 value is a coincidental artifact of a fixed output palette (see text), not a real alpha-dependent faithfulness effect.

Reconciling the introduction's headline claim. We hypothesized that accuracy and faithfulness would prove decoupled. The honest finding is narrower: we validated that SGF's machinery can detect decoupling when it exists (E1), and we demonstrate on *two independent model families* that a number-only benchmark's accuracy score can be completely uninformative about scale-grounding behavior (E2's $\mathrm{Acc@10\%}=0$ for both, alongside nonzero but low SFS for both) – but we cannot claim the accuracy-faithfulness *correlation* is decoupled, coupled, or anything else at this tolerance, because accuracy never varies enough to correlate against for either model (E4). That this holds across two differently trained, differently sized, differently served models (one open-weight and local, one closed and API-served) is stronger evidence than a single-model result could give that the finding is about the task and tolerance, not about one model's training idiosyncrasies. We consider this worth publishing rather than discarding: it identifies a real failure mode (models too ungrounded to be usefully wrong in a scale-consistent way defeat the decoupling test itself, not just the accuracy test) and it is exactly the kind of result the field needs more of if quantitative VLM benchmarks are to be trusted – a protocol, validated end to end, applied honestly, that reports a null result when that is what the data show. The $\mathrm{Acc@30\%}$ divergence between models (Table 3) looked like a concrete lead for recovering the originally hypothesized decoupled pattern at a looser tolerance; we checked this directly (the τ-sweep in the E4 discussion above) and it does not hold – the correlation is negative everywhere it is computable, and the apparent accuracy gain driving it is itself a session-specific confound. We report the negative result rather than leave the lead open, since a reader would otherwise reasonably ask whether we had checked.

7 Reproducibility

We release `sgf_metrics.py` (numpy-only) implementing SFS, CG, HPH, bootstrap CIs, and a paired sign test, with a synthetic smoke test that verifies the metric separates a faithful measurer, a partial measurer, and a prior-driven guesser. The perturbation renderer, prompts, and oracle scripts are released with the data, including both inference clients used (local Qwen2.5-VL via `transformers`, and Gemini-2.5-Flash-Lite via the OpenRouter API) so either model's results can be reproduced or a new model substituted with minimal changes. Pinned versions and exact model identifiers are listed in the runbook.

8 Limitations

Two models, both saturated – broader than one model but still not the full comparison the protocol is designed to support. An earlier draft of this submission reported results for a single open-weight VLM because our evaluation environment initially had no API access; we later obtained limited API budget and added Gemini-2.5-Flash-Lite to E2 and E4 specifically to close that gap. The result did not change the substantive limitation, it generalized it: both models independently saturate at $\mathrm{Acc@10\%}{=}0$, so E4's decoupling question remains unanswerable as specified, now for two model families rather than one. We did not have budget or access to extend this to a third, higher-capability frontier model (e.g. a top-tier proprietary model at full context and resolution), nor to systematically vary model *capability tier* rather than just family, which is what the protocol's central comparison actually calls for. This is still the most valuable next step for anyone extending this work, and the $\mathrm{Acc@30\%}$ divergence between our two models (Table 3) suggests it may be tractable without needing a third model at all – rerunning E4 at a coarser tolerance on the same two models is a natural first extension.

A model that fails saturates the very test designed to characterize it. Our headline finding is that both Qwen2.5-VL-7B-Instruct and Gemini-2.5-Flash-Lite are non-responsive enough that $\mathrm{Acc@10\%}{=}0$ leaves no accuracy variance to correlate against faithfulness, independently and pooled. This is itself informative – it shows number-only benchmarks can be completely silent about grounding even in the failure case, not only the success case – but it means SGF's decoupling analysis needs at least one model with non-degenerate accuracy *at the tolerance used* to be conclusive, which we did not have among the models we could afford to evaluate.

Dataset scale and session exclusion. The dataset is a single phenomenon, further narrowed from five recorded sessions to three after verification (Section 4), and model evaluation used a 12-clip subset of those three. Breadth across phenomena and larger item counts are future work; the protocol is designed to enable both without modification.

A session-specific engagement confound in E3, partially but not fully fixable. Five of twelve E3 items originally could not be scored because the model failed a trivially-easy control question on that session's footage; we traced this to a genuine camera-framing issue (low dynamic range concentrated in a thin surface strip, Section 6) rather than a model or pipeline defect. A targeted crop-and-contrast-enhance fix recovered 1 of the 5 (coverage is now 8 of 12, not 7); the remaining 4 include the one clip with a genuine second-droplet confound (unfixable by contrast, since the ambiguity is about which object is being asked about) and 3 that still fail despite visibly clear enhanced footage, for reasons we have not fully diagnosed. E3's $\mathrm{HPH}{=}0$ finding should be quoted as covering 8 of 12 items, not all 12.

Spatial, not temporal, calibration. SGF as presented perturbs the spatial scale only, not the time axis, so it tests spatial-calibration grounding, not temporal grounding; frame rate is held fixed throughout.

Oracle measurement error. The CV oracle has its own measurement error. We validated it against free-fall physics rather than treat it as exact ground truth (Section 4), and 14 of 48 valid oracle velocities are lower-confidence estimates from short tracks, flagged as such rather than silently pooled with the higher-confidence majority.

Calibration elicitation assumes engagement. Eliciting the model's calibration read $\hat{c}$ assumes the model attempts to report it; models that decline are scored as ungrounded ($\mathrm{CG}{=}0$ for that item), which may understate ability for a model that is appropriately cautious rather than genuinely unable to read the scale. We did not observe this pattern in our one evaluated model (declines were rare outside the E3 hidden-prior question, which is a different elicitation by design) but flag it as a scoring assumption for future models that may behave differently.

9 Ethics and Responsible Research

The data are physical measurements with no human subjects. The protocol is a diagnostic and is not intended to certify any model as a measurement instrument for safety-critical use. AI tools were used to draft text and code; the human authors are responsible for and have verified all content, including proofs and the method.

References

[1] Stanislaw Antol et al. Vqa: Visual question answering. *Proceedings of the IEEE International Conference on Computer Vision*, 2015. % VERIFY.

[2] Shuai Bai et al. Qwen2.5-vl technical report. *arXiv preprint arXiv:2502.13923*, 2025. % VERIFY.

[3] Chow and colleagues. Physbench: Benchmarking and enhancing vision-language models for physical world understanding, 2025. arXiv:2501.16411. % VERIFY author list.

[4] Cross-modal synergy authors. Measuring cross-modal synergy: A benchmark for vlm explainability, 2026. arXiv:2605.22168. % VERIFY author list.

[5] Berthold K.P. Horn and Brian G. Schunck. Determining optical flow. *Artificial Intelligence*, 17:185–203, 1981. % VERIFY.

[6] IRIS authors. Iris: A real-world benchmark for inverse recovery and identification of physical dynamic systems from monocular video, 2026. arXiv:2603.16432. % VERIFY author list.

[7] Christophe Josserand and Sigurdur T. Thoroddsen. Drop impact on a solid surface. *Annual Review of Fluid Mechanics*, 2016. % VERIFY.

[8] Tamera Lanham et al. Measuring faithfulness in chain-of-thought reasoning. *arXiv preprint arXiv:2307.13702*, 2023. % VERIFY.

[9] Medical VLM faithfulness authors. Evaluating reasoning faithfulness in medical vision-language models using multimodal perturbations, 2025. arXiv:2510.11196. % VERIFY author list.

[10] Morpheus authors. Morpheus: Benchmarking physical reasoning of video generative models with real physical experiments, 2025. arXiv:2504.02918. % VERIFY author list.

[11] PhysicsMind authors. Physicsmind: Sim and real mechanics benchmarking for physical reasoning and prediction in foundational vlms and world models, 2026. arXiv:2601.16007. % VERIFY author list.

[12] QuantiPhy authors. Quantiphy: A quantitative benchmark evaluating physical reasoning abilities of vision-language models, 2025. arXiv:2512.19526. % VERIFY author list.

[13] Romain Rioboo, Marco Marengo, and Cameron Tropea. Time evolution of liquid drop impact onto solid, dry surfaces. *Experiments in Fluids*, 2002. % VERIFY – drop impact spreading reference, confirm exact venue.

[14] RL-VLM robustness authors. On robustness and chain-of-thought consistency of rl-finetuned vlms, 2026. arXiv:2602.12506. % VERIFY author list.

[15] Step-grounding faithfulness authors. Step-level visual grounding faithfulness predicts out-of-distribution generalization in long-horizon vision-language models, 2026. arXiv:2603.06828. % VERIFY author list.

[16] Miles Turpin et al. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Advances in Neural Information Processing Systems*, 2023. % VERIFY.

[17] Visual thinking faithfulness authors. On the faithfulness of visual thinking: Measurement and enhancement, 2025. arXiv:2510.23482. % VERIFY author list.

[18] Kepeng Xu et al. Allegory of the cave: Measurement-grounded vision-language learning, 2026. arXiv:2605.11727. % VERIFY full author list.