


ITEM	PART #	DESCRIPTION	QTY	ITEM	PART #	DESCRIPTION	QTY
I	100-112	O-RING	2	15	530-50202	CUSHION CHECK PLUG	I
2	100-118	O RING	I	16	540-0500	BALL CHECK	1
3	100-135	O RING	I	17	657-50813	GLAND - ROD PACKING	ı
4	100-155	O RING	I	18	657-50843	ROD BEARING	I
5	100-258	O RING	2	19	660-10087	PISTON-MODIFIED "U"	I
6	133-0068-0050-050	BACK UP WASHER	2	20	660-20167	CAP - CLEVIS	I
7	133-0600-0537-062	WASHER B/U	2	21	660-51007	TUBE	1
8	150-0600-0537	U CUP	2	22	660-51047	TIE ROD	4
9	167-500-0350	ROD WIPER	I	23	660-52656	PISTON ROD - CUSHION REAR	1
10	197-0387-0350-037	ROD SEAL	I	24	660-55266	HEAD - STOCK	1
П	345-02528-0087	SOCKET HEAD SCREW	8	25	668-40073	CUSHION RETAINER	1
12	355-02520-031-130	SOCKET SET SCREW	2				
13	425-10014	HEX NUT	4				
14	530-50102	CUSHION ADJUST SCREW	1				


ALL (2) PLACE DIMENSIONS 060 ARE NOMINAL	0HHC01000CR0350S2-NI00PI5C0078-Y03YI7
--	---------------------------------------

POSITION DIAGRAM FOR PORTS, CUSHION ADJUSTING SCREWS, CUSHION CHECKS & AIR BLEEDS









SEAL KIT NOTES	COMMENTS:
SEAL KIT RECOMMENDED INCLUDES ITEMS #I THRU #10, & #18	I) DIMENSIONS MARKED '* 'INCLUDE 14" STROKE. 2) 3-1/2" DIA STYLE 2 ROD.
TORQUE NOTES	3) I" NPT PORTS POS I & 5. 4) CUSHION REAR, POS 7, 8.
ITEM #11 - 10 FT-LBS	5) U CUP PISTON
PROPERTY OF THE SHEFFER CORPORATION THIS DRAWING FURNISHED FOR ENGINEERING INFORMATION AND REFERENCE ONLY AND DOES NOT CONVEY ANY REPRODUCTION OR MEG RIGHTS	6) NO CLEVIS PIN 7) PAINT GRAY ACRYLIC.

CUSTOMER NAME:	KAMAN INDUSTRIAL TECHNOLOGIES		CUST. P/N:	CUST. P/N:				THE SHEFFER CORPORATION			
MODEL NO:	6HHCI4CRAKPY		PR MAX EXT.	3000	PSI.		CINCINNATI, OHIO 45242				
BORE: 6"	PORT POS:	I & 5	PR MAX RET.	3000	) PSI.		6" HH SERIES - CLEVIS MOUNT 3-I/2" DIA ROD STYLE 2 CUSHIONED REAR			-	
STROKE: 14"	CUSH ADJ SCR POS: 7		MEDIUM:	MEDIUM:			DR. JRB 6/24/22 SCALE 1:2				
ROD STYLE: 2	CUSH CHEC	<b>K POS</b> : 8	TEMP:	P:		3374420 USED ON	CK.	010 0124122	APPR.	1.2	
CERTIFIED BY	DATE	APPROVED BY	DATE	(	0600HHC01000CR0			0350S2-NI00PI5C0078-Y03YI7			