1231.5 248 455.5 124.5 116st 52 318 48 .12 116st 118 PF3/8".PLUG 2-M16X2P.DF 116ST 74ST 42ST 55.5 DUST SEAL (NOK) DSI(Ø120x130x8X6) 3-PROMITI SENSOR PF 3/8" TAP (DRAIN) OIL SEAL (NOK) U-PACKING(NOK) ISI 120 (ø120xø135x9) ø30 C'BORE DP 3 175 U-PACKING (NOK) ø7 DRILL THRU' 265 8-M10 WRENCH BOLT UPH22(Ø22xØ35x10) BALL BEARING BALL BEARING O-RING G270(BUR) TCN-Ø65xØ90x13 74st G145 D-RING 0-RING O-RING 116st G240(BUR) U-PACKING (NOK) G155 12-M20 WRENCH BOLT MARKED (L): INTERMEDIATE DIA D-RING ISI $120(\phi 120 \times \phi 135 \times 9.BUR)$ U-PACKING (NOK) MARKED (M): EXPANDED DIA WEARING OIL SEAL (NOK) 6-M33X3.5P TAP THRU. T/W = - KqØ120xØ125x20L MARKED (N) : COLLAPSED DIA $ICN-\emptyset120\times\emptyset150\times14$ Ø250XØ272X30L P22(BUR) DUST SEAL (NOK) DSI 120X130X8X6 | URETHANE | -M12 WRENCH BOLT WEARING \ U-PACKING (NOK) ISI 120X135X9 NITRILE. ø280Xø272X25L u-packing (nok) M16 HEX' HEAD BOLT 16-M20 WRENCH BOLT ROTO SEAL 0-RING(NOK) G145 NBR USH(Ø230XØ250X12.BUR) Ø22XØ29.5X3.2 WRENCH BOLT M10x40L S45C ROD BUSH Ø120XØ200 HBsC3 e WRENCH BOLT M12x40L SCM435 d OIL SEAL (NOK) TCN Ø22xØ35x8 NBR STOPPER 64T SS400 0 - RING(NOK)NBR P65 O-RING(NOK) P80 NBR SPECIFICATIONS TCN Ø65xØ90x13 b OIL SEAL (NOK) CYLINDER ROD ø120X579.5L NBR SCM440 $a \mid O-RING(NOK)$ G145 WEARING TURCITE - Ø120x125x20 NBR CYLINDER SPEC. 16 JOINT COVER ISI 125X135X9(BUR3T) Ø210 S45C U-PACKING (NOK) JRETHANE ø250/ø280 BORE - USH 260X280X14(BUR.4 a STEEL RING STEEL SWPA U-PACKING (NOK) NBR ROD Ø120 PF 1" TAP 15 PISTON SEAL ø118 CARBON CYLINDER PISTON S45C - Ø280 STROKE 116(42+74)mm a HEX.HEAD BOLT, C/W 3-ø20 DRILLS THRI M5x20L WEARING LUYTEX - Ø250XØ272X30L S45C TYPE FA S45C SET SCREW 14 SEAL COVER 4T SS400 - M6x10L SECTION "B"-"B" NBR - USH 230X250X12(BUR.4⁻ WRENCH BOLT M12x30L U-PACKING(NOK) SCM435 Q'TY 1 SET (See Dwg - 11004) (See Dwg - 11004) CYLINDER PISTON S45C - Ø250 b OIL SEAL (NOK) TCN-120X150X14 NBR ROTO SEAL(KASTAS) 23 COVER 3T SS400 a 0-RING G155 NBR NBR+T - | ø22Xø29.5X3.2 22 STOPPER 0-RING(NOK) 13 JOINT COVER NBR Ø85 S45C S45C Ø210 NOTE 21 ACRYL PLATE 4.5T ACRYL b BALL BEARING O-RING(NOK)NBR P22(BUR-2EA-) #6019 PUR. 1. Rod Hard Chrome Plating:20 more than S45C O-RING(NOK) NBR - G40 WRENCH BOLT M12x30L a BALL BEARING #6924 PUR. 2. Operating Pressure:100 f/ S45C - G120 a WRENCH BOLT M6x10L 12 JOINT BODY Ø210 S45C O-RING(NOK)NBR 3. Test Pressure:150 f/ 4.5T **SS400** 20 SENSOR BOX d HEX. HEAD BOLT, S/W M16x60L SCM435 8 O-RING(NOK) NBR - P20 a HEX.HEAD BOLT M6x15L S45C c DOWEL PIN S45C WRENCH BOLT SCM435 - G240(BUR) ø8x18L b U-PACKING (NOK)UPH Ø22xØ35x10 19 PLATE 4T SS400 HEAD COVER SS400 - M20x60L NBR 18 BUSH ø40 BC6 a BEARING NUT/WASHER AN19/AW19 PUR. PLUG SS400 c SNAP RING S45C R35 PUR JOINT SHAFT CYLINDER TUBE STPG38 PT 3/8" ø259 WRENCH BOLT b BEARING #6003 PUR) BUSH ø22Xø30X25L BC6 SCM435 - | ø250Xø350X415L ANO3 PUR O-RING & BACK UP RING - M20x60L a BEARING NUT a WRENCH BOLT M6x15L S45C -BR.TEFLON 17 SENSOR BAR S45C 9 HALF PLATE ROD COVER G270 ø22X745L ø54 S45C SS400 MAT'(KS) UNIT TOTAL PERUNIT TOTAL

QUANTITY WEIGHT(kg) UNIT TOTAL PERUNIT TOTAL
QUANTITY WEIGHT(kg) MAT'(KS) UNIT TOTAL PERUNIT TOTAL
QUANTITY WEIGHT(kg) MAT'(KS) DESCRIPTION REMARK'S DESCRIPTION REMARK'S DESCRIPTION REMARK'S 1:2 PROJECTION JSW Steel Limited A1 DIMENSION mm ALL WELDING SYMBOLS ARE UNLESS SURFACE FINISH SYMBOLS COMPARISON JSW Vijaynagar PLANT | ITEM No. 1.1.04 OTHERWISE SPECIFIED. S EQUIPMENT 1.1.04 No.1 PAY OFF REEL A 27.12.18 FOR APPROVAL ALLOWABLE TOLERANCE LIMIT FOR MACHINED
 V
 V
 V
 V
 V
 V
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓
 ✓</ D.Y.K S.M.B C.S.K D.S.H CCL FACILITY ASSEMBLY (4/5) PART UNLESS OTHERWISE SPECIFIED DWG. JSW-3-1104-M31-11004 A SYMBOLS DRAWEN CHECKED REVIEWED APPROVED ₩ DRAWEN CHECKED REVIEWED APPROVED ₩ NO. REVISIONS & DESCRIPTION Checked 3.2 1.6 0.8 0.2 25 12.5 6.3 50 posco D.Y.K S.M.B C.S.K D.S.H DWG. NO. OOWAN VIII. NAWOO
Engineering & Consulting SIGNA TURE RMAX NON 100S 50S 포스코건설 25S | 12.5S | 6.3S | 3.2S | 0.8S DATE ² 27.12.18

A1 (841x594)