





## SPECIFICATION

- |                   |  |
|-------------------|--|
| 1)BORE            | : Ø200mm                                 |
| 2)ROD             | : Ø110 mm                                |
| 3)STROKE          | : 105 mm                                 |
| 4)WORKING PR.     | : 160 BAR                                |
| 5)TEST PR.        | : 240 BAR                                |
| 6)AMB TEMP.       | : 80° C                                  |
| 7)TYPE            | : DOUBLE ACTING (CUSHIONED AT BOTH ENDS) |
| 8)MOUNTING        | : MT3, HEAD END, CIRCULAR FLANGE         |
| 9)OPERATING MEDIA | : MINERAL OIL                            |
| 10)SEAL           | : IMPORTED/VITON                         |

UNSPECIFIED TOLERANCES ON LINEAR DIMENSION IS:7215														
0.5-6		>6-30		>30-120		>120-400		>400-1000		>1000-2000		>2000-4000		
± 0.1		± 0.2		± 0.3		± 0.5		± 0.8		± 1.2		± 2		
<div> <b>Steel Coated Products Ltd.</b> B-6, MIDC-TARAPUR, BOISAR MAHARASHTRA</div>									DATE		04.08.22		SCALE- 1:5	
									DRN		V.BRITTO		SIZE- A3	
									CHD		V.RAJPUT		PROJ	
									APPD.		S.GUPTA			
SURFACE FINISH				TITLE					ALL DIMENSION ARE IN MM. UNLESS OTHERWISE SPECIFIED.				REV R0	
	RAW 50			HYDRAULIC CYLINDER  FOR MANDREL EXPAND/COLLAPSE					SHEET VELJAN 064 R749					
	ROUGH 25/12.5								DRG. NO.  ECL-21-001/4					
	SMOOTH 6.3/3.2/1.6													
	GRIND 0.8/0.4			M/C.		UNCOILER								