

Basic Syntax in Java

Comments

There are two types of comments in Java: inline, and block.

```
// This is an inline comment. It only
includes this line.

/*
   This is a block comment. Anything between
the asterisks is part of the comment.
*/
```

Printing

In Java, you can print statements using `System.out.print()` and `System.out.println()`. The latter ends with a new line.

```
System.out.print("I'm first!");
System.out.println("I'm second!");
System.out.print("I'm last!");

/* Prints:
I'm first!I'm second!
I'm last!
*/
```

Variable Types

Variables are used to name, store, and reference different types of data.

Primitive data types are predefined types of data and include `int`, `double`, `boolean`, and `char`.

Reference data types contain references to an object. An example reference data type is `String`.

```
// int - stores whole numbers:
int num = 10;

// double - stores decimal numbers:
double dec = 4.99;

// boolean - stores true or false values:
boolean isTrue = true;

// char - stores a single character value:
char firstLetter = 'A';

// String - stores multiple characters:
String message = "hello there";
```

Manipulating Number Variables

Different math operations can be applied to `int`, `double`, and `float` data types.

```
int a = 3;
int b = 5;

int num1;
num1 = a + a; // num1 now equals 6
num1 = a - b; // num1 now equals -2
num1 = a * b; // num1 now equals 15
num1 = 9 / a; // num1 now equals 3
num1 = 10 % a; // num1 now equals 1

int num2 = 10;
num2 -= a; // num2 now equals 8
num2 += b; // num2 now equals 13
num2 %= 6; // num2 now equals 1
num2 *= 4; // num2 now equals 4
num2 /= 2; // num2 now equals 2

int num3 = 3;
num3++; // num3 now equals 4
num3--; // num3 now equals 3
```

Conditional Statements

In Java, conditional statements execute code based on the truth value of given `boolean` expressions.

```
boolean expression1 = false;
boolean expression2 = false;
boolean expression3 = true;

if (expression1) {
    System.out.println("The first expression is true");
} else if (expression2) {
    System.out.println("The second expression is true");
} else if (expression3) {
    System.out.println("The third expression is true");
} else {
    System.out.println("All other expressions were false");
}

// Prints: The third expression is true
```

Comparison and Logical Operators

Conditional operators and logical operators evaluate the relationship between values in order to determine a `true` or `false` value.

```
// Comparison Operators:
int a = 1;
int b = 5;

System.out.println(a > b); // Prints: false
System.out.println(a < b); // Prints: true
System.out.println(a >= 1); // Prints: true
System.out.println(a + 4 <= b); // Prints:
true
System.out.println(a == 1); // Prints: true
System.out.println(b != 5); // Prints: false


// Logical Operators:
System.out.println(!true); // Prints: false
System.out.println(!false); // Prints: true


System.out.println(true && true); // Prints:
true
System.out.println(true && false); // Prints:
false
System.out.println(false && true); // Prints:
false
System.out.println(false && false); //
Prints: false


System.out.println(true || true); // Prints:
true
System.out.println(true || false); // Prints:
true
System.out.println(false || true); // Prints:
true
System.out.println(false || false); //
Prints: false
```

Loops

Java has four kinds of loops that rely on a `boolean` condition and continue to iterate until the condition is no longer true:

- `while` loops
- `do-while` loops
- `for` loops
- `for-each` loops

// An example of a `while` loop:

```
int x = 0;
while (x < 2) {
    System.out.println(x);
    x++;
} // Prints: 0 and 1
```

// An example of a `do-while` loop:

```
do {
    System.out.println("Impossible!");
} while (2 == 4); // Prints: Impossible!
```

// An example of a `for` loop:

```
for (int i = 0; i < 10; i++) {
    System.out.println(i);
} // Prints: 0 to 9, inclusive
```

// An example of a `for-each` loop:

```
String[] colors = {"Red", "Blue", "Yellow"};
for (String c : colors) {
    System.out.println(c);
} // Prints: Red, Blue, and Yellow
```

break and continue

Java has two keywords that help further control the number of iterations in a loop:

- `break` is used to exit, or break, a loop. Once `break` is executed, the loop will stop iterating.
- `continue` can be placed inside of a loop if we want to skip an iteration. If `continue` is executed, the current loop iteration will immediately end, and the next iteration will begin.

// An example of a break statement:

```
for (int i = 0; i < 10; i++) {
    System.out.println(i);
    if (i == 4) {
        break;
    }
} // Prints: 0 to 4, inclusive
```

// An example of a continue statement:

```
int[] numbers = {1, 2, 3, 4, 5};
for (int i = 0; i < numbers.length; i++) {
    if (numbers[i] % 2 == 0) {
        continue;
    }
    System.out.println(numbers[i]);
} // Prints 1, 3, and 5
```

Methods

A method is a modular, reusable block of code that can be called throughout a program to complete a certain task.

/*

The following method is a public method called `findSum`. The method takes in two `int` parameters called `int1` and `int2`. This method returns an `int` value.

*/

```
public static int findSum(int num1, int num2)
{
    return num1 + num2;
}
```

```
public static void main(String[] args) {
    // Call the method with the arguments 3 and
    4
    int sum = findSum(3,4);
    System.out.println(sum); // Prints: 7
}
```

String Methods

Java's `String` class has many useful methods including:

- `.length()` , which returns the length of the `String`
- `.concat()` , which concatenates two `String` s together
- `.equals()` , which checks for `String` equality
- `.indexOf()` , which returns the index of the first occurrence of a specified character
- `.charAt()` , which returns the character at a specified index
- `.substring()` , which extracts a substring

```
// Using the .length() method:
String str = "Hello World!";
System.out.println(str.length()); // Prints:
12
```

```
// Using the .concat() method:
String name = "Code";
name = name.concat("cademy");
System.out.println(name); // Prints:
Codecademy
```

```
// Using the .equals() method:
String flavor1 = "Mango";
String flavor2 = "Matcha";
System.out.println(flavor1.equals(flavor2));
// Prints: false
```

```
// Using the .indexOf() method:
String letters = "ABCDEFGH IJKLMN";
System.out.println(letters.indexOf("C")); //
Prints: 2
```

```
// Using the .charAt() method:
String currency = "Yen";
System.out.println(currency.charAt(2)); //
Prints: n
```

```
// Using the .substring() method
String line = "It was the best of times, it
was the worst of times.";
System.out.println(line.substring(26)); //
Prints: it was the worst of times.
System.out.println(line.substring(7, 24)); //
Prints: the best of times
```