

Irish Dataset

1) Classification



Iris Versicolor



Iris Setosa



Iris Virginica

load dataset

In []:

```
#import seaborn library เพื่อใช้ในการวาดภาพ
import seaborn as sns; sns.set(color_codes=True)
iris = sns.load_dataset('iris') #อ่าน dataset ที่ชื่อ iris ซึ่งมีอยู่ใน seaborn library
iris.head()
```

In []:

```
X_iris = iris.drop('species', axis=1) #ตัด feature ที่ชื่อ species ออก
y_iris = iris['species'] #กำหนดให้ feature ที่ชื่อ species เป็น target output
```

In []:

```
X_iris #แสดง input feature 150 rows x 4 columns
```

In []:

```
X_iris.shape
```

In []:

```
y_iris #แสดง output feature 150 rows x 1 column
```

In []:

```
y_iris.shape
```

In []:

```
#seaborn.pairplot => Plot pairwise relationships in a dataset.  
sns.pairplot(iris, hue='species', height=1.5);
```

In []:

```
#Count Plot displays the number of observations for a categorical variable using bars.  
sns.countplot(x='species',data=iris, palette="OrRd")
```

In []:

```
from sklearn.model_selection import train_test_split #Split arrays or matrices into random  
Xtrain, Xtest, ytrain, ytest = train_test_split(X_iris, y_iris, random_state=1)  
#Xtrain => training data  
#Xtest => testing data  
#ytrain => training target data  
#ytest => testing target data
```

Choose Model

In []:

```
from sklearn.naive_bayes import GaussianNB # 1. choose model class Gaussian Naive Bayes  
model = GaussianNB() # 2. instantiate model  
model.fit(Xtrain, ytrain) # 3. fit model to data using training data  
y_model = model.predict(Xtest) # 4. predict on new data testing data
```

Evaluate Model

In []:

```
from sklearn.metrics import accuracy_score #Accuracy classification score  
accuracy_score(ytest, y_model) #comparing real target (ytest) with predicted target (y_model)
```

In []:



```
# credit code: https://www.kaggle.com/grfiv4/plot-a-confusion-matrix

def plot_confusion_matrix(cm,
                          target_names,
                          title='Confusion matrix',
                          cmap=None,
                          normalize=True):

    """
    given a sklearn confusion matrix (cm), make a nice plot

    Arguments
    -----
    cm:          confusion matrix from sklearn.metrics.confusion_matrix

    target_names: given classification classes such as [0, 1, 2]
                  the class names, for example: ['high', 'medium', 'low']

    title:       the text to display at the top of the matrix

    cmap:        the gradient of the values displayed from matplotlib.pyplot.cm
                  see http://matplotlib.org/examples/color/colormaps_reference.html
                  plt.get_cmap('jet') or plt.cm.Blues

    normalize:   If False, plot the raw numbers
                  If True, plot the proportions

    Usage
    -----
    plot_confusion_matrix(cm          = cm,                  # confusion matrix created by
                                                              # sklearn.metrics.confusion_m
                          normalize   = True,              # show proportions
                          target_names = y_labels_vals,     # list of names of the classe
                          title       = best_estimator_name) # title of graph

    Citiation
    -----
    http://scikit-learn.org/stable/auto_examples/model_selection/plot_confusion_matrix.html

    """
    import matplotlib.pyplot as plt
    import numpy as np
    import itertools

    accuracy = np.trace(cm) / float(np.sum(cm))
    misclass = 1 - accuracy

    if cmap is None:
        cmap = plt.get_cmap('Blues')

    plt.figure(figsize=(10, 10))
    plt.imshow(cm, interpolation='nearest', cmap=cmap)
    plt.title(title)
    plt.colorbar()

    if target_names is not None:
        tick_marks = np.arange(len(target_names))
        plt.xticks(tick_marks, target_names, rotation=45)
        plt.yticks(tick_marks, target_names)
```

```

if normalize:
    cm = cm.astype('float') / cm.sum(axis=1)[:, np.newaxis]

thresh = cm.max() / 1.5 if normalize else cm.max() / 2
for i, j in itertools.product(range(cm.shape[0]), range(cm.shape[1])):
    if normalize:
        plt.text(j, i, "{:0.4f}".format(cm[i, j]),
                  horizontalalignment="center",
                  color="white" if cm[i, j] > thresh else "black")
    else:
        plt.text(j, i, "{:,}".format(cm[i, j]),
                  horizontalalignment="center",
                  color="white" if cm[i, j] > thresh else "black")

plt.tight_layout()
plt.ylabel('True label')
plt.xlabel('Predicted label\naccuracy={:0.4f}; misclass={:0.4f}'.format(accuracy, misclass))
plt.show()

```

In []:



```

from sklearn.metrics import confusion_matrix
plot_confusion_matrix(cm = confusion_matrix(ytest, y_model),
                      normalize = False,
                      target_names = ['setosa', 'versicolor', 'virginica'],
                      title = "Confusion Matrix")

```

Saving and loading a model with pickle

In []:



```

import pickle

# Save an existing model to file
# wb = write binary
pickle.dump(model, open("model/iris_model.pkl", "wb"))

```

In []:



```

# Load a saved model
loaded_pickle_model = pickle.load(open("model/iris_model.pkl", "rb"))

```

In []:



```

# Make predictions and evaluate the loaded model
pickle_y_preds = loaded_pickle_model.predict(Xtest)
pickle_y_preds

```

In []:



```

from sklearn.naive_bayes import GaussianNB
plot_confusion_matrix(cm = confusion_matrix(ytest, pickle_y_preds),
                      normalize = False,
                      target_names = ['setosa', 'versicolor', 'virginica'],
                      title = "Confusion Matrix")

```

In []:



```
#using heatmap
from sklearn.naive_bayes import GaussianNB
import matplotlib.pyplot as plt
mat = confusion_matrix(ytest, pickle_y_preds)
label = ['setosa', 'versicolor', 'virginica']
sns.heatmap(mat.T, square=True, annot=True, fmt='d', xticklabels=label, yticklabels=label, cmap=
plt.xlabel('true label')
plt.ylabel('predicted label');
```

2) Irish Clustering

In []:



```
from sklearn.decomposition import PCA # 1. Choose the model class
model = PCA(n_components=2) # 2. Instantiate (2 dimensions) the model with hyperparameters
model.fit(X_iris) # 3. Fit to data. Notice y is not specified!
X_2D = model.transform(X_iris) # 4. Transform the data to two dimensions
```

In []:



X_iris

In []:



X_2D

In []:



```
iris['PCA1'] = X_2D[:, 0] #ค่าข้อมูล dimension ที่ 1
iris['PCA2'] = X_2D[:, 1] #ค่าข้อมูล dimension ที่ 2
sns.lmplot("PCA1", "PCA2", hue='species', data=iris, fit_reg=False);
```

In []:



```
from sklearn.mixture import GaussianMixture # 1. Choose the model class (Gaussian mixture m
model = GaussianMixture(n_components=3, covariance_type='full') # 2. Instantiate the model
model.fit(X_iris) # 3. Fit to data. Notice y is not specified!
y_gmm = model.predict(X_iris) # 4. Determine cluster label
```

In []:



```
iris['cluster'] = y_gmm
sns.lmplot("PCA1", "PCA2", data=iris, hue='species', col='cluster', fit_reg=False);
# input variables: PCA1, PCA2
# data : iris
# hue: วาดรูปตาม feature ที่ชื่อว่า species
# col: แสดงลำดับของ cluster
# fit_reg: ประมาณการ plot regression model
```

