Q1.

```
Q1.scala - Visual Studio Code
                                                                                             ×
File Edit Selection View Go Run Terminal Help
                                                                                            ▶ Ш …
      Q1.scala X
      home > nimal > Desktop > UCSC > lab_session1 > pracitcal_9 > ■ Q1.scala > {} Q1 > ๗ main
             ala.io.StdIn.readDouble
Q
og
             ain(args:Array[String]): Unit = {
             al calcInterest = (deposit:Double,rate:Double) => deposit * rate/100
             al findInterest = (deposit:Double) => deposit match {
  case x if x <= 20000 => calcInterest(x,2)
                case x if x <= 200000 => calcInterest(x,4)
                case x if x \le 2000000 \Rightarrow calcInterest(x,3.5)
                case x => calcInterest(x,6.5)
<u>_</u>6
             rint("Enter the deposit amount: ")
             ar depositInput =readDouble()
        16
             rintln(s"The interest for deposit : ${findInterest(depositInput)}")
m
                                                                         TERMINAL
     • nimal@nimal:~/Desktop/UCSC/lab session1/pracitcal 9$ scala Q1.scala
       Enter the deposit amount: 25000
       The interest for deposit : 1000.0
     o nimal@nimal:~/Desktop/UCSC/lab session1/pracitcal 9$
    Ø0A0 ₩0
                                         Q Ln 16, Col 77 Spaces: 4 UTF-8 LF Scala @ Go Live 🕢 Prettier
```

