

OOPs with Java Mock 1

Total points 22/40

The respondent's email (**maheshpatil9691@gmail.com**) was recorded on submission of this form.

✓ Which is the data type used mostly to handle streams and buffers in Java *1/1 language?

- ☐ short
- ☐ int
- ☒ byte
- ☐ float



✓ Memory is allocated to an object once the execution of ___ is over in Java *1/1 language.

- ☐ main method
- ☒ constructor
- ☐ destructor
- ☐ None



✗ Select all the correct statements about HashSet and LinkedHashSet * 0/1

- ☐ HashSet always maintain the insertion order of the elements
- ☐ LinkedHashSet maintains the ordering of the elements and guarantees insertion order
- ☒ HashSet does not necessarily maintain the insertion order of the elements ✓
- ☒ HashSet and LinkedHashSet are the implementing classes of the Set interface ✓
- ☐ HashSet and LinkedHashSet are the implementing classes of the SortedSet interface

Correct answer

- ☒ LinkedHashSet maintains the ordering of the elements and guarantees insertion order
- ☒ HashSet does not necessarily maintain the insertion order of the elements
- ☒ HashSet and LinkedHashSet are the implementing classes of the Set interface

✗ Implicit Type Conversion in Java is also called ___? * 0/1

- ☒ Narrowing Type Conversion ✗
- ☐ Widening Type Conversion
- ☐ No Type Conversion
- ☐ None of the above

Correct answer

- ☒ Widening Type Conversion

✓ What is the output of the Java code snippet? `byte a = 0b0000_0001; * 1/1`
`System.out.println(~a);`

- ☐ -1
- ☒ -2
- ☐ 254
- ☐ +127



✓ A BREAK statement inside a Loop like WHILE, FOR, DO WHILE and Enhanced-FOR causes the program execution __ Loop. *1/1

- ☒ Exit
- ☐ Continuation with next iteration
- ☐ Never exit
- ☐ None



✓ How many maximum numbers of objects can be created from a single Class in Java? *1/1

- ☐ 32
- ☐ 64
- ☐ 256
- ☒ None



✓ What is the output of the below Java code snippet? *

1/1

```
float a = 8.2/2;  
System.out.println(a);
```

- ☐ 4.1
- ☐ 8.1
- ☐ 4
- ☒ Compiler error



✓ Lazy initialization of array requires the keyword "new" to allocate memory *1/1
to the array and its elements. State TRUE or FALSE.

- ☒ True
- ☐ False



✗ Select the correct output of the execution of the below program: *

0/1

```
public static void main(String[] args) {  
    SortedSet ss=new TreeSet();  
    ss.add("a");  
    ss.add("b");  
    ss.add("c");  
    ss.add("d");  
    ss.add("e");  
    ss.add("f");  
    ss.add("g");  
    SortedSet ss2=ss.tailSet("e");  
    Iterator ssitr2=ss2.iterator();  
    while(ssitr2.hasNext())  
    {  
        System.out.println(ssitr2.next().toString());  
    }  
}
```

- ☐ e,f,g
- ☒ f,g
- ☐ Run-time exception

✗

Correct answer

- ☒ e,f,g

✓ What is the output of the below Java program? public class Constructor * 1/1

```
{ int count=10;
Constructor2(int count)
{ System.out.println("Count=" + count); }
public static void main(String[] args)
{ Constructor2 con = new Constructor2();
}}
```

- ☐ Count=0
- ☐ Count=10
- ☒ Compiler error
- ☐ None of the above



✓ State TRUE or FALSE. In Java, a public class or abstract-class or interface *1/1 must be kept in a separate .java file.

- ☒ True
- ☐ False



✓ What is the output of the Java program below? int b=20; * 1/1

```
switch(b)
{
default: System.out.println("LION");
}
```

- ☐ No output
- ☒ LION
- ☐ Compiler error as there are no CASE statements.
- ☐ None



✓ What is the output of the following Java Code? *

1/1

```
int a=9;  
float b = a/2;  
System.out.println(b);
```

- ☒ 4.0
- ☐ 4.5
- ☐ 5.0
- ☐ None of the above



✓ What is the output of the Java code snippet? *

1/1

```
int a = 260;  
byte b= (byte)a;  
System.out.println(b);
```

- ☐ 0
- ☒ 4
- ☐ 255
- ☐ 260



✓ What is the output of the below Java code snippet? *

1/1

```
char ch = 'A';  
int a = ch + 1;  
ch = (char)a;  
System.out.println(ch);
```

- ☐ 66
- ☐ A
- ☒ B
- ☐ 65



✓ Which Interface does not allow duplicates? *

1/1

- ☐ List
- ☒ Set
- ☐ Map
- ☐ SortedMap



✗ Java object assignment happens by ____.

0/1

- ☒ Pass by Value
- ☐ Pass by Reference



Correct answer

- ☒ Pass by Reference

✗ You can not inherit a Superclass's constructor even after using inheritance in Java. State TRUE or FALSE.

*0/1

☐ True

☒ False

✗

Correct answer

☒ True

✗ What is the output of the below Java code with constructors? *

0/1

```
enum Human
{ KID(10), BOY(30), MAN(60);
  Human(int weight)
  { System.out.println("Weight: " + weight);
  }
}

public class EnumTest5 {
  public static void main(String[] args)
  { Human he = Human.KID; }
}
```

☐ Weight: 10 Weight: 30 Weight: 60

☐ Weight: 10 Weight: 10 Weight: 10

☒ Weight: 0 Weight: 0 Weight: 0

✗

☐ No output

Correct answer

☒ Weight: 10 Weight: 30 Weight: 60

✗ What is the output of the Java code snippet? *

0/1

```
int a=10, b=20;  
int c = a++*2;  
int d = --b*2;  
System.out.println(c + "," + d);
```

☐ 20,40

☐ 22,40

☐ 20,38

☒ 22,38

✗

Correct answer

☒ 20,38

✗ Which of these is synchronized? *

0/1

☐ TreeMap

☐ HashMap

☐ Hashtable

☒ All

✗

Correct answer

☒ Hashtable

PRN *

43

✗ Select the classes which have a comparator() method *

0/1

☐ ArrayList

☐ HashMap

☒ TreeSet

✓

☒ HashSet

✗

☐ TreeMap

Correct answer

☒ TreeSet

☒ TreeMap

Name *

Mahesh Patil

✗ What is the default value of an element of Object type array? *

0/1

☐ 0

☐ null

☐ -1

☒ Garbage value

✗

Correct answer

☒ null

✓ Java uses ___ type of memory to implement Recursion. *

1/1

- ☐ Heap
- ☒ Stack
- ☐ Register
- ☐ None



✓ Java allows calling or invoking a method from a constructor. State TRUE or FALSE. *1/1

- ☒ True
- ☐ False



✗ What is the output of the Java code snippet? *

0/1

```
byte b = 25;  
b++;  
b = b+1;  
System.out.println(b);
```

- ☐ 25
- ☐ 26
- ☒ 27
- ☐ Compiler error



Correct answer

- ☒ Compiler error

✓ The List is a collection that contains only unique elements *

1/1

- ☐ True
- ☒ False



✓ What is the output of the Java code snippet? *

1/1

```
int a=5, b=6;  
if(a++ == --b)  
{ System.out.println("5=5"); }  
else { System.out.println("NONE"); }
```

- ☐ NONE
- ☒ 5=5
- ☐ Compiler error
- ☐ None of the above



✓ What is a Widening Type Conversion in Java? *

1/1

- ☐ Conversion of data from higher data type to lower data type
- ☒ Conversion of data from lower data type to higher data type
- ☐ Conversion of data from any data type to any data type
- ☐ None of the above



✗ What is the output of Java program below? `int num=40; *
switch(num) {
case 5: System.out.println("FIVE"); break;
case 35+5: System.out.println("FORTY"); break;
case 20+30: System.out.println("FIFTY"); }`

0/1

- ☐ FIVE
- ☐ FORTY
- ☐ FIFTY
- ☒ Compiler error

✗

Correct answer

- ☒ FORTY

✗ What does a Data Type in Java refers to? *

0/1

- ☒ The place where data is stored
- ☐ The technique how data is retrieved
- ☐ The type or variety of data being handled for reading and writing
- ☐ None of the above

✗

Correct answer

- ☒ The type or variety of data being handled for reading and writing

✗ What was the reason for huge initial success of Java? *

0/1

- ☐ WWW (World Wide Web)
- ☐ Smart TV Evolution
- ☐ Smart Home Automation
- ☒ None of the above

✗

Correct answer

- ☒ WWW (World Wide Web)

✗ What is the character encoding standard used in Java language? *

0/1

- ☒ ASCII
- ☐ Unicode
- ☐ Bytecode
- ☐ none

✗

Correct answer

- ☒ Unicode

✓ In Java, local variables are stored in __ memory and instance variables are stored in __ memory.

*1/1

- ☐ Stack, Stack
- ☐ Heap, Heap
- ☒ Stack, Heap
- ☐ Heap, Stack

✓

✓ What is the output of the below Java program with arrays? String[] colors *1/1
= {"RED";"YELLOW";"WHITE"}; System.out.print(colors[2]);

- ☐ RED
- ☐ YELLOW
- ☐ WHITE
- ☒ Compiler error



✗ Choose the correct option based on this program: *

0/1

```
import java.util.*;
class UtilitiesTest
{
    public static void main(String[] args)
    {
        List < int > intList = new ArrayList < > ();
        intList.add(10);
        intList.add(20);
        System.out.println("The list is: " + intList);
    }
}
```

- ☒ It prints the following: The list is: [10, 20]
- ☐ It prints the following: The list is: [20, 10]
- ☐ It results in a compiler error
- ☐ It results in a runtime exception



Correct answer

- ☒ It results in a compiler error

✗ How many objects are eligible for garbage collection after execution of line ? *0/1

```
public class Test
{
    public static void main(String[] args)
    {
        m1(); // Line
    }
    static void m1()
    {
        Test t1 = new Test();
        Test t2 = new Test();
    }
}
```

☒ 0

☐ 1

☐ 2

☐ 3

✗

Correct answer

☒ 2

✗ Among Postfix Decrement and Prefix Increment operators in Java, which operator has less priority? *0/1

- ☒ Postfix Decrement has less priority than Prefix Increment ✗
- ☐ Prefix Increment has less priority than Postfix Decrement
- ☐ Both operators have same priority
- ☐ None of the above

Correct answer

- ☒ Prefix Increment has less priority than Postfix Decrement

✓ What is the need for Autoboxing and Unboxing in Java? *

1/1

- ☐ Reduces code to be written by developers to convert from Wrapper to Primitive vice versa
- ☐ Compile time is reduced due to fixed methods followed to automatically convert Objects and Primitives
- ☐ Auto-unboxing improves memory efficiency by converting Wrapper to Primitive and process when object version is not needed
- ☒ All the above ✓

