

WPT Mock Test I

Total points 39/40 ?

✓ 1. How do you confirm that a document is written in HTML5? * 1/1

- ☐ The server wraps the webpage in an HTML5 wrapper.
- ☒ Use the <!DOCTYPE html> declaration that starts the document. ✓
- ☐ The browser receives encoding from the server to display the document with HTML5.
- ☐ It is enclosed in a <html> tag.

✓ 2. In the code below, what is the purpose of the id attribute? * 1/1
`<p id="warning">Be careful when installing this product.</p>`

- ☒ It establishes that id is a unique identifier in the document, used for styling CSS, scripting, and linking within a webpage. ✓
- ☐ It establishes that id is a unique identifier in the document, used for styling CSS and with Javascript code.
- ☐ It establishes that id may be used for styling CSS several times per page.
- ☐ It establishes that id is a unique identifier in the website, used for styling CSS, scripting, and linking within a webpage.

✓ 3. Which choice uses the correct terminology in describing this markup: <p>info</p>? *1/1

- ☐ The element opener is <p>, the element closer is </p>, and the element information is info.
- ☐ The start tag is <p>, the end tag is </p>, and the enclosed HTML is info.
- ☒ The start tag is <p>, the end tag is </p>, and the element content is info. ✓
- ☐ The start element is <p>, the end element is </p>, and the tag content is info.



✓ 4. Which tag is the root element of an HTML document? * 1/1

- ☐ <!DOCTYPE html>
- ☒ <html>
- ☐ <body>
- ☐ <root>



✓ 5. Review the code below. What is the absolute URL for a page called **page.html**? *1/1

<base href="http://www.linkedin.com/dir/" />

- ☒ <http://www.linkedin.com/dir/page.html>
- ☐ <http://127.0.0.1/linkedin.com/page.html>
- ☐ <http://www.linkedin.com/page.html>
- ☐ <http://localhost/linkedin.com/dir/page.html>



✓ 6. What is the correct way to include a stylesheet named **style.css** in the <head> of your document? *1/1

- ☐ <style link="style.css">
- ☒ <link rel="stylesheet" href="style.css">
- ☐ <style src="style.css"></style>
- ☐ <link style="style.css">



✓ 7. Which HTML element is the container for all the renderable aspects of the document? *1/1

- ☐ head
- ☒ body
- ☐ title
- ☐ meta



✓ 8. What is the default method for form submission? * 1/1

- ☒ GET
- ☐ POST
- ☐ PUT
- ☐ SUBMIT



✓ 9. What is the correct HTML element for inserting a line break? * 1/1

- ☐ <break>
- ☐ <lb>
- ☒

- ☐



✓ 10. In this example, what is the selector, property, and value? * 1/1

p { color: #000000; }

- ☐ "p" is the selector, "#000000" is the property, "color" is the value
- ☒ "p" is the selector, "color" is the property, "#000000" is the value
- ☐ "color" is the selector, "#000000" is the property, "#p" is the value
- ☐ "color" is the selector, "p" is the property, "#000000" is the value



✓ 11. When using flexbox, the "justify-content" property can be used to distribute the space between the flex items along the main axis. Which value should be used to evenly distribute the flex items within the container shown below? *1/1



- ☐ justify-content: space-around;
- ☐ justify-content: center;
- ☐ justify-content: auto;
- ☒ justify-content: space-between;



✓ 12. What is the difference between the margin and padding properties? * 1/1

- ☐ Margin adds space around and inside of an element; padding adds space only inside of an element.
- ☒ Margin adds space around an element; padding adds space inside of an element. ✓
- ☐ Margin adds a line around an element, padding adds space inside of an element.
- ☐ Margin adds space inside of an element, padding adds space around an element.

✓ 13. How is a forEach statement different from a for statement? * 1/1

- ☐ Only a for statement uses a callback function.
- ☒ A for statement is generic, but a forEach statement can be used only with an array. ✓
- ☐ Only a forEach statement lets you specify your own iterator.
- ☐ A forEach statement is generic, but a for statement can be used only with an array.

✓ 14. Review the code below. Which statement calls the addTax function and passes 50 as an argument? *1/1

```
function addTax(total) {  
  return total * 1.05;  
}
```

- ☐ addTax = 50;
- ☐ return addTax 50;
- ☒ addTax(50); ✓
- ☐ addTax 50;

✓ 15. Which statement creates a new object using the Person constructor? *1/1
Which statement creates a new Person object called "student"?

- ☒ var student = new Person(); ✓
- ☐ var student = construct Person;
- ☐ var student = Person();
- ☐ var student = construct Person();



- ✓ 16. Which snippet could you add to this code to print "food" to the console?

*1/1

```
class Animal {  
  static belly = [];  
  eat() {  
    Animal.belly.push('food');  
  }  
}  
let a = new Animal();  
a.eat();  
console.log(/* Snippet Here */); //Prints food
```

- ☐ a.prototype.belly[0]
- ☐ Object.getPrototypeOf(a).belly[0]
- ☒ Animal.belly[0]
- ☐ a.belly[0]



- ✓ 17. How would you reference the text 'avenue' in the code shown? *

1/1

```
let roadTypes = ['street', 'road', 'avenue', 'circle'];
```

- ☐ roadTypes.2
- ☐ roadTypes[3]
- ☐ roadTypes.3
- ☒ roadTypes[2]



- ✓ 18. What is the result of running this statement? *

1/1

```
console.log(typeof 42);
```

- ☐ 'float'
- ☐ 'value'
- ☒ 'number'
- ☐ 'integer'



✓ 19. Which method converts JSON data to a JavaScript object? * 1/1

- ☐ JSON.fromString();
- ☒ JSON.parse()
- ☐ JSON.toObject()
- ☐ JSON.stringify()



✓ 20. What would be the result in the console of running this code? * 1/1

```
for (var i = 0; i < 5; i++) {  
  console.log(i);  
}
```

- ☐ 1 2 3 4 5
- ☐ 1 2 3 4
- ☒ 0 1 2 3 4
- ☐ 0 1 2 3 4 5



✓ 21. Which Variable-defining keyword allows its variable to be accessed (as undefined) before the line that defines it? *1/1

- ☐ all of them
- ☐ const
- ☒ var
- ☐ let



✓ 22. What is the result of running this code? *

1/1

```
sum(10, 20);  
diff(10, 20);  
function sum(x, y) {  
  return x + y;  
}  
  
let diff = function (x, y) {  
  return x - y;  
};
```

- ☐ 30, ReferenceError, 30, -10
- ☒ 30, ReferenceError
- ☐ 30, -10
- ☐ ReferenceError, -10



✓ 23. Which keyword is used to create an error? *

1/1

- ☒ throw
- ☐ exception
- ☐ catch
- ☐ error



✓ 24. What statement can be used to skip an iteration in a loop? *

1/1

- ☐ break
- ☐ pass
- ☐ skip
- ☒ continue



✓ 25. Which choice is a valid example for an arrow function? * 1/1

- ☒ (a,b) => c ✓
- ☐ a, b => {return c;}
- ☐ a, b => c
- ☐ { a, b } => c

✓ 26. Which term is commonly used to refer to converting data to JSON? * 1/1

- ☐ unpacking
- ☒ serialization ✓
- ☐ deserialization
- ☐ parsing

✓ 27. Which code uses the correct JSON syntax to encode the key/value pair shown? *1/1

accountNum: '000605802'

- ☐ accountNum: 000605802
- ☐ accountNum: "000605802"
- ☐ "accountNum": 000605802
- ☒ "accountNum": "000605802" ✓

✓ 28. Transferring JSON information from client to server and back again often includes HTTP requests. Method includes HTTP requests. Method with the best choice describing its use. choice describing its use.

1. Sends data to specific server to create or update information.
2. Sends data to specific server to create or update information without the risk of creating the resource
3. Previews what the GET request response might be without the body of the text.
4. Learns the communication channels used by the target source.
5. Requests information from a specific source.
6. Removes information.

- ☐ 1.GET 2.PUT 3.HEADER 4.OPTIONS [5.POST](#) 6.DELETE
- ☐ [1.POST](#) 2.DELETE 3.OPTIONS 4.HEADER 5.GET 6.PUT
- ☒ [1.POST](#) 2.PUT 3.HEADER 4.OPTIONS 5.GET 6.DELETE ✓
- ☐ 1.GET 2.TRASFER 3.OPTIONS 4.HEADER [5.POST](#) 6.PUT

✓ 29. How do you start a Node application, if the entry file is indexjs? * 1/1

- ☐ nodemon start
- ☐ start index.js
- ☒ node index.js
- ☐ node start



✓ 30. What can you export with module.exports? * 1/1

- ☐ only objects.
- ☐ only functions
- ☐ only variables and arrays
- ☒ functions, objects, arrays, or anything you assign to the module



✓ 31. If you want to import just the Component from the React library, what syntax do you use? *1/1

- ☐ import React.Component from 'react'
- ☐ import [Component] from 'react'
- ☐ import Component from 'react'
- ☒ import { Component } from 'react'



✓ 32. If you see the following import in a file, what is being used for state management in the component? *1/1
import React, {useState} from 'react';

- ☒ React Hooks
- ☐ stateful components
- ☐ math
- ☐ class components



✗ 33. Using object literal enhancement, you can put values back into an object. When you log person to the console, what is the output?

*0/1

```
const name = 'Rachel';  
const age = 31;  
const person = { name, age };  
console.log(person);
```

- ☐ {{name: "Rachel", age: 31}}
- ☒ {name: "Rachel", age: 31}
- ☐ {person: "Rachel", person: 31}
- ☐ {person: {name: "Rachel", age: 31}}

✗

Correct answer

- ☒ {person: "Rachel", person: 31}

✓ 34. A representation of a user interface that is kept in memory and is synced with the "real" DOM is called what?

*1/1

- ☒ virtual DOM
- ☐ DOM
- ☐ virtual elements
- ☐ shadow DOM

✓

✓ 35. What package contains the render() function that renders a React element tree to the DOM?

*1/1

- ☐ React
- ☒ ReactDOM
- ☐ Render
- ☐ DOM

✓



✓ 36. Which answer best describes a function component? *

1/1

- ☐ A function component is the same as a class component.
- ☒ A function component accepts a single props object and returns a React element. ✓
- ☐ A function component is the only way to create a component.
- ☐ A function component is required to create a React component.

✓ 37. If you wanted to display the count state value in the component, what do you need to add to the curly braces in the h1? *1/1

```
class Ticker extends React.component {  
  constructor(props) {  
    super(props);  
    this.state = { count: 0 };  
  }  
  render() {  
    return <h1>{ }</h1>;  
  }  
}
```

- ☒ this.state.count ✓
- ☐ count
- ☐ state
- ☐ state.count

✓ 38. Which function is used to update state variables in a React class component? *1/1

- ☐ replaceState
- ☐ refreshState
- ☐ updateState
- ☒ setState ✓



✓ 39. What is setCount? *

1/1

```
const [count, setCount] = useState(0);
```

- ☐ the initial state value
- ☐ a variable
- ☐ a state object
- ☒ a function to update the state



✓ 40. What command can you use to generate a React project? *

1/1

- ☐ react-starter
- ☒ create-react-app
- ☐ react-gen
- ☐ react-start



This content is neither created nor endorsed by Google. - [Terms of Service](#) - [Privacy Policy](#)

Google Forms





