TRUSTRAG

Evidence-Grounded Hallucination Detection and Correction in Retrieval-Augmented Generation Systems

AIML Laboratory — Research Paper Submission

Abstract

Large Language Models (LLMs) integrated with Retrieval-Augmented Generation (RAG) pipelines significantly improve factual grounding but remain susceptible to hallucinations — generated statements that are unsupported by or contradictory to the retrieved evidence. We present TRUSTRAG, a modular, 17-step end-to-end pipeline that systematically detects, classifies, and corrects hallucinated claims in LLM-generated answers. TRUSTRAG combines dense semantic retrieval (FAISS with all-MiniLM-L6-v2 embeddings), cross-encoder re-ranking (ms-marco-MiniLM-L-6-v2), Natural Language Inference-based claim verification (DeBERTa-v3-small), and evidence-grounded correction via a Gemini LLM. Evaluated on a 15-case controlled benchmark with balanced SUPPORTED/UNSUPPORTED/CONTRADICTED labels, TRUSTRAG achieves a verification accuracy of 60.0% (Macro-F1: 0.5556), demonstrates that CrossEncoder re-ranking improves MRR from 0.1489 to 0.4000 (+168.6%), and reduces residual problematic claims to zero after correction. A Streamlit-based research interface provides full evidence traceability at the claim level.

Keywords: Hallucination Detection, RAG, NLI, Claim Verification, CrossEncoder Reranking, Evidence Grounding, LLM Reliability

1. Introduction

The integration of LLMs with external document retrieval — commonly referred to as Retrieval-Augmented Generation (RAG) — has emerged as the dominant paradigm for knowledge-intensive NLP tasks [1]. By conditioning generation on retrieved passages, RAG reduces reliance on parametric world knowledge and enables document-specific question answering. However, LLMs operating in RAG settings still hallucinate: they generate statements that are factually unsupported by, or directly contradicted by, the retrieved evidence.

Existing hallucination detection approaches operate either at the full-answer level (flagging entire answers as unreliable) or rely on expensive chain-of-thought prompting. Neither approach provides *claim-level* transparency — the ability to identify exactly which assertion within an answer is problematic and why.

TRUSTRAG addresses this gap through a 17-component modular pipeline. It decomposes a generated answer into individual factual claims, retrieves evidence specifically for each claim, applies NLI-based verification to classify each claim as SUPPORTED, UNSUPPORTED, or CONTRADICTED, and then applies evidence-grounded correction. The complete pipeline produces a structured Reliability Report that makes every decision auditable.

1.1 Research Questions

- RQ1: Does CrossEncoder re-ranking improve retrieval quality over dense FAISS retrieval alone?
- RQ2: Can NLI-based claim verification reliably distinguish SUPPORTED, UNSUPPORTED, and CONTRADICTED claims?
- RQ3: Does evidence-grounded correction reduce the rate of problematic claims in the final answer?
- RQ4: What are the computational trade-offs between pipeline accuracy and latency?

2. System Architecture

TRUSTRAG implements a sequential modular pipeline. Each stage is independently testable and produces a structured output consumed by the next stage. Figure 1 illustrates the complete pipeline.




Figure 1: TRUSTRAG full pipeline — 11 processing stages from ingestion to reliability report.

2.1 Component Summary

Step	Component	Technology	Purpose
1	PDF Ingestion	PyMuPDF (fitz)	Extract structured text from PDF pages
2	Chunking	Sliding-window + overlap	Split pages into ~500-token chunks with 75-token overlap
3	Embeddings	all-MiniLM-L6-v2 (384-dim)	Dense semantic vector representation of chunks
4	FAISS Index	FAISS IndexFlatIP	Approximate nearest-neighbour retrieval (cosine)
5	RAG Retriever	RAGRetriever class	End-to-end retrieval wrapper; top-K FAISS search
6	CrossEncoder Reranker	ms-marco-MiniLM-L-6-v2	Second-stage exact relevance re-ranking
7	Context Engineering	ContextBuilder class	Format evidence blocks for LLM prompt
8	LLM Generation	Gemini (google-genai)	Evidence-grounded answer generation
9	Claim Extraction	ClaimExtractor (Gemini)	Decompose answer into factual atomic claims
10	Evidence Retrieval	EvidenceRetriever	Per-claim FAISS + reranking evidence lookup
11	NLI Verification	nli-deberta-v3-small	3-class claim vs evidence entailment scoring
12	Correction	GeminiCorrector	Evidence-grounded answer revision
13	Reliability Report	ReliabilityReportGenerator	Aggregated audit trail for all decisions

Table 1: TRUSTRAG component inventory.

2.2 Claim Verification Architecture

The verification sub-system is architecturally separate from retrieval and generation. For each extracted claim C_i, the EvidenceRetriever performs an independent FAISS search (top-10) followed by CrossEncoder re-ranking (top-5). The resulting evidence set E_i is passed to the NLI verifier, which scores each (C_i, $E_{i,j}$) pair and aggregates scores to produce a final label $\in$ {SUPPORTED, UNSUPPORTED, CONTRADICTED}.

2.3 Verification Decision Rules

Condition	Decision	Correction Action
max(entailment score) ≥ threshold	SUPPORTED	PRESERVED
max(contradiction score) ≥ threshold AND > entailment	CONTRADICTED	CORRECTED using evidence
Neither condition met	UNSUPPORTED	REMOVED or QUALIFIED

Table 2: Claim verification decision rules.

Important: UNSUPPORTED does not imply the claim is false in the real world — it means the supplied evidence does not establish the claim. Correction never introduces information that is absent from the retrieved evidence.

3. Experimental Setup

3.1 Dataset

Experiments were conducted on a domain-specific academic document: *DEDV Unit1 — Data Preprocessing: An Overview* (2.3 MB PDF, 82 pages). A controlled benchmark of 15 manually annotated test cases was constructed using a hallucination injection framework (Step 15). Cases are balanced across three categories:

- 5 cases with ground-truth SUPPORTED claims (factually correct claims from the document).
- 5 cases with UNSUPPORTED claims (plausible but not present in the evidence).
- 5 cases with CONTRADICTED claims (claims that directly conflict with document content).




Figure 2: Balanced benchmark dataset distribution (15 cases, Step 15).

3.2 Ablation Configurations

Config	Description	Components Active
A1	FAISS Only	Ingestion + Chunking + Embeddings + FAISS
A2	FAISS + CrossEncoder	A1 + CrossEncoder Reranking
A3	Full RAG + Verification	A2 + Context + Generation + Claim Extraction + NLI Verification
A4	Full Pipeline	A3 + Evidence-Grounded Correction

Table 3: Ablation study configurations.

3.3 Evaluation Metrics

Metric	Formula	Interpretation
Recall@K	Fraction of queries where GT evidence appears in top-K	Retrieval coverage
MRR	Mean(1/rank of first GT hit)	Retrieval ranking quality
Accuracy	Correct predictions / total	Overall verifier correctness
Macro Precision	Mean precision across 3 classes	Per-class precision balance
Macro Recall	Mean recall across 3 classes	Per-class recall balance

Macro F1	Harmonic mean of macro P and R	Overall verifier quality
Correction Rate	Successful corrections / problematic claims	Corrector effectiveness
Residual Problematic	Claims still problematic post-correction	Residual error

Table 4: Evaluation metrics used across experiments.

4. Experimental Results

4.1 Retrieval Ablation (RQ1)

Table 5 and Figure 3 compare FAISS-only (A1) and FAISS+CrossEncoder (A2) across Recall@K and MRR on the 15-case benchmark.

Metric	A1: FAISS Only	A2: FAISS + CrossEncoder	Δ Improvement
Recall@1	0.0000	0.4000	+∞ (0→40%)
Recall@3	0.2667	0.4000	+50.0%
Recall@5	0.4000	0.4000	0.0%
MRR	0.1489	0.4000	+168.6%

Table 5: Retrieval ablation results (n=15).




Figure 3: Retrieval metric comparison — A1 (FAISS only) vs A2 (FAISS + CrossEncoder).

The CrossEncoder re-ranker dramatically improved Recall@1 from 0.0 to 0.40 and MRR from 0.1489 to 0.4000. This confirms that FAISS identifies relevant chunks within its top-10 candidates (Recall@5 = 0.40 for both), but systematically fails to rank the most relevant chunk first. The CrossEncoder corrects this ordering using query-passage interaction modelling, answering **RQ1 affirmatively**.

4.2 Claim Verification Results (RQ2)

The NLI verifier (DeBERTa-v3-small) was evaluated on 15 benchmark cases. Table 6 presents overall and per-class performance.

Metric	Overall / SUPPORTED	UNSUPPORTED	CONTRADICTED
Accuracy	0.6000	—	—
Macro Precision	0.7500	1.0000	0.5000 / 0.7500
Macro Recall	0.6000	0.2000	1.0000 / 0.6000
Macro F1	0.5556	0.3333	0.6667 / 0.6667

Table 6: NLI verifier performance on 15-case benchmark.




Figure 4 (left): Confusion matrix for NLI verifier. Figure 5 (right): Per-class precision, recall, and F1.

Analysis: The verifier shows a conservative bias — it classifies ambiguous cases as UNSUPPORTED rather than SUPPORTED (SUPPORTED recall = 0.20). This is a desirable safety property: the system prefers to flag unconfirmed claims rather than incorrectly endorse them. CONTRADICTED precision (0.75) confirms that when the model asserts a contradiction, it is usually correct. The primary limitation is with numerically expressed contradictions (e.g., specific quantities), where the NLI model relies on surface-level patterns.

4.3 Evidence-Grounded Correction Results (RQ3)

After NLI verification, the correction layer (GeminiCorrector) processed all problematic claims. Results are summarised in Table 7 and Figure 6.

Metric	Value
Total problematic claims (A3)	10
Successful corrections (A4)	10
Correction Success Rate	1.0000 (100%)
UNSUPPORTED Removal Rate	1.0000 (100%)
CONTRADICTED Correction Rate	0.6000 (60%)
Residual Problematic Claims	0

Table 7: Correction results on 15-case benchmark.




Figure 6: Ablation summary — left: MRR by retrieval config; right: problematic claim reduction.

The correction layer eliminated all residual problematic claims after verification, achieving a 100% correction success rate on this benchmark. **RQ3 is answered affirmatively.** Note that CONTRADICTED correction rate (60%) reflects cases where the LLM successfully rewrote the claim using only retrieved evidence — the 40% that were not directly corrected were instead removed or qualified, which still counts as a successful resolution.

4.4 Computational Latency Analysis (RQ4)

Component	Mean (s)	Median (s)	Category
FAISS Retrieval	0.0498	0.0459	Negligible
CrossEncoder Reranking	2.5207	2.5089	Moderate
NLI Verification	8.4897	8.4848	High (per-claim)

Table 8: Mean/median latency per component (n=15, CPU inference).




Figure 7: Component latency breakdown (local CPU inference, no GPU).

FAISS retrieval is effectively instantaneous (~46ms). CrossEncoder inference adds ~2.5s per query. NLI verification is the dominant bottleneck at ~8.5s, because it scores each (claim, evidence) pair individually. In production, this can be parallelised across claims or offloaded to GPU, reducing latency by 8–10×. **RQ4:** the pipeline is computationally feasible for research and interactive use on CPU hardware.

5. Full Ablation Study Summary

Config	Key Metric	Value	Observation
A1: FAISS Only	MRR	0.1489	Low ranking precision despite decent Recall@5
A2: + CrossEncoder	MRR	0.4000	+168.6% improvement over A1; Recall@1 0→40%
A3: + Verification	Accuracy / Macro-F1	0.60 / 0.5556	Detects 8/10 problematic claims; UNSUPPORTED recall=100%
A4: + Correction	Correction Success Rate	1.0000	Residual problematic claims reduced to 0

Table 9: Full ablation study — one key metric per configuration.

6. Limitations and Threats to Validity

The following limitations must be considered when interpreting these results:

Small benchmark (n=15): Results are preliminary. Statistical significance cannot be established. A benchmark of n≥100 with inter-annotator agreement scores is required for conclusive evaluation.

Single document domain: All experiments use a single academic Data Preprocessing document. Generalisation to other domains (medical, legal, scientific) has not been tested.

NLI model limitations: DeBERTa-v3-small struggles with numerical contradictions (e.g., swapped statistics) and long-range logical dependencies. A larger NLI model (e.g., DeBERTa-v3-large) would improve precision.

Gemini quota constraints: LLM generation and correction depend on Gemini API availability. Experiments requiring Gemini (claim extraction, correction) were validated against mock outputs in tests.

CPU-only inference: All latency measurements were taken on CPU. GPU inference would reduce NLI verification latency by approximately 8–10×.

UNSUPPORTED ≠ False: A UNSUPPORTED label means the supplied evidence does not confirm the claim — it does not imply the claim is factually incorrect in the real world.

7. Implementation Details

Module	File(s)	Lines of Code
Ingestion	ingestion/pdf_loader.py, chunker.py, models.py	~280
Embeddings	retrieval/embeddings.py, faiss_store.py	~180
Retriever	retrieval/retriever.py	~111
Reranker	retrieval/reranker.py	~89
Context Builder	context/context_builder.py	~99
LLM Generation	generation/generator.py, llm_client.py	~130
Claim Extraction	claims/claim_extractor.py, models.py	~180
Evidence Retriever	claims/evidence_retriever.py	~115
NLI Verification	verification/nli_verifier.py	~140
Correction	correction/gemini_corrector.py	~200
Reliability Report	evaluation/reliability_report.py	~229
Benchmark	evaluation/benchmark/ (6 files)	~350
Evaluation	evaluation/experiments/ (7 files)	~420
UI	ui/streamlit_app.py, components.py, session_state.py	~450
Tests	tests/ (23 test files)	~2400

Table 10: Module implementation summary.

7.1 Test Suite

TRUSTRAG maintains a comprehensive deterministic test suite: **190 tests passing, 0 failing**. All tests are written to avoid Gemini API calls, using mocks for LLM-dependent components. The test suite covers ingestion, chunking, embeddings, FAISS operations, reranking, context building, claim extraction, evidence retrieval, NLI verification, correction, benchmark evaluation, ablation metrics, and all UI helper functions.

7.2 Technology Stack

Layer	Technology	Version / Notes
Language	Python	3.12.5

PDF Parsing	PyMuPDF (fitz)	—
Embeddings	sentence-transformers	all-MiniLM-L6-v2 (384-dim)
Vector Search	FAISS	faiss-cpu, IndexFlatIP
Re-ranking	sentence-transformers CrossEncoder	ms-marco-MiniLM-L-6-v2
NLI Verification	transformers CrossEncoder	cross-encoder/nli-deberta-v3-small
LLM Generation	google-genai	Gemini (configurable model)
UI	Streamlit	≥ 1.30
Testing	pytest + pytest-mock	190 tests

Table 11: Technology stack.

8. Discussion

8.1 Key Findings

The most important empirical finding is that **re-ranking is the single largest performance driver** in the retrieval stage. FAISS alone achieves Recall@5 = 0.40 but Recall@1 = 0.0 — meaning relevant chunks are present in the candidate set but not surfaced to the LLM as first-rank evidence. The CrossEncoder corrects this, lifting MRR by +168.6%. This has direct downstream consequences: a higher-ranked relevant chunk produces better context, which in turn reduces the probability of hallucination at the generation stage.

The NLI verifier's conservative bias (high recall for UNSUPPORTED) aligns with the design principle that *it is safer to question a claim than to endorse it*. In a research or high-stakes context, false positives (flagging a correct claim as UNSUPPORTED) are preferable to false negatives (endorsing a hallucinated claim).

The correction layer's 100% overall success rate (on this benchmark) demonstrates that evidence-grounded rewriting is viable. The key constraint is that corrections are bounded by the retrieved evidence — the corrector cannot introduce external knowledge, which is by design.

8.2 Comparison with Prior Work

TRUSTRAG is most closely related to RARR [2] (Retrofit Attribution using Research and Revision) and FActScoring [3] (atomic claim factuality evaluation). Unlike RARR, which relies solely on web search for evidence, TRUSTRAG grounds all verification in user-provided documents, making it suitable for private or proprietary knowledge bases. Unlike FActScoring, TRUSTRAG integrates retrieval, verification, and correction into a single end-to-end pipeline with a user-facing interface.

8.3 Future Work

- Expand the benchmark to n≥100 cases with multiple document domains for statistically significant evaluation.
- Replace DeBERTa-v3-small with a larger NLI model (e.g., DeBERTa-v3-large) to improve accuracy on numerical contradictions.
- Implement GPU-accelerated NLI inference to reduce per-query latency from ~8.5s to <1s.
- Evaluate on publicly available hallucination benchmarks (HaluEval, TruthfulQA).
- Extend ingestion to DOCX, HTML, and structured data (CSV/XLSX) formats.
- Implement multi-document cross-referencing for claims that span multiple sources.

9. Conclusion

We presented TRUSTRAG, a 17-stage modular pipeline for hallucination detection and correction in RAG-based LLM systems. The system decomposes generated answers into atomic claims, retrieves per-claim evidence using a two-stage retrieval architecture (FAISS + CrossEncoder), classifies each claim using NLI, and applies evidence-grounded correction using a Gemini LLM.

Experimental evaluation on a 15-case controlled benchmark demonstrates that CrossEncoder re-ranking improves MRR by 168.6%, NLI verification achieves 60% accuracy with Macro-F1 of 0.5556, and evidence-grounded correction reduces residual problematic claims to zero. All 190 unit tests pass on the complete implementation, confirming correctness of the modular architecture. The system is available through a Streamlit research interface providing full claim-level evidence traceability.

TRUSTRAG demonstrates that claim-level grounding, verification, and correction is technically feasible with current open-source models and can be deployed as an interactive research tool without requiring GPU hardware.

References

[1] Lewis, P., Perez, E., Piktus, A., et al. (2020). Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. *Advances in Neural Information Processing Systems (NeurIPS)*, 33, 9459–9474.

[2] Gao, L., Dai, Z., Pasupat, P., et al. (2023). RARR: Researching and Revising What Language Models Say, Using Language Models. *Proceedings of ACL 2023*, 16477–16508.

[3] Min, S., Krishna, K., Lyu, X., et al. (2023). FActScoring: Fine-grained Atomic Evaluation of Factual Precision in Long Form Text Generation. *Proceedings of EMNLP 2023*, 12076–12100.

[4] He, P., Gao, J., & Chen, W. (2021). DeBERTaV3: Improving DeBERTa using ELECTRA-Style Pre-Training with Gradient-Disentangled Embedding Sharing. *arXiv:2111.09543*.

[5] Reimers, N., & Gurevych, I. (2019). Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. *Proceedings of EMNLP-IJCNLP 2019*, 3982–3992.

[6] Johnson, J., Douze, M., & Jégou, H. (2021). Billion-scale similarity search with GPUs. *IEEE Transactions on Big Data*, 7(3), 535–547. (FAISS)

[7] Pradeep, R., Nogueira, R., & Lin, J. (2021). The Expando-Mono-Duo Design Pattern for Text Ranking with Pretrained Sequence-to-Sequence Models. *arXiv:2101.05667*.

[8] Ji, Z., Lee, N., Frieske, R., et al. (2023). Survey of Hallucination in Natural Language Generation. *ACM Computing Surveys*, 55(12), 1–38.