
No More Whack-a-Mole:

How to Find and Prevent Entire Classes of Security Vulnerabilities






About Me



- → Developer Advocate for GitHub
 - ◆ (formerly Semmle, acquired by GitHub)
 - (formerly core developer for LGTM.com)
- → Passionate about Open Source, Security, Privacy, Cryptography, Vulnerability Research, Code Quality & Lighting.
- → Twitter: @samlanning GitHub: @s0



A story of many bugs (CVE-2017-8046)



https://blog.semmle.com/spring-data-rest-CVE-2017-8046-ql/







A story of many bugs 2




See Also: CVE-2012-0391, CVE-2012-0392, CVE-2012-0394, CVE-2013-1965, CVE-2013-1966, CVE-2013-2115, CVE-2013-2134, CVE-2013-2135, CVE-2016-0785, CVE-2016-3090





https://www.reddit.com/r/gifs/comments/2nyeb1/arcade_game_for_cats/







Solution:

When a new mistake is discovered, try and find similar mistakes across your code base

Variant Analysis?

"After doing this [root cause analysis], our next step is variant analysis: finding and investigating any variants of the vulnerability. It's important that we find all such variants and patch them simultaneously, otherwise we bear the risk of these being exploited in the wild."

- Steven Hunter, MSRC Vulnerabilities & Mitigations team







```
SPR = Product::select('id', 'image', 'mirror')-whereIn('cat_id', [156,162])-where('color_id', 13);
Idea
                                   sbar = new ProgressBar(5this->output, SPR->count());
bootstrap
                                    Sbar->setFormat('deh....
                                                                  ---(1->setBarkidth(50)->start();
config
database
                                    Sprod
node modules
                                               , sproduct->imau
resources
                                    _contents(config('app.url
                                                                                         eruz/min/" . Sproduct->image);
                                 ublic_path('imgs/products/vi
storage
                                                                                            's/min/' . Sproduct->image);
tests
                                                                                             tt->image, Stile min);
.env.example
                             params->unique('name') as $par
gitattributes
                                                                                               V" . Sproduct⇒inage);
.gitignore
                                                                                                y" . Sproduct⇒image);
htaccess
                                                                                                image, Sfile_min);
                             nts->where('id', $par->pivot->
.local.env
.phpstorm.meta.php
.prod.env
                              t' => $var=>sort, 'name' => $v
123.php
ide helper.php
artisan
                                                                                           still:
composer json
                                   Unique('name') as par
                                                                                          Aderbib:
composer lock
                                      '->where('id', $par->pivot
                                          ' $var->sort, 'name' =
                             33
                             34
                                                                                  riants=sumere('id', Svariant_id)=>first();
                             35
                             36
                             38
                                             Svariant = $this->model->categories->first();
                             39
                             40
                                             Sgender = Swartant->gender:
```

pitmebel

Code Navigation / IDE



* sourcegraph


















Never enough security researchers



Even hi-tech leaders, can't find enough talent


The security skills gap is only expected to grow








Automating Variant Analysis







Automating Variant Analysis









```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // get first argument -
    // from Chakra, acquire pointer to array
    BYTE* pBuffer;
    UINT bufferSize;
    hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
    // get second argument -
    // from Chakra, obtain an integer value
    int someValue;
    hr = Jscript::VarToInt(args[2], &someValue);
    // perform some operation on the array acquired previously
    doSomething(pBuffer, bufferSize);
C++
```







```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // get first argument -
    // from Chakra, acquire pointer to array
    BYTE* pBuffer;
    UINT bufferSize;
   hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
    // from Chakra, obtain an integer value
    int someValue;
    hr = Jscript::VarToInt(args[2], &someValue);
    doSomething(pBuffer, bufferSize);
C++
```







```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // get first argument -
    // from Chakra, acquire pointer to array
    BYTE* pBuffer;
    UINT bufferSize;
    hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
    // get second argument -
    // from Chakra, obtain an integer value
    int someValue;
    hr = Jscript::VarToInt(args[2], &someValue);
    doSomething(pBuffer, bufferSize);
C++
```







```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // get first argument -
    // from Chakra, acquire pointer to array
    BYTE* pBuffer;
    UINT bufferSize;
    hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
    // get second argument -
    // from Chakra, obtain an integer value
    int someValue;
    hr = Jscript::VarToInt(args[2], &someValue);
    // perform some operation on the array acquired previously
    doSomething(pBuffer, bufferSize);
C++
```







```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // from Chakra, acquire pointer to array
    BYTE* pBuffer;
    UINT bufferSize;
    hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
    // from Chakra, obtain an integer value
    int someValue;
    hr = Jscript::VarToInt(args[2], &someValue);
    // perform some operation on the array acquired previously
    doSomething(pBuffer, bufferSize);
C++
```







```
var buf = new ArrayBuffer(length);
var arr = new Uint8Array(buf);
var param = {}
param.valueOf = function() {
    neuter(buf); // neuter `buf` by e.g. posting it to a web worker
    gc(); // trigger garbage collection
    return 0;
};
vulnerableFunction(arr, param);
JavaScript
```







```
var buf = new ArrayBuffer(length);
var arr = new Uint8Array(buf);

var param = {}
param.valueOf = function() {
    neuter(buf); // neuter `buf` by e.g. posting it to a web worker gc(); // trigger garbage collection return 0;
};

vulnerableFunction(arr, param);

JavaScript
```







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
   // variable is defined at "def", and used at "use"
   v.getAnAccess() = def and v.getAnAccess() = use
   // "call" may eventually call a function that calls back into JS code
   and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
   // "call" happens after "def"
   and def.getASuccessor+() = call
   // "use" happens after "call"
   and call.getASuccessor+() = use
   select def, call, use
Query
```

*slightly modified query from:







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
  v.getAnAccess() = def and v.getAnAccess() = use
  // "call" may eventually call a function that calls back into JS code
  and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
  and def.getASuccessor+() = call
  and call.getASuccessor+() = use
select def, call, use
Query
```

*slightly modified query from:







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
   // variable is defined at "def", and used at "use"
   v.getAnAccess() = def and v.getAnAccess() = use
   // "call" may eventually call a function that calls back into JS code
   and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
   // "call" happens after "def"
   and def.getASuccessor+() = call
   // "use" happens after "call"
   and call.getASuccessor+() = use
   select def, call, use
Query
```

*slightly modified query from:







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
    // variable is defined at "def", and used at "use"
    v.getAnAccess() = def and v.getAnAccess() = use
    // "call" may eventually call a function that calls back into JS code
    and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
    // "call" happens after "def"
    and def.getASuccessor+() = call
    // "use" happens after "call"
    and call.getASuccessor+() = use

    select def, call, use

Query
```

*slightly modified query from:







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
    // variable is defined at "def", and used at "use"

> v.getAnAccess() = def and v.getAnAccess() = use
    // "call" may eventually call a function that calls back into JS code
    and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
    // "call" happens after "def"
    and def.getASuccessor+() = call
    // "use" happens after "call"
    and call.getASuccessor+() = use
    select def, call, use
Query
```

*slightly modified query from:







```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // from Chak va, acquire pointer to array
    BYTE* pBuffer;
    UINT bufferSize:
    hr = Jscrip*:GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
                                                     def
    // get second argument -
    // from Chakra, obtain an integer value
    int someValue
    hr = Jscript::VarToInt(args[2], &someValue);
    // perform some operation on the array acquired previously
    doSomething(pBuffer, bufferSize);
                    use
C++
```







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
   // variable is defined at "def", and used at "use"
   v.getAnAccess() = def and v.getAnAccess() = use
   // "call" may eventually call a function that calls back into JS code
   and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
   // "call" happens after "def"
   and def.getASuccessor+() = call
   // "use" happens after "call"
   and call.getASuccessor+() = use
   select def, call, use
Query
```

*slightly modified query from:







```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // from Chakra, acquire pointer to array
    BYTE* pBuffer;
    UINT bufferSize;
    hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
    // from Chakra, obtain an integer value
    int someValue;
    hr = Jscript::VarToInt(args[2], &someValue);
    doSomething(pBuffer, bufferSize);
C++
```







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
   // variable is defined at "def", and used at "use"
   v.getAnAccess() = def and v.getAnAccess() = use
   // "call" may eventually call a function that calls back into JS code
   and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
   // "call" happens after "def"
   and def.getASuccessor+() = call
   // "use" happens after "call"
   and call.getASuccessor+() = use
   select def, call, use
Query
```

*slightly modified query from:







```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    // get first argument -
    // from Chakra, acquire pointer to array
    BYTE* pBuffer;
                                             1st
    UINT bufferSize;
    hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
                                                    def
    // from Chakra, obtain an integer value
    int someValue;
                         2nd
    hr = Jscript::VarToInt(args[2], &someValue);
    doSomething(pBuffer, bufferSize);
C++
```







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
    // variable is defined at "def", and used at "use"
    v.getAnAccess() = def and v.getAnAccess() = use
    // "call" may eventually call a function that calls back into JS code
    and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
    // "call" happens after "def"
    and def.getASuccessor+() = call
    // "use" happens after "call"
    and call.getASuccessor+() = use
    select def, call, use
Query
```

*slightly modified query from:









```
HRESULT SomeClass::vulnerableFunction(Var* args, UINT argCount, Var* retVal)
    BYTE* pBuffer;
    UINT bufferSize;
    hr = Jscript::GetTypedArrayBuffer(args[1], &pBuffer, &bufferSize);
    // from Chakra, obtain an integer value
    int someValue; 1st
    hr = Jscript::VarToInt(args[2], &someValue);
    doSomething(pBuffer, bufferSize);
              2nd
                    use
C++
```







```
from Variable v, TypedArrayBufferPointer def, FunctionCall call, VariableAccess use
where
   // variable is defined at "def", and used at "use"
   v.getAnAccess() = def and v.getAnAccess() = use
   // "call" may eventually call a function that calls back into JS code
   and exists(Function g | g.hasName("MethodCallToPrimitive") and call.getTarget().calls+(g))
   // "call" happens after "def"
   and def.getASuccessor+() = call
   // "use" happens after "call"
   and call.getASuccessor+() = use
   select def, call, use
Query
```

*slightly modified query from:







Beyond your own code

- → Make your (general-purpose) queries/checks open source!
- → Use external queries/checks!













Metadata	Name (path)	Data
<metadata></metadata>	lib/foo	<7731911f
<metadata></metadata>	lib/bar	<236dbe48
<metadata></metadata>	usr/foo	<e80b70d2< td=""></e80b70d2<>
<metadata></metadata>	usr/foo/bar	<63f30ae0









```
../../.bashrc
../../../../etc/crontab
```







```
Enumeration<ZipEntry> entries = zip.getEntries()
while (entries.hasMoreElements()) {
    ZipEntry e = entries.nextElement();
    File f = new File(destinationDir, e.getName());
    InputStream input = zip.getInputStream(e);
    IOUtils.copy(input, write(f));
Java
```








```
Enumeration<ZipEntry> entries = zip.getEntries()
while (entries.hasMoreElements()) {
    ZipEntry e = entries.nextElement();
 → File f = new File(destinationDir, e.getName());
    InputStream input = zip.getInputStream(e);
    IOUtils.copy(input, write(f));
Java
```










```
Enumeration<ZipEntry> entries = zip.getEntries()
while (entries.hasMoreElements()) {
    ZipEntry e = entries.nextElement();
    File f = new File(destinationDir, e.getName());

    if (!f.toPath().normalize().startsWith(destinationDir.toPath()))
        throw new IOException("Bad zip entry");
    InputStream input = zip.getInputStream(e);
    IOUtils.copy(input, write(f));
}
Java
```













No vulnerability response process?

Independent security researcher / consultant?

Get Started

- → Writing / Maintaining Software?
 - Look at which tools other teams are using
 - Try out a selection, choose what works for you
- → Security Researcher?
 - Experiment writing checks / queries with different technologies, see what works for you
 - Blog posts from researchers finding variants









Recap

- → You should do variant analysis (if creating software)
- → Better yet, you should do *automated* variant analysis
- → Checks should be run *continuously*, not once-off!
- → Use and contribute to open-source queries / checks
- → Can use variant analysis to supercharge research
- → VA *compliments* (not replaces) other security practices









Thank You

Questions?





