




# Object Oriented Programming

First Lesson. (Most Important)






# Object Oriented





- A program is made up of many cooperating objects
- Instead of being the “whole program” - each object is a little “island” within the program and cooperatively working with other objects
- A program is made up of one or more objects working together - objects make use of each other’s capabilities


# Object

- An Object is a bit of self-contained Code and Data
- A key aspect of the Object approach is to break the problem into smaller understandable parts (divide and conquer)
- Objects have boundaries that allow us to ignore un-needed detail
- We have been using objects all along: String Objects, Integer Objects, Dictionary Objects, List Objects...









# Definitions



- **Class** - a template
- **Method or Message** - A defined capability of a class
- **Field or attribute**- A bit of data in a class
- **Object or Instance** - A particular instance of a class



# Terminology: Class



Defines the abstract characteristics of a thing (object), including the thing's characteristics (its attributes, **fields** or **properties**) and the thing's behaviors (the things it can do, or **methods**, operations or features). One might say that a **class** is a **blueprint** or factory that describes the nature of something. For example, the **class** Dog would consist of traits shared by all dogs, such as breed and fur color (characteristics), and the ability to bark and sit (behaviors).

[http://en.wikipedia.org/wiki/Object-oriented\\_programming](http://en.wikipedia.org/wiki/Object-oriented_programming)

# Terminology: Instance



One can have an **instance** of a class or a particular object.

The **instance** is the actual object created at runtime. In programmer jargon, the Lassie object is an **instance** of the Dog class. The set of values of the attributes of a particular **object** is called its **state**. The **object** consists of state and the behavior that's defined in the object's class.

Object and Instance are often used interchangeably.

[http://en.wikipedia.org/wiki/Object-oriented\\_programming](http://en.wikipedia.org/wiki/Object-oriented_programming)

# Terminology: Method



An object's abilities. In language, **methods** are verbs. Lassie, being a Dog, has the ability to bark. So bark() is one of Lassie's methods. She may have other **methods** as well, for example sit() or eat() or walk() or save\_timmy(). Within the program, using a **method** usually affects only one particular object; all Dogs can bark, but you need only one particular dog to do the barking

Method and Message are often used interchangeably.

[http://en.wikipedia.org/wiki/Object-oriented\\_programming](http://en.wikipedia.org/wiki/Object-oriented_programming)

# Some Python Objects

```
>>> x = 'abc'
>>> type(x)
<class 'str'>
>>> type(2.5)
<class 'float'>
>>> type(2)
<class 'int'>
>>> y = list()
>>> type(y)
<class 'list'>
>>> z = dict()
>>> type(z)
<class 'dict'>
```

```
>>> dir(x)
[ ... 'capitalize', 'casefold', 'center', 'count',
'encode', 'endswith', 'expandtabs', 'find',
'format', ... 'lower', 'lstrip', 'maketrans',
'partition', 'replace', 'rfind', 'rindex', 'rjust',
'rstrip', 'split', 'splitlines', 'startswith', 'strip', 'swapcase',
'title', 'translate', 'upper', 'zfill']
>>> dir(y)
[... 'append', 'clear', 'copy', 'count', 'extend',
'index', 'insert', 'pop', 'remove', 'reverse',
'sort']
>>> dir(z)
[..., 'clear', 'copy', 'fromkeys', 'get', 'items',
'keys', 'pop', 'popitem', 'setdefault', 'update',
'values']
```

# A Sample Class



class is a reserved  
word

Each PartyAnimal  
object has a bit of  
code

Tell the an object  
to run the party()  
code within it

```
class PartyAnimal:  
    x = 0
```

```
    def party(self) :  
        self.x = self.x + 1  
        print("So far",self.x)
```

```
an = PartyAnimal()
```

```
an.party()  
an.party()  
an.party()
```

This is the template  
for making  
PartyAnimal objects

Each PartyAnimal  
object has a bit of  
data

Construct a  
PartyAnimal object  
and store in an

PartyAnimal.party(an)

```
class PartyAnimal:
```

```
    x = 0
```

```
    def party(self) :
```

```
        self.x = self.x + 1
```

```
        print("So far",self.x)
```

```
an = PartyAnimal()
```

```
an.party()
```

```
an.party()
```

```
an.party()
```

```
$ python party1.py
```

```
class PartyAnimal:
```

```
    x = 0
```

```
    def party(self) :
```

```
        self.x = self.x + 1
```

```
        print("So far",self.x)
```

```
an = PartyAnimal()
```

```
an.party()
```

```
an.party()
```

```
an.party()
```

```
$ python party1.py
```

an

x

0

party()



```
class PartyAnimal:
```

```
    x = 0
```

```
    def party(self) :
```

```
        self.x = self.x + 1
```

```
        print("So far",self.x)
```

```
an = PartyAnimal()
```

```
an.party()
```

```
an.party()
```

```
an.party()
```

```
$ python party1.py
```

```
So far 1
```

```
So far 2
```

```
So far 3
```

an  
self

x

party()

```
PartyAnimal.party(an)
```

# Playing with `dir()` and `type()`

# A Nerdy Way to Find Capabilities

- The `dir()` command lists capabilities
- Ignore the ones with underscores - these are used by Python itself
- The rest are real operations that the object can perform
- It is like `type()` - it tells us something \*about\* a variable

```
>>> y = list()
>>> type(y)
<class 'list'>
>>> dir(x)
['__add__', '__class__',
 '__contains__', '__delattr__',
 '__delitem__', '__delslice__',
 '__doc__', ... '__setitem__',
 '__setslice__', '__str__',
 'append', 'clear', 'copy',
 'count', 'extend', 'index',
 'insert', 'pop', 'remove',
 'reverse', 'sort']
>>>
```

```
class PartyAnimal:
    x = 0

    def party(self) :
        self.x = self.x + 1
        print("So far",self.x)

an = PartyAnimal()
```

```
print("Type", type(an))
print("Dir ", dir(an))
```

We can use `dir()` to find the “capabilities” of our newly created class.

```
$ python party3.py
Type <class '__main__.PartyAnimal'>
Dir  ['__class__', ... 'party', 'x']
```

# Try dir() with a String

```
>>> x = 'Hello there'
>>> dir(x)
['__add__', '__class__', '__contains__', '__delattr__',
 '__doc__', '__eq__', '__ge__', '__getattribute__',
 '__getitem__', '__getnewargs__', '__getslice__', '__gt__',
 '__hash__', '__init__', '__le__', '__len__', '__lt__',
 '__repr__', '__rmod__', '__rmul__', '__setattr__', '__str__',
 'capitalize', 'center', 'count', 'decode', 'encode', 'endswith',
 'expandtabs', 'find', 'index', 'isalnum', 'isalpha', 'isdigit',
 'islower', 'isspace', 'istitle', 'isupper', 'join', 'ljust',
 'lower', 'lstrip', 'partition', 'replace', 'rfind', 'rindex',
 'rjust', 'rpartition', 'rsplit', 'rstrip', 'split',
 'splitlines', 'startswith', 'strip', 'swapcase', 'title',
 'translate', 'upper', 'zfill']
```



# Object Lifecycle



[http://en.wikipedia.org/wiki/Constructor\\_\(computer\\_science\)](http://en.wikipedia.org/wiki/Constructor_(computer_science))



# Object Lifecycle



- Objects are created, used, and discarded
- We have special blocks of code (methods) that get called
  - At the moment of creation (constructor)
  - At the moment of destruction (destructor)
- Constructors are used a lot
- Destructors are seldom used

# Constructor

The primary purpose of the constructor is to set up some instance variables to have the proper initial values when the object is created



```
class PartyAnimal:
    x = 0

    def __init__(self):
        print('I am
constructed')

    def party(self) :
        self.x = self.x + 1
        print('So far',self.x)

    def __del__(self):
        print('I am destroyed',
self.x)

an = PartyAnimal()
an.party()
an.party()
an = 42
```

```
$ python party4.py
I am constructed
So far 1
So far 2
I am destroyed 2
an contains 42
```

The constructor and destructor are optional. The constructor is typically used to set up variables. The destructor is seldom used.

# Constructor



In **object oriented programming**, a **constructor** in a class is a special block of statements called when an **object** is created

[http://en.wikipedia.org/wiki/Constructor\\_\(computer\\_science\)](http://en.wikipedia.org/wiki/Constructor_(computer_science))

# Many Instances

- We can create **lots of objects** - the class is the template for the object
- We can store each **distinct object** in its own variable
- We call this having multiple **instances** of the same class
- Each **instance** has its own copy of the **instance variables**

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, z):
        self.name = z
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

s = PartyAnimal("Sally")
j = PartyAnimal("Jim")

s.party()
j.party()
s.party()
```

**Constructors** can have additional **parameters**. These can be used to set up **instance variables** for the particular instance of the class (i.e., for the particular object).

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, z):
        self.name = z
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

s = PartyAnimal("Sally")
j = PartyAnimal("Jim")

s.party()
j.party()
s.party()
```

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, z):
        self.name = z
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

s = PartyAnimal("Sally")
j = PartyAnimal("Jim")

s.party()
j.party()
s.party()
```

S

x: 0

name:

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, z):
        self.name = z
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

s = PartyAnimal("Sally")
j = PartyAnimal("Jim")

s.party()
j.party()
s.party()
```

We have two  
independent  
instances

s

x: 0

name: Sally

j

x: 0

name: Jim

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, z):
        self.name = z
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

s = PartyAnimal("Sally")
j = PartyAnimal("Jim")

s.party()
j.party()
s.party()
```

Sally constructed  
Jim constructed  
Sally party count 1  
Jim party count 1  
Sally party count 2



# Inheritance

<http://www.ibiblio.org/g2swap/byteofpython/read/inheritance.html>

# Inheritance

- When we make a new class - we can reuse an existing class and **inherit** all the capabilities of an existing class and then add our own little bit to make our new class
- Another form of store and reuse
- Write once - reuse many times
- The new class (child) has all the capabilities of the old class (parent) - and then some more

# Terminology: Inheritance



‘Subclasses’ are more specialized versions of a class, which **inherit** attributes and behaviors from their parent classes, and can introduce their own.

[http://en.wikipedia.org/wiki/Object-oriented\\_programming](http://en.wikipedia.org/wiki/Object-oriented_programming)

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, nam):
        self.name = nam
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

class FootballFan(PartyAnimal):
    points = 0
    def touchdown(self):
        self.points = self.points + 7
        self.party()
        print(self.name, "points", self.points)
```

```
s = PartyAnimal("Sally")
s.party()
```

```
j = FootballFan("Jim")
j.party()
j.touchdown()
```

**FootballFan** is a class which extends **PartyAnimal**. It has all the capabilities of **PartyAnimal** and more.

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, nam):
        self.name = nam
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

class FootballFan(PartyAnimal):
    points = 0
    def touchdown(self):
        self.points = self.points + 7
        self.party()
        print(self.name, "points", self.points)
```

```
s = PartyAnimal("Sally")
s.party()
```

```
j = FootballFan("Jim")
j.party()
j.touchdown()
```

S

x:

name: Sally

```
class PartyAnimal:
    x = 0
    name = ""
    def __init__(self, nam):
        self.name = nam
        print(self.name, "constructed")

    def party(self) :
        self.x = self.x + 1
        print(self.name, "party count", self.x)

class FootballFan(PartyAnimal):
    points = 0
    def touchdown(self):
        self.points = self.points + 7
        self.party()
        print(self.name, "points", self.points)
```

```
s = PartyAnimal("Sally")
s.party()
```

```
j = FootballFan("Jim")
j.party()
j.touchdown()
```

j

x:

name: Jim

points:



# Encapsulation



# Encapsulation

- Encapsulation gives you more control over the degree of coupling in your code, it allows a class to change its implementation without affecting other parts of the code.
- Why would you create them? Because some of the private values you may want to change after creation of the object while others may not need to be changed at all.





# Encapsulation





# Encapsulation



# Encapsulation

The method can actually be called using  
`redcar._Car__updateSoftware()`



# Encapsulation



# Encapsulation

```
#!/usr/bin/env python

class Car:

    __maxspeed = 0
    __name = ""

    def __init__(self):
        self.__maxspeed = 200
        self.__name = "Supercar"

    def drive(self):
        print 'driving. maxspeed ' + str(self.__maxspeed)

    def setMaxSpeed(self, speed):
        self.__maxspeed = speed

redcar = Car()
redcar.drive()
redcar.setMaxSpeed(320)
redcar.drive()
```

# Definitions


- **Class** - a template
- **Attribute** - A variable within a class
- **Method** - A function within a class
- **Object** - A particular instance of a class
- **Constructor** - Code that runs when an object is created
- **Inheritance** - The ability to extend a class to make a new class.





Write a Python class to convert an  
integer to a roman numeral.


Assignment






Write a Python class to convert a roman numeral to an integer.

Assignment








Write a Python class to find validity of a string of parentheses, '(', ')', '{', '}', '[' and ']'. These brackets must be close in the correct order, for example "()" and "()[]{}" are valid but "[()", "({[]]" and "{{{" are invalid.


Assignment



Write a Python class to get all possible  
unique subsets from a set of distinct  
integers.


Assignment





Write a Python class to find the three  
elements that sum to zero from a set of  
n real numbers.

Assignment



Thank you  
Miss You...

