


Files in Python

First Lesson.



Opening a File

- Before we can read the contents of the file, we must tell Python which file we are going to work with and what we will be doing with the file
- This is done with the `open()` function
- `open()` returns a “file handle” - a variable used to perform operations on the file
- Similar to “File -> Open” in a Word Processor


Using `open()`

```
fhand = open('mbox.txt', 'r')
```

- `handle = open(filename, mode)`
- returns a handle use to manipulate the file
- `filename` is a string
- `mode` is optional and should be 'r' if we are planning to read the file and 'w' if we are going to write to the file

What is a Handle?

```
>>> fhand = open('mbox.txt')
>>> print(fhand)
<_io.TextIOWrapper name='mbox.txt' mode='r' encoding='UTF-8'>
```



When Files are Missing

```
>>> fhand = open('stuff.txt')
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
FileNotFoundError: [Errno 2] No such file or
directory: 'stuff.txt'
```

The newline Character

- We use a special character called the “**newline**” to indicate when a line ends
- We represent it as `\n` in strings
- **Newline** is still one character - not two

```
>>> stuff = 'Hello\nWorld!'
>>> stuff
'Hello\nWorld!'
>>> print(stuff)
Hello
World!
>>> stuff = 'X\nY'
>>> print(stuff)
X
Y
>>> len(stuff)
3
```

File Processing

A text file can be thought of as a sequence of lines

```
From: stephen.marquard@uct.ac.za Sat Jan  5 09:14:16 2008
Return-Path: <postmaster@collab.sakaiproject.org>
Date: Sat, 5 Jan 2008 09:12:18 -0500
To: source@collab.sakaiproject.org
From: stephen.marquard@uct.ac.za
Subject: [sakai] svn commit: r39772 - content/branches/
```

```
Details: http://source.sakaiproject.org/viewsvn/?view=rev&rev=39772
```

File Processing

A text file has **newlines** at the end of each line

```
From stephen.marquard@uct.ac.za Sat Jan  5 09:14:16 2008\nReturn-Path: <postmaster@collab.sakaiproject.org>\nDate: Sat, 5 Jan 2008 09:12:18 -0500\nTo: source@collab.sakaiproject.org\nFrom: stephen.marquard@uct.ac.za\nSubject: [sakai] svn commit: r39772 - content/branches/\n\n\nDetails:\nhttp://source.sakaiproject.org/viewsvn/?view=rev&rev=39772\n
```


File Handle as a Sequence

- A **file handle** open for read can be treated as a **sequence** of strings where each line in the file is a string in the sequence
- We can use the **for** statement to iterate through a **sequence**
- Remember - a **sequence** is an ordered set

```
xfile = open('mbox.txt')  
for cheese in xfile:  
    print(cheese)
```

Counting Lines in a File

- Open a **file** read-only
- Use a **for** loop to read each line
- **Count** the lines and print out the number of lines

```
fhand = open('mbox.txt')
count = 0
for line in fhand:
    count = count + 1
print('Line Count:', count)
```

```
$ python open.py
Line Count: 132045
```

Reading the *Whole* File

We can **read** the whole
file (newlines and all)
into a **single string**

```
>>> fhand = open('mbox-short.txt')
>>> inp = fhand.read()
>>> print(len(inp))
94626
>>> print(inp[:20])
From stephen.marquar
```

Searching Through a File

We can put an **if** statement in our **for** loop to only print lines that meet some criteria

```
fhand = open('mbox-short.txt')  
for line in fhand:  
    if line.startswith('From:') :  
        print(line)
```

OOPS!

What are all these blank lines doing here?

- Each **line** from the file has a **newline** at the end
- The **print** statement adds a **newline** to each line

```
From: stephen.marquard@uct.ac.za\n\nFrom: louis@media.berkeley.edu\n\nFrom: zqian@umich.edu\n\nFrom: rjlowe@iupui.edu\n\n...
```

Searching Through a File (fixed)

- We can strip the whitespace from the right-hand side of the string using `rstrip()` from the string library
- The newline is considered “white space” and is **stripped**

```
fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if line.startswith('From:') :
        print(line)
```

```
From: stephen.marquard@uct.ac.za
From: louis@media.berkeley.edu
From: zqian@umich.edu
From: rjlowe@iupui.edu
....
```

Skipping with continue


We can conveniently skip a line by using the **continue** statement

```
fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if not line.startswith('From:') :
        continue
    print(line)
```

Using **in** to Select Lines

We can look for a string
anywhere **in** a **line** as our
selection criteria


```
fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if not '@uct.ac.za' in line :
        continue
    print(line)
```



```
From stephen.marquard@uct.ac.za Sat Jan  5 09:14:16 2008
X-Authentication-Warning: set sender to stephen.marquard@uct.ac.za using
-f
From: stephen.marquard@uct.ac.za
Author: stephen.marquard@uct.ac.za
From david.horwitz@uct.ac.za Fri Jan  4 07:02:32 2008
X-Authentication-Warning: set sender to david.horwitz@uct.ac.za using
-f...
```



```
fname = input('Enter the file name: ')
fhand = open(fname)
count = 0
for line in fhand:
    if line.startswith('Subject:') :
        count = count + 1
print('There were', count, 'subject lines in', fname)
```



Prompt for File Name



Enter the file name: mbox.txt
There were 1797 subject lines in mbox.txt

Enter the file name: mbox-short.txt
There were 27 subject lines in mbox-short.txt

Bad File Names

```
fname = input('Enter the file name: ')
try:
    fhand = open(fname)
except:
    print('File cannot be opened:', fname)
    quit()

count = 0
for line in fhand:
    if line.startswith('Subject:') :
        count = count + 1
print('There were', count, 'subject lines in',
fname)
```

Enter the file name: mbox.txt

There were 1797 subject lines in mbox.txt


Enter the file name: na na boo boo

File cannot be opened: na na boo boo



Write a Python program to read an
entire text file.


Assignment





Write a Python program to read first n
lines of a file.


Assignment





Write a Python program to append text
to a file and display the text.


Assignment





Write a Python program to read last n
lines of a file.


Assignment






Write a Python program to read a file
line by line and store it into a list.

Assignment



Lists (Collections) in Python

Second Lesson.





Programming

- **Algorithm**

- A set of rules or steps used to solve a problem

- **Data Structure**

- A particular way of organizing data in a computer

<https://en.wikipedia.org/wiki/Algorithm>

https://en.wikipedia.org/wiki/Data_structure

What is Not a “Collection”?

Most of our **variables** have one value in them - when we put a new value in the **variable**, the old value is overwritten

```
$ python
>>> x = 2
>>> x = 4
>>> print(x)
4
```

A List is a Kind of Collection



- A **collection** allows us to put many values in a single “**variable**”
- A **collection** is nice because we can carry all **many values** around in one convenient package.

```
friends = [ 'Joseph', 'Glenn', 'Sally' ]
```

```
carryon = [ 'socks', 'shirt', 'perfume' ]
```

List Constants

- **List** constants are surrounded by square brackets and the elements in the list are separated by commas
- A **list** element can be any Python object - even **another list**
- A **list** can be empty

```
>>> print([1, 24, 76])
[1, 24, 76]
>>> print(['red', 'yellow',
'blue'])
['red', 'yellow', 'blue']
>>> print(['red', 24, 98.6])
['red', 24, 98.6]
>>> print([ 1, [5, 6], 7])
[1, [5, 6], 7]
>>> print([])
[]
```

We Already Use Lists!

```
for i in [5, 4, 3, 2, 1] :  
    print(i)  
print('Blastoff!')
```

5

4

3

2

1

Blastoff!

Lists and Definite Loops - Best Pals

```
friends = ['Joseph', 'Glenn', 'Sally']  
for friend in friends :  
    print('Happy New Year:', friend)  
print('Done!')
```



Happy New Year: Joseph
Happy New Year: Glenn
Happy New Year: Sally
Done!

```
z = ['Joseph', 'Glenn', 'Sally']  
for x in z:  
    print('Happy New Year:', x)  
print('Done!')
```



Looking Inside Lists

Just like strings, we can get at any single element in a list using an index specified in **square brackets**

Joseph	Glenn	Sally
0	1	2

```
>>> friends = [ 'Joseph', 'Glenn', 'Sally'
]
>>> print(friends[1])
Glenn
>>>
```

Lists are Mutable

- Strings are “immutable” - we cannot change the contents of a string - we must make a new string to make any change
- Lists are “mutable” - we can change an element of a list using the index operator

```
>>> fruit = 'Banana'
>>> fruit[0] = 'b'
Traceback
TypeError: 'str' object does not
support item assignment
>>> x = fruit.lower()
>>> print(x)
banana
>>> lotto = [2, 14, 26, 41, 63]
>>> print(lotto)
[2, 14, 26, 41, 63]
>>> lotto[2] = 28
>>> print(lotto)
[2, 14, 28, 41, 63]
```


How Long is a List?

- The `len()` function takes a `list` as a parameter and returns the number of `elements` in the `list`
- Actually `len()` tells us the number of elements of any set or sequence (such as a string...)

```
>>> greet = 'Hello Bob'
>>> print(len(greet))
9
>>> x = [ 1, 2, 'joe', 99]
>>> print(len(x))
4
>>>
```

Using the range Function

- The **range** function returns a **list of numbers** that range from zero to one less than the **parameter**
- We can construct an index loop using **for** and an integer **iterator**

```
>>> print(range(4))
[0, 1, 2, 3]
>>> friends = ['Joseph', 'Glenn', 'Sally']
>>> print(len(friends))
3
>>> print(range(len(friends)))
[0, 1, 2]
>>>
```

A Tale of Two Loops...

```
friends = ['Joseph', 'Glenn',  
           'Sally']  
  
for friend in friends :  
    print('Happy New Year:', friend)  
  
for i in range(len(friends)) :  
    friend = friends[i]  
    print('Happy New Year:', friend)
```

```
>>> friends = ['Joseph', 'Glenn',  
               'Sally']  
>>> print(len(friends))  
3  
>>> print(range(len(friends)))  
[0, 1, 2]  
>>>
```

Happy New Year: Joseph
Happy New Year: Glenn
Happy New Year: Sally

Concatenating Lists Using +

We can create a new list
by adding two existing
lists together

```
>>> a = [1, 2, 3]
>>> b = [4, 5, 6]
>>> c = a + b
>>> print(c)
[1, 2, 3, 4, 5, 6]
>>> print(a)
[1, 2, 3]
```

Lists Can Be Sliced Using :

```
>>> t = [9, 41, 12, 3, 74, 15]
>>> t[1:3]
[41, 12]
>>> t[:4]
[9, 41, 12, 3]
>>> t[3:]
[3, 74, 15]
>>> t[:]
[9, 41, 12, 3, 74, 15]
```

Remember: Just like in strings, the second number is “up to but not including”

List Methods

```
>>> x = list()
>>> type(x)
<type 'list'>
>>> dir(x)
['append', 'count', 'extend', 'index', 'insert',
'pop', 'remove', 'reverse', 'sort']
>>>
```

<http://docs.python.org/tutorial/datastructures.html>

Building a List from Scratch

- We can create an empty **list** and then add elements using the **append** method
- The **list** stays in order and new elements are **added** at the end of the **list**

```
>>> stuff = list()
>>> stuff.append('book')
>>> stuff.append(99)
>>> print(stuff)
['book', 99]
>>> stuff.append('cookie')
>>> print(stuff)
['book', 99, 'cookie']
```

Is Something in a List?

- Python provides two **operators** that let you check if an item is in a list
- These are logical operators that return **True** or **False**
- They do not modify the list

```
>>> some = [1, 9, 21, 10, 16]
>>> 9 in some
True
>>> 15 in some
False
>>> 20 not in some
True
>>>
```


Lists are in Order


- A **list** can hold many items and keeps those items in the order until we do something to change the order
- A **list** can be **sorted** (i.e., change its order)
- The **sort** method (unlike in strings) means “**sort yourself**”

```
>>> friends = [ 'Joseph', 'Glenn', 'Sally' ]
>>> friends.sort()
>>> print(friends)
['Glenn', 'Joseph', 'Sally']
>>> print(friends[1])
Joseph
>>>
```

Built-in Functions and Lists


- There are a number of **functions** built into **Python** that take **lists** as parameters
- Remember the loops we built? These are much simpler.

```
>>> nums = [3, 41, 12, 9, 74, 15]
>>> print(len(nums))
6
>>> print(max(nums))
74
>>> print(min(nums))
3
>>> print(sum(nums))
154
>>> print(sum(nums)/len(nums))
25.6
```



```
total = 0
count = 0
while True :
    inp = input('Enter a number: ')
    if inp == 'done' : break
    value = float(inp)
    total = total + value
    count = count + 1
```

```
average = total / count
print('Average:', average)
```



```
Enter a number: 3
Enter a number: 9
Enter a number: 5
Enter a number: done
Average: 5.66666666667
```

```
numlist = list()
while True :
    inp = input('Enter a number: ')
    if inp == 'done' : break
    value = float(inp)
    numlist.append(value)

average = sum(numlist) / len(numlist)
print('Average:', average)
```

Best Friends: Strings and Lists

```
>>> abc = 'With three words'
>>> stuff = abc.split()
>>> print(stuff)
['With', 'three', 'words']
>>> print(len(stuff))
3
>>> print(stuff[0])
With
```

```
>>> print(stuff)
['With', 'three', 'words']
>>> for w in stuff :
...     print(w)
...
With
Three
Words
>>>
```

Split breaks a string into parts and produces a list of strings. We think of these as words. We can **access** a particular word or **loop** through all the words.

```
>>> line = 'A lot of spaces'
>>> etc = line.split()
>>> print(etc)
['A', 'lot', 'of', 'spaces']
>>>
>>> line = 'first;second;third'
>>> thing = line.split()
>>> print(thing)
['first;second;third']
>>> print(len(thing))
1
>>> thing = line.split(';')
>>> print(thing)
['first', 'second', 'third']
>>> print(len(thing))
3
>>>
```

- When you do not specify a **delimiter**, multiple spaces are treated like one delimiter
- You can specify what **delimiter** character to use in the **splitting**

From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008

```
fhand = open('mbox-short.txt')
for line in fhand:
    line = line.rstrip()
    if not line.startswith('From ') :
continue
    words = line.split()
    print(words[2])
```

Sat
Fri
Fri
Fri
...

```
>>> line = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
>>> words = line.split()
>>> print(words)
['From', 'stephen.marquard@uct.ac.za', 'Sat', 'Jan', '5', '09:14:16',
'2008']
>>>
```

The Double Split Pattern

Sometimes we split a line one way, and then grab one of the pieces of the line and split that piece again

From **stephen.marquard@uct.ac.za** Sat Jan 5 09:14:16 2008

```
words = line.split()  
email = words[1]  
print pieces[1]
```

The Double Split Pattern

From **stephen.marquard@uct.ac.za** Sat Jan 5 09:14:16 2008

```
words = line.split()  
email = words[1]  
print pieces[1]
```

stephen.marquard@uct.ac.za

The Double Split Pattern

From **stephen.marquard@uct.ac.za** Sat Jan 5 09:14:16 2008

```
words = line.split()
email = words[1]
pieces = email.split('@')
print pieces[1]
```

```
stephen.marquard@uct.ac.za
['stephen.marquard', 'uct.ac.za']
```

The Double Split Pattern

From **stephen.marquard@uct.ac.za** Sat Jan 5 09:14:16 2008


```
words = line.split()
email = words[1]
pieces = email.split('@')
print(pieces[1])
```

```
stephen.marquard@uct.ac.za
['stephen.marquard', 'uct.ac.za']
'uct.ac.za'
```



Write a Python program to sum all the
items in a list.


Assignment





Write a Python program to multiplies all
the items in a list.


Assignment





Write a Python program to get the
largest number from a list.


Assignment





Write a Python program to get the
smallest number from a list.


Assignment





Write a Python program to remove
duplicates from a list.

Assignment



Thank you
Miss You...

