Smart Car Parking SystemDesign Minor Project Report

Submitted for the partial fulfilment of the degree of

Bachelor of Technology In Electronics Engineering

Submitted By

Ratnesh Asati 0901EC221087

Rikki Rajak 0901EC221088

UNDER THE SUPERVISION AND GUIDANCE OF

Dr. Deepak Batham

Assistant Professor

Department of Electronics Engineering



MADHAVINSTITUTE OF TECHNOLOGY& SCIENCE, GWALIOR (M.P.), INDIA

Deemed University

(Declared under Distinct Category by Ministry of Education, Government of India)

NAAC ACCREDITED WITH A++ GRADE

Jan-Jun 2025

DECLARATION BY THE CANDIDATE

I hereby declare that the work entitled "Smart Car Parking system Design" is my work, conducted under the supervision of Dr. Deepak Batham, Assistant Professor, during the session July-Dec 2024. The report submitted by me is a record of Bonafide work carried out by me.

I further declare that the work reported in this report has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

Ratnesh Asati (0901EC221087)

Rikki Rajak (0901EC221088)

Date: 29-04-2025

Place: Gwalior

This is to certify that the above statement made by the candidates is correct to the best of my knowledge and belief.

Guided By: 25 20104125

Dr. Deepak Batham Assistant Professor

Department of Electronics MITS, Gwalior

Departmental Project Coordinator

Dr. Varun Sharma

Assistant Professor

Department of Electronics

MITS, Gwalior

Dr. Vandana Vikas Thakre

Professor and Head

Department of Electronics

MITS, Gwalior

PLAGIARISM CHECK CERTIFICATE

This is to certify that I/we, a student of B.Tech. in Electronics Engineering have checked my complete report entitled "Smart Car Parking System Design" for similarity/plagiarism using the "Turnitin" software available in the institute.

This is to certify that the similarity in my report is found to be 23% which is within the specified limit (30%). The full plagiarism report along with the summary is enclosed.

Ratnesh Asati (0901EC221087)

Rikki Rajak (0901EC221088) Ren

Checked & Approved By:

Dr. R. P. Narwaria

Assistant Professor

Department of Electronics MITS, Gwalior

ABSTRACT

More automobiles have made it more of an issue to park in the present metropolitan setting, which has generated traffic congestion, lost time, and increased levels of pollution. The intention of this Arduino Uno intelligent parking system design is to develop an efficient and friendly parking system. To sense automobiles in parking lots and report parking availability in real time, the system incorporates ultrasonic sensors. The users can quickly locate available parking spaces because the Arduino Uno processes sensor data which is then displayed on an LCD screen or wirelessly sent to a smartphone app. The system is designed to optimize parking space usage, minimize automobile emissions, and reduce search time for a parking space. The Smart Parking System is a cost-effective and scalable solution for future smart cities.

ACKNOWLEDGEMENT

I give thanks here in my heart to everyone who has encouraged me and led the way toward this project.

First and foremost, I am thankful to Dr. R K Pandit, Vice-Chancellor of Madhav Institute of Technology and Science, Deemed University, for giving me the opportunity to do this project and creating an academic environment that is very nurturing and gets better with research growth.

I am also thankful to have an opportunity to record my heartfelt thanks to Dr.Manjaree Pandit, Dean(FoET). Her continued encouragement and valuable advice helped shape the direction of this project during the course of my studies.

Special thanks should be given to the project guide, Dr. Deepak Batham, whom I have worked with sincerely and dedicated myself to and guided me regarding such a project's execution with correct insight and technical guidance throughout its development. His deep knowledge and constant encouragement have been vital to successfully completing this project. I am very thankful for the time and effort he dedicated to helping me realize this work's objectives. I would like to thank my friends, colleagues, and family members for their support and encouragement during the completion of this project.

Last but not least, I would thank the Madhav Institute of Technology and Science, Department of Electronics, for all that is required to successfully complete this project.

Ratnesh Asati (0901EC221087)

Rikki Rajak (0901EC221088)

CONTENT

Table of Contents

Declaration by the Candidate	.i
Plagiarism Check Certificatei	ii
Abstract	iii
Acknowledgementiv	V
Content	7
Acronymsv	⁄i
List of Figures	ii
Chapter 1: Introduction.	1
Chapter 2: Literature Survey	2
Chapter 3: Methodology	3
Chapter 4: COMPONENT INTRODUCTION	.5
Chapter 5:CIRCUIT DIAGRAM	7
Chapter 6: WORKING PROJECT	8
Chapter 7: WORKING	.9
Chapter 8: CONCLUSION1	1
References	2
Turnitin Plagiarism Report	3

ACRONYMS

Acronym	Full Form		
DC	Direct Current		
AC	Alternating Current		
IR	Infrared		
IOT	Internet Of Things		
LCD	Liquid Crystal display		
LED	Light Emitting diode		
IDE	Integrated Development Environment		
MIPL	Mixed Integer Linear Program		
RFID	Radio Frequency Identification		
I ² C	Inter integrated circuit		

LIST OF FIGURES

Sr. No.	Name of Figure	Figure Number	Page Number
1.	Circuit diagram	Figure 5.1	7
2.	Project Hardware	Figure 5.2	7
3.	Working Project	Figure 6.1-6.4	8
4.	Flow Chart	Figure 7.1	10
5.	Arduino Uno	Figure 4.1	5
6.	Servo Motor	Figure 4.2	5
7.	IR Proximity Sensor	Figure 4.3	6
8.	16X2 I2C LCD Display	Figure 4.4	6
9.	Jumper Wires	Figure 4.5	6

CHAPTER 1: INTRODUCTION

In the fast-developing urban areas of today, parking has proven to be a significant problem caused by the ever-increasing number of vehicles and restricted parking areas. Conventional parking systems tend to cause wastage of time, traffic jams, and driver frustration. To counteract all these issues, smart parking systems are being created to maximize the utilization of existing parking spaces in an efficient manner. This project involves a Smart Parking System based on an Arduino Uno microcontroller. The system employs sensors to identify vehicles occupying parking spaces and send real-time information to users. It aims to make the parking management process automated by tracking the occupied status of all parking spaces and showing the information on an Liquid Crystal display(LCD) screen or through an application interface. Through the use of Arduino Uno's ease of use, low costs, and high flexibility, the suggested system has a cost-cutting solution, which can scale to be deployed in small-sized parking lots as well as more extensive commercial spaces. It benefits not only from enhanced user usability but also supports traffic congestion avoidance and environmental sensitivity.

CHAPTER 2: LITERATURE SURVEY

This chapter is a review of existing literature on the subject of autonomous robots, IoT integration, and computer vision as how other similar projects have explored these technologies.

- 1. A Cloud-Based Smart-Parking System Based on Internet-of-Things Technologies---This work presents an innovative algorithm which enhances the capability of existing cloud based smart parking system [1] and further constructs a network structure in accordance with the Internet of Things technology. This system assists the users to find an available parking space with less cost based on new performance metrics that is car matic. This metrics will calculate the user spaces in every car park. To improve the parking management, an intelligent parking system was designed which minimized the role of hiring individuals to keep the parking system. In this paper it suggests an effective cloud-based Smart parking system based on the Internet of Things. The information that contains the vehicle GPS location and distance between car parks and number of free parking space in car parks will be transmitted to the data center. Here the data centre is envisaged in the form of a cloud server that computes the fee of a user parking request and this data is updated periodically and made available to the vehicles on the network at any moment in time. In this system proposed, every car park is an IoT network and it stands alone as an independent car park. This paper utilizes a system model with wireless access in an open-sourced physical computing platform based on Arduino utilizing RFID technology. It utilizes smartphone that serves as the user interface between the cloud and the cars to verify the viability of the suggested system
- 2. A New "Smart Parking" System Based on Reservations and Optimal Resource Utilization[2]. This technology has a new smart parking system for cities. Depending on the user's proximity to the parking lot and parking cost, this system allocates and books a parking space for the driver. It also ensures that the whole parking capacity is utilized optimally. At each decision point in a time-driven process, their approach solves a Mixed Integer Linear Program (MILP) problem. There is a solution for each MILP that offers the best available allocation according to the user's status data at hand and also allows for arbitrary events such as requests from new users and availability of parking spots. To avoid potential conflicts with parking slot reservations and to ensure that a user never gets assigned a parking space whose value is more than the existing cost function value, the allocation is made at the next decision point. This method ensures reservations and improved response from the system.

CHAPTER 3: METHODOLOGY

Smart Vehicle Parking System using Arduino UNO Smart stopping is the designing, developing, and implementing a major edge-stopping innovation. Drivers can locate an empty space with the help of this vehicle stopping system. It checks whether a vehicle is present or not using the IR Proximity sensors in every stopping point. It is demonstrated that the Brilliant Parking Framework is a precise, efficient, and cost-effective means to inform street customers of the specific locations of available parking spaces.

1. The following are the elements of the proposed framework:

- Drivers find nearby available parking spaces.
- The mobility clog is minimized when fewer drivers try to stop.
- Avoids dangerous atmospheric deviations and air pollution.
- Strong, sturdy, and scalable.
- Extends the urban range and shortens the driving stretch.
- Provides means to speed up parking spot management and accurately measure car occupancy gradually.

3.2 Disgrace parking:

It is disgraceful parking when a vehicle is parked in such a manner that it occupies two parking slots instead of one. When a driver is negligent with the rights of another driver, parking can happen. The evolution of intelligent parking systems with automation addresses this.

3.3 Circuit Connections:

- Connect the IR sensors VCC and GND pins to the Arduino board's 5V and GND pins, respectively.
- The signal pins of the IR sensors (ir_enter, ir_back, and ir_car1 through ir_car4) must be connected to any Arduino digital input pins that are available (pins 2, 4, 5, 6, 7, 8).
- Connect the servo motor signal wire to pin 3 of the digital output of the Arduino.
- Connect the SDA and SCL pins of the LCD module to the Arduino's corresponding SDA and SCL pins (A4 and A5 in most Arduino boards).
- Connect the LCD module's VCC and GND pins to the Arduino board's 5V and GND pins, respectively.

3.4 Coding using Arduino UNO:

```
#include <Wire.h>
 1
 2
     #include <LiquidCrystal I2C.h>
     LiquidCrystal I2C lcd(0x27,16,2);
 3
 4
     #include <Servo.h>
     Servo myservo;
     int IR1 = 2;
 6
 7
     int IR2 = 3;
     int Slot = 4; //Total number of parking Slots
 9
     int flag1 = 1;
10
     int flag2 = 1;
11
     void setup() {
     Serial.begin(9600);
12
     lcd.init(); //initialize the lcd
13
     lcd.backlight(); //open the backlight
14
15
     pinMode(IR1, INPUT);
     pinMode(IR2, INPUT);
16
17
     myservo.attach(4);
18
     myservo.write(100);
19
     lcd.setCursor (0,0);
     lcd.print(" ARDUINO ");
20
     lcd.setCursor (0,1);
21
     lcd.print(" PARKING SYSTEM ");
22
23
     delay (2000);
24
     lcd.clear();
25
     }
26
     void loop(){
     if(digitalRead (IR1) == LOW && flag1==0){
27
28
     if(Slot>0){flag1=1;
     if(flag2==0){myservo.write(0); Slot = Slot-1;}
29
30
     }else{
31
     lcd.setCursor (0,0);
     lcd.print(" SORRY :( ");
33
     lcd.setCursor (0,1);
     lcd.print(" Parking Full ");
34
35
     delay (3000);
36
     lcd.clear();
37
38
     if(digitalRead (IR2) == LOW && flag2==0){flag2=1;
40
     if(flag1==0){myservo.write(0); Slot = Slot+1;}
41
42
     if(flag1==1 && flag2==1){
43
     delay (1000);
     myservo.write(100);
     flag1=0, flag2=0;
45
46
     lcd.setCursor (0,0);
47
     lcd.print(" WELCOME! ");
49
     lcd.setCursor (0,1);
50
     lcd.print("Slot Left: ");
     lcd.print(Slot);
51
52
     }
```

CHAPTER 4: COMPONENTINT RODUCTION

1. ARDUINO UNO:- The ATmega328P is the basis for the Arduino UNO microcontroller board. It has a 16 MHz ceramic resonator, 6 analog inputs, 14 digital input/output pins (six of which can be used as PWM outputs), a USB port, a power jack, an ICSP header, and a reset button. All you need to power the microcontroller is provided; to begin, simply plug it into a computer using a USB cable or power it with a battery or AC-to-DC adapter. You can try out your UNO without worrying too much about messing it up; worst case, you can always start over by replacing the chip for a few dollars.



Fig 4.1 Arduino

2. SERVO MOTORS - An electric motor that can be controlled to move accurately, typically position, speed, or torque, is referred to as a servo motor. Robotics, automaton, CNC devices, and radio-controlled devices use it extensively. Normally used in closed systems, servo motors are provided with feedback (e.g., position) and correct themselves to realize and maintain a desired output.



Fig 4.2 Servo Motor

2. INFRARED SENSOR- An infrared (IR) sensor is a device used to sense objects or measure distance using infrared radiation (light waves slightly longer than the visible spectrum). Simply, it can check if something is there without touching it.



Fig 4.3 Infrared sensor

5. 16 X 2 I 2 C LED- With a 16x2 LCD, two lines containing 16 characters each can be displayed on the screen. Normally, a microcontroller (e.g., Arduino, ESP32, etc.) interfaces to an LCD (e.g., popular HD44780-based ones) through a huge number of pins (at least 6–10 wires). A small I2C adaptor module, usually a PCF8574 I/O expander, is mounted on the back of an I2C 16x2 LCD. When I2C (Inter-Integrated Circuit) connection is utilized, the LCD only needs two wires for power and data: Data Line (SDA), Clock Line (SCL) Along with VCC and GND



Fig 4.4 16X2 I2C LCD Display

5. JUMPING WIRES- A jumper wire is a short electrical wire used commonly during testing or prototyping to connect elements on a breadboard or among other circuit elements.types:male to male,female to male,female to female.



Fig 4.5 Jumper wires

CHAPTER 5: CIRCUIT DIAGRAM




Fig 5.1 Circuit Diagram of Smart Car parking System




Fig 5.2 Smart Car parking System

CHAPTER 6: WORKING PROJECT






Fig 6.1 Working Model

Fig 6.2 Working Model



Fig 6.3 Working Model




Fig 6.4 Working Model

CHAPTER 7: WORKING

Employing infrared sensors, a servo motor, and a microcontroller to track, control, and display real-time parking space availability, the Arduino Uno Smart Car Parking System works on the principle of automated vehicle detection and controlled parking space access.

KEY WORKING PRINCIPLE:

1. PARKING SPACE SENSOR:- There is an ultrasonic sensor installed on every parking space. The Infrared proximity sensor keeps track of the car's proximity as it enters a space, and when the car is present (distance < threshold), the sensor triggers the Arduino. The Arduino switches on an LED (red when occupied, green when available) depending on this information.

CIRCUIT SENSOR:- There is an echo pin and a trigger for each Infrared proximity sensor. The echo pin will receive the pulse that is triggered by the trigger pin. Arduino computes the car's distance from the time elapsed for the return of the pulse.

- 2. CONTROL OF ENTRY AND EXIT:- Control of entry and exit is maintained by a gate system or servo motor. The sensor identifies whether an available spot exists when a vehicle drives into the parking lot. Based on the data processed, the Arduino releases the gate (controlled by a servo motor or relay) for admission if a slot is vacant.

 The machine can be made to ring a buzzer or give a message if it is displayed on an LCD screen to inform users that no more spots are available when the parking lot is full.
- 3. INFORMATION DISPLAY: LEDs:- These show whether a parking space is available (green) or taken (red). There can be an optional LCD display that indicates the number of parking spaces left and guides the vehicle to one.
- 4. DETECTION AND INDICATION:- The parking space becomes indicated as vacant when the vehicle departs, as identified by the ultrasonic sensor. The other drivers may then observe the vacant space once the Arduino makes the color of the LED shift from red (occupied) to green (vacant). To offer sound input, the system can also produce a sound using the buzzer if a car is parked or if the parking area is full.
- 5. PARKING CAPACITY AND MANAGEMENT:- The Arduino can be set to constantly keep track of the number of total vehicles and empty spaces. For distant monitoring, there is an even more advanced variant that can even send parking status notifications to a web dashboard or mobile app.

FLOW CHART




Figure 7.1 Flow Chart Of Smart Car Parking System

CHAPTER 8: CONCLUSION

In a new city, our project assists drivers in parking by identifying vacant spots. This system efficiently reduces the average parking wait time for users. The proposed system provides the optimal solution, with most cars successfully locating an available parking spot. Our preliminary test results show that the performance of the Arduino UNO-based system can effectively address the needs of today's parking challenges, minimizing the time required to find an available space and offering real-time information rendering. Improved performance, lower costs, and a successful large-scale parking system are all offered by this intelligent parking system. When a vehicle enters the parking lot, the driver parks it in the nearest available space. When the slot is taken, the LED light glows, and when it is vacant, the LED light automatically switches off to indicate that the space is available for use by someone. Moreover, it eliminates the necessity for automobiles to navigate through congested car parks in a city.

REFERENCES

- 1 K.Ashokkumar a, Baron Sam , R.Arshadprabhu , Britto. "Cloud Based Intelligent Transport System". Procedia Computer Science, volume 50, pp. 58-63, 2015.
- 2 Yanfeng Geng and Christos G. Cassandras. "A NewSmart Parking System Based on Optimal ResourceAllocation and Reservations". IEEE Transaction onIntelligent Transportation Systems, volume 14, pp. 1129-1139, April 2013
- 3 Cui Shiyao, Wu Ming, Liu Chen, Rong Na . "The Research and Implement of the Intelligent Parking Reservation Management System Based on ZigBee Technology". Measuring Technology and Mechatronics Automation (ICMTMA) , pp. 741-744, January 2014.
- 4 Z. Ji, I. Ganchev, M. O'Droma, and X. Zhang, ``A cloud-based intelligent car parking services for smart cities," in Proc. 31st URSI General Assembly Sci. Symp. (URSI GASS), Aug. 2014.
- 5 Arduino IDE Software: https://www.arduino.cc/en/software

Rikki

ratnesh & rikki (1)-1.pdf

Madhay Institute of Technology & Science

Document Details

Submission ID

trn:oid:::28506:93494659

Submission Date

Apr 29, 2025, 4:43 PM GMT+5:30

Download Date

Apr 29, 2025, 4:45 PM GMT+5:30

File Name

ratnesh & rikki (1)-1.pdf

File Size

1.3 MB

14 Pages

2.206 Words

11,282 Characters

29% Overall Similarity

ninell sotal of all matches, including overlapping sources, for each database

Filtered from the Report

· Bibliography

Match Groups

39 Not Cited or Quoted 29% Matches with neither in-lest citation nor quotation marks.

a Missing Quotations 0% Matches that are still very similar to source material

8 Missing Citation 0% Matches that have quotation marks, but no in-text chappin.

8 Cited and Quoted 0% Matches with in-text citation present, but no quotation marks.

Integrity Flags

O Integrity Flags for Review

No europeious test manipulations found

Top Sources

21% @ Internet sources

14% Di Publications

23% . Submitted works (Student Papers).

Our system's algorithms look deeply at a document for any inconsistences that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

99 Not Cited or Quoted 29%

souther with neither in-cert situation nor quotation marks

@ a Missing Quotations on

ALID For that are still very similar to source material.

— 0 Missing Citation 0%

Marches that have quotasion marks, but no in cost citation

. 0 Cited and Quoted 0%

Marches with in-text crution present, but no quotation marks

Top Sources

21% @ Internet sources

14% **B**D Publications

23% . Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

Internet.

www.coursehero.com

15%

Submitted works

De Montfort University on 2025-04-20

2%

Submitted works

Institute of Research & Postgraduate Studies, Universiti Kuala Lumpur on 2024-0...

<1%

Submitted works

Australian College of Kuwait on 2024-04-24

<196

Submitted works

Notre Dame of Marbel University on 2025-04-11

<1%

Internet


www.ece.anits.edu.in

<196

Submitted works


Asia Pacific University College of Technology and Innovation (UCTI) on 2024-05-21

<146



Manchester Metropolitan University on 2023-05-12

<1%



Colorado School of Mines on 2021-05-01

<1%



Submitted works

Kabarak University on 2023-08-15

<136

125/4/28

Submitted works	
um Veteran Jakarta on 2024-01-15	1%
Internet.	1%
plactips .	1700
Internet	
The state of the s	1%
Submitted works	<1%
catsu on 2024-05-22	
Internet	
18brary.net	<1%
Submitted works Submitted works Mumbai on 2021-08-06	<1%
K.). Somalya College of Engineering Vidyavihar, Mumbai on 2021-08-06	
5 Submitted works	Care C
University of Portsmouth on 2021-12-03	<1%
Submitted works	<1%
University of Salford on 2022-01-25	
1 Internet	<1%
dipace usu ac.bd	
Internet	
philipapers.org	<1%
Submitted works	<1%
INTI Universal Holdings SDM BHD on 2025-04-16	
Submitted works	
Sminburne University of Technology on 2023-04-02	<1%
Yanleng Geng, Christos G. Cassandras. "A new "smart parking" s	<1%
Yanleng Geng, Christos G. Cassandras. A Inc. 1	
Submitted works	<1%

University of Central Lancashure on 2025-04-23

Turnitin Page 4 of 18. househy Overview