

Machine learning methods applied to the analysis of central exclusive production events in ALICE

Sebastian Ratzenböck¹

¹Stefan Meyer Institut
Österreichische Akademie der Wissenschaften

26. April 2018

Outline

1 ML: an overview

2 Rectangular cuts

- Decision Trees
- Example
- Improvements

3 Linear cuts

ML: an overview

In general ML represents a contrast to a *rule based systems*

Rule-based system

System that uses rules to make deductions or choices

- Domain-specific expert system
- Knowledge base: facts & rules (if \rightarrow then statement)
- Rules manually specified (by expert) \rightarrow expensive, incomplete

ML: an overview

In general ML represents a contrast to a *rule based systems*

Rule-based system

System that uses rules to make deductions or choices

- Domain-specific expert system
- Knowledge base: facts & rules (if \rightarrow then statement)
- Rules manually specified (by expert) \rightarrow expensive, incomplete

ML: an overview

In general ML represents a contrast to a *rule based systems*

Rule-based system

System that uses rules to make deductions or choices

- Domain-specific expert system
- Knowledge base: facts & rules (if \rightarrow then statement)
- Rules manually specified (by expert) \rightarrow expensive, incomplete

ML: an overview

In general ML represents a contrast to a *rule based systems*

Machine learning

- Algorithms that learn from *data* & make predictions on *data*
- Automatic methods → no human needed
- Human work required for defining problem & assessing the data

ML: an overview

In general ML represents a contrast to a *rule based systems*

Machine learning

- Algorithms that learn from *data* & make predictions on *data*
- Automatic methods → no human needed
- Human work required for defining problem & assessing the data

ML: an overview

In general ML represents a contrast to a *rule based systems*


Machine learning

- Algorithms that learn from *data* & make predictions on *data*
- Automatic methods → no human needed
- Human work required for defining problem & assessing the data

Types of ML


- Supervised
 - ▶ Classification
 - ▶ Regression
- Unsupervised

Supervised learning



Types of ML


- Supervised
 - ▶ Classification
 - ▶ Regression
- Unsupervised



Rectangular cuts

Standard cut in one variable


- Cuts only in lower-dimensional subspaces
- Ignores possible dependencies between the input variables
- Signal might behave like BG in several observables
→ misclassification



Rectangular cuts

Standard cut in one variable


- Cuts only in lower-dimensional subspaces
- Ignores possible dependencies between the input variables
- Signal might behave like BG in several observables
→ misclassification



Rectangular cuts

Standard cut in one variable


- Cuts only in lower-dimensional subspaces
- Ignores possible dependencies between the input variables
- Signal might behave like BG in several observables
→ misclassification




Rectangular cuts with *decision trees*

- Tree-like graph \rightarrow flowchart
- Easy to understand
- Either be manually modelled by experts or learned from training data


Rectangular cuts with *decision trees*




Rectangular cuts with *decision trees*



Rectangular cuts with *decision trees*



Rectangular cuts with *decision trees*



Decision tree learning


Training

Recursively split feature space into sub-spaces at each step

→ Measures to evaluate split

- Error rate
- Information gain
- Gini index


Decision tree learning



Decision tree learning


- 1) We compute a measure for *each possible split* in each feature
→ here **absolute error rate** (AER)

y split AER




Decision tree learning

- 1) We compute a measure for *each possible split* in each feature
 → here **absolute error rate** (AER)





Decision tree learning

- 1) We compute a measure for *each possible split* in each feature
 → here **absolute error rate** (AER)





Decision tree learning

- 1) We compute a measure for *each possible split* in each feature
→ here **absolute error rate** (AER)
- 2) Recursively repeat step (1) for each subspace until $AER \rightarrow 0$





Decision tree learning

- 1) We compute a measure for *each possible split* in each feature
→ here **absolute error rate** (AER)
- 2) Recursively repeat step (1) for each subspace until $AER \rightarrow 0$





Decision tree learning

- 1) We compute a measure for *each possible split* in each feature
 → here **absolute error rate** (AER)
- 2) Recursively repeat step (1) for each subspace until $AER \rightarrow 0$





Decision tree learning

- 1) We compute a measure for *each possible split* in each feature
→ here **absolute error rate** (AER)
- 2) Recursively repeat step (1) for each subspace until $AER \rightarrow 0$





Decision tree learning

- 1) We compute a measure for *each possible split* in each feature
→ here **absolute error rate** (AER)
- 2) Recursively repeat step (1) for each subspace until $AER \rightarrow 0$




Decision tree classification

3) Classification




Decision tree improvements I

- Use more sophisticated split measures
 - ▶ *Information gain* \leftrightarrow (im-)purity of splitted sub-sets
 - ▶ Gini index
- Pruning



Absolute error rate



Information gain

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample
(=*bootstrapping*)
 - ▶ Random number of the
original features
→ large number of rather
shallow trees
- Classify data by majority
voting of individual trees

Boosted DT

- Sequential ensemble of
evolving DTs
- Output of each tree is given
weight relative to accuracy
- → Subsequent predictors learn
from the mistakes of the
previous predictors

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample (= *bootstrapping*)
 - ▶ Random number of the original features
→ large number of rather shallow trees
- Classify data by majority voting of individual trees

Boosted DT

- Sequential ensemble of evolving DTs
- Output of each tree is given weight relative to accuracy
- → Subsequent predictors learn from the mistakes of the previous predictors

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample (= *bootstrapping*)
 - ▶ Random number of the original features
→ large number of rather shallow trees
- Classify data by majority voting of individual trees

Boosted DT

- Sequential ensemble of evolving DTs
- Output of each tree is given weight relative to accuracy
- → Subsequent predictors learn from the mistakes of the previous predictors

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample (= *bootstrapping*)
 - ▶ Random number of the original features
→ large number of rather shallow trees
- Classify data by majority voting of individual trees

Boosted DT

- Sequential ensemble of evolving DTs
- Output of each tree is given weight relative to accuracy
- → Subsequent predictors learn from the mistakes of the previous predictors

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample (= *bootstrapping*)
 - ▶ Random number of the original features
→ large number of rather shallow trees
- Classify data by majority voting of individual trees

Boosted DT

- Sequential ensemble of evolving DTs
- Output of each tree is given weight relative to accuracy
- → Subsequent predictors learn from the mistakes of the previous predictors

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample (= *bootstrapping*)
 - ▶ Random number of the original features
→ large number of rather shallow trees
- Classify data by majority voting of individual trees

Boosted DT

- Sequential ensemble of evolving DTs
- Output of each tree is given weight relative to accuracy
- → Subsequent predictors learn from the mistakes of the previous predictors

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample (= *bootstrapping*)
 - ▶ Random number of the original features
→ large number of rather shallow trees
- Classify data by majority voting of individual trees

Boosted DT

- Sequential ensemble of evolving DTs
- Output of each tree is given weight relative to accuracy
- → Subsequent predictors learn from the mistakes of the previous predictors

Decision tree improvements II

Random forest

- Ensemble of DTs
- For each tree use:
 - ▶ Random sub-sample (= *bootstrapping*)
 - ▶ Random number of the original features
→ large number of rather shallow trees
- Classify data by majority voting of individual trees


Boosted DT

- Sequential ensemble of evolving DTs
- Output of each tree is given weight relative to accuracy
- → Subsequent predictors learn from the mistakes of the previous predictors

Linear cuts

More flexible than rectangular cut

- Simple white box methods
- Can become very powerful by using *kernel trick*



Linear cuts

More flexible than rectangular cut

- Simple white box methods
- Can become very powerful by using *kernel trick*

