

828 GRILL

Full-Stack Web Build — Master Prompt

Next.js · Neon PostgreSQL · Stripe · NextAuth · Vercel

This document is the complete, unabridged prompt to be pasted directly into Z.ai to upgrade the 828 Grill website (Site 3 foundation) by merging in the full component architecture, stores, pages, and data from ZIP 2. Every instruction, every file, and every line of code is reproduced exactly — nothing omitted.

PROMPT PREAMBLE

You are rebuilding the 828 Grill website. You already have the Next.js foundation (Site 3). You need to upgrade it by merging in the full component architecture, stores, pages, and data from a second codebase (ZIP 2). Follow every instruction below exactly. Do not improvise.

WHAT YOU HAVE (Site 3 — keep all of this)

The following elements already exist in the Site 3 Next.js foundation. Do NOT remove or replace any of them. Everything below is additive or a targeted upgrade only.

- Next.js 14 App Router framework
- Brand voice: "Fire. Smoke. Craft." tagline
- Hero with full-bleed image, ember overlay, Bebas Neue display font
- Scrolling marquee ticker (HAND-SMASHED PATTIES · SLOW-SMOKED DAILY etc.)
- SEO metadata in layout.tsx
- Color tokens: #0D0D0D bg, #1A1A1A cards, #E8531A accent, #F5F0E8 text, #888888 muted
- Vercel deployment target

STEP 1 — Install Dependencies

Add the following to package.json dependencies and run install:

```
zustand
lucide-react
@stripe/stripe-js
```

@stripe/react-stripe-js

STEP 2 — Fix the Hero Headline Typo

In the Home page hero section, find the headline. It currently reads TASTETHE FIRE (missing space). Fix it to read exactly:

TASTE THE FIRE

STEP 3 — Create the Cart Store with localStorage Persistence

Create `src/store/cart.ts` — uses Zustand persist middleware so the cart survives page refreshes:

FILE: `src/store/cart.ts`

```
import { create } from 'zustand';
import { persist } from 'zustand/middleware';

export interface CartItem {
  menuItemId: string;
  name: string;
  price: number;
  imageUrl: string;
  quantity: number;
}

interface CartStore {
  items: CartItem[];
  addItem: (item: Omit<CartItem, 'quantity'>) => void;
  removeItem: (menuItemId: string) => void;
  updateQuantity: (menuItemId: string, quantity: number) => void;
  clearCart: () => void;
  getTotal: () => number;
  getItemCount: () => number;
}

export const useCartStore = create<CartStore>()(
  persist(
    (set, get) => ({
      items: [],

      addItem: (item) => {
        set((state) => {
          const existing = state.items.find(
            i => i.menuItemId === item.menuItemId
          );
          if (existing) {
            return {
              items: state.items.map(i =>
                i.menuItemId === item.menuItemId
                  ? { ...i, quantity: i.quantity + 1 }
                  : i
            );
          }
        });
      }
    })
  )
);
```

```

        ),
      };
    }
    return { items: [...state.items, { ...item, quantity: 1 }] };
  });
},

removeItem: (menuItemId) =>
  set((state) => ({
    items: state.items.filter(i => i.menuItemId !== menuItemId),
  })),

updateQuantity: (menuItemId, quantity) => {
  if (quantity <= 0) { get().removeItem(menuItemId); return; }
  set((state) => ({
    items: state.items.map(i =>
      i.menuItemId === menuItemId ? { ...i, quantity } : i
    ),
  }));
},

clearCart: () => set({ items: [] }),

getTotal: () =>
  get().items.reduce((t, i) => t + i.price * i.quantity, 0),

getItemCount: () =>
  get().items.reduce((c, i) => c + i.quantity, 0),
}),
{ name: '828-grill-cart' }
)
);

```

STEP 4 — Create the Auth Store

Create `src/store/auth.ts` — persists session across reloads, stores registered users in `localStorage`:

FILE: `src/store/auth.ts`

```

import { create } from 'zustand';
import { persist } from 'zustand/middleware';

export interface OrderItem {
  name: string;
  price: number;
  quantity: number;
}

export interface OrderRecord {
  id: string;
  items: OrderItem[];
  total: number;
  status: string;
  createdAt: string;
}

```

```

}

export interface User {
  id: string;
  name: string;
  email: string;
  phone?: string;
  address?: string;
  orders?: OrderRecord[];
}

interface AuthStore {
  user: User | null;
  isAuthenticated: boolean;
  login: (email: string, password: string) => Promise<boolean>;
  register: (data: {
    name: string;
    email: string;
    password: string;
    phone?: string;
    address?: string;
  }) => Promise<boolean>;
  logout: () => void;
  addOrder: (order: OrderRecord) => void;
}

export const useAuthStore = create<AuthStore>()(
  persist(
    (set, get) => ({
      user: null,
      isAuthenticated: false,

      login: async (email, password) => {
        await new Promise(r => setTimeout(r, 600));
        const stored = JSON.parse(
          localStorage.getItem('828-grill-users') || '[]'
        );
        const found = stored.find(
          (u: any) => u.email === email && u.password === password
        );
        if (found) {
          const { password: _, ...user } = found;
          set({ user, isAuthenticated: true });
          return true;
        }
        return false;
      },

      register: async (data) => {
        await new Promise(r => setTimeout(r, 600));
        const stored = JSON.parse(
          localStorage.getItem('828-grill-users') || '[]'
        );
        if (stored.find((u: any) => u.email === data.email)) return false;
        const newUser = { ...data, id: `usr_${Date.now()}`, orders: [] };
        stored.push(newUser);
        localStorage.setItem('828-grill-users', JSON.stringify(stored));
      }
    })
  )
);

```

```

    const { password: _, ...user } = newUser;
    set({ user, isAuthenticated: true });
    return true;
  },

  logout: () => set({ user: null, isAuthenticated: false }),

  addOrder: (order) =>
    set((state) => {
      if (!state.user) return state;
      const updatedUser = {
        ...state.user,
        orders: [order, ...(state.user.orders || [])],
      };
      const stored = JSON.parse(
        localStorage.getItem('828-grill-users') || '[]'
      );
      const idx = stored.findIndex((u: any) => u.id === updatedUser.id);
      if (idx >= 0) {
        stored[idx] = { ...stored[idx], orders: updatedUser.orders };
        localStorage.setItem('828-grill-users', JSON.stringify(stored));
      }
      return { user: updatedUser };
    }),
  },
  {
    name: '828-grill-auth',
    partialize: (s) => ({
      user: s.user,
      isAuthenticated: s.isAuthenticated,
    }),
  }
)
);

```

STEP 5 — Create the Menu Data File

Create `src/data/menu.ts` — all 16 items across 4 categories (Burgers, Sides, Drinks, Combos):

FILE: `src/data/menu.ts`

```

export interface MenuItem {
  id: string;
  name: string;
  description: string;
  price: number;
  category: 'Burgers' | 'Sides' | 'Drinks' | 'Combos';
  imageUrl: string;
  available: boolean;
  popular?: boolean;
}

export const menuItems: MenuItem[] = [
  // BURGERS

```

```
{ id: 'burger-1', name: 'Classic Smash Burger',
  description: 'Double smash patties, American cheese, pickles, grilled onions, 828 secret sauce on a toasted brioche bun.',
  price: 12.99, category: 'Burgers', imageUrl: '/menu/burger-classic.jpg',
  available: true, popular: true },

{ id: 'burger-2', name: 'Smoked Brisket Burger',
  description: '12-hour smoked brisket patty, pepper jack cheese, crispy bacon, smoked gremolata, charcoal bun.',
  price: 15.99, category: 'Burgers', imageUrl: '/menu/burger-smoked.jpg',
  available: true, popular: true },

{ id: 'burger-3', name: 'Truffle Mushroom Burger',
  description: 'Wagyu blend patty, sauteed wild mushrooms, truffle aioli, aged gruyere, arugula.',
  price: 17.99, category: 'Burgers', imageUrl: '/menu/burger-classic.jpg',
  available: true },

{ id: 'burger-4', name: 'Spicy Jalapeno Inferno',
  description: 'Ghost pepper patty, habanero cheese, pickled jalapenos, chipotle mayo, fire-grilled bun.',
  price: 14.99, category: 'Burgers', imageUrl: '/menu/burger-smoked.jpg',
  available: true },

{ id: 'burger-5', name: 'BBQ Bacon Deluxe',
  description: 'Smoked beef patty, thick-cut bacon, cheddar, crispy onion strings, Texas-style BBQ sauce.',
  price: 14.49, category: 'Burgers', imageUrl: '/menu/burger-classic.jpg',
  available: true, popular: true },

// SIDES
{ id: 'side-1', name: 'Crispy Smoke Fries',
  description: 'Hand-cut fries tossed in smoked paprika and sea salt. Crispy outside, fluffy inside.',
  price: 5.99, category: 'Sides', imageUrl: '/menu/sides-fries.jpg',
  available: true, popular: true },

{ id: 'side-2', name: 'Loaded Cheese Fries',
  description: 'Golden fries topped with melted cheddar, bacon bits, jalapenos, and sour cream drizzle.',
  price: 8.99, category: 'Sides', imageUrl: '/menu/sides-fries.jpg',
  available: true },

{ id: 'side-3', name: 'Grilled Corn Elote',
  description: 'Char-grilled corn on the cob with cotija cheese, chili powder, lime, and crema.',
  price: 6.49, category: 'Sides', imageUrl: '/menu/sides-fries.jpg',
  available: true },

// DRINKS
{ id: 'drink-1', name: 'Vanilla Ember Shake',
  description: 'Thick vanilla bean milkshake with a hint of smoked cinnamon, topped with whipped cream.',
  price: 7.99, category: 'Drinks', imageUrl: '/menu/drinks-shake.jpg',
  available: true, popular: true },

{ id: 'drink-2', name: 'Bourbon Cherry Shake',
  description: 'Rich cherry shake with a splash of bourbon, cherry garnish, dark chocolate drizzle.',
  price: 9.49, category: 'Drinks', imageUrl: '/menu/drinks-shake.jpg',
  available: true },

{ id: 'drink-3', name: 'Craft Root Beer',
  description: 'House-brewed root beer served over hand-cut ice. Classic, refreshing, and bold.',
  price: 4.49, category: 'Drinks', imageUrl: '/menu/drinks-shake.jpg',
  available: true },
```

```

{ id: 'drink-4', name: 'Smoked Lemonade',
  description: 'Fresh-squeezed lemonade with applewood smoke infusion, honey, and mint.',
  price: 5.99, category: 'Drinks', imageUrl: '/menu/drinks-shake.jpg',
  available: true },

// COMBOS
{ id: 'combo-1', name: 'Mega Grill Combo',
  description: 'Classic Smash Burger + Smoke Fries + Vanilla Ember Shake. The ultimate 828 experience.',
  price: 22.99, category: 'Combos', imageUrl: '/menu/combos-mega.jpg',
  available: true, popular: true },

{ id: 'combo-2', name: 'Brisket Feast',
  description: 'Smoked Brisket Burger + Loaded Cheese Fries + Bourbon Cherry Shake.',
  price: 29.99, category: 'Combos', imageUrl: '/menu/combos-mega.jpg',
  available: true },

{ id: 'combo-3', name: 'Family Fire Pack',
  description: '4 Classic Smash Burgers + 2 Large Smoke Fries + 4 Craft Root Beers. Feed the whole crew.',
  price: 59.99, category: 'Combos', imageUrl: '/menu/combos-mega.jpg',
  available: true },

{ id: 'combo-4', name: 'Date Night Duo',
  description: '2 Truffle Mushroom Burgers + Grilled Corn Elote + 2 Smoked Lemonades.',
  price: 44.99, category: 'Combos', imageUrl: '/menu/combos-mega.jpg',
  available: true },
];

```

STEP 6 — Upgrade the Navbar

Replace the existing Navbar component entirely. Uses cart store for live badge count, auth store for sign-in state, and a working mobile hamburger menu. Uses Next.js Link with href — NOT React Router to prop.

FILE: components/Navbar.tsx

```

'use client';
import { useState } from 'react';
import Link from 'next/link';
import { usePathname } from 'next/navigation';
import { ShoppingBag, User, Menu as MenuIcon, X } from 'lucide-react';
import { useCartStore } from '@store/cart';
import { useAuthStore } from '@store/auth';

export default function Navbar() {
  const [isOpen, setIsOpen] = useState(false);
  const pathname = usePathname();
  const itemCount = useCartStore(s => s.getItemCount());
  const isAuthenticated = useAuthStore(s => s.isAuthenticated);

  const navLinks = [
    { path: '/', label: 'Home' },
    { path: '/menu', label: 'Menu' },
  ];

  const isActive = (path: string) =>

```

```

    path === '/' ? pathname === '/' : pathname.startsWith(path);

return (
  <nav className="fixed top-0 left-0 right-0 z-50
    bg-[#0D0D0D]/90 backdrop-blur-xl border-b border-white/5">
    <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8">
      <div className="flex items-center justify-between h-16 sm:h-20">

        <Link href="/"
          className="font-display text-3xl sm:text-4xl text-[#F5F0E8]">
          828 <span className="text-[#E8531A]">GRILL</span>
        </Link>

        <div className="hidden md:flex items-center gap-8">
          {navLinks.map(link => (
            <Link key={link.path} href={link.path}
              className={`text-sm tracking-wider uppercase transition-colors
                ${isActive(link.path)}
                ? 'text-[#E8531A]'
                : 'text-[#888] hover:text-[#F5F0E8]'}`}>
              {link.label}
            </Link>
          ))}
        </div>

        <div className="flex items-center gap-3 sm:gap-4">
          <Link href="/cart"
            className="relative p-2 text-[#888]
              hover:text-[#F5F0E8] transition-colors">
            <ShoppingBag className="w-5 h-5 sm:w-6 sm:h-6" />
            {itemCount > 0 && (
              <span className="absolute -top-1 -right-1 bg-[#E8531A]
                text-white text-xs font-bold rounded-full w-5 h-5
                flex items-center justify-center">
                {itemCount}
              </span>
            )}
          </Link>

          {isAuthenticated ? (
            <Link href="/account"
              className="p-2 text-[#888] hover:text-[#F5F0E8] transition-colors">
              <User className="w-5 h-5 sm:w-6 sm:h-6" />
            </Link>
          ) : (
            <Link href="/auth/login"
              className="hidden sm:inline-flex items-center px-5 py-2
                bg-[#E8531A] hover:bg-[#E8531A]/90 text-white
                text-sm font-semibold rounded-lg transition-all">
              Sign In
            </Link>
          )}

          <button onClick={() => setIsOpen(!isOpen)}
            className="md:hidden p-2 text-[#888] hover:text-[#F5F0E8]">
            {isOpen
              ? <X className="w-6 h-6" />

```



```

      : <MenuIcon className="w-6 h-6" />
    </button>
  </div>
</div>
</div>

{isOpen && (
  <div className="md:hidden bg-[#0D0D0D]/98 backdrop-blur-xl
    border-t border-white/5">
    <div className="px-4 py-4 space-y-1">
      {navLinks.map(link => (
        <Link key={link.path} href={link.path}
          onClick={() => setIsOpen(false)}
          className={`block px-4 py-3 rounded-lg text-sm
            tracking-wider uppercase transition-colors
            ${isActive(link.path)}
            ? 'text-[#E8531A] bg-[#E8531A]/10'
            : 'text-[#888] hover:text-[#F5F0E8] hover:bg-white/5'`}>
          {link.label}
        </Link>
      ))}
      <Link href="/cart" onClick={() => setIsOpen(false)}
        className="flex items-center gap-3 px-4 py-3 rounded-lg
          text-sm text-[#888] hover:text-[#F5F0E8] hover:bg-white/5">
        <ShoppingBag className="w-5 h-5" /> Cart ({itemCount})
      </Link>
      {isAuthenticated ? (
        <Link href="/account" onClick={() => setIsOpen(false)}
          className="flex items-center gap-3 px-4 py-3 rounded-lg
            text-sm text-[#888] hover:text-[#F5F0E8] hover:bg-white/5">
          <User className="w-5 h-5" /> My Account
        </Link>
      ) : (
        <Link href="/auth/login" onClick={() => setIsOpen(false)}
          className="block px-4 py-3 bg-[#E8531A] text-white
            text-sm font-semibold rounded-lg text-center">
          Sign In
        </Link>
      )}
    </div>
  </div>
)}
</nav>
);
}

```

STEP 7 — Create the MenuItemCard Component

Create components/MenuItemCard.tsx — Popular badge, hover-reveal add button, "Added checkmark" animation state, Next.js Image with fill prop:

FILE: components/MenuItemCard.tsx

```
'use client';
```

```

import { useState } from 'react';
import Image from 'next/image';
import { Plus, Star } from 'lucide-react';
import { useCartStore } from '@store/cart';
import { MenuItem } from '@data/menu';

export default function MenuItemCard({ item }: { item: MenuItem }) {
  const addItem = useCartStore(s => s.addItem);
  const [added, setAdded] = useState(false);

  const handleAdd = () => {
    addItem({
      menuItemId: item.id,
      name: item.name,
      price: item.price,
      imageUrl: item.imageUrl,
    });
    setAdded(true);
    setTimeout(() => setAdded(false), 1200);
  };

  return (
    <div className="group bg-[#1A1A1A] rounded-2xl overflow-hidden
      border border-white/5 hover:border-[#E8531A]/30
      transition-all duration-300 hover:shadow-xl hover:shadow-black/30">

      <div className="relative overflow-hidden aspect-[4/3]">
        <Image src={item.imageUrl} alt={item.name} fill
          className="object-cover group-hover:scale-110
            transition-transform duration-700" />
        <div className="absolute inset-0 bg-gradient-to-t
          from-[#1A1A1A] via-transparent to-transparent" />

        {item.popular && (
          <div className="absolute top-3 left-3 flex items-center gap-1
            bg-[#E8531A] text-white px-3 py-1 rounded-full text-xs
            font-semibold">
            <Star className="w-3 h-3 fill-white" /> Popular
          </div>
        )}

        <button onClick={handleAdd}
          className={`absolute bottom-3 right-3 p-3 rounded-full
            transition-all duration-300
            ${added
              ? 'bg-green-500 scale-110'
              : 'bg-[#E8531A] opacity-0 group-hover:opacity-100'}`}
          aria-label={`Add ${item.name} to cart`}>
          {added
            ? <span className="text-white text-sm font-bold">v</span>
            : <Plus className="w-5 h-5 text-white" />}
        </button>
      </div>

      <div className="p-5">
        <div className="flex items-start justify-between gap-2 mb-2">
          <h3 className="font-display text-xl text-[#F5F0E8] leading-tight">

```

```

      {item.name}
    </h3>
    <span className="font-display text-xl text-[#E8531A] flex-shrink-0">
      ${item.price.toFixed(2)}
    </span>
  </div>
  <p className="text-[#888] text-sm leading-relaxed line-clamp-2">
    {item.description}
  </p>
  <button onClick={handleAdd}
    className={`mt-4 w-full py-2.5 rounded-xl text-sm font-semibold
      transition-all duration-300
      ${added
        ? 'bg-green-500/20 text-green-400 border border-green-500/30'
        : 'bg-[#E8531A] hover:bg-[#E8531A]/90 text-white'}`}>
    {added ? 'Added to Cart' : 'Add to Cart'}
  </button>
</div>
</div>
);
}

```

STEP 8 — Create the Menu Page

Create `app/menu/page.tsx` — sticky category filter bar with emoji icons, item count label, responsive 4-column grid:

FILE: `app/menu/page.tsx`

```

'use client';
import { useState } from 'react';
import { Flame } from 'lucide-react';
import { menuItems } from '@data/menu';
import MenuItemCard from '@components/MenuItemCard';

const categories = ['All', 'Burgers', 'Sides', 'Drinks', 'Combos'] as const;
const categoryEmoji: Record<string, string> = {
  Burgers: 'Burgers',
  Sides: 'Sides',
  Drinks: 'Drinks',
  Combos: 'Combos',
};

export default function MenuPage() {
  const [active, setActive] = useState<string>('All');
  const filtered =
    active === 'All'
      ? menuItems
      : menuItems.filter(i => i.category === active);

  return (
    <div className="min-h-screen pt-20 sm:pt-24">

      <div className="bg-[#141414] border-b border-white/5">
        <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8

```

```

      py-16 sm:py-20">
      <div className="flex items-center gap-3 mb-4">
        <Flame className="w-5 h-5 text-[#E8531A]" />
        <span className="text-[#E8531A] text-sm font-semibold
          tracking-wider uppercase">Order Online</span>
      </div>
      <h1 className="font-display text-5xl sm:text-7xl text-[#F5F0E8]">
        OUR MENU
      </h1>
      <p className="text-[#888] text-lg mt-3 max-w-xl">
        Handcrafted, flame-grilled, and built to order. Choose your fire.
      </p>
    </div>
  </div>

  <div className="sticky top-16 sm:top-20 z-40 bg-[#0D0D0D]/95
    backdrop-blur-xl border-b border-white/5">
    <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8">
      <div className="flex items-center gap-2 py-4 overflow-x-auto">
        {categories.map(cat => (
          <button key={cat} onClick={() => setActive(cat)}
            className={`flex items-center gap-2 px-5 py-2.5
              rounded-xl text-sm font-semibold whitespace-nowrap
              transition-all
              ${active === cat
                ? 'bg-[#E8531A] text-white shadow-lg shadow-[#E8531A]/25'
                : 'bg-[#1A1A1A] text-[#888] hover:text-[#F5F0E8]
                  hover:bg-[#222]'}`}>
              {cat}
            </button>
          )))}
      </div>
    </div>
  </div>

  <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8
    py-10 sm:py-14">
    <div className="mb-8">
      <h2 className="font-display text-3xl text-[#F5F0E8]">
        {active === 'All' ? 'Full Menu' : active}
      </h2>
      <p className="text-[#888] text-sm mt-1">
        {filtered.length} item{filtered.length !== 1 ? 's' : ''} available
      </p>
    </div>
    <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3
      xl:grid-cols-4 gap-6">
      {filtered.map(item => (
        <MenuItemCard key={item.id} item={item} />
      )))}
    </div>
  </div>
</div>
);
}

```

STEP 9 — Create the Cart Page

Create `app/cart/page.tsx` — thumbnails via Next.js Image, +/- quantity controls, trash icon, delivery fee \$3.99, 7% tax, grand total, routes to `/checkout` or `/auth/login`:

FILE: `app/cart/page.tsx`

```
'use client';
import Link from 'next/link';
import Image from 'next/image';
import { Trash2, Plus, Minus, ShoppingBag, ArrowLeft } from 'lucide-react';
import { useCartStore } from '@store/cart';
import { useAuthStore } from '@store/auth';

export default function CartPage() {
  const items = useCartStore(s => s.items);
  const updateQuantity = useCartStore(s => s.updateQuantity);
  const removeItem = useCartStore(s => s.removeItem);
  const total = useCartStore(s => s.getTotal());
  const isAuthenticated = useAuthStore(s => s.isAuthenticated);

  const deliveryFee = 3.99;
  const tax = total * 0.07;
  const grandTotal = total + deliveryFee + tax;

  if (items.length === 0) return (
    <div className="min-h-screen pt-20 sm:pt-24 flex items-center justify-center px-4">
      <div className="text-center">
        <div className="w-20 h-20 bg-[#1A1A1A] rounded-full flex items-center justify-center mx-auto mb-6">
          <ShoppingBag className="w-10 h-10 text-[#888]" />
        </div>
        <h1 className="font-display text-4xl text-[#F5F0E8] mb-3">
          Cart is Empty
        </h1>
        <p className="text-[#888] text-lg mb-8">
          Add some fire to your order.
        </p>
        <Link href="/menu"
          className="inline-flex items-center gap-2 bg-[#E8531A] hover:bg-[#E8531A]/90 text-white px-8 py-4 rounded-xl font-semibold transition-all">
          Browse Menu
        </Link>
      </div>
    </div>
  );

  return (
    <div className="min-h-screen pt-20 sm:pt-24">
      <div className="max-w-5xl mx-auto px-4 sm:px-6 lg:px-8 py-10 sm:py-14">
        <div className="flex items-center gap-3 mb-2">
          <Link href="/menu"
            className="text-[#888] hover:text-[#F5F0E8] transition-colors">
```

```

      <ArrowLeft className="w-5 h-5" />
    </Link>
    <h1 className="font-display text-4xl sm:text-5xl text-[#F5F0E8]">
      Your Cart
    </h1>
  </div>
  <p className="text-[#888] mb-8">
    {items.length} item{items.length !== 1 ? 's' : ''} ready to fire up
  </p>

  <div className="grid grid-cols-1 lg:grid-cols-3 gap-8 lg:gap-12">
    <div className="lg:col-span-2 space-y-4">
      {items.map(item => (
        <div key={item.menuItemId}
          className="bg-[#1A1A1A] rounded-2xl p-4 sm:p-5
            border border-white/5 flex gap-4 sm:gap-6 items-center">
          <div className="w-20 h-20 sm:w-24 sm:h-24 rounded-xl
            overflow-hidden flex-shrink-0 relative">
            <Image src={item.imageUrl} alt={item.name}
              fill className="object-cover" />
          </div>
          <div className="flex-1 min-w-0">
            <h3 className="font-display text-lg text-[#F5F0E8]">
              {item.name}
            </h3>
            <p className="text-[#E8531A] font-semibold">
              ${item.price.toFixed(2)}
            </p>
          </div>
          <div className="flex items-center gap-2 sm:gap-3">
            <div className="flex items-center bg-[#0D0D0D]
              rounded-lg border border-white/10">
              <button
                onClick={() => updateQuantity(
                  item.menuItemId, item.quantity - 1)}
                className="p-2 sm:p-2.5 text-[#888]
                  hover:text-[#F5F0E8] transition-colors">
                <Minus className="w-4 h-4" />
              </button>
              <span className="px-3 sm:px-4 text-sm font-semibold
                text-[#F5F0E8] min-w-[2rem] text-center">
                {item.quantity}
              </span>
              <button
                onClick={() => updateQuantity(
                  item.menuItemId, item.quantity + 1)}
                className="p-2 sm:p-2.5 text-[#888]
                  hover:text-[#F5F0E8] transition-colors">
                <Plus className="w-4 h-4" />
              </button>
            </div>
            <button onClick={() => removeItem(item.menuItemId)}
              className="p-2 text-[#888] hover:text-red-500
                transition-colors">
              <Trash2 className="w-5 h-5" />
            </button>
          </div>
        </div>
      ))}
    </div>
  </div>

```

```

        <div className="text-right min-w-[4rem]">
          <p className="font-semibold text-[#F5F0E8]">
            ${item.price * item.quantity.toFixed(2)}
          </p>
        </div>
      </div>
    )}}
  </div>

  <div className="lg:col-span-1">
    <div className="bg-[#1A1A1A] rounded-2xl p-6
      border border-white/5 sticky top-40">
      <h3 className="font-display text-xl text-[#F5F0E8] mb-5">
        Order Summary
      </h3>
      <div className="space-y-3 text-sm">
        <div className="flex justify-between text-[#888]">
          <span>Subtotal</span><span>${total.toFixed(2)}</span>
        </div>
        <div className="flex justify-between text-[#888]">
          <span>Delivery Fee</span><span>${deliveryFee.toFixed(2)}</span>
        </div>
        <div className="flex justify-between text-[#888]">
          <span>Tax (7%)</span><span>${tax.toFixed(2)}</span>
        </div>
        <div className="border-t border-white/10 pt-3
          flex justify-between font-semibold text-[#F5F0E8]">
          <span>Total</span>
          <span className="text-lg">${grandTotal.toFixed(2)}</span>
        </div>
      </div>
      <Link
        href={isAuthenticated ? '/checkout' : '/auth/login'}
        className="block w-full mt-6 py-4 rounded-xl text-center
          bg-[#E8531A] hover:bg-[#E8531A]/90 text-white
          font-semibold transition-all">
        {isAuthenticated
          ? 'Proceed to Checkout'
          : 'Sign In to Checkout'}
      </Link>
      <Link href="/menu"
        className="flex items-center justify-center gap-2 mt-3
          text-[#888] hover:text-[#E8531A] text-sm transition-colors">
        <ArrowLeft className="w-4 h-4" /> Continue Shopping
      </Link>
    </div>
  </div>
</div>
</div>
</div>
);
}

```

STEP 10 — Create the Two-Step Checkout Page

Create app/checkout/page.tsx — Step 1: Delivery Info (phone, address, notes). Step 2: Payment (card number with auto-formatting, expiry, CVC). Pre-fills from user profile. Shows delivery fee + tax + grand total. Includes demo notice. Spins for 2 seconds then routes to /order/[id]:

FILE: app/checkout/page.tsx

```
'use client';
import { useState } from 'react';
import { useRouter } from 'next/navigation';
import { CreditCard, Lock, ArrowLeft, MapPin, Phone } from 'lucide-react';
import Image from 'next/image';
import { useCartStore } from '@store/cart';
import { useAuthStore } from '@store/auth';

export default function CheckoutPage() {
  const router = useRouter();
  const items = useCartStore(s => s.items);
  const total = useCartStore(s => s.getTotal());
  const clearCart = useCartStore(s => s.clearCart);
  const user = useAuthStore(s => s.user);
  const addOrder = useAuthStore(s => s.addOrder);

  const [step, setStep] = useState<'info' | 'payment'>('info');
  const [isProcessing, setIsProcessing] = useState(false);
  const [formData, setFormData] = useState({
    phone: user?.phone || '',
    address: user?.address || '',
    notes: '',
    cardNumber: '',
    cardName: '',
    expiry: '',
    cvc: '',
  });

  const deliveryFee = 3.99;
  const tax = total * 0.07;
  const grandTotal = total + deliveryFee + tax;

  const handleChange = (field: string, value: string) =>
    setFormData(p => ({ ...p, [field]: value }));

  const handlePayment = async (e: React.FormEvent) => {
    e.preventDefault();
    setIsProcessing(true);
    await new Promise(r => setTimeout(r, 2000));
    const orderId = `ORD-${Date.now().toString().slice(-8)}`;
    addOrder({
      id: orderId,
      items: items.map(i => ({
        name: i.name,
        price: i.price,
        quantity: i.quantity,
      })),
      total: grandTotal,
      status: 'confirmed',
    });
  };
}
```



```

      createdAt: new Date().toISOString(),
    });
    clearCart();
    router.push(`/order/${orderId}`);
  };

  if (!user) { router.push('/auth/login'); return null; }
  if (items.length === 0) { router.push('/menu'); return null; }

  return (
    <div className="min-h-screen pt-20 sm:pt-24">
      <div className="max-w-5xl mx-auto px-4 sm:px-6 lg:px-8 py-10 sm:py-14">

        <div className="flex items-center gap-3 mb-2">
          <button
            onClick={() =>
              step === 'payment' ? setStep('info') : router.push('/cart')
            }
            className="text-[#888] hover:text-[#F5F0E8] transition-colors"
            <ArrowLeft className="w-5 h-5" />
          </button>
          <h1 className="font-display text-4xl sm:text-5xl text-[#F5F0E8]">
            Checkout
          </h1>
        </div>

        {/ * Step Indicators */}
        <div className="flex items-center gap-4 my-8">
          {[ 'Delivery Info', 'Payment' ].map((label, i) => (
            <div key={label} className="flex items-center gap-2 text-sm">
              <div className={`flex items-center gap-2 text-sm
                ${i === 0 ? step === 'info' : step === 'payment'
                  ? 'text-[#E8531A]' : 'text-[#888]'} `}>
                <div className={`w-8 h-8 rounded-full flex items-center justify-center font-semibold
                  ${i === 0 ? step === 'info' : step === 'payment'
                    ? 'bg-[#E8531A] text-white'
                    : 'bg-[#1A1A1A] text-[#888]'} `}>
                  {i + 1}
                </div>
                <span className="hidden sm:inline">{label}</span>
              </div>
              {i === 0 && <div className="w-12 h-px bg-white/10 ml-2" />}
            </div>
          ))}
        </div>

        <div className="grid grid-cols-1 lg:grid-cols-3 gap-8 lg:gap-12">
          <div className="lg:col-span-2">

            {/ * STEP 1: Delivery Info */}
            {step === 'info' ? (
              <form
                onSubmit={(e) => { e.preventDefault(); setStep('payment'); }}
                className="bg-[#1A1A1A] rounded-2xl p-6 border border-white/5 space-y-5">
                <h2 className="font-display text-2xl text-[#F5F0E8]">

```

```

    Delivery Details
  </h2>
  <div className="relative">
    <label className="block text-sm text-[#888] mb-2">
      Phone Number
    </label>
    <Phone className="absolute left-3 top-[2.4rem]
      w-5 h-5 text-[#888]" />
    <input type="tel" value={formData.phone}
      onChange={e => handleChange('phone', e.target.value)}
      required placeholder="(555) 123-4567"
      className="w-full bg-[#0D0D0D] border border-white/10
        rounded-xl pl-11 pr-4 py-3 text-[#F5F0E8]
        placeholder-[#555] focus:border-[#E8531A]
        focus:outline-none transition-colors" />
  </div>
  <div className="relative">
    <label className="block text-sm text-[#888] mb-2">
      Delivery Address
    </label>
    <MapPin className="absolute left-3 top-[2.4rem]
      w-5 h-5 text-[#888]" />
    <input type="text" value={formData.address}
      onChange={e => handleChange('address', e.target.value)}
      required placeholder="123 Street, City, State ZIP"
      className="w-full bg-[#0D0D0D] border border-white/10
        rounded-xl pl-11 pr-4 py-3 text-[#F5F0E8]
        placeholder-[#555] focus:border-[#E8531A]
        focus:outline-none transition-colors" />
  </div>
  <div>
    <label className="block text-sm text-[#888] mb-2">
      Order Notes (Optional)
    </label>
    <textarea value={formData.notes}
      onChange={e => handleChange('notes', e.target.value)}
      rows={3} placeholder="Any special instructions?"
      className="w-full bg-[#0D0D0D] border border-white/10
        rounded-xl px-4 py-3 text-[#F5F0E8]
        placeholder-[#555] focus:border-[#E8531A]
        focus:outline-none transition-colors resize-none" />
  </div>
  <button type="submit"
    className="w-full py-4 rounded-xl bg-[#E8531A]
      hover:bg-[#E8531A]/90 text-white font-semibold
      transition-all">
    Continue to Payment
  </button>
</form>

) : (
  /* STEP 2: Payment */
  <form onSubmit={handlePayment}
    className="bg-[#1A1A1A] rounded-2xl p-6
      border border-white/5 space-y-5">
    <div>
      <h2 className="font-display text-2xl text-[#F5F0E8] mb-1">

```

```

      Payment Details
    </h2>
    <div className="flex items-center gap-2 text-[#888] text-sm">
      <Lock className="w-4 h-4" />
      <span>Secured by Stripe - 256-bit encryption</span>
    </div>
  </div>

  <div className="relative">
    <label className="block text-sm text-[#888] mb-2">
      Card Number
    </label>
    <CreditCard className="absolute left-3 top-[2.4rem]
      w-5 h-5 text-[#888]" />
    <input type="text" value={formData.cardNumber}
      placeholder="4242 4242 4242 4242"
      required minLength={16}
      onChange={e => {
        const v = e.target.value
        .replace(/\D/g, '').slice(0, 16);
        handleChange('cardNumber',
          v.replace(/(\d{4})/g, '$1 ').trim());
      }}
      className="w-full bg-[#0D0D0D] border border-white/10
        rounded-xl pl-11 pr-4 py-3 text-[#F5F0E8]
        placeholder-[#555] focus:border-[#E8531A]
        focus:outline-none transition-colors font-mono" />
  </div>

  <div>
    <label className="block text-sm text-[#888] mb-2">
      Cardholder Name
    </label>
    <input type="text" value={formData.cardName}
      placeholder={user.name} required
      onChange={e => handleChange('cardName', e.target.value)}
      className="w-full bg-[#0D0D0D] border border-white/10
        rounded-xl px-4 py-3 text-[#F5F0E8] placeholder-[#555]
        focus:border-[#E8531A] focus:outline-none
        transition-colors" />
  </div>

  <div className="grid grid-cols-2 gap-4">
    <div>
      <label className="block text-sm text-[#888] mb-2">
        Expiry
      </label>
      <input type="text" value={formData.expiry}
        placeholder="MM/YY" required maxLength={5}
        onChange={e => {
          let v = e.target.value
          .replace(/\D/g, '').slice(0, 4);
          if (v.length >= 2)
            v = v.slice(0, 2) + '/' + v.slice(2);
          handleChange('expiry', v);
        }}
        className="w-full bg-[#0D0D0D] border border-white/10

```

```

        rounded-xl px-4 py-3 text-[#F5F0E8]
        placeholder-[#555] focus:border-[#E8531A]
        focus:outline-none transition-colors font-mono" />
    </div>
    <div>
      <label className="block text-sm text-[#888] mb-2">
        CVC
      </label>
      <input type="text" value={formData.cvc}
        placeholder="123" required maxLength={3}
        onChange={e => handleChange('cvc',
          e.target.value.replace(/\D/g, '').slice(0, 3))}
        className="w-full bg-[#0D0D0D] border border-white/10
        rounded-xl px-4 py-3 text-[#F5F0E8]
        placeholder-[#555] focus:border-[#E8531A]
        focus:outline-none transition-colors font-mono" />
    </div>
  </div>

  <button type="submit" disabled={isProcessing}
    className="w-full py-4 rounded-xl bg-[#E8531A]
    hover:bg-[#E8531A]/90 text-white font-semibold
    transition-all disabled:opacity-70
    flex items-center justify-center gap-2">
    {isProcessing ? (
      <>
        <div className="w-5 h-5 border-2 border-white/30
          border-t-white rounded-full animate-spin" />
        Processing...
      </>
    ) : (
      <>
        <Lock className="w-4 h-4" />
        Pay ${grandTotal.toFixed(2)}
      </>
    )}
  </button>
  <p className="text-[#888] text-xs text-center">
    Demo mode - use any card details to simulate payment.
  </p>
</form>
)}
</div>

{/* Order Summary Sidebar */}
<div className="lg:col-span-1">
  <div className="bg-[#1A1A1A] rounded-2xl p-6
    border border-white/5 sticky top-40">
    <h3 className="font-display text-xl text-[#F5F0E8] mb-5">
      Your Order
    </h3>
    <div className="space-y-3 mb-5">
      {items.map(item => (
        <div key={item.menuItemId}
          className="flex items-center gap-3">
            <div className="w-10 h-10 rounded-lg overflow-hidden
              flex-shrink-0 relative">

```

```

        <Image src={item.imageUrl} alt={item.name}
          fill className="object-cover" />
      </div>
      <div className="flex-1 min-w-0">
        <p className="text-sm text-[#F5F0E8] truncate">
          {item.name}
        </p>
        <p className="text-xs text-[#888]">
          Qty: {item.quantity}
        </p>
      </div>
      <p className="text-sm text-[#F5F0E8]">
        ${item.price * item.quantity}.toFixed(2)}
      </p>
    </div>
  )}
</div>
<div className="border-t border-white/10 pt-4
  space-y-2 text-sm">
  <div className="flex justify-between text-[#888]">
    <span>Subtotal</span><span>${total.toFixed(2)}</span>
  </div>
  <div className="flex justify-between text-[#888]">
    <span>Delivery</span><span>${deliveryFee.toFixed(2)}</span>
  </div>
  <div className="flex justify-between text-[#888]">
    <span>Tax</span><span>${tax.toFixed(2)}</span>
  </div>
  <div className="border-t border-white/10 pt-2
    flex justify-between font-semibold text-[#F5F0E8]">
    <span>Total</span>
    <span className="text-lg">${grandTotal.toFixed(2)}</span>
  </div>
</div>
</div>
</div>
</div>
</div>
);
}

```

STEP 11 — Create Auth Pages — Login and Register

Login page: `app/auth/login/page.tsx`

Email + password with show/hide toggle, loading spinner, error state, link to register:

FILE: `app/auth/login/page.tsx`

```

'use client';
import { useState } from 'react';
import Link from 'next/link';
import { useRouter } from 'next/navigation';

```

```

import { Eye, EyeOff, Flame } from 'lucide-react';
import { useAuthStore } from '@store/auth';

export default function LoginPage() {
  const router = useRouter();
  const login = useAuthStore(s => s.login);
  const [email, setEmail] = useState('');
  const [password, setPassword] = useState('');
  const [showPw, setShowPw] = useState(false);
  const [error, setError] = useState('');
  const [loading, setLoading] = useState(false);

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setError('');
    setLoading(true);
    const ok = await login(email, password);
    setLoading(false);
    if (ok) { router.push('/menu'); }
    else { setError('Invalid email or password.')}
  };

  return (
    <div className="min-h-screen flex items-center justify-center
      px-4 pt-20 pb-12">
      <div className="w-full max-w-md">
        <div className="text-center mb-10">
          <Link href="/" className="inline-block mb-6">
            <span className="font-display text-5xl text-[#E8531A]">
              828 GRILL
            </span>
          </Link>
          <h1 className="font-display text-4xl text-[#F5F0E8] mb-2">
            Welcome Back
          </h1>
          <p className="text-[#888]">Sign in to continue ordering</p>
        </div>

        <form onSubmit={handleSubmit}
          className="bg-[#1A1A1A] rounded-2xl p-6 sm:p-8
            border border-white/5 space-y-5">
          {error && (
            <div className="bg-red-500/10 border border-red-500/30
              rounded-xl p-4">
              <p className="text-red-400 text-sm">{error}</p>
            </div>
          )}
          <div>
            <label className="block text-sm text-[#888] mb-2">Email</label>
            <input type="email" value={email}
              onChange={e => setEmail(e.target.value)}
              required placeholder="your@email.com"
              className="w-full bg-[#0D0D0D] border border-white/10
                rounded-xl px-4 py-3 text-[#F5F0E8] placeholder-[#555]
                focus:border-[#E8531A] focus:outline-none transition-colors" />
          </div>
        </div>
      </div>
    </div>
  );
}

```

```

<label className="block text-sm text-[#888] mb-2">Password</label>
<div className="relative">
  <input type={showPw ? 'text' : 'password'} value={password}
    onChange={e => setPassword(e.target.value)}
    required placeholder="....."
    className="w-full bg-[#0D0D0D] border border-white/10
      rounded-xl px-4 py-3 pr-12 text-[#F5F0E8]
      placeholder-[#555] focus:border-[#E8531A]
      focus:outline-none transition-colors" />
  <button type="button" onClick={() => setShowPw(!showPw)}
    className="absolute right-3 top-1/2 -translate-y-1/2
      text-[#888] hover:text-[#F5F0E8]">
    {showPw
      ? <EyeOff className="w-5 h-5" />
      : <Eye className="w-5 h-5" />}
  </button>
</div>
</div>
<button type="submit" disabled={loading}
  className="w-full py-4 rounded-xl bg-[#E8531A]
    hover:bg-[#E8531A]/90 text-white font-semibold
    transition-all disabled:opacity-70
    flex items-center justify-center gap-2">
  {loading ? (
    <>
      <div className="w-5 h-5 border-2 border-white/30
        border-t-white rounded-full animate-spin" />
      Signing In...
    </>
  ) : (
    <>
      <Flame className="w-5 h-5" /> Sign In
    </>
  )}
</button>
</form>

<p className="text-center text-[#888] text-sm mt-6">
  No account yet?{' '}
  <Link href="/auth/register"
    className="text-[#E8531A] font-medium">
    Create one
  </Link>
</p>
</div>
</div>
);
}

```

Register page: `app/auth/register/page.tsx`

All five fields: Full Name, Email, Password (min 8), Phone (optional), Delivery Address (optional):

FILE: `app/auth/register/page.tsx`

```
'use client';
```

```

import { useState } from 'react';
import Link from 'next/link';
import { useRouter } from 'next/navigation';
import { Eye, EyeOff, Flame } from 'lucide-react';
import { useAuthStore } from '@store/auth';

export default function RegisterPage() {
  const router = useRouter();
  const register = useAuthStore(s => s.register);
  const [form, setForm] = useState({
    name: '', email: '', password: '', phone: '', address: '',
  });
  const [showPw, setShowPw] = useState(false);
  const [error, setError] = useState('');
  const [loading, setLoading] = useState(false);
  const set = (f: string, v: string) => setForm(p => ({ ...p, [f]: v }));

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setError('');
    if (form.password.length < 8) {
      setError('Password must be at least 8 characters.');
```

```

    return;
  }
  setLoading(true);
  const ok = await register({
    name: form.name,
    email: form.email,
    password: form.password,
    phone: form.phone || undefined,
    address: form.address || undefined,
  });
  setLoading(false);
  if (ok) { router.push('/account'); }
  else { setError('An account with this email already exists.');
```

```

  };

  const inputClass = [
    'w-full bg-[#0D0D0D] border border-white/10 rounded-xl',
    'px-4 py-3 text-[#F5F0E8] placeholder-[#555]',
    'focus:border-[#E8531A] focus:outline-none transition-colors',
  ].join(' ');

  return (
    <div className="min-h-screen flex items-center justify-center
      px-4 pt-20 pb-12">
      <div className="w-full max-w-md">
        <div className="text-center mb-10">
          <Link href="/" className="inline-block mb-6">
            <span className="font-display text-5xl text-[#E8531A]">
              828 GRILL
            </span>
          </Link>
          <h1 className="font-display text-4xl text-[#F5F0E8] mb-2">
            Join the Fire
          </h1>
          <p className="text-[#888]">Create your account and start ordering</p>

```



```

</div>

<form onSubmit={handleSubmit}
  className="bg-[#1A1A1A] rounded-2xl p-6 sm:p-8
    border border-white/5 space-y-4">
  {error && (
    <div className="bg-red-500/10 border border-red-500/30
      rounded-xl p-4">
      <p className="text-red-400 text-sm">{error}</p>
    </div>
  )}

  <div>
    <label className="block text-sm text-[#888] mb-2">
      Full Name *
    </label>
    <input type="text" value={form.name}
      onChange={e => set('name', e.target.value)}
      required placeholder="John Smith" className={inputClass} />
  </div>

  <div>
    <label className="block text-sm text-[#888] mb-2">Email *</label>
    <input type="email" value={form.email}
      onChange={e => set('email', e.target.value)}
      required placeholder="your@email.com" className={inputClass} />
  </div>

  <div>
    <label className="block text-sm text-[#888] mb-2">
      Password * (min 8 chars)
    </label>
    <div className="relative">
      <input type={showPw ? 'text' : 'password'} value={form.password}
        onChange={e => set('password', e.target.value)}
        required minLength={8} placeholder="....."
        className={` ${inputClass} pr-12`} />
      <button type="button" onClick={() => setShowPw(!showPw)}
        className="absolute right-3 top-1/2 -translate-y-1/2
          text-[#888] hover:text-[#F5F0E8]">
        {showPw
          ? <EyeOff className="w-5 h-5" />
          : <Eye className="w-5 h-5" />}
      </button>
    </div>
  </div>

  <div>
    <label className="block text-sm text-[#888] mb-2">
      Phone Number (Optional)
    </label>
    <input type="tel" value={form.phone}
      onChange={e => set('phone', e.target.value)}
      placeholder="(555) 123-4567" className={inputClass} />
  </div>

</div>

```

```

    <label className="block text-sm text-[#888] mb-2">
      Delivery Address (Optional)
    </label>
    <input type="text" value={form.address}
      onChange={e => set('address', e.target.value)}
      placeholder="123 Street, City, State ZIP"
      className={inputClass} />
  </div>

  <button type="submit" disabled={loading}
    className="w-full py-4 rounded-xl bg-[#E8531A]
      hover:bg-[#E8531A]/90 text-white font-semibold
      transition-all disabled:opacity-70
      flex items-center justify-center gap-2 mt-2">
    {loading ? (
      <>
        <div className="w-5 h-5 border-2 border-white/30
          border-t-white rounded-full animate-spin" />
        Creating Account...
      </>
    ) : (
      <>
        <Flame className="w-5 h-5" /> Create Account
      </>
    )}
  </button>
</form>

<p className="text-center text-[#888] text-sm mt-6">
  Already have an account?{' '}
  <Link href="/auth/login" className="text-[#E8531A] font-medium">
    Sign in
  </Link>
</p>
</div>
</div>
);
}

```

STEP 12 — Create the Account Page

Create `app/account/page.tsx` — avatar (first-letter initial with orange gradient), profile card with phone and address, full order history with status badges and per-item breakdown:

FILE: `app/account/page.tsx`

```

'use client';
import Link from 'next/link';
import { useRouter } from 'next/navigation';
import { Logout, MapPin, Phone, Package } from 'lucide-react';
import { useAuthStore } from '@store/auth';

export default function AccountPage() {
  const router = useRouter();

```

```

const user = useAuthStore(s => s.user);
const logout = useAuthStore(s => s.logout);

if (!user) { router.push('/auth/login'); return null; }

return (
  <div className="min-h-screen pt-20 sm:pt-24">
    <div className="max-w-4xl mx-auto px-4 sm:px-6 lg:px-8
      py-10 sm:py-14">

      <div className="flex items-center justify-between mb-10">
        <div>
          <h1 className="font-display text-4xl sm:text-5xl text-[#F5F0E8]">
            My Account
          </h1>
          <p className="text-[#888] mt-1">Profile and order history</p>
        </div>
        <button
          onClick={() => { logout(); router.push('/'); }}
          className="flex items-center gap-2 px-5 py-2.5 bg-[#1A1A1A]
            border border-white/10 rounded-xl text-[#888]
            hover:text-red-400 hover:border-red-400/30 transition-all">
          <LogOut className="w-4 h-4" />
          <span className="text-sm font-medium">Sign Out</span>
        </button>
      </div>

      <div className="bg-[#1A1A1A] rounded-2xl p-6 sm:p-8
        border border-white/5 mb-8">
        <div className="flex items-center gap-5 mb-8">
          <div className="w-16 h-16 bg-gradient-to-br from-[#E8531A]
            to-[#C44412] rounded-full flex items-center justify-center
            text-2xl font-bold text-white">
            {user.name.charAt(0).toUpperCase()}
          </div>
          <div>
            <h2 className="font-display text-2xl text-[#F5F0E8]">
              {user.name}
            </h2>
            <p className="text-[#888] text-sm">{user.email}</p>
          </div>
        </div>

        <div className="grid grid-cols-1 sm:grid-cols-2 gap-4">
          <div className="flex items-center gap-3 bg-[#0D0D0D]
            rounded-xl p-4 border border-white/5">
            <Phone className="w-5 h-5 text-[#E8531A] flex-shrink-0" />
            <div>
              <p className="text-xs text-[#888] uppercase tracking-wider">
                Phone
              </p>
              <p className="text-[#F5F0E8] text-sm">
                {user.phone || 'Not set'}
              </p>
            </div>
          </div>

          <div className="flex items-center gap-3 bg-[#0D0D0D]
            rounded-xl p-4 border border-white/5">

```

```

    <MapPin className="w-5 h-5 text-[#E8531A] flex-shrink-0" />
  <div>
    <p className="text-xs text-[#888] uppercase tracking-wider">
      Address
    </p>
    <p className="text-[#F5F0E8] text-sm">
      {user.address || 'Not set'}
    </p>
  </div>
</div>
</div>
</div>

<div>
  <h3 className="font-display text-2xl text-[#F5F0E8] mb-6
    flex items-center gap-2">
    <Package className="w-5 h-5 text-[#E8531A]" /> Order History
  </h3>
  {user.orders && user.orders.length > 0 ? (
    <div className="space-y-4">
      {user.orders.map(order => (
        <div key={order.id}
          className="bg-[#1A1A1A] rounded-2xl p-5 border
            border-white/5 hover:border-[#E8531A]/20 transition-colors">
          <div className="flex items-center justify-between mb-4">
            <div className="flex items-center gap-3">
              <span className="font-mono text-sm text-[#E8531A]
                bg-[#E8531A]/10 px-3 py-1 rounded-lg">
                {order.id}
              </span>
              <span className={`text-xs px-2.5 py-1 rounded-full
                font-semibold
                ${order.status === 'confirmed' ||
                  order.status === 'paid'
                  ? 'bg-green-500/10 text-green-400'
                  : 'bg-blue-500/10 text-blue-400'}`}>
                {order.status.toUpperCase()}
              </span>
            </div>
            <span className="text-[#888] text-sm">
              {new Date(order.createdAt).toLocaleDateString('en-US', {
                month: 'short', day: 'numeric', year: 'numeric',
              })}
            </span>
          </div>
          <div className="space-y-2">
            <div className="flex justify-between text-sm">
              <span className="text-[#F5F0E8]">
                {item.quantity}x {item.name}
              </span>
              <span className="text-[#888]">
                ${(item.price * item.quantity).toFixed(2)}
              </span>
            </div>
          </div>
        </div>
      )})}
    </div>
  )}
</div>

```

```

      <div className="border-t border-white/5 mt-3 pt-3
        flex justify-between">
        <span className="text-[#888] text-sm">Total</span>
        <span className="text-[#F5F0E8] font-semibold">
          ${order.total.toFixed(2)}
        </span>
      </div>
    </div>
  )}}
</div>
) : (
  <div className="bg-[#1A1A1A] rounded-2xl p-10
    border border-white/5 text-center">
    <Package className="w-12 h-12 text-[#888] mx-auto mb-4" />
    <p className="text-[#888] text-lg">No orders yet</p>
    <Link href="/menu"
      className="inline-flex items-center gap-2 mt-5
        bg-[#E8531A] hover:bg-[#E8531A]/90 text-white
        px-6 py-3 rounded-xl text-sm font-semibold transition-all">
      Order Now
    </Link>
  </div>
  )}
</div>
</div>
</div>
);
}

```

STEP 13 — Create the Order Confirmation Page

Create `app/order/[id]/page.tsx` — green checkmark, order ID badge, itemised receipt, delivery address, 30-45 min ETA, Order More and View Orders buttons:

FILE: `app/order/[id]/page.tsx`

```

'use client';
import Link from 'next/link';
import { CheckCircle, Flame, ArrowRight, MapPin } from 'lucide-react';
import { useAuthStore } from '@store/auth';

export default function OrderConfirmationPage() {
  const user = useAuthStore(s => s.user);
  const order = user?.orders?.[0];

  return (
    <div className="min-h-screen pt-20 sm:pt-24">
      <div className="max-w-2xl mx-auto px-4 sm:px-6 py-10 sm:py-20">

        <div className="text-center mb-10">
          <div className="w-20 h-20 bg-green-500/10 rounded-full
            flex items-center justify-center mx-auto mb-6">
            <CheckCircle className="w-10 h-10 text-green-500" />
          </div>

```

```

<h1 className="font-display text-4xl sm:text-5xl
  text-[#F5F0E8] mb-3">
  Order Confirmed!
</h1>
<p className="text-[#888] text-lg">
  Your fire is being prepared.
  Thank you for choosing 828 Grill.
</p>
</div>

{order && (
  <div className="bg-[#1A1A1A] rounded-2xl border border-white/5
    overflow-hidden">
    <div className="bg-[#E8531A]/10 border-b border-[#E8531A]/20
      px-6 py-4 flex items-center justify-between">
      <div className="flex items-center gap-2">
        <Flame className="w-4 h-4 text-[#E8531A]" />
        <span className="text-[#E8531A] text-sm font-medium">
          Order Placed Successfully
        </span>
      </div>
    </div>
    <span className="font-mono text-sm text-[#F5F0E8]
      bg-[#0D0D0D] px-3 py-1 rounded-lg">
      {order.id}
    </span>
  </div>

  <div className="p-6">
    <div className="space-y-3 mb-6">
      {order.items.map((item, i) => (
        <div key={i}
          className="flex items-center justify-between text-sm">
          <div className="flex items-center gap-3">
            <span className="bg-[#0D0D0D] text-[#E8531A] w-6 h-6
              rounded-md flex items-center justify-center
              text-xs font-bold">
              {item.quantity}
            </span>
            <span className="text-[#F5F0E8]">{item.name}</span>
          </div>
          <span className="text-[#888]">
            ${item.price * item.quantity}.toFixed(2)}
          </span>
        </div>
      )})}
    </div>

    {user?.address && (
      <div className="flex items-start gap-3 bg-[#0D0D0D]
        rounded-xl p-4 mb-6 border border-white/5">
        <MapPin className="w-5 h-5 text-[#E8531A] mt-0.5
          flex-shrink-0" />
        <div>
          <p className="text-xs text-[#888] uppercase
            tracking-wider mb-1">Delivering to</p>
          <p className="text-[#F5F0E8] text-sm">
            {user.address}
          </p>
        </div>
      </div>
    )}
  )}
)

```

```

        </p>
      </div>
    </div>
  })

  <div className="border-t border-white/10 pt-4
    flex justify-between">
    <span className="text-[#888] font-medium">Total Paid</span>
    <span className="text-2xl font-semibold text-[#F5F0E8]">
      ${order.total.toFixed(2)}
    </span>
  </div>

  <div className="mt-6 bg-[#E8531A]/5 rounded-xl p-4
    border border-[#E8531A]/20 flex items-center gap-3">
    <div className="w-10 h-10 bg-[#E8531A]/10 rounded-full
      flex items-center justify-center flex-shrink-0">
      <span className="text-lg">ETA</span>
    </div>
    <div>
      <p className="text-[#F5F0E8] text-sm font-medium">
        Estimated Delivery
      </p>
      <p className="text-[#888] text-sm">30 to 45 minutes</p>
    </div>
  </div>
</div>
</div>
  })

  <div className="mt-8 flex flex-col sm:flex-row items-center
    justify-center gap-4">
    <Link href="/menu"
      className="flex items-center gap-2 bg-[#E8531A]
        hover:bg-[#E8531A]/90 text-white px-8 py-4 rounded-xl
        font-semibold transition-all w-full sm:w-auto justify-center">
      Order More <ArrowRight className="w-5 h-5" />
    </Link>
    <Link href="/account"
      className="flex items-center justify-center px-8 py-4
        rounded-xl border border-white/10 text-[#F5F0E8]
        hover:bg-white/5 transition-all w-full sm:w-auto font-semibold">
      View Orders
    </Link>
  </div>
</div>
</div>
  );
}

```

STEP 14 — Update Home Page to Use Real Menu Data

In the existing Home page (app/page.tsx or app/page.tsx depending on your structure), find wherever featured items are currently hardcoded or use placeholder data. Add these imports at the top and replace the featured items section:

ADD TO TOP OF: app/page.tsx

```
import { menuItems } from '@/data/menu';
import MenuItemCard from '@/components/MenuItemCard';
```

REPLACE featured items grid with:

```
// Inside the component, derive featured items from real data:
const featuredItems = menuItems.filter(item => item.popular);

// In the JSX, replace whatever was there with:
<div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3
  xl:grid-cols-4 gap-6 mt-12">
  {featuredItems.map(item => (
    <MenuItemCard key={item.id} item={item} />
  ))}
</div>
```

STEP 15 — Final Checks — Required Before Completing

After generating all files, verify every item in this checklist before considering the build done:

✓ **use client directive on every interactive file**

Every file that uses useState, useEffect, useRouter, usePathname, or any Zustand store import MUST have 'use client'; as the very first line, before any import statements. Missing this causes hydration errors in Next.js.

✓ **Next.js Link uses href not to**

All Link components must use href="/path" syntax. The 'to' prop is React Router DOM syntax and will throw a TypeScript error in Next.js. Check every Link in every file.

✓ **HTML img tags replaced with Next.js Image**

All plain HTML img tags must be replaced with the Next.js Image component imported from 'next/image'. For images with dynamic sizing, use the fill prop inside a parent div that has position:relative and a defined size.

✓ **No vercel.json rewrites needed**

Next.js App Router handles all routing natively via the app/ directory. Do NOT add any rewrite rules to vercel.json as they are unnecessary and will conflict with the App Router.

✓ **No react-router-dom anywhere in the project**

Confirm there is no HashRouter, BrowserRouter, Routes, Route, useNavigate, useLocation, or any other import from 'react-router-dom' in the project. These came from ZIP 2 and must not be carried over to this Next.js build.

✓ **Zustand persist middleware on both stores**

Both useCartStore (src/store/cart.ts) and useAuthStore (src/store/auth.ts) must be wrapped with the persist() middleware from 'zustand/middleware' and each must have a unique name key: '828-grill-cart' and '828-grill-auth'.

✓ **Hero headline reads TASTE THE FIRE (with space)**

Confirm the hero section headline reads 'TASTE THE FIRE' with a space between TASTE and THE. The original Site 3 had a typo 'TASTETHE FIRE' that must be fixed.

✓ **Site 3 design elements are all untouched**

The following must remain exactly as they were in Site 3: the tagline 'Fire. Smoke. Craft.', the scrolling marquee ticker, the SEO metadata in layout.tsx, the color palette (#0D0D0D, #E8531A, #F5F0E8), and the hero image. Nothing from Site 3 design was to be removed or overwritten.

END OF PROMPT · 828 Grill LLC · Full-Stack Build Reference · Prepared by Roy Aloo · rauell.systems