



Arrays and structures

Bachelor of Science - École polytechnique

gael.thomas@inria.fr

Key concepts

■ Array: homogenous

- To declare an array: `type var[n];`
- To access an array: `var[n]`

■ Structure: heterogeneous

- To define a type: `struct name_of_the_struct { ... };`
- To declare a structure: `struct name_of_the_struct var;`
- To access a field: `var.field_name`

Complex data structures

- The C language provides two kinds of complex data structures
 - **Array**: to store **homogenous** elements
 - **Structure**: to store **heterogeneous** elements

17	3	4	18	13	1
----	---	---	----	----	---

An array of 6 **int**

'a'	3	3.14
-----	---	------

A structure with a **char**, an **int** and a **float**

Array declaration

- To declare an array: `type name[n]`
 - `type` gives the type of the elements
 - `name` is the name of the variable
 - `[...]` indicates that we declare an array
 - `n` is the number of elements of the array

```
int main(int argc, char** argv) {  
    int tab[3];  
    return 0;  
}
```

Note: the number of elements is fixed at declaration and cannot change later

Declaration and initialization

- We can initialize an array when we declare it
 - With `type name[n] = { v0, v1, v2, ... };`
 - In this case, we can omit `n` (deduced from the initializer)

```
int main(int argc, char** argv) {  
    int tab[] = { 1, 2, 3 };  
    return 0;  
}
```

Array access

- To access an array: `name[idx]`
 - `name` gives the name of the variable
 - `[...]` indicates an array access
 - `idx` gives the index of the accessed element

```
int main(int argc, char** argv) {  
    int tab[3];  
    for(int i=0; i<3; i++) {  
        tab[i] = i + 1;  
    }  
    return 0;  
}
```

Array and function call

- To declare a function parameter with an array type
 - `type name[]`

```
void f(int tab[]) {  
    for(int i=0; i<3; i++) {  
        printf("%d\n", tab[i]);  
    } // print 1, 2, 3  
}  
  
int main(int argc, char** argv) {  
    int tab[3] = { 1, 2, 3 };  
    f(tab);  
    return 0;  
}
```

Array and function call

- To declare a function parameter with an array type
 - `type name[]`

```
void f(int tab[]) {  
    for(int i=0; i<3; i++) {  
        printf("%d\n", tab[i]);  
    } // print 1, 2, 3  
}  
  
int main(int argc, char** argv) {  
    int tab[3] = { 1, 2, 3 };  
    f(tab);  
}
```

Note: if `f` modifies `tab`, this modifies the `tab` of `main`
(we say that an array is passed by pointer - explained in a next lesson)

Structure declaration

- To declare a structure: first, define a new type with

```
struct name_of_the_struct {  
    type1 field_name_1;  
    type2 field_name_2;  
    ...  
};
```

```
struct strange {  
    char c;  
    int i;  
    float f;  
};
```

c, i and f are called the **fields** of the structure

Structure declaration

- To declare a structure: first, define a new type with

```
struct name_of_the_struct {  
    type1 field_name_1;  
    type2 field_name_2;  
    ...  
};
```

```
struct strange {  
    char c;  
    int i;  
    float f;  
};
```

- The new type is used to create symbols to access the fields
 - `c` is the 0th element of the structure
 - `i` is the 1st element of the structure
 - `f` is the 2nd element of the structure

Structure declaration

- Then you can declare a variable with the new type

```
struct name_of_the_struct var_name;
```

```
struct strange {  
    char c;  
    int i;  
    float f;  
};  
  
int main(int argc, char* argv[]) {  
    struct strange var;  
    return 0;  
}
```

Declaration and initialisation

- You can initialize a structure when you declare it with
= { .field1: val1, .field2: val2, ... };

```
struct strange {  
    char c;  
    int i;  
    float f;  
};  
  
int main(int argc, char* argv[]) {  
    struct strange var = { .c: 'a', .i: 3, .f: 3.14 };  
    return 0;  
}
```

'a'	3	3.14
-----	---	------

Declaration and initialisation

- Or with the fields given in the definition order
= { val1, val2, ... };

```
struct strange {  
    char c;  
    int i;  
    float f;  
};  
  
int main(int argc, char* argv[]) {  
    struct strange var = { 'a', 3, 3.14 };  
    return 0;  
}
```

'a'	3	3.14
-----	---	------

Structure access

- To access a field, use the symbol dot

`var_name.field_name`

```
struct strange {  
    char c;  
    int i;  
    float f;  
};  
  
int main(int argc, char* argv[]) {  
    struct strange var;  
    var.c = 'a';  
    var.i = 3;  
    var.f = 3.14;  
    printf("%c %d %f\n", var.c, var.i, var.f);  
    return 0;  
}
```

Structure and functions

- To declare a function parameter with a `struct` type

`struct name_of_the_struct arg_name`

```
void f(struct strange var) {  
    printf("%c %d %f\n", var.c, var.i, var.f);  
}  
  
int main(int argc, char* argv[]) {  
    struct strange var = { .c: 'a', .i: 3, .f: 3.14 };  
    f(var);  
    return 0;  
}
```

Structure and functions

- To declare a function parameter with a `struct` type

`struct name_of_the_struct arg_name`

```
void f(struct strange var) {  
    printf("%c %d %f\n", var.c, var.i, var.f);  
}  
  
int main(int argc, char* argv[]) {  
    struct strange var = { .c: 'a', .i: 3, .f: 3.14 };  
    f(var);  
    return 0;  
}
```

Note: if `f` modifies `var`, this **does not** modifies the `var` of `main` (we say that an array is passed by copy - explained in a next lesson)

Key concepts

■ Array: homogenous

- To declare an array: `type var[n];`
- To access an array: `var[n]`

■ Structure: heterogeneous

- To define a type: `struct name_of_the_struct { ... };`
- To declare a structure: `struct name_of_the_struct var;`
- To access a field: `var.field_name`