Enetres

ghost-local Data Dictionary

1/26/2021





Table of contents

ghost-local	6
1. Tables	6
1.1. Table: actions	6
1.2. Table: api_keys	6
1.3. Table: app_fields	6
1.4. Table: app_settings	7
1.5. Table: apps	7
1.6. Table: brute	8
1.7. Table: email_batches	8
1.8. Table: email_recipients	8
1.9. Table: emails	9
1.10. Table: integrations	9
1.11. Table: invites	10
1.12. Table: labels	10
1.13. Table: members	
1.14. Table: members_labels	
1.15. Table: members_stripe_customers	11
1.16. Table: members_stripe_customers_subscriptions	12
1.17. Table: migrations	12
1.18. Table: migrations_lock	13
1.19. Table: mobiledoc_revisions	13
1.20. Table: permissions	13
1.21. Table: permissions_apps	14
1.22. Table: permissions_roles	14
1.23. Table: permissions_users	14
1.24. Table: posts	14
1.25. Table: posts_authors	15
1.26. Table: posts_meta	15
1.27. Table: posts_tags	16
1.28. Table: roles	16
1.29. Table: roles_users	16
1.30. Table: sessions	17
1.31. Table: settings	17
1.32. Table: snippets	17
1.33. Table: sqlite_sequence	18
1.34. Table: tags	18
1.35. Table: tokens	19
1.36. Table: users	19
1.37. Table: webhooks	20

Legend

- **?** Primary key
- Primary key disabled
- 1 User-defined primary key
- **?** Unique key
- ¶ Unique key disabled
- 1 User-defined unique key
- Active trigger
- Disabled trigger
- → Many to one relation
- $\succ_{\mathbf{i}}$ User-defined many to one relation
- ✓ User-defined one to many relation
- \succ User-defined many to many relation
- One to one relation
- user-defined one to one relation
- •**@** Input
- @ Output
- Input/Output
- Uses dependency
- User-defined uses dependency
- Used by dependency
- 🛅 User-defined used by dependency

ghost-local

1. Tables

1.1. Table: actions

Columns

	Name	Data type	Description / Attributes
目	id	varchar(24)(24)	Default: NULL
■	resource_id	varchar(24)(24)	Nullable Default: NULL
■	resource_type	varchar(50)(50)	Default: NULL
目	actor_id	varchar(24)(24)	Default: NULL
目	actor_type	varchar(50)(50)	Default: NULL
■	event	varchar(50)(50)	Default: NULL
■	context	text(0)	Nullable Default: NULL
	created_at	datetime(3)	Default: NULL

1.2. Table: api_keys

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	type	varchar(50)(50)	Default: NULL
▤	secret	varchar(191)(191)	Default: NULL
	role_id	varchar(24)(24)	Nullable Default: NULL
	integration_id	varchar(24)(24)	Nullable Default: NULL
	user_id	varchar(24)(24)	Nullable Default: NULL
	last_seen_at	datetime(3)	Nullable Default: NULL
	last_seen_version	varchar(50)(50)	Nullable Default: NULL
目	created_at	datetime(3)	Default: NULL
▤	created_by	varchar(24)(24)	Default: NULL
	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.3. Table: app_fields

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	key	varchar(50)(50)	Default: NULL
■	value	text(0)	Nullable Default: NULL
■	type	varchar(50)(50)	Default: html
■	app_id	varchar(24)(24)	Default: NULL
	relatable_id	varchar(24)(24)	Default: NULL
■	relatable_type	varchar(50)(50)	Default : posts
■	active	boolean(1)	Default: 1
■	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.4. Table: app_settings

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	key	varchar(50)(50)	Default: NULL
■	value	text(0)	Nullable Default: NULL
■	app_id	varchar(24)(24)	Default: NULL
■	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.5. Table: apps

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	name	varchar(191)(191)	Default: NULL
■	slug	varchar(191)(191)	Default: NULL
■	version	varchar(50)(50)	Default: NULL
	status	varchar(50)(50)	Default : inactive

	Name	Data type	Description / Attributes
E	created_at	datetime(3)	Default: NULL
E	created_by	varchar(24)(24)	Default: NULL
E	updated_at	datetime(3)	Nullable Default: NULL
E	updated_by	varchar(24)(24)	Nullable Default: NULL

1.6. Table: brute

Columns

	Name	Data type	Description / Attributes
■	key	varchar(191)(191)	Default: NULL
■	firstRequest	bigint(19)	Default: NULL
■	lastRequest	bigint(19)	Default: NULL
■	lifetime	bigint(19)	Default: NULL
■	count	integer(9)	Default: NULL

1.7. Table: email_batches

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	email_id	varchar(24)(24)	Default: NULL
	provider_id	varchar(255)(255)	Nullable Default: NULL
■	status	varchar(50)(50)	Default: pending
■	created_at	datetime(3)	Default: NULL
■	updated_at	datetime(3)	Default: NULL

1.8. Table: email_recipients

CO11	Columns				
		Name	Data type	Description / Attributes	
■		id	varchar(24)(24)	Default: NULL	
■		email_id	varchar(24)(24)	Default: NULL	
		member_id	varchar(24)(24)	Default: NULL	
		batch_id	varchar(24)(24)	Default: NULL	
		processed_at	datetime(3)	Nullable Default: NULL	
		delivered_at	datetime(3)	Nullable Default: NULL	
■		opened_at	datetime(3)	Nullable Default: NULL	

	Name	Data type	Description / Attributes
	failed_at	datetime(3)	Nullable Default: NULL
■	member_uuid	varchar(36)(36)	Default: NULL
■	member_email	varchar(191)(191)	Default: NULL
■	member_name	varchar(191)(191)	Nullable Default: NULL

1.9. Table: emails

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	post_id	varchar(24)(24)	Default: NULL
■	uuid	varchar(36)(36)	Default: NULL
■	status	varchar(50)(50)	Default: pending
■	recipient_filter	varchar(50)(50)	Default: paid
■	error	varchar(2000)(2000)	Nullable Default: NULL
	error_data	text(0)	Nullable Default: NULL
■	email_count	integer(9)	Default: 0
■	delivered_count	integer(9)	Default: 0
目	opened_count	integer(9)	Default: 0
目	failed_count	integer(9)	Default: 0
■	subject	varchar(300)(300)	Nullable Default: NULL
■	from	varchar(2000)(2000)	Nullable Default: NULL
	reply_to	varchar(2000)(2000)	Nullable Default: NULL
	html	text(0)	Nullable Default: NULL
■	plaintext	text(0)	Nullable Default: NULL
■	track_opens	boolean(1)	Default: 0
▤	submitted_at	datetime(3)	Default: NULL
▤	created_at	datetime(3)	Default: NULL
	created_by	varchar(24)(24)	Default: NULL
	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.10. Table: integrations

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
	type	varchar(50)(50)	Default: custom
■	name	varchar(191)(191)	Default: NULL
■	slug	varchar(191)(191)	Default: NULL
■	icon_image	varchar(2000)(2000)	Nullable Default: NULL
■	description	varchar(2000)(2000)	Nullable Default: NULL
	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.11. Table: invites

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	role_id	varchar(24)(24)	Default: NULL
■	status	varchar(50)(50)	Default: pending
■	token	varchar(191)(191)	Default: NULL
▤	email	varchar(191)(191)	Default: NULL
■	expires	bigint(19)	Default: NULL
■	created_at	datetime(3)	Default: NULL
▤	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.12. Table: labels

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
	name	varchar(191)(191)	Default: NULL
■	slug	varchar(191)(191)	Default: NULL
	created_at	datetime(3)	Default: NULL
	created_by	varchar(24)(24)	Default: NULL

	Name	Data type	Description / Attributes
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.13. Table: members

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
B	uuid	varchar(36)(36)	Nullable Default: NULL
■	email	varchar(191)(191)	Default: NULL
B	name	varchar(191)(191)	Nullable Default: NULL
B	note	varchar(2000)(2000)	Nullable Default: NULL
B	geolocation	varchar(2000)(2000)	Nullable Default: NULL
B	subscribed	boolean(1)	Nullable Default: 1
■	email_count	integer(9)	Default: 0
■	email_opened_count	integer(9)	Default: 0
B	email_open_rate	integer(9)	Nullable Default: NULL
▤	created_at	datetime(3)	Default: NULL
▤	created_by	varchar(24)(24)	Default: NULL
B	updated_at	datetime(3)	Nullable Default: NULL
B	updated_by	varchar(24)(24)	Nullable Default: NULL

1.14. Table: members_labels

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	member_id	varchar(24)(24)	Default: NULL
■	label_id	varchar(24)(24)	Default: NULL
	sort_order	integer(9)	Default: 0

1.15. Table: members_stripe_customers

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL

	Name	Data type	Description / Attributes
■	member_id	varchar(24)(24)	Default: NULL
目	customer_id	varchar(255)(255)	Default: NULL
■	name	varchar(191)(191)	Nullable Default: NULL
■	email	varchar(191)(191)	Nullable Default: NULL
■	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.16. Table: members_stripe_customers_subscriptions

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	customer_id	varchar(255)(255)	Default: NULL
■	subscription_id	varchar(255)(255)	Default: NULL
■	plan_id	varchar(255)(255)	Default: NULL
■	status	varchar(50)(50)	Default: NULL
■	cancel_at_period_end	boolean(1)	Default: 0
	cancellation_reason	varchar(500)(500)	Nullable Default: NULL
■	current_period_end	datetime(3)	Default: NULL
	start_date	datetime(3)	Default: NULL
	default_payment_card_last4	varchar(4)(4)	Nullable Default: NULL
■	created_at	datetime(3)	Default: NULL
	created_by	varchar(24)(24)	Default: NULL
	updated_at	datetime(3)	Nullable Default: NULL
	updated_by	varchar(24)(24)	Nullable Default: NULL
■	plan_nickname	varchar(50)(50)	Default: NULL
■	plan_interval	varchar(50)(50)	Default: NULL
■	plan_amount	integer(9)	Default: NULL
■	plan_currency	varchar(191)(191)	Default: NULL

1.17. Table: migrations

	Name	Data type	Description / Attributes
	id	integer(9)	Default: NULL
■	name	varchar(255)(255)	Nullable Default: NULL
	version	varchar(255)(255)	Nullable Default: NULL
B	currentVersion	varchar(255)(255)	Nullable Default: NULL

1.18. Table: migrations_lock

Columns

	Name	Data type	Description / Attributes
目	lock_key	varchar(191)(191)	Default: NULL
■	locked	boolean(1)	Nullable Default: 0
■	acquired_at	datetime(3)	Nullable Default: NULL
■	released_at	datetime(3)	Nullable Default: NULL

1.19. Table: mobiledoc_revisions

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	post_id	varchar(24)(24)	Default: NULL
■	mobiledoc	text(0)	Nullable Default: NULL
■	created_at_ts	bigint(19)	Default: NULL
■	created_at	datetime(3)	Default: NULL

1.20. Table: permissions

		Name	Data type	Description / Attributes	
■		id	varchar(24)(24)	Default: NULL	
■		name	varchar(50)(50)	Default: NULL	
■		object_type	varchar(50)(50)	Default: NULL	
■		action_type	varchar(50)(50)	Default: NULL	
		object_id	varchar(24)(24)	Nullable Default: NULL	
B		created_at	datetime(3)	Default: NULL	
■		created_by	varchar(24)(24)	Default: NULL	

	Name	Data type	Description / Attributes
	updated_at	datetime(3)	Nullable Default: NULL
	updated_by	varchar(24)(24)	Nullable Default: NULL

1.21. Table: permissions_apps

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	app_id	varchar(24)(24)	Default: NULL
	permission_id	varchar(24)(24)	Default: NULL

1.22. Table: permissions_roles

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	role_id	varchar(24)(24)	Default: NULL
■	permission_id	varchar(24)(24)	Default: NULL

1.23. Table: permissions_users

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	user_id	varchar(24)(24)	Default: NULL
■	permission_id	varchar(24)(24)	Default: NULL

1.24. Table: posts

	2014111119			
		Name	Data type	Description / Attributes
目		id	varchar(24)(24)	Default: NULL
目		uuid	varchar(36)(36)	Default: NULL
目		title	varchar(2000)(2000)	Default: NULL
■		slug	varchar(191)(191)	Default: NULL
		mobiledoc	text(0)	Nullable Default: NULL
■		html	text(0)	Nullable Default: NULL
■		comment_id	varchar(50)(50)	Nullable Default: NULL
■		plaintext	text(0)	Nullable Default: NULL

	Name	Data type	Description / Attributes
B	feature_image	varchar(2000)(2000)	Nullable Default: NULL
■	featured	boolean(1)	Default: 0
■	type	varchar(50)(50)	Default: post
▤	status	varchar(50)(50)	Default: draft
	locale	varchar(6)(6)	Nullable Default: NULL
	visibility	varchar(50)(50)	Default: public
■	email_recipient_filter	varchar(50)(50)	Default: none
	author_id	varchar(24)(24)	Default: NULL
	created_at	datetime(3)	Default: NULL
	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL
■	published_at	datetime(3)	Nullable Default: NULL
■	published_by	varchar(24)(24)	Nullable Default: NULL
■	custom_excerpt	varchar(2000)(2000)	Nullable Default: NULL
■	codeinjection_head	text(0)	Nullable Default: NULL
■	codeinjection_foot	text(0)	Nullable Default: NULL
■	custom_template	varchar(100)(100)	Nullable Default: NULL
	canonical_url	text(0)	Nullable Default: NULL

1.25. Table: posts_authors

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	post_id	varchar(24)(24)	Default: NULL
■	author_id	varchar(24)(24)	Default: NULL
	sort_order	integer(9)	Default: 0

1.26. Table: posts_meta

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL

	Name	Data type	Description / Attributes
■	post_id	varchar(24)(24)	Default: NULL
■	og_image	varchar(2000)(2000)	Nullable Default: NULL
■	og_title	varchar(300)(300)	Nullable Default: NULL
■	og_description	varchar(500)(500)	Nullable Default: NULL
■	twitter_image	varchar(2000)(2000)	Nullable Default: NULL
	twitter_title	varchar(300)(300)	Nullable Default: NULL
■	twitter_description	varchar(500)(500)	Nullable Default: NULL
■	meta_title	varchar(2000)(2000)	Nullable Default: NULL
■	meta_description	varchar(2000)(2000)	Nullable Default: NULL
■	email_subject	varchar(300)(300)	Nullable Default: NULL

1.27. Table: posts_tags

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	post_id	varchar(24)(24)	Default: NULL
■	tag_id	varchar(24)(24)	Default: NULL
■	sort_order	integer(9)	Default: 0

1.28. Table: roles

Columns

		Name	Data type	Description / Attributes	
		id	varchar(24)(24)	Default: NULL	
■		name	varchar(50)(50)	Default: NULL	
B		description	varchar(2000)(2000)	Nullable Default: NULL	
■		created_at	datetime(3)	Default: NULL	
■		created_by	varchar(24)(24)	Default: NULL	
B		updated_at	datetime(3)	Nullable Default: NULL	
■		updated_by	varchar(24)(24)	Nullable Default: NULL	

1.29. Table: roles_users

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	role_id	varchar(24)(24)	Default: NULL
■	user_id	varchar(24)(24)	Default: NULL

1.30. Table: sessions

Columns

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	session_id	varchar(32)(32)	Default: NULL
■	user_id	varchar(24)(24)	Default: NULL
■	session_data	varchar(2000)(2000)	Default: NULL
■	created_at	datetime(3)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL

1.31. Table: settings

Columns

	Name	Data type	Description / Attributes
目	id	varchar(24)(24)	Default: NULL
■	group	varchar(50)(50)	Default: core
▤	key	varchar(50)(50)	Default: NULL
■	value	text(0)	Nullable Default: NULL
■	type	varchar(50)(50)	Default: NULL
	flags	varchar(50)(50)	Nullable Default: NULL
■	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
	updated_at	datetime(3)	Nullable Default: NULL
	updated_by	varchar(24)(24)	Nullable Default: NULL

1.32. Table: snippets

	Name	Data type	Description / Attributes
■	id	varchar(24)(24)	Default: NULL
■	name	varchar(191)(191)	Default: NULL
	mobiledoc	text(0)	Default: NULL

	Name	Data type	Description / Attributes
■	created_at	datetime(3)	Default: NULL
▤	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
■	updated_by	varchar(24)(24)	Nullable Default: NULL

1.33. Table: sqlite_sequence

Columns

	Name	Data type	Description / Attributes
	name		Nullable Default: NULL
	seq		Nullable Default: NULL

1.34. Table: tags

	Name	Data type	Description / Attributes
	id	varchar(24)(24)	Default: NULL
■	name	varchar(191)(191)	Default: NULL
■	slug	varchar(191)(191)	Default: NULL
■	description	text(0)	Nullable Default: NULL
■	feature_image	varchar(2000)(2000)	Nullable Default: NULL
	parent_id	varchar(191)(191)	Nullable Default: NULL
■	visibility	varchar(50)(50)	Default: public
■	og_image	varchar(2000)(2000)	Nullable Default: NULL
■	og_title	varchar(300)(300)	Nullable Default: NULL
■	og_description	varchar(500)(500)	Nullable Default: NULL
■	twitter_image	varchar(2000)(2000)	Nullable Default: NULL
	twitter_title	varchar(300)(300)	Nullable Default: NULL
	twitter_description	varchar(500)(500)	Nullable Default: NULL
■	meta_title	varchar(2000)(2000)	Nullable Default: NULL
	meta_description	varchar(2000)(2000)	Nullable Default: NULL

	Name	Data type	Description / Attributes
■	codeinjection_head	text(0)	Nullable Default: NULL
■	codeinjection_foot	text(0)	Nullable Default: NULL
	canonical_url	varchar(2000)(2000)	Nullable Default: NULL
■	accent_color	varchar(50)(50)	Nullable Default: NULL
■	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
	updated_at	datetime(3)	Nullable Default: NULL
	updated_by	varchar(24)(24)	Nullable Default: NULL

1.35. Table: tokens

Columns

	Name	Data type	Description / Attributes
▤	id	varchar(24)(24)	Default: NULL
■	token	varchar(32)(32)	Default: NULL
	data	varchar(2000)(2000)	Nullable Default: NULL
■	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL

1.36. Table: users

COLUMB				
		Name	Data type	Description / Attributes
■		id	varchar(24)(24)	Default: NULL
目		name	varchar(191)(191)	Default: NULL
目		slug	varchar(191)(191)	Default: NULL
▤		password	varchar(60)(60)	Default: NULL
▤		email	varchar(191)(191)	Default: NULL
		profile_image	varchar(2000)(2000)	Nullable Default: NULL
■		cover_image	varchar(2000)(2000)	Nullable Default: NULL
■		bio	text(0)	Nullable Default: NULL
		website	varchar(2000)(2000)	Nullable Default: NULL
		location	text(0)	Nullable Default: NULL

	Name	Data type	Description / Attributes
■	facebook	varchar(2000)(2000)	Nullable Default: NULL
	twitter	varchar(2000)(2000)	Nullable Default: NULL
	accessibility	text(0)	Nullable Default: NULL
▤	status	varchar(50)(50)	Default: active
	locale	varchar(6)(6)	Nullable Default: NULL
■	visibility	varchar(50)(50)	Default: public
	meta_title	varchar(2000)(2000)	Nullable Default: NULL
	meta_description	varchar(2000)(2000)	Nullable Default: NULL
	tour	text(0)	Nullable Default: NULL
	last_seen	datetime(3)	Nullable Default: NULL
■	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
	updated_at	datetime(3)	Nullable Default: NULL
	updated_by	varchar(24)(24)	Nullable Default: NULL

1.37. Table: webhooks

	Sold in its				
		Name	Data type	Description / Attributes	
■		id	varchar(24)(24)	Default: NULL	
目		event	varchar(50)(50)	Default: NULL	
▤		target_url	varchar(2000)(2000)	Default: NULL	
■		name	varchar(191)(191)	Nullable Default: NULL	
■		secret	varchar(191)(191)	Nullable Default: NULL	
目		api_version	varchar(50)(50)	Default: v2	
■		integration_id	varchar(24)(24)	Nullable Default: NULL	
目		status	varchar(50)(50)	Default: available	
		last_triggered_at	datetime(3)	Nullable Default: NULL	
■		last_triggered_status	varchar(50)(50)	Nullable Default: NULL	
■		last_triggered_error	varchar(50)(50)	Nullable Default: NULL	

	Name	Data type	Description / Attributes
	created_at	datetime(3)	Default: NULL
■	created_by	varchar(24)(24)	Default: NULL
■	updated_at	datetime(3)	Nullable Default: NULL
B	updated_by	varchar(24)(24)	Nullable Default: NULL

