

What is Java?

Java is a programming language and a platform. Java is a high level, robust, object-oriented and secure programming language.

Java was developed by Sun Microsystems (which is now the subsidiary of Oracle) in the year 1995. James Gosling is known as the father of Java. Before Java, its name was Oak. Since Oak was already a registered company, so James Gosling and his team changed the name from Oak to Java.

Platform: Any hardware or software environment in which a program runs, is known as a platform. Since Java has a runtime environment (JRE) and API, it is called a platform.

Application

According to Sun, 3 billion devices run Java. There are many devices where Java is currently used. Some of them are as follows:

- Desktop Applications such as acrobat reader, media player, antivirus, etc.
- Web Applications such as irctc.co.in, javatpoint.com, etc.
- Enterprise Applications such as banking applications.
- Mobile
- Embedded System
- Smart Card
- Robotics
- Games, etc.

Types of Java Applications

There are mainly 4 types of applications that can be created using Java programming:

1) Standalone Application

Standalone applications are also known as desktop applications or window-based applications. These are traditional software that we need to install on every machine. Examples of standalone application are Media player, antivirus, etc. AWT and Swing are used in Java for creating standalone applications.

2) Web Application

An application that runs on the server side and creates a dynamic page is called a web application. Currently, Servlet, JSP, Struts, Spring, Hibernate, JSF, etc. technologies are used for creating web applications in Java.

3) Enterprise Application

An application that is distributed in nature, such as banking applications, etc. is called an enterprise application. It has advantages like high-level security, load balancing, and clustering. In Java, EJB is used for creating enterprise applications.

4) Mobile Application

An application which is created for mobile devices is called a mobile application. Currently, Android and Java ME are used for creating mobile applications.

Java Platforms / Editions

There are 4 platforms or editions of Java:

1) Java SE (Java Standard Edition)

It is a Java programming platform. It includes Java programming APIs such as java.lang, java.io, java.net, java.util, java.sql, java.math etc. It includes core topics like OOPs, String, Regex, Exception, Inner classes, Multithreading, I/O Stream, Networking, AWT, Swing, Reflection, Collection, etc.

2) Java EE (Java Enterprise Edition)

It is an enterprise platform that is mainly used to develop web and enterprise applications. It is built on top of the Java SE platform. It includes topics like Servlet, JSP, Web Services, EJB, JPA, etc.

3) Java ME (Java Micro Edition)

It is a micro platform that is dedicated to mobile applications.


4) JavaFX

It is used to develop rich internet applications. It uses a lightweight user interface API.

Features of Java

The primary objective of Java programming language creation was to make it portable, simple and secure programming language. Apart from this, there are also some excellent features which play an important role in the popularity of this language. The features of Java are also known as Java buzzwords.

A list of the most important features of the Java language is given below.



1. Simple
2. Object-Oriented
3. Portable
4. Platform independent
5. Secured
6. Robust
7. Architecture neutral
8. Interpreted
9. High Performance
- 10.Multithreaded
- 11.Distributed
- 12.Dynamic

Simple

Java is very easy to learn, and its syntax is simple, clean and easy to understand. According to Sun Microsystem, Java language is a simple programming language because:

- Java syntax is based on C++ (so easier for programmers to learn it after C++).
- Java has removed many complicated and rarely-used features, for example, explicit pointers, operator overloading, etc.
- There is no need to remove unreferenced objects because there is an Automatic Garbage Collection in Java.

Object-oriented

Java is an object-oriented programming language. Everything in Java is an object. Object-oriented means we organize our software as a combination of different types of objects that incorporate both data and behaviour.

Object-oriented programming (OOPs) is a methodology that simplifies software development and maintenance by providing some rules.


Basic concepts of OOPs are:

1. Object
2. Class
3. Inheritance
4. Polymorphism
5. Abstraction
6. Encapsulation

Platform Independent

Java is platform independent because it is different from other languages like C, C++, etc. which are compiled into platform specific machines while Java is a write once, run anywhere language. A platform is the hardware or software environment in which a program runs.

There are two types of platforms software-based and hardware-based. Java provides a software-based platform.



The Java platform differs from most other platforms in the sense that it is a software-based platform that runs on top of other hardware-based platforms. It has two components:

1. Runtime Environment
2. API (Application Programming Interface)


Java code can be executed on multiple platforms, for example, Windows, Linux, Sun Solaris, Mac/OS, etc. Java code is compiled by the compiler and converted into bytecode. This bytecode is a platform-independent code because it can be run on multiple platforms, i.e., Write Once and Run Anywhere (WORA).

Secured

Java is best known for its security. With Java, we can develop virus-free systems.

Java is secured because:

- No explicit pointer
- Java Programs run inside a virtual machine sandbox



- **ClassLoader:** Classloader in Java is a part of the Java Runtime Environment (JRE) which is used to load Java classes into the Java Virtual Machine dynamically. It adds security by separating the package for the classes of the local file system from those that are imported from network sources.
- **Bytecode Verifier:** It checks the code fragments for illegal code that can violate access rights to objects.
- **Security Manager:** It determines what resources a class can access such as reading and writing to the local disk.

Java language provides these securities by default. Some security can also be provided by an application developer explicitly through SSL, JAAS, Cryptography, etc.

Robust

The English meaning of Robust is strong. Java is robust because:

- It uses strong memory management.
 - There is a lack of pointers that avoids security problems.
 - Java provides automatic garbage collection which runs on the Java Virtual Machine to get rid of objects which are not being used by a Java application anymore.
 - There are exception handling and the type checking mechanism in Java.
- All these points make Java robust.

Architecture-neutral

Java is architecture neutral because there are no implementation dependent features, for example, the size of primitive types is fixed.

In C programming, int data type occupies 2 bytes of memory for 32-bit architecture and 4 bytes of memory for 64-bit architecture. However, it occupies 4 bytes of memory for both 32 and 64-bit architectures in Java.

Portable

Java is portable because it facilitates you to carry the Java bytecode to any platform. It doesn't require any implementation.

High-performance

Java is faster than other traditional interpreted programming languages because Java bytecode is "close" to native code. It is still a little bit slower than a compiled language (e.g., C++). Java is an interpreted language that is why it is slower than compiled languages, e.g., C, C++, etc.

Distributed

Java is distributed because it facilitates users to create distributed applications in Java. RMI and EJB are used for creating distributed applications. This feature of Java makes us able to access files by calling the methods from any machine on the internet.

Multi-threaded

A thread is like a separate program, executing concurrently. We can write Java programs that deal with many tasks at once by defining multiple threads. The main advantage of multi-threading is that it doesn't occupy memory for each thread. It shares a common memory area. Threads are important for multi-media, Web applications, etc.

Dynamic

Java is a dynamic language. It supports the dynamic loading of classes. It means classes are loaded on demand. It also supports functions from its native languages, i.e., C and C++.

Creating Hello World Example

Let's create the hello java program:

```
class Simple{  
  
    public static void main(String args[]){  
  
        System.out.println("Hello Java");  
  
    }  
  
}
```

Parameters used in First Java Program

Let's see what is the meaning of class, public, static, void, main, String[], System.out.println().

- class keyword is used to declare a class in Java.
- public keyword is an access modifier that represents visibility. It means it is visible to all.
- static is a keyword. If we declare any method as static, it is known as the static method. The core advantage of the static method is that there is no need to create an object to invoke the static method. The main() method is executed by the JVM, so it doesn't require creating an object to invoke the main() method. So, it saves memory.
- void is the return type of the method. It means it doesn't return any value.
- main represents the starting point of the program.
- String[] args or String args[] is used for command line argument. We will discuss it in coming section.

- `System.out.println()` is used to print statement. Here, `System` is a class, `out` is an object of the `PrintStream` class, `println()` is a method of the `PrintStream` class.

Difference between JDK, JRE, and JVM

JVM

JVM (Java Virtual Machine) is an abstract machine. It is called a virtual machine because it doesn't physically exist. It is a specification that provides a runtime environment in which Java bytecode can be executed. It can also run those programs which are written in other languages and compiled to Java bytecode.

JVMs are available for many hardware and software platforms. JVM, JRE, and JDK are platform dependent because the configuration of each OS is different from each other. However, Java is platform independent. There are three notions of the JVM: specification, implementation, and instance.


The JVM performs the following main tasks:

- Loads code
- Verifies code
- Executes code
- Provides runtime environment

JRE

JRE is an acronym for Java Runtime Environment. It is also written as Java RTE (Runtime Environment). The Java Runtime Environment is a set of software tools which are used for developing Java applications. It is used to provide the runtime environment. It is the implementation of JVM. It physically exists. It contains a set of libraries + other files that JVM uses at runtime.

The implementation of JVM is also actively released by other companies besides Sun Micro Systems.




JDK

JDK is an acronym for Java Development Kit. The Java Development Kit (JDK) is a software development environment which is used to develop Java applications and applets. It physically exists. It contains JRE + development tools.

JDK is an implementation of any one of the below given Java Platforms released by Oracle Corporation:

- Standard Edition Java Platform
- Enterprise Edition Java Platform
- Micro Edition Java Platform

The JDK contains a private Java Virtual Machine (JVM) and a few other resources such as an interpreter/loader (java), a compiler (javac), an archiver (jar), a documentation generator (Javadoc), etc. to complete the development of a Java Application.



Java Variables


A variable is a container which holds the value while the Java program is executed. A variable is assigned with a data type.

Variable is a name of memory location. There are three types of variables in java: local, instance and static.

There are two types of data types in Java: primitive and non-primitive.

Variable

A variable is the name of a reserved area allocated in memory. In other words, it is a name of the memory location. It is a combination of "vary + able" which means its value can be changed.




```
int data=50;//Here data is variable
```


Types of Variables

There are three types of variables in Java:

- local variable
- instance variable
- static variable

Types of Variables



1) Local Variable

A variable declared inside the body of the method is called local variable. You can use this variable only within that method and the other methods in the class aren't even aware that the variable exists.

A local variable cannot be defined with "static" keyword.

2) Instance Variable

A variable declared inside the class but outside the body of the method, is called an instance variable. It is not declared as static.

It is called an instance variable because its value is instance-specific and is not shared among instances.

3) Static variable

A variable that is declared as static is called a static variable. It cannot be local. You can create a single copy of the static variable and share it among all the instances of the class. Memory allocation for static variables happens only once when the class is loaded in the memory.

Example to understand the types of variables in java

```
public class A
{
    static int m=100;//static variable
    void method()
    {
        int n=90;//local variable
    }
    public static void main(String args[])
    {
        int data=50;//instance variable
    }
}
//end of class
```

Java Variable Example: Add Two Numbers

```
public class Simple{
    public static void main(String[] args){
        int a=10;
        int b=10;
        int c=a+b;
        System.out.println(c);
    }
}
```

Data Types in Java

Data types specify the different sizes and values that can be stored in the variable.

There are two types of data types in Java:

Primitive data types: The primitive data types include boolean, char, byte, short, int, long, float and double.

Non-primitive data types: The non-primitive data types include Classes, Interfaces, and Arrays.


Java Primitive Data Types

In Java language, primitive data types are the building blocks of data manipulation. These are the most basic data types available in Java language.

Java is a statically-typed programming language. It means, all variables must be declared before its use. That is why we need to declare variable's type and name.

There are 8 types of primitive data types:

- boolean data type
- byte data type
- char data type
- short data type
- int data type
- long data type
- float data type
- double data type



| Data Type | Default Value | Default size |
|-----------|---------------|--------------|
| boolean | false | 1 bit |
| char | '\u0000' | 2 byte |
| byte | 0 | 1 byte |
| short | 0 | 2 byte |
| int | 0 | 4 byte |
| long | 0L | 8 byte |
| float | 0.0f | 4 byte |
| double | 0.0d | 8 byte |

Boolean Data Type

The Boolean data type is used to store only two possible values: true and false. This data type is used for simple flags that track true/false conditions.

The Boolean data type specifies one bit of information, but its "size" can't be defined precisely.

Example:

```
Boolean one = false
```

Byte Data Type

The byte data type is an example of primitive data type. It is an 8-bit signed two's complement integer. Its value-range lies between -128 to 127 (inclusive). Its minimum value is -128 and maximum value is 127. Its default value is 0.

The byte data type is used to save memory in large arrays where the memory savings is most required. It saves space because a byte is 4 times smaller than an integer. It can also be used in place of "int" data type.

Example:

```
byte a = 10, byte b = -20
```

Short Data Type

The short data type is a 16-bit signed two's complement integer. Its value-range lies between -32,768 to 32,767 (inclusive). Its minimum value is -32,768 and maximum value is 32,767. Its default value is 0.

The short data type can also be used to save memory just like byte data type. A short data type is 2 times smaller than an integer.

Example:

```
short s = 10000, short r = -5000
```

Int Data Type

The int data type is a 32-bit signed two's complement integer. Its value-range lies between - 2,147,483,648 (-2^{31}) to 2,147,483,647 ($2^{31} - 1$) (inclusive). Its minimum value is - 2,147,483,648 and maximum value is 2,147,483,647. Its default value is 0.

The int data type is generally used as a default data type for integral values unless if there is no problem about memory.

Example:

```
int a = 100000, int b = -200000
```

Long Data Type

The long data type is a 64-bit two's complement integer. Its value-range lies between -9,223,372,036,854,775,808 (-2^{63}) to 9,223,372,036,854,775,807 ($2^{63} - 1$) (inclusive). Its minimum value is - 9,223,372,036,854,775,808 and maximum value is 9,223,372,036,854,775,807. Its default value is 0. The long data type is used when you need a range of values more than those provided by int.

Example:

```
long a = 100000L, long b = -200000L
```

Float Data Type

The float data type is a single-precision 32-bit IEEE 754 floating point. Its value range is unlimited. It is recommended to use a float (instead of double) if you need to save memory in large arrays of floating point numbers. The float data type should never be used for precise values, such as currency. Its default value is 0.0F.

Example:

```
float f1 = 234.5f
```

Double Data Type

The double data type is a double-precision 64-bit IEEE 754 floating point. Its value range is unlimited. The double data type is generally used for decimal values just like float. The double data type also should never be used for precise values, such as currency. Its default value is 0.0d.

Example:

```
double d1 = 12.3
```

Char Data Type

The char data type is a single 16-bit Unicode character. Its value-range lies between '\u0000' (or 0) to '\uffff' (or 65,535 inclusive). The char data type is used to store characters.

Example:

```
char letterA = 'A'
```