

Product specifications

Eaton DH364NRK

Catalog Number: DH364NRK

Eaton Enhanced visible blade single-throw safety switch, 200 A, ddfdfdf NEMA 3R, Painted galvanized steel, Class H, Fusible with neutral,fdfdf Three-pole, Four-wire, 600 V, Max Hp: 50, 50/ 125, 150 hp (1/3PHdfdfdf @480, 600 V), #6-250 kcmil Cu/Alfdfdfdf



Catalog Number
DH364NRK

Product Length/Depth 30 in

Product Width
18 in

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the

date of shipment of the Product, whichever occurs first.

Certifications
UL Listedddfdfdf

Physical Attributes

- Enclosure
 - NEMA 3R
- Enclosure material
 - Painted galvanized steel
- Fuse class provision
 - Class H
- Fuse configuration
 - Fusible with neutral
- Number Of Poles
 - Three-pole
- Number of wires
 - 4
- Type
 - Heavy duty fusible safety switch

Performance Ratings

- Amperage Rating
 - 200A
- HP rating - max
 - 50, 50/ 125, 150 hp (1/3PH @480, 600 V)
- NEMA rating
 - NEMA 3R
- Voltage rating
 - 600 V

Miscellaneous

- Product Category
 - Heavy Duty,
Fusible with neutral

Resources

- Catalogs
- Specifications and datasheets

Eaton DH364NRK

Catalog Number: DH364NRK

Eaton Enhanced visible blade single-throw safety switch, 200 A, NEMA 3R, Painted galvanized steel, Class H, Fusible with neutral, Three-pole, Four-wire, 600 V, Max Hp: 50, 50/ 125, 150 hp (1/3PH @480, 600 V), #6-250 kcmil Cu/Al



Height

Catalog Number

DH364NRK

Product Length/Depth 30 in

Product Width

18 in

Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the

Product

Product or eighteen (18) months from the

date of shipment of the Product, whichever occurs first.

Certifications

UL Listed

Physical Attributes

- Enclosure
 - NEMA 3R
- Enclosure material
 - Painted galvanized steel
- Fuse class provision
 - Class H
- Fuse configuration
 - Fusible with neutral
- Number Of Poles
 - Three-pole
- Number of wires
 - 4
- Type
 - Heavy duty fusible safety switch

Performance Ratings

- Amperage Rating
 - 200A
- HP rating - max
 - 50, 50/ 125, 150 hp (1/3PH @480, 600 V)
- NEMA rating
 - NEMA 3R
- Voltage rating
 - 600 V

Miscellaneous

- Product Category
 - Heavy Duty,
Fusible with neutral

Resources

- Catalogs
- Specifications and datasheets