

```

#include<stdlib.h>
#include<stdio.h>

typedef struct dll {
    int data;
    struct dll * left ;
    struct dll * right;
}dll;

dll * head = NULL;
int count = 0;

dll * createnode() {
    dll * newnode = (dll *)malloc(sizeof(dll));
    printf("Enter the data element : ");
    scanf("%d" , &newnode->data);
    newnode->left = NULL;
    newnode->right = NULL;
    count++;
    return newnode;
}

void insert() {
    if (head == NULL) {
        printf("Creating the very first node.\n");
        head = createnode();
    }
    else {
        printf("Enter the posistion at which you want to insert
(between 0 and %d) : " , count);
        int pos;
        scanf("%d", &pos);
        if(pos <= count && pos>-1) {
            dll * temp = createnode();
            if(pos == 0) {
                temp->right = head;
                head->left = temp;
                head = temp;
            }
            else {
                dll * trav = head;
                for(int i = 0 ; i < pos-1 ; i++ )
                    trav = trav->right;

                temp->left = trav;
                temp->right = trav->right;
                trav->right = temp;
            }
        }
        else
            printf("Invalid Input.\n");
    }
}

void delete() {
    if(head == NULL)
        printf("Doubly Linked List is empty.\n");
}

```

```

    else {
        printf("Enter the position at which you want to delete
(between 0 and %d) : " , count-1);
        int pos;
        scanf("%d", &pos);
        if(pos < count && pos>=-1) {
            if(pos == 0) {
                printf("Element %d deleted.\n" , head->data);
                head = head->right;
            }
            else {
                dll * trav = head;
                for(int i = 0 ; i < pos ; i++ )
                    trav = trav->right;
                printf("Element %d deleted.\n" , trav->data);
                dll * back = trav->left;
                dll * front = trav->right;
                back->right = front;
                if (front != NULL)
                    front->left = back;
                trav = NULL;
            }
        }
        else
            printf("Invalid input.\n");
    }
}

void display() {
    if(head != NULL) {
        dll * strt = head;
        printf("Elements of list are : ");
        while(strt != NULL) {
            printf("%d " , strt->data);
            strt = strt->right;
        }
        printf("\n");
    }
    else
        printf("Doubly Linked List is empty.\n");
}

void main() {
    printf("-----Doubly Linked List-----\n");
    printf("We follow zero based index.\n");
    printf("Enter the operation to be performed.\n");
    int ch , flag =1;
    while(flag) {
        printf("1.Insert \t 2.Display \t 3.Delete \t 4.Exit :
");
        scanf("%d" , &ch);
        switch(ch) {
            case 1 : insert();
                        break;
            case 2 : display();
                        break;
            case 3 : delete();
        }
    }
}

```

```
                break;
case 4 : flag = 0;
                break;
default : printf("Invalid Input.\n");
                break;
        }
}
}
```