

Script

Qsn1.

Create a script with name `/root/foo.sh` that does the following

- when run as `/root/foo.sh RedHat` produces the output **fedora** on stdout
- when run as `/root/foo.sh fedora` it produces the output **redhat** on stdout
- when running with an argument different from redhat and fedora then it produces `"/root/foo.sh redhat|fedora"`
- when run without argument it sends the following output to stderr: "Please enter argument".

Qsn2.

When you run the script it should ask you to enter a value. And compare that value with 100 and 200.

- If the number you entered is more than 200 stdout is **"more than 200"**
- If the number which you entered is less than 100 stdout is **"less than 100"**
- If the number is more than 100 and less than 200 then the output is **"bingo"**

Qsn3.

If the argument is not entered, the script should stop and exit with the output **"Please enter argument!!!"**

If the script is not run by root, then the script should stop and exit with the output **"This script must run only by root"**

If the argument count is less than 3, then the script should stop and exit with the output **"enter more than 3 arguments"**

If the argument count is equal to 3 or more than 3, then print all of them (must use `$@`)

Qsn4.

create a text file with name **usernames** and enter 4 usernames

create a text file with name **passwords** and enter 4 passwords

Create a script with the name **create_users.sh** which will read from a text file and create 4 users. Passwords must be set from the **password** file. (password `-stdin`)

Before checking if the user is already on the system then don't create. If not, then create.

Backup with tar and gzip all 4 users' home directories and copy them to **/backups** folder

Qsn5.

Disk həcminə baxın və bütün disk həcmələrini (df) yoxlayın. Use hissesi 80%-dən çox olan halda mail göndərin.

Qsn6.

Scriptin seçilmiş hissəsini case ilə edib screen atın.

```
#!/bin/bash
```

```
## for;
```

```
#set -x
```

```
for i in u11 u22 u33 u44 u55
```

```
do
```

```
    if grep -q $i /etc/passwd
```

```
    then
```

```
        echo "$i istifadəçisi vardır"
```

```
        echo "Silmək istəyirsinizmi? Yes/No"
```

```
        read cavab
```

```
        echo "Sizin cavabınız $cavab oldu"
```

```
        if [ $cavab == Yes ]; then
```

```
            userdel -r $i;
```

```
            echo $i istifadəçisini sildiniz;
```

```
        elif [ $cavab == No ]; then
```

```
            echo $i useri silmediniz;
```

```
        else
```

```
            echo "Yes/No seçmeli idiniz"
```

```
        fi
```

```
    else
```

```
useradd $i;
```

```
echo $i istifadecisi elave olundu;
```

```
fi
```

```
done
```

```
exit 0
```