

Name, Surname:

You can add print screens. Make answers understandable for me.

Note: After finishing tasks change file name to
“Linux_std_Yourname_Yoursurname.docx”

1. Create new user with your name.

```
#useradd <yourname>
```

2. Set password to that user

```
#passwd <your_username>
```

3. Run command to login with that username.

```
#su - <your_username>
```

4. Check which user you are.

```
#whoami
```

5. Now change directory to user's home directory. And list all files including all hidden files. Redirect command result to newfile11.log

6. Now change to directory /etc/sysconfig and try to create new file (pay attention, you should login with new user not with root). Redirect result to newfile11.log. Pay attention not to delete old lines in newfile11.log.

7. Run:

```
$touch ~/olanfayl /etc/sysconfig/yenifile
```

Redirect both STDERR and STDOUT to same file.

8. Write an example command that results with stderr and stdout. The result of command should redirect separately to files. Standard output to output.log, standard error to error.log file.

9. Sometimes we don't need to store result of command. Instead of redirecting to a regular file we can redirect command result to /dev/null. It discards storing command result.

Write command that results with error and redirect it to /dev/null

10. Meaning of

a. >

b. >>

- c. 1>
- d. 1>
- e. 2>
- f. 2>>
- g. \$cmd > file.log 2>&1
- h. \$cmd >> file.log 2>&1
- i. \$cmd > /dev/null
- j. \$cmd 2> 1.log 1>2.log
- k. | (pipe)

11. Yazılan əməlləri icra edin. Hər birini anlamağa çalışın. Çox praktik və vacib məsələ olduğunu unutmayın.

```
-bash-4.2$ r=rus
-bash-4.2$ echo $r
rus
-bash-4.2$ p=t$$ffdd$$dd
-bash-4.2$ echo $p
t6955ffdd6955dd
-bash-4.2$ p="t$$ffdd$$dd"
-bash-4.2$ echo $p
t6955ffdd6955dd
-bash-4.2$ p='t$$ffdd$$dd'
-bash-4.2$ echo $p
t$$ffdd$$dd
-bash-4.2$ s=hdhdhd!!!lllddl | less
-bash: !lllddl: event not found
-bash-4.2$ s=hdhdhd!!!lllddl | less
-bash: !lllddl: event not found
-bash-4.2$ s=hdhdhd!!!lllddl
-bash: !lllddl: event not found
-bash-4.2$
-bash-4.2$ s="hdhdhd!!!lllddl"
-bash: !lllddl: event not found
-bash-4.2$ s='hdhdhd!!!lllddl'
-bash-4.2$ echo $s
hdhdhd!!!lllddl
-bash-4.2$
-bash-4.2$ echo pwd
pwd
-bash-4.2$ echo "pwd"
pwd
-bash-4.2$ echo 'pwd'
pwd
-bash-4.2$ echo `pwd`
/export/home/aurora/
-bash-4.2$ echo "hazirki direktoriyam: $pwd"
hazirki direktoriyam:
-bash-4.2$ echo "hazirki direktoriyam: `pwd`"
hazirki direktoriyam: /export/home/aurora/
-bash-4.2$ echo 'hazirki direktoriyam: `pwd`'
hazirki direktoriyam: `pwd`
-bash-4.2$ echo `hazirki direktoriyam: `pwd``
-bash: hazirki: command not found
pwd
-bash-4.2$ █
```

1. string icerisinde \$ olanda ne bash verir. sizce niyə?
2. string icerisinde !!! (2 ve daha cox nida) olanda ne bash verir sizce nie?
3. "" , ' , ` > bu 3 dirnaq arasinda ne kimi ferqler var. Cox praktik meseledir mutleq bilmelisiz.
4. " " ile ' ' arasindaki ferq nedir. qosha dirnaq ve tek dirnaq arasindaki ferq nedir.
5. `` (esc altinda yerleshen dirnaq) hansı hallarda istifade edilir?