What a reward model can show depends on who stopped the episode: failure judges and monitors on a low-cost arm

Ravindu Somawansa
Shisso Robotics

Abstract

Watching a robot run only up to half the length of the task's longest run, elapsed time already separates failed from successful runs with AUROC 0.851 within policy (CI 0.829–0.873) on 2,047 public SO-101 rollouts from 7 policies: failed runs are slow, not timed out (only 8.7 % reach the task's longest length). The dataset's stopping rule decides what a reward model can show: where runs end at a time limit, elapsed time is the reward model to beat; where an operator stops them, length is blind and a judge at rest works. Over the whole run, length gives 0.938 pooled and 0.942 within policy; two zero-shot reward models proposed as failure detectors score below it: Robometer-4B 0.818 pooled (within policy pending) and TOPReward with an 8B video-language model 0.653 pooled, 0.661 within policy. On 69 of our own operator-stopped rollouts length carries nothing (0.56), and TOPReward's 0.82 there is below what policy identity alone gives (0.87). A deterministic top-camera check at rest makes no false positive; a robot-trained 27B judge separates every failure from every success (AUROC 1.00; 8 of 8 at 2 of 42 at a threshold chosen on the same episodes), and its base model does almost as well given the same input; every mid-episode monitor we tested misses its bar. Report a length baseline, within policy, and say who stopped the episodes.

1 Introduction

A reward model that scores robot rollouts is also a failure detector, and papers evaluate it as one. None of the reward-model papers in our library reports how far plain episode length gets on the same data. We measure it on a public SO-101 benchmark and on our own rollouts, with the analyses frozen before the numbers, and set every learned judge and monitor we ran against it.

2 Data and labels

ArmnetBench v0.1 (SO-101, 8 tasks, 7 policies): 2,047 policy rollouts with a success or failure class (515 successes, 1,532 failures); teleoperated episodes excluded. Our rollouts: 88 labelled bowls-task episodes on one SO-101 and a Jetson Orin NX, and the 50-episode subset (42 successes, 8 failures) every monitor gate used. Labels are the operator's, not blind to policy.




Figure 1: Failure AUROC on ArmnetBench (95 % CIs): episode length vs two zero-shot reward models (Robometer-4B, TOPReward with Qwen3-VL-8B).

3 The length baseline

Pooled over policies, length gives 0.938 (CI 0.925–0.951); Robometer-4B, run zero-shot as its authors ship it, 0.818 (CI 0.790–0.843; within policy pending its per-episode scores); TOPReward (Qwen3-VL-8B, no training; the primary score, fixed in the protocol before any score, is the paper's success score, the sum of its two standardised components) 0.653 pooled (CI 0.623–0.684) and 0.661 within policy (CI 0.631–0.692), below length by -0.31 to -0.25 (paired 95 % CI). Its full-video Yes/No component alone, descriptive: 0.678 within policy. Within each policy, length ranges 0.91–0.96, pair-weighted 0.942 (CI 0.927–0.956): it is not the policy identity (Fig. 1).

4 Is it the timeout?

Only 8.7 % of failures run to the task's longest episode. Observing length only up to half of that, when 88 % of failures but 19 % of successes are still running, gives 0.851 within policy (CI 0.829–0.873; Fig. 2; TOPReward on frames up to the same cut: 0.667): failed rollouts are slow, not timed out. Both pre-registered readings hold: length is a within-policy null, and it is more than the timeout. On our own operator-stopped rollouts the same baseline




Figure 2: Length observed up to a fraction of the task's longest episode, AUROC within policy (band: 95 % CI).




Figure 3: Fifty own rollouts: failures caught (of 8) vs successes flagged (of 42). Circles: mid-episode monitors; shaded: their bar ($\geq$ 5/8 at $\leq$ 1/20). Squares: judges at rest (one score per finished episode) at their in-sample G-flora operating point; the monitor bar does not apply to them.

is at chance (0.56 on 69; 0.52 on all 88). Neither reward model beats the policy-identity null there: TOPReward 0.82 (CI 0.70–0.93) against 0.87 for policy identity alone, and 0.78 on the 50 episodes without TurboVLA (17 of the 25 failures in the 69 come from TurboVLA); Robometer 0.577 against 0.878 on 88. The baseline depends on how episodes end, which is why it must be reported per dataset; what works on operator-stopped runs is the judge at rest (§5).

5 Judges and monitors on our rollouts

At rest. A deterministic top-camera check (colour masks and geometry, no learning) is right on 94.3 % of judged episodes with 0 false positives (Wilson 0–13 two-view clip and NVIDIA's prompt, Flora-Rewarder-27B separates every failure from every success (AUROC 1.00, the threshold-free number); at its gate's operating point, a score threshold chosen on these same 50 episodes, it flags 8 / 8 failures at 2 / 42 successes (Wilson on the false alarms 1–16 model Qwen3.5-27B gets 7 / 8 at 2 / 42 on the same input at its own in-sample threshold; a 9B model (0.75) and Gemini 3.8 Flash (0.96, one false alarm over the bar) do not pass. The input format, not the robot fine-tune, decided the result.

Mid-episode. A Gemini sliding-window judge catches 0 / 8; the surprise of a separate world model 2 / 8 (AUROC 0.86, Wilson 7–59 the world model's latent reached 0.93 in a first version that read elapsed time; the preregistered second version, without time or length, catches 3 / 8 at 5 / 42 (AUROC 0.79 vs 0.71 with shuffled actions; Wilson 14–69 ($\geq$ 5 / 8 at $\leq$ 1 / 20), and the first version's result is withdrawn (Fig. 3).

6 Limitations

Two task families (ArmnetBench's eight tasks, our bowls task); our labels are the operator's and not blind; the risk head is trained and tested on the same 50 episodes (5-fold by episode: episodes do not leak, tasks and policies do); Robometer under the within-policy and truncation analyses is pending its per-episode scores; TOPReward's prefix count, frames per query and Yes/No wording are not given in its paper and are ours; the operating points of Flora, Qwen3.5-27B and Gemini are chosen in-sample on the 50 episodes they are scored on (their AUROCs are not); 17 of the 25 failures in our 69 rollouts are TurboVLA's, so on our set any score that reads the policy gets the identity null for free; the timeout is approximated by each task's longest episode.

References

Robometer 2603.02115 · SARM 2509.25358 · TOPReward 2602.19313 · VLLR 2604.00055 · SARM2 2606.10305 · STDR 2606.31377 · No Free Checker 2609.09250 · FARM 2609.11445 · ReAP 2610.16309 · SAFE 2506.09937 · FAIL-Detect 2503.08558 · VLA-Corrector 2609.06508 · Spotter 2609.36808 · REMORA 2610.39125 · ArmnetBench 2607.24481 · SO-101 benchmark 2606.08881.