


Introduction to Parsing

Context-free grammars

Comp 412

Finally, the box moved ...




Copyright 2017, Keith D. Cooper & Linda Torczon, all rights reserved.

Students enrolled in Comp 412 at Rice University have explicit permission to make copies of these materials for their personal use.

Faculty from other educational institutions may use these materials for nonprofit educational purposes, provided this copyright notice is preserved.

The Front End



Scanner looks at every character

- Converts stream of chars to stream of classified words:
 - <word, part of speech>
 - Sometimes call this pair a “token”
- Efficiency & scalability matter

Parser looks at every token

- Determines if the stream of tokens forms a sentence in the source language
- Fits tokens to some syntactic model, or grammar, for the source language

The Study of Parsing



Parsing is the process of discovering a *derivation* for some sentence

- Need mathematical model of syntax — a grammar G
- Need an algorithm to test membership in $L(G)$
- Need to remember that our goal is to build parsers, not to study the interesting if arcane mathematics of arbitrary languages

Roadmap for our study of parsing

1. Context-free grammars & derivations
2. Top-down parsing
 - Top-down parsers explore the possibilities of syntax in a systematic way
 - A file of code has a limited number of words that can occur at its start
3. Bottom-up parsing
 - Bottom-up parsers build on the detailed structure of the input stream
 - Each classified word can affect the interpretation of past & future words

Specifying Syntax: Context-Free Grammars



Context-free syntax is specified with a *context-free grammar* (CFG)

This **CFG** defines the set of noises that sheep normally make

0	<i>SheepNoise</i>	→	<i>SheepNoise</i>	<u>baa</u>
1			<u>baa</u>	

See the digression about
BNF on p. 87 of EaC2e

It is written in a variant of Backus-Naur form (**BNF**)

Formally, a **CFG** is a four tuple, $G = (S, N, T, P)$

- S is the *start symbol* of the grammar
 - $L(G)$ is the set of sentences that can be derived from S
- N is a set of *nonterminal symbols* or syntactic variables
- T is a set of *terminal symbols* or words
- P is a set of *productions* or *rewrite rules*

SheepNoise

baa

$P: N \rightarrow (N \cup T)^+$

We will defer the definition of “context free” for a few slides.

Deriving Sentences with a CFG



We can use the *SheepNoise* grammar to derive sentences

– use the productions as rewrite rules

Rule	Sentential Form
—	<i>SheepNoise</i>
1	<u>baa</u>

Rule	Sentential Form
—	<i>SheepNoise</i>
0	<i>SheepNoise</i> <u>baa</u>
1	<u>baa</u> <u>baa</u>

Rule	Sentential Form
—	<i>SheepNoise</i>
0	<i>SheepNoise</i> <u>baa</u>
0	<i>SheepNoise</i> <u>baa</u> <u>baa</u>
1	<u>baa</u> <u>baa</u> <u>baa</u>

And, so on ...

While this example is cute, it quickly runs out of intellectual steam ...

A **sentential form** is a string of terminal & nonterminal symbols that is a valid step in some derivation.

Context-Free Grammars



What makes a grammar “context free” ?

Productions in the *SheepNoise* grammar have a specific form:

0	<i>SheepNoise</i>	→	<i>SheepNoise</i>	<u>baa</u>
1			<u>baa</u>	

Each production has *a single nonterminal symbol on its left hand side*, which makes it impossible to encode either left or right context.

⇒ The grammar is *context free*

A context-sensitive grammar can have ≥ 1 symbol on its lhs.

- **CSG**'s have not found widespread application in compilers

lhs \equiv left-hand side
rhs \equiv right hand side

Notice that $L(\textit{SheepNoise})$ is actually a regular language: baa baa*

RLs \subset CFLs

Digression: The Chomsky Hierarchy



Noam Chomsky proposed a hierarchy of languages

PL microsyntax

Type 3 grammars are regular grammars (equivalent to **REs**)

- Single **NT** on *lhs*; *rhs* has one **T** & (optionally) one **NT**
- Corresponds to a **DFA**

PL syntax

Type 2 grammars are context-free grammars


- Single **NT** on *lhs*; *rhs* has string of grammar symbols
- Corresponds to a **push-down automaton**

Type 1 grammars are *context-sensitive grammars*

- Productions of form $\alpha A \beta \rightarrow \gamma$, where α , β , and γ are strings in $(T \cup NT)$
- Corresponds to a **linear bounded automaton**

Type 0 grammars are unrestricted grammars

- Includes all formal grammars
- Corresponds to a **Turing machine**



The Chomsky Hierarchy of Grammars

Limits of Regular Languages

$RL's \subset CFL's$



Does it matter that $RL's \subset CFL's$?

You cannot construct **DFA's** to recognize these languages

- $L = \{ p^k q^k \}$ *(parentheses, brackets)*
- $L = \{ wcw^r \mid w \in \Sigma^* \}$

Neither of these is a regular language *(nor an RE)*

Constructs like these are important to programming languages

But, this is a little subtle. You can construct **DFA's** for

- Strings with alternating 0's and 1's
 $(\epsilon \mid 1)(01)^*(\epsilon \mid 0)$
- Strings with an even number of 0's and 1's

RE's can count bounded sets and bounded differences



Terminology for Derivations

The point of parsing is to discover a derivation

A derivation consists of a series of rewrite steps

$$S \Rightarrow \gamma_0 \Rightarrow \gamma_1 \Rightarrow \gamma_2 \Rightarrow \dots \Rightarrow \gamma_{n-1} \Rightarrow \gamma_n \Rightarrow \text{sentence}$$

- Each γ_i is a sentential form
 - If γ contains only terminal symbols, γ is a **sentence** in $L(G)$
 - If γ contains 1 or more non-terminals, γ is a **sentential form**
- To get γ_i from γ_{i-1} , expand some **NT** $A \in \gamma_{i-1}$ by using $A \rightarrow \beta$
 - Replace the occurrence of $A \in \gamma_{i-1}$ with β to get γ_i
 - Replacing the leftmost **NT** at each step, creates a **leftmost** derivation
 - Replacing the rightmost **NT** at each step, creates a **rightmost** derivation

A **left-sentential form** occurs in a *leftmost* derivation

A **right-sentential form** occurs in a *rightmost* derivation

NT \cong nonterminal symbol

S is the start symbol for the grammar G

Terminology for Derivations



The point of parsing is to discover a derivation

Top down ↓	Rule	Sentential Form	↑ Bottom up
	—	<i>SheepNoise</i>	
	0	<i>SheepNoise</i> <u>baa</u>	
	0	<i>SheepNoise</i> <u>baa</u> <u>baa</u>	
	1	<u>baa</u> <u>baa</u> <u>baa</u>	

Three-word SheepNoise

- A top-down parse begins with the grammar's start symbol and works toward the sentence
- A bottom-up parse starts with the words in the sentence and works towards the start symbol

In the general case¹, discovering a derivation looks expensive

- Many alternatives & combinations, possible backtracking
- Derivation must be guided by the actual words in the sentence
- Fortunately, programming languages tend to have simple syntax
- Understanding parsing will help you see why PLs look as they do!

¹ e.g., Chomsky 0 or 1 grammars

A Better Example

Not a regular language



SheepNoise is quite limited. Let's consider a more interesting example.

0	<i>Start</i>	→	<i>Brackets</i>
1	<i>Brackets</i>	→	(<i>Brackets</i>)
2			[<i>Brackets</i>]
3			()
4			[]

Rule	Sentential Form
—	<i>Start</i>
0	<i>Brackets</i>
1	(<i>Brackets</i>)
2	([<i>Brackets</i>])
3	([()])

Two flavors of nested brackets

Derivation of “([()])”

- A sequence of rewrites that produces a sentence is a *derivation*
- Process of discovering a derivation is called *parsing*

We denote this derivation: $Start \Rightarrow^* ([()])$

Brackets




A derivation corresponds to a *derivation tree* or *parse tree*

Rule	Sentential Form
—	<i>Start</i>
0	<i>Brackets</i>
1	<i>[Brackets]</i>
2	<i>[[Brackets]]</i>
3	<i>[[()]]</i>

$Start \Rightarrow^* ([()])$

The derivation gives us the grammatical structure of the input sentence, which was completely missing in RE / DFA recognizers.



Parse tree for this derivation

A Simple Expression Grammar



CFGs are used to define many programming language constructs

0	$Expr$	\rightarrow	$Expr\ Op\ Expr$
1			<u>number</u>
2			<u>identifier</u>
3	Op	\rightarrow	<u>plus</u>
4			<u>minus</u>
5			<u>times</u>
6			<u>divide</u>

**Expressions over +, -, *, /
numbers, & identifiers**

When a syntactic category has just one lexeme, as with plus and minus, we will often write it as just the lexeme.

COMP 412, Fall 2017

Rule	Sentential Form
—	$Expr$
0	$Expr\ Op\ Expr$
2	$\langle \underline{id}, x \rangle\ Op\ Expr$
4	$\langle \underline{id}, x \rangle\ -\ Expr$
0	$\langle \underline{id}, x \rangle\ -\ Expr\ Op\ Expr$
1	$\langle \underline{id}, x \rangle\ -\ \langle \underline{num}, 2 \rangle\ Op\ Expr$
5	$\langle \underline{id}, x \rangle\ -\ \langle \underline{num}, 2 \rangle\ * Expr$
2	$\langle \underline{id}, x \rangle\ -\ \langle \underline{num}, 2 \rangle\ * \langle \underline{id}, y \rangle$

Derivation of $x - 2 * y$

And, if you skipped class & are reading the slides, you should know that this grammar is a very bad way to define expressions

A Simple Expression Grammar



Constructing a derivation

- At each step, we select an **NT** in the current string to replace
- Different choices can lead to different derivations

Two derivations are of interest

- ***Leftmost derivation*** — replace, at each step, the leftmost **NT**
- ***Rightmost derivation*** — replace, at each step, the rightmost **NT**

These are the two systematic derivations (*We don't care about random orders*)

The example on the preceding slide was a *leftmost* derivation

- Of course, there is also a *rightmost* derivation
- In this example, the rightmost derivation is different

Leftmost and Rightmost Derivations



Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
2	<i><id,x> Op Expr</i>
4	<i><id,x> — Expr</i>
0	<i><id,x> — Expr Op Expr</i>
1	<i><id,x> — <num,2> Op Expr</i>
5	<i><id,x> — <num,2> * Expr</i>
2	<i><id,x> — <num,2> * <id,y></i>

Leftmost Derivation of $x - 2 * y$

Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
2	<i>Expr Op <id,y></i>
5	<i>Expr * <id,y></i>
0	<i>Expr Op Expr * <id,y></i>
1	<i>Expr Op <num,2> * <id,y></i>
4	<i>Expr — <num,2> * <id,y></i>
2	<i><id,x> — <num,2> * <id,y></i>


Rightmost Derivation of $x - 2 * y$

- In both cases, $Expr \Rightarrow^* \text{identifier} - \text{number} + \text{identifier}$
- The two derivations produce different parse trees & evaluation orders

Leftmost Derivation



Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
2	<u><id,x></u> <i>Op Expr</i>
4	<u><id,x></u> — <i>Expr</i>
0	<u><id,x></u> — <i>Expr Op Expr</i>
1	<u><id,x></u> — <u><num,2></u> <i>Op Expr</i>
5	<u><id,x></u> — <u><num,2></u> * <i>Expr</i>
2	<u><id,x></u> — <u><num,2></u> * <u><id,y></u>




*In a postorder treewalk, this parse tree evaluates as $x - (2 * y)$*

Parse tree for the leftmost derivation

Rightmost Derivation



Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
2	<i>Expr Op</i> < <u>id</u> ,y>
5	<i>Expr</i> * < <u>id</u> ,y>
0	<i>Expr Op Expr</i> * < <u>id</u> ,y>
1	<i>Expr Op</i> < <u>num</u> ,2> * < <u>id</u> ,y>
4	<i>Expr</i> — < <u>num</u> ,2> * < <u>id</u> ,y>
2	< <u>id</u> ,x> — < <u>num</u> ,2> * < <u>id</u> ,y>



*In a postorder treewalk, this parse tree evaluates as $(x - 2) * y$*

Parse tree for the rightmost derivation

Evaluation Order: Why Do We Care?



The leftmost & rightmost derivations for $x - 2 * y$ produced different evaluation orders.

- These two orders may produce different results, even with integers
 - $x - (2 * y)$ is different than $(x - 2) * y$, for most values of x & y
 - In floating point, the problem can arise with a string of the same operator
- Standard algebra specifies both an evaluation order (*left to right*) and a precedence (*parentheses; multiply and divide; add and subtract*)

The compiler must pay attention to the intended order of evaluation

Floating-point Numbers are not Real Numbers

- Finite magnitude (e.g., -2^{31} to $2^{31}-1$) introduces overflow & underflow
- Floating-point arithmetic causes unexpected losses of precision
 - There exist x , y , & z such that $x + y > 0$, $(x + y) + z > z$, but $x + (y + z) = z$

Reminder: Why Do We Care About Ambiguity?



It is easy to get lost in language theory

The point of this course is language translation


- Build an executable image that implements the source program
- *Implements* implies that the source program has well-defined meaning

Ambiguity is the opposite of “well-defined”

- Ambiguous constructs have multiple meanings
- A program with multiple meanings is not, in general, a good thing

Programming languages (& their designers) should abhor ambiguity

Leftmost & Rightmost Parse Trees



The two parse trees generate different evaluation orders

Different parse trees for leftmost & rightmost derivations means that the underlying grammar is ambiguous

→ Not a good thing.

Ambiguity



The grammar has multiple leftmost derivations (& rightmost derivations)

Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
2	<i><id,x> Op Expr</i>
4	<i><id,x> — Expr</i>
0	<i><id,x> — Expr Op Expr</i>
1	<i><id,x> — <num,2> Op Expr</i>
5	<i><id,x> — <num,2> * Expr</i>
2	<i><id,x> — <num,2> * <id,y></i>

Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Expr</i>
0	<i>Expr Op Expr Op Expr</i>
2	<i><id,x> Op Expr Op Expr</i>
4	<i><id,x> — Expr Op Expr</i>
1	<i><id,x> — <num,2> Op Expr</i>
5	<i><id,x> — <num,2> * Expr</i>
1	<i><id,x> — <num,2> * <id,y></i>

Any grammar that has multiple leftmost (or multiple rightmost) derivations for a single sentence is an **ambiguous** grammar.

⇒ *Ambiguity is bad in a programming language*

Ambiguity



What should you do with an ambiguous grammar?

You rewrite it to remove the ambiguity.

0	<i>Expr</i>	→	<i>Expr Op Expr</i>
1			<u>number</u>
2			<u>identifier</u>
3	<i>Op</i>	→	<u>plus</u>
4			<u>minus</u>
5			<u>times</u>
6			<u>divide</u>

Ambiguous Grammar

0	<i>Expr</i>	→	<i>Expr Op Value</i>
1			<i>Value</i>
2	<i>Value</i>	→	<u>number</u>
3			<u>identifier</u>
4	<i>Op</i>	→	<u>plus</u>
5			<u>minus</u>
6			<u>times</u>
7			<u>divide</u>

Rewritten Grammar

In this case, the ambiguity that we see arises from the fact that rule 0 generates *Expr*, its lhs, at both the right & left ends of its rhs.

⇒ *The ambiguity allows derivations with the wrong evaluation order*

Ambiguity



Leftmost derivation of $x - 2 * y$

0	<i>Expr</i>	→	<i>Expr Op Value</i>
1			<i>Value</i>
2	<i>Value</i>	→	<u>number</u>
3			<u>identifier</u>
4	<i>Op</i>	→	<u>plus</u>
5			<u>minus</u>
6			<u>times</u>
7			<u>divide</u>

Rule	Sentential Form
—	<i>Expr</i>
0	<i>Expr Op Value</i>
0	<i>Expr Op Value Op Value</i>
1	<i>Value Op Value Op Value</i>
3	<id,x> <i>Op Value Op Value</i>
5	<id,x> — <i>Value Op Value</i>
2	<id,x> — <num,2> <i>Op Value</i>
6	<id,x> — <num,2> * <i>Value</i>
3	<id,x> — <num,2> * <id,y>

The unambiguous grammar requires one more step in this derivation: the rewrite through *Value* for **x**.

Seems like a small price to pay. (TANSTAAFL)

Ambiguity



Definitions

- A context-free grammar G is **ambiguous** if there exists has more than one leftmost derivation for some sentence in $L(G)$
- A context-free grammar G is **ambiguous** if there exists has more than one rightmost derivation for some sentence in $L(G)$
- A context-free grammar G is **ambiguous** if the rightmost and leftmost derivations produce different parse trees
 - *However, the rightmost and leftmost derivations may differ*

The classic example — the if-then-else problem

0	$Stmt \rightarrow \underline{if} \ Expr \ \underline{then} \ Stmt$
1	$\underline{if} \ Expr \ \underline{then} \ Stmt \ \underline{else} \ Stmt$
2	$\dots other \ statements \dots$


Ambiguity




The straightforward if-then-else grammar is ambiguous

Consider the sentential form:

if $Expr_1$ then if $Expr_2$ then $Stmt_1$ else $Stmt_2$



production 2, then production 1



production 1, then production 2

Two parse trees, two meanings

Ambiguity

The new grammar forces the structure
to match the desired meaning.



Rewriting the grammar to remove the ambiguity

- Must rewrite the grammar to avoid generating the problem
- Match each else to innermost unmatched if (*common sense rule*)

0	<i>Stmt</i>	→	<u>if</u> <i>Expr</i> <u>then</u> <i>Stmt</i>
1			<u>if</u> <i>Expr</i> <u>then</u> <i>WithElse</i> <u>else</u> <i>Stmt</i>
2			... other statements ...
3	<i>WithElse</i>	→	<u>if</u> <i>Expr</i> <u>then</u> <i>WithElse</i> <u>else</u> <i>WithElse</i>
4			... other statements ...

The critical point: the
if-then case is not in
... other statements ...

With this grammar, the example has only one rightmost derivation

Intuition: once inside a *WithElse*, derivation cannot generate an unmatched else
... a final if without an else can only come through rule 2 ...

Ambiguity



Derivation for the example sentence

if $Expr_1$ then if $Expr_2$ then $Stmt_1$ else $Stmt_2$

Rule	Sentential Form
—	$Stmt$
0	<u>if</u> $Expr$ <u>then</u> $Stmt$
1	<u>if</u> $Expr$ <u>then</u> <u>if</u> $Expr$ <u>then</u> $WithElse$ <u>else</u> $Stmt$
2	<u>if</u> $Expr$ <u>then</u> <u>if</u> $Expr$ <u>then</u> $WithElse$ <u>else</u> S_2
4	<u>if</u> $Expr$ <u>then</u> <u>if</u> $Expr$ <u>then</u> S_1 <u>else</u> S_2
?	<u>if</u> $Expr$ <u>then</u> <u>if</u> E_2 <u>then</u> S_1 <u>else</u> S_2
?	<u>if</u> E_1 <u>then</u> <u>if</u> E_2 <u>then</u> S_1 <u>else</u> S_2

Other productions to derive $Exprs$

The new grammar has only one **rightmost** derivation for the example

A Final Word on IF-THEN-ELSE



The IF-THEN-ELSE ambiguity is a bit more subtle than it looks

```
Stmts  →  Stmts Stmt
        |  Stmt
Stmt    →  Reference ≡ Expr
        |  IF ( Expr ) THEN Stmt
        |  IF ( Expr ) THEN Stmt
                ELSE Stmt
```

... where *Reference* and *Expr* are NTs defined elsewhere

We know how to fix this ambiguity using the “withelse” rewrite

What happens if we add a *Stmt* that contains *Stmt*?

```
Stmt    →  WHILE ( Expr ) Stmts
```

Stmt can derive **IF-THEN-ELSE**, which creates an ambiguity when a **WHILE** is inside an **IF-THEN** or an **IF-THEN-ELSE**

→ *Either disallow IF-THEN inside while or require brackets around Stmts list*

Deeper Ambiguity



Ambiguity usually refers to confusion in the CFG

Overloading can create deeper confusions about meaning

$a = f(17)$

In many Algol-like languages, f can be either a function or a subscripted variable

Disambiguating this confusion requires context

- Need values of declarations
- Really an issue of *type*, not context-free syntax
- Requires an extra-grammatical solution (not in the **CFG**)
- Must handle these with a different mechanism
 - Step outside grammar rather than use a more complex grammar

The alternative: *change the syntax*
C introduced square brackets for subscripts
BCPL used $!$, the indirection operator

Ambiguity - the Final Word



Ambiguity arises from two distinct sources

- Confusion in the context-free syntax
- Confusion that requires context to resolve

(if-then-else)

(overloading)

Resolving ambiguity

- To remove context-free ambiguity, rewrite the grammar
- To handle context-sensitive ambiguity takes cooperation
 - Knowledge of declarations, types, ...
 - Accept a superset of $L(G)$ & check it by other means[†]
 - This is a language design problem

Sometimes, the compiler writer accepts an ambiguous grammar

- Parsing techniques that “do the right thing”
- *i.e.*, always select the same derivation