




COMP 412
FALL 2017

Syntax Analysis, VII

One more LR(1) example, plus some more stuff

Comp 412



Copyright 2017, Keith D. Cooper & Linda Torczon, all rights reserved.

Students enrolled in Comp 412 at Rice University have explicit permission to make copies of these materials for their personal use.

Faculty from other educational institutions may use these materials for nonprofit educational purposes, provided this copyright notice is preserved.

Chapter 3 in EaC2e

Computing Closures

Review



Closure(s) adds all the possibilities for the items already in s

- Any item $[A \rightarrow \beta \bullet B \delta, \underline{a}]$ where $B \in NT$ implies $[B \rightarrow \bullet \tau, x]$ for each production that has B on the *lhs*, and each $x \in \text{FIRST}(\delta \underline{a})$
- Since $\beta B \delta$ is valid, any way to derive $\beta B \delta$ is valid, too

The Algorithm

Closure(s)

while (s is still changing)

\forall items $[A \rightarrow \beta \bullet B \delta, \underline{a}] \in s$

lookahead $\leftarrow \text{FIRST}(\delta \underline{a})$ // δ might be ε

\forall productions $B \rightarrow \tau \in P$

$\forall \underline{b} \in \text{lookahead}$

if $[B \rightarrow \bullet \tau, \underline{b}] \notin s$

then $s \leftarrow s \cup \{ [B \rightarrow \bullet \tau, \underline{b}] \}$

- Classic fixed-point method
- Halts because $s \subset I$, the set of all items (*finite*)
- Worklist version is faster
- **Closure** “fills out” a state s

Generate new lookaheads.
See note on p. 128

Computing Gotos

Review



Goto(s,x) computes the state that the parser would reach if it recognized an *x* while in state *s*

- ***Goto***({ $[A \rightarrow \beta \bullet X \delta, \underline{a}]$ }, *X*) produces { $[A \rightarrow \beta X \bullet \delta, \underline{a}]$ } *(obviously)*
- It finds all such items & uses *Closure()* to fill out the state

The Algorithm

```
Goto( s, X )  
  new  $\leftarrow \emptyset$   
   $\forall$  items  $[A \rightarrow \beta \bullet X \delta, \underline{a}] \in s$   
    new  $\leftarrow new \cup \{ [A \rightarrow \beta X \bullet \delta, \underline{a}] \}$   
  return Closure( new )
```

- ***Goto***() models a transition in the automaton
- Straightforward computation
- ***Goto***() is not a fixed-point method (but it calls ***Closure***())

Goto in this construction is analogous to ***Move*** in the subset construction.

Building the Canonical Collection

Review



Start from $s_0 = \text{Closure}([S' \rightarrow \bullet S, \underline{\text{EOF}}])$

Repeatedly construct new states, until all are found

The Algorithm

```
 $s_0 \leftarrow \text{Closure}(\{[S' \rightarrow \bullet S, \underline{\text{EOF}}]\})$   
 $S \leftarrow \{s_0\}$   
 $k \leftarrow 1$   
while ( $S$  is still changing)  
   $\forall s_j \in S \text{ and } \forall x \in (T \cup NT)$   
     $s_k \leftarrow \text{Goto}(s_j, x)$   
    record  $s_j \rightarrow s_k$  on  $x$   
  if  $s_k \notin S$  then  
     $S \leftarrow S \cup \{s_k\}$   
     $k \leftarrow k + 1$ 
```

- Fixed-point computation
- Loop adds to S (*monotone*)
- $S \subseteq 2^{\text{ITEMS}}$, so S is finite
- *Worklist version is faster because it avoids duplicated effort*

This membership / equality test requires careful and/or clever implementation.

Filling in the ACTION and GOTO Tables

Review



The Table Construction Algorithm

x is the state number

```

 $\forall$  set  $S_x \in S$ 
   $\forall$  item  $i \in S_x$ 
    if  $i$  is  $[A \rightarrow \beta \bullet \underline{a} \delta, \underline{b}]$  and  $\text{goto}(S_x, \underline{a}) = S_k, \underline{a} \in T$ 
      then  $\text{ACTION}[x, \underline{a}] \leftarrow \text{"shift } k\text{"}$ 
    else if  $i$  is  $[S' \rightarrow S \bullet, \underline{\text{EOF}}]$ 
      then  $\text{ACTION}[x, \underline{\text{EOF}}] \leftarrow \text{"accept"}$ 
    else if  $i$  is  $[A \rightarrow \beta \bullet, \underline{a}]$ 
      then  $\text{ACTION}[x, \underline{a}] \leftarrow \text{"reduce } A \rightarrow \beta\text{"}$ 
   $\forall n \in NT$ 
    if  $\text{goto}(S_x, n) = S_k$ 
      then  $\text{GOTO}[x, n] \leftarrow k$ 
```

• before $T \Rightarrow$ shift

have Goal \Rightarrow accept

• at end \Rightarrow reduce

Many items generate no table entry

- Placeholder before a NT does not generate an **ACTION** table entry
- **Closure**() instantiates $\text{FIRST}(X)$ directly for $[A \rightarrow \beta \bullet X \delta, \underline{a}]$

Another Example

(*grammar & sets*)



Simplified, right recursive expression grammar

0	<i>Goal</i>	\rightarrow	<i>Expr</i>
1	<i>Expr</i>	\rightarrow	<i>Term</i> - <i>Expr</i>
2			<i>Term</i>
3	<i>Term</i>	\rightarrow	<i>Factor</i> * <i>Term</i>
4			<i>Factor</i>
5	<i>Factor</i>	\rightarrow	<u>id</u>

SYMBOL	FIRST
<i>Goal</i>	{ <u>id</u> }
<i>Expr</i>	{ <u>id</u> }
<i>Term</i>	{ <u>id</u> }
<i>Factor</i>	{ <u>id</u> }
-	{ - }
*	{ * }
<u>id</u>	{ <u>id</u> }

Simplified Expression Grammar

Building the
Collection



Initialization Step

$$s_0 \leftarrow \text{closure}(\{ [Goal \rightarrow \bullet Expr, EOF] \})$$
$$\{ [Goal \rightarrow \bullet Expr, EOF],$$
$$[Expr \rightarrow \bullet Term - Expr, EOF], [Expr \rightarrow \bullet Term, EOF],$$
$$[Term \rightarrow \bullet Factor * Term, EOF], [Term \rightarrow \bullet Factor * Term, -],$$
$$[Term \rightarrow \bullet Factor, EOF], [Term \rightarrow \bullet Factor, -],$$
$$[Factor \rightarrow \bullet \underline{id}, EOF], [Factor \rightarrow \bullet \underline{id}, -], [Factor \rightarrow \bullet \underline{id}, *] \}$$
$$S \leftarrow \{s_0\}$$

Item in **black** is the initial item.
Items in **gray** are added by *closure()*.

Simplified Expression Grammar

Building the
Collection



Iteration 1

$s_1 \leftarrow \text{goto}(s_0, \text{Expr})$

$s_2 \leftarrow \text{goto}(s_0, \text{Term})$

$s_3 \leftarrow \text{goto}(s_0, \text{Factor})$

$s_4 \leftarrow \text{goto}(s_0, \underline{\text{id}})$

*Goal, *, & - generate empty sets*

Iteration 2

$s_5 \leftarrow \text{goto}(s_2, -)$

$s_6 \leftarrow \text{goto}(s_3, *)$

Goal, Expr, Term, Factor, & id generate empty sets

Iteration 3

$s_7 \leftarrow \text{goto}(s_5, \text{Expr})$

$s_8 \leftarrow \text{goto}(s_6, \text{Term})$

*Goal, *, & - generate empty sets. Term, Factor, & id start to re-create existing sets.*



$s_0 \leftarrow \text{closure}(\{ [Goal \rightarrow \bullet Expr, EOF] \})$
 $\{ [Goal \rightarrow \bullet Expr, EOF],$
 $[Expr \rightarrow \bullet Term - Expr, EOF], [Expr \rightarrow \bullet Term, EOF],$
 $[Term \rightarrow \bullet Factor * Term, EOF], [Term \rightarrow \bullet Factor * Term, -],$
 $[Term \rightarrow \bullet Factor, EOF], [Term \rightarrow \bullet Factor, -],$
 $[Factor \rightarrow \bullet \underline{id}, EOF], [Factor \rightarrow \bullet \underline{id}, -], [Factor \rightarrow \bullet \underline{id}, *] \}$

$s_1 \leftarrow \text{goto}(s_0, Expr)$
 $\{ [Goal \rightarrow Expr \bullet, EOF] \}$

$s_2 \leftarrow \text{goto}(s_0, Term)$
 $\{ [Expr \rightarrow Term \bullet - Expr, EOF], [Expr \rightarrow Term \bullet, EOF] \}$

$s_3 \leftarrow \text{goto}(s_0, Factor)$
 $\{ [Term \rightarrow Factor \bullet * Term, EOF], [Term \rightarrow Factor \bullet * Term, -],$
 $[Term \rightarrow Factor \bullet, EOF], [Term \rightarrow Factor \bullet, -] \}$

Items in **black** are core items, generated by moving the placeholder.
Items in **gray** are added by *closure()*.



$s_4 \leftarrow \text{goto}(s_0, \underline{\text{id}})$

$\{ [Factor \rightarrow \underline{\text{id}} \bullet, EOF], [Factor \rightarrow \underline{\text{id}} \bullet, -], [Factor \rightarrow \underline{\text{id}} \bullet, *] \}$

$s_5 \leftarrow \text{goto}(s_2, -)$

$\{ [Expr \rightarrow Term - \bullet Expr, EOF], [Expr \rightarrow \bullet Term - Expr, EOF],$
 $[Expr \rightarrow \bullet Term, EOF],$
 $[Term \rightarrow \bullet Factor * Term, -], [Term \rightarrow \bullet Factor, -],$
 $[Term \rightarrow \bullet Factor * Term, EOF], [Term \rightarrow \bullet Factor, EOF],$
 $[Factor \rightarrow \bullet \underline{\text{id}}, *], [Factor \rightarrow \bullet \underline{\text{id}}, -], [Factor \rightarrow \bullet \underline{\text{id}}, EOF] \}$

$s_6 \leftarrow \text{goto}(s_3, *)$

$\{ [Term \rightarrow Factor * \bullet Term, EOF], [Term \rightarrow Factor * \bullet Term, -],$
 $[Term \rightarrow \bullet Factor * Term, EOF], [Term \rightarrow \bullet Factor * Term, -],$
 $[Term \rightarrow \bullet Factor, EOF], [Term \rightarrow \bullet Factor, -],$
 $[Factor \rightarrow \bullet \underline{\text{id}}, EOF], [Factor \rightarrow \bullet \underline{\text{id}}, -], [Factor \rightarrow \bullet \underline{\text{id}}, *] \}$

Items in **black** are core items, generated by moving the placeholder.
Items in **gray** are added by *closure()*.



$s_7 \leftarrow \text{goto}(s_5, \text{Expr})$
 $\{ [\text{Expr} \rightarrow \text{Term} - \text{Expr} \bullet, \text{EOF}] \}$

goto(s_5 , *Term*) recreates s_2

goto(s_5 , *Factor*) recreates s_3

goto(s_5 , id) recreates s_4

$s_8 \leftarrow \text{goto}(s_6, \text{Term})$
 $\{ [\text{Term} \rightarrow \text{Factor} * \text{Term} \bullet, \text{EOF}], [\text{Term} \rightarrow \text{Factor} * \text{Term} \bullet, -] \}$

goto(s_6 , *Term*) recreates s_3

goto(s_6 , id) recreates s_4

The next iteration creates no new sets.

Items in **black** are core items, generated by moving the placeholder.
Items in **gray** are added by *closure()*.

Simplified Expression Grammar

Recorded Transitions



The Goto Relationship

(recorded during the construction)

State	Expr	Term	Factor	-	*	<u>id</u>
s_0	1	2	3			4
s_1						
s_2				5		
s_3					6	
s_4						
s_5	7	2	3			4
s_6		8	3			4
s_7						
s_8						

Simplified Expression Grammar


Filling in the Tables



The algorithm produces the following tables

State	ACTION				GOTO		
	<u>id</u>	-	*	EOF	<i>Expr</i>	<i>Term</i>	<i>Factor</i>
s_0	s 4				1	2	3
s_1				acc			
s_2		s 5		r 3			
s_3		r 5	s 6	r 5			
s_4		r 6	r 6	r 6			
s_5	s 4				7	2	3
s_6	s 4					8	3
s_7				r 2			
s_8		r 4		r 4			

Brief Commercial: Why Are We Doing This?



The goal of this exercise is to automate construction of parsers

- Compiler writer provides a **CFG** written in modified **BNF**
- Tools provide an efficient and correct parser
 - *One that works well with an automatically generated scanner*
- **LR** parser generators accept the largest class of grammars that are deterministically parsable, and they are highly efficient
 - *Generated parsers are preferable to hand-coded ones for large grammars*

Shrinking the ACTION and GOTO Tables



Three classic options:

- Combine terminals such as number & identifier, \pm & \mp , $*$ & $/$
 - Directly removes a column, may remove a row
 - For expression grammar, 198 (vs. 384) table entries
- Combine rows or columns
 - Implement identical rows once & remap states
 - Requires extra indirection on each lookup
 - Use separate mappings for ACTION & GOTO
- Use another construction algorithm
 - Both **LALR(1)** and **SLR(1)** produce smaller tables
 - *LALR(1) represents each state with its “core” items*
 - *SLR(1) uses LR(0) items and the FOLLOW set*
 - Implementations are readily available

Shrinking the Grammar



The Classic Expression Grammar

0	Goal	→	Expr
1	Expr	→	Expr + Term
2			Expr - Term
3			Term
4	Term	→	Term * Factor
5			Term / Factor
6			Factor
7	Factor	→	(Expr)
8			<u>number</u>
9			<u>id</u>

Canonical construction produces 32 states

- $32 \times (9 + 3) = 384$ ACTION/GOTO entries
- Large table, but still just 1.5kb

	Action Table								
State	eof	+	−	×	÷	()	num	name
0						s 4		s 5	s 6
1	acc	s 7	s 8						
2	r 4	r 4	r 4	s 9	s 10				
3	r 7	r 7	r 7	r 7	r 7				
4						s 14		s 15	s 16
5	r 9	r 9	r 9	r 9	r 9				
6	r 10	r 10	r 10	r 10	r 10				
7						s 4		s 5	s 6
8						s 4		s 5	s 6
9						s 4		s 5	s 6
10						s 4		s 5	s 6
11		s 21	s 22				s 23		
12		r 4	r 4	s 24	s 25		r 4		
13		r 7	r 7	r 7	r 7		r 7		
14						s 14		s 15	s 16
15		r 9	r 9	r 9	r 9		r 9		
16		r 10	r 10	r 10	r 10		r 10		
17	r 2	r 2	r 2	s 9	s 10				
18	r 3	r 3	r 3	s 9	s 10				
19	r 5	r 5	r 5	r 5	r 5				
20	r 6	r 6	r 6	r 6	r 6				
21						s 14		s 15	s 16
22						s 14		s 15	s 16
23	r 8	r 8	r 8	r 8	r 8				
24						s 14		s 15	s 16
25						s 14		s 15	s 16
26		s 21	s 22				s 31		
27		r 2	r 2	s 24	s 25		r 2		
28		r 3	r 3	s 24	s 25		r 3		
29		r 5	r 5	r 5	r 5		r 5		
30		r 6	r 6	r 6	r 6		r 6		
31		r 8	r 8	r 8	r 8		r 8		

■ FIGURE 3.31 Action Table for the Classic Expression Grammar.

Shrinking the Grammar



We can combine some of the syntactically equivalent symbols

- Combine + and – into AddSub
- Combine * and / into MulDiv
- Combine identifier and number into Val

0	<i>Goal</i>	→	<i>Expr</i>
1	<i>Expr</i>	→	<i>Expr</i> <u>AddSub</u> <i>Term</i>
2			<i>Term</i>
3	<i>Term</i>	→	<i>Term</i> <u>MulDiv</u> <i>Factor</i>
4			<i>Factor</i>
5	<i>Factor</i>	→	(<i>Expr</i>)
6			<u>Val</u>

This grammar has

- Fewer terminals
- Fewer productions

Which leads to

- Fewer columns in ACTION
- Fewer states, which leads to fewer rows in both tables

The “Reduced” Expression Grammar

Shrinking the Grammar



The Resulting Tables

0	Goal	→	Expr
1	Expr	→	Expr <u>AddSub</u> Term
2			Term
3	Term	→	Term <u>MulDiv</u> Factor
4			Factor
5	Factor	→	(Expr)
6			<u>Val</u>

	Action Table						Goto Table		
	eof	addsub	muldiv	()	val	Expr	Term	Factor
0				s 4		s 5	1	2	3
1	acc	s 6							
2	r 3	r 3	s 7						
3	r 5	r 5	r 5						
4				s 11		s 12	8	9	10
5	r 7	r 7	r 7						
6				s 4		s 5		13	3
7				s 4		s 5			14
8		s 15				s 16			
9		r 3	s 17			r 3			
10		r 5	r 5			r 5			
11				s 11		s 12	18	9	10
12		r 7	r 7			r 7			
13	r 2	r 2	s 7						
14	r 4	r 4	r 4						
15				s 11		s 12		19	10
16	r 6	r 6	r 6						
17				s 11		s 12			20
18		s 15				s 21			
19		r 2	s 17			r 2			
20		r 4	r 4			r 4			
21		r 6	r 6			r 6			

(b) Action and Goto Tables for the Reduced Expression Grammar

■ FIGURE 3.33 The Reduced Expression Grammar and its Tables.

- 22 states
- $22 * (6 + 3) = 198$ ACTION/GOTO entries
- 48.4% reduction $(384 - 198) / 384$
- Builds (essentially) the same parse tree

Shrinking the ACTION and GOTO Tables



Three classic options:

- Combine terminals such as number & identifier, \pm & \mp , $*$ & $/$
 - Directly removes a column, may remove a row
 - For expression grammar, 198 (vs. 384) table entries
- Combine rows or columns
 - Implement identical rows once & remap states
 - Requires extra indirection on each lookup
 - Use separate mappings for ACTION & GOTO
- Use another construction algorithm
 - Both **LALR(1)** and **SLR(1)** produce smaller tables
 - *LALR(1)* represents each state with its “core” items
 - *SLR(1)* uses *LR(0)* items and the **FOLLOW** set
 - Implementations are readily available

left-recursive expression
grammar with precedence,
see § 3.6.2 in EAC

classic space-time
tradeoff

Fewer grammars,
same languages

LR(k) versus LL(k)



Finding the next step in a derivation

LR(k) \Rightarrow Each reduction in the parse is detectable with

- \rightarrow the complete left context,
- \rightarrow the reducible phrase, itself, and
- \rightarrow the k terminal symbols to its right

generalizations of
LR(1) and LL(1) to
longer lookaheads

LL(k) \Rightarrow Parser must select the expansion based on

- \rightarrow The complete left context
- \rightarrow The next k terminals

Thus, **LR(k)** examines more context

The question is, do languages fall in the gap between LR(k) and LL(k)?



LR(1) versus LL(1)

The following **LR(1)** grammar has no **LL(1)** counterpart

- The Canonical Collection has 18 sets of LR(1) Items
 - It is not a simple grammar
 - It is, however, LR(1)

0	<i>Goal</i>	→	<i>S</i>
1	<i>S</i>	→	<i>A</i>
2			<i>B</i>
3	<i>A</i>	→	(<i>A</i>)
4			<u><i>a</i></u>
5	<i>B</i>	→	(<i>B</i> >
6			<u><i>b</i></u>

- It requires an arbitrary lookahead to choose between *A* & *B*
- An **LR(1)** parser can carry the left context (the '(' s) until it sees *a* or *b*
- The table construction will handle it
- In contrast, an **LL(1)** parser cannot decide whether to expand *Goal* by *A* or *B*
 - *No amount of massaging the grammar and no amount of lookahead will resolve this problem*

More precisely, the language described by this **LR(1)** grammar cannot be described with an **LL(1)** grammar. In fact, the language has no **LL(*k*)** grammar, for finite *k*.

ACTION & GOTO Tables for Waite's Example



	EOF	()	<u>a</u>	}
s_0		s 4		s 5	
s_1	acc				
s_2	r 2				
s_3	r 3				
s_4		s 8		s 9	
s_5	r 5				
s_6			s 10		
s_7					s 11
s_8		s 8		s 9	
s_9			r 5		r 7
s_{10}	r 4				
s_{11}	r 6				
s_{12}			s 14		
s_{13}					s 15
s_{14}			r 4		
s_{15}					r 6

	S	A	B
s_0	1	2	3
s_1			
s_2			
s_3			
s_4		6	7
s_5			
s_6			
s_7			
s_8		12	13
s_9			
s_{10}			
s_{11}			
s_{12}			
s_{13}			
s_{14}			
s_{15}			

0	Start	→	A
1			B
2	A	→	(A)
3			<u>a</u>
4	B	→	(B }
5			<u>a</u>

LR(k) versus LL(k)



Other Non-LL Grammars

0	$B \rightarrow R$
1	$\mid (B)$
2	$R \rightarrow E = E$
3	$E \rightarrow \underline{a}$
4	$\mid \underline{b}$
5	$\mid (E + E)$

Example from D.E Knuth, "Top-Down Syntactic Analysis," *Acta Informatica*, 1:2 (1971), pages 79-110

0	$S \rightarrow \underline{a} A \underline{b}$
1	$\mid \underline{c}$
2	$A \rightarrow \underline{b} S$
3	$\mid B \underline{b}$
4	$B \rightarrow \underline{a} A$
5	$\mid \underline{c}$

Example from Lewis, Rosenkrantz, & Stearns book, "Compiler Design Theory," (1976), Figure 13.1

This grammar is actually LR(0)

LR(k) versus LL(k)



Finding the next step in a derivation

LR(k) \Rightarrow Each reduction in the parse is detectable with

- \rightarrow the complete left context,
- \rightarrow the reducible phrase, itself, and
- \rightarrow the k terminal symbols to its right

LL(k) \Rightarrow Parser must select the expansion based on

- \rightarrow The complete left context
- \rightarrow The next k terminals

Thus, LR(k) examines more context



*“... in practice, **programming languages** do not actually seem to fall in the gap between LL(1) languages and deterministic languages”*

*J.J. Horning, “LR Grammars and Analysers”,
in *Compiler Construction, An Advanced Course*, Springer-Verlag, 1976*

Left Recursion versus Right Recursion



- Right recursion
 - Required for termination in top-down parsers
 - Uses (on average) more stack space
 - Naïve right recursion produces right-associativity
- Left recursion
 - Works fine in bottom-up parsers
 - Limits required stack space
 - Naïve left recursion produces left-associativity
- Rule of thumb
 - Left recursion for bottom-up parsers
 - Right recursion for top-down parsers



Left Recursion versus Right Recursion



A real example, from the lab 1 ILOC simulator's front end

The simulator was built by two of my successful Ph.D.s

- It is actually a more complex piece of software than you might guess
- The front end is an LR(1) parser, generated by Bison
- The grammar contained the following productions:

```
instruction_list  : instruction  
                  | label_def instruction  
                  | instruction instruction_list  
                  | label_def instruction instruction_list
```

When my colleague first ran the timing blocks through the simulator, it exploded with the error message “memory exhausted”.

⇒ What happened?

Left Recursion versus Right Recursion



A real example, from the lab 1 simulator's front end

```
instruction_list  :  instruction  
                   |  label_def instruction  
                   |  instruction instruction_list  
                   |  label_def instruction instruction_list
```

right recursion

- The parse stack overflowed as it tried to instantiate the *instruction_list*

Left Recursion versus Right Recursion



A real example, from the lab 1 simulator's front end

```
instruction_list  :  instruction  
                  |  label_def instruction  
                  |  instruction instruction_list  
                  |  label_def instruction instruction_list
```

right recursion

- The parse stack overflowed as it tried to instantiate the *instruction_list*
- The fix was easy

```
instruction_list  :  instruction  
                  |  label_def instruction  
                  |  instruction_list instruction  
                  |  instruction_list label_def instruction
```

left recursion

- This grammar has (small) bounded stack space & (thus) scales well

Error Detection and Recovery



Error Detection

- Recursive descent
 - Parser takes the last else clause in a routine
 - Compiler writer can code almost any arbitrary action
- Table-driven **LL(1)**
 - In state s_i facing word x , entry is an error
 - Report the error, valid entries in row for s_i encode possibilities
- Table-driven **LR(1)**
 - In state s_i facing word x , entry is an error
 - Report the error, shift states in row encode possibilities
 - Can precompute better messages from **LR(1)** items

Error Detection and Recovery



Error Recovery

- Table-driven **LL(1)**
 - Treat as missing token, e.g. ' $_$ ' \Rightarrow expand by desired symbol
 - Treat as extra token, e.g., ' $x - + y$ ', \Rightarrow pop stack and move ahead
- Table-driven **LR(1)**
 - Treat as missing token, e.g. ' $_$ ', \Rightarrow shift the token
 - Treat as extra token, e.g., ' $x - + y$ ', \Rightarrow don't shift the token

Can pre-compute sets of states
with appropriate entries...

Error Detection and Recovery



One common strategy is “hard token” recovery

Skip ahead in input until we find some “hard” token, e.g. ‘;’

- ‘;’ separates statements, makes a logical break in the parse
- Resynchronize state, stack, and input to point after hard token
 - LL(1): pop stack until we find a row with entry for ‘;’
 - LR(1): pop stack until we find a state with a reduction on ‘;’
- Does not correct the input, rather it allows parse to proceed

```
NT ← pop()
repeat until Table[NT,‘;’] ≠ error
    NT ← pop()
token ← NextToken()
repeat until token = ‘;’
    token ← NextToken()
```


Resynchronizing an LL(1) parser

```
repeat until token = ‘;’
    shift token
    shift  $s_e$ 
    token ← NextToken()
reduce by error production
// pops all that state off stack
```

Resynchronizing an LR(1) parser



Hierarchy of Context-Free Grammars



- Operator precedence includes some ambiguous grammars
- Note sub-categories of **LR(1)**
- **LL(1)** is a subset of **SLR(1)**

The inclusion hierarchy for context-free grammars