

Revolutionary Changes in Acute Lymphoblastic Leukaemia Classification: The Impact of Deep Learning Convolutional Neural Networks

Retinderdeep Singh
Chitkara University Institute of
Engineering and Technology,
Chitkara
University, Punjab, India
retinderdeepsingh@chitkara.edu.
in

Neha Sharma
Chitkara University Institute of
Engineering and Technology,
Chitkara
University, Punjab, India
sharma.neha@chitkara.e
du.in

Priyanshi Aggarwal
Computer Science &
Engineering
Graphic Era Hill University,
Dehradun, Uttarakhand, India,
248002
priyanshiaggarwal98@
gmail.com

Mukesh Singh
Computer Science & Engineering
Graphic Era Deemed to be University,
Dehradun, Uttarakhand, India, 248002
mukeshsingh.cse@geu.ac.in

Kanegonda Ravi Chythanya
School of Computer Science &
Artificial Intelligence, SR University,
Warangal
chythu536@gmail.com

Abstract— Blood cancers categorised as acute lymphoblastic leukaemia (ALL) pose a substantial threat to global public health and require extremely nuanced diagnostic techniques. This research study provides a substantial advancement in the field of blood cancer diagnosis through the development and implementation of an innovative Convolutional Neural Network model. On the basis of a large dataset of Blood Cells Cancer (ALL), which encompasses a variety of cellular morphologies associated with ALL, this model is constructed. The model under consideration is trained using deep learning methodologies and this dataset. The primary aim of this research endeavour is to improve the accuracy and reliability of blood cancer detection, a critical factor in facilitating timely and effective medical intervention. A fine-tuned CNN model is capable of identifying minute irregularities and patterns that may be detected in images of blood cells. This can assist the CNN model in distinguishing between benign and malignant cells accurately. To achieve higher degrees of specificity and sensitivity, the model's parameters are refined during the training process. The proposed CNN model exhibits an exceptional degree of performance, achieving an astounding accuracy rate of 96.92% after the training phase concludes. Blood cancer is accurately diagnosed with a substantial degree of precision by the model, which is substantial evidence of its extraordinary accuracy and underscores its potential as a critical diagnostic tool in clinical settings.

Keywords—CNN, Acute Lymphoblastic Leukaemia, Blood Cancer, Deep Learning.

I. INTRODUCTION

The field of global healthcare is facing a significant obstacle in the shape of blood malignancies, particularly acute lymphoblastic leukaemia (ALL), which has to be addressed. Considering the intricate biological manifestations and the possibility of fast advancement that are linked with the condition, an early and correct diagnosis plays an incredibly essential role in facilitating the development of efficient treatment strategies and enhancing the results for patients. With regard to this particular context, the use of cutting-edge computational methods, namely

Convolutional Neural Networks (CNNs), has presented one-of-a-kind opportunities for improving the precision and efficiency of blood cancer detection. The development of artificial intelligence has made it feasible for these chances to become available with greater ease. Using the potential of an innovative convolutional neural network (CNN) architecture, the authors of this paper conduct a comprehensive examination into the detection of haematological malignancies, namely acute lymphoblastic leukaemia (ALL). The pressing need for trustworthy and speedy diagnostic tools that have the potential to improve upon the methods that are now used in clinical settings is a major factor that contributes significantly to the importance of this endeavour. The manual examination of blood cell samples is often used in conventional diagnostic procedures. This approach is prone to subjectivity and the chance that a person may make an error. The use of artificial intelligence and deep learning models has the potential to address the problems that have been outlined above by offering a data-centric technique that is able to analyse huge datasets with an unprecedented level of accuracy and efficiency [1].

This investigation is based on the development and improvement of a CNN model via the use of the Blood Cells Cancer dataset. This model served as the basis for this research. The dataset has a comprehensive representation of the alterations associated with Acute Lymphoblastic Leukaemia (ALL), since it contains a broad variety of cellular morphologies. The suggested model aims to obtain a better degree of accuracy in differentiating between healthy and cancerous blood cells by making use of the inherent capacity of Convolutional Neural Networks (CNNs) to recognise complex patterns inside images. This skill allows CNNs to analyse and classify images. The need to improve existing diagnostic techniques and the possibility of having an effect on patient outcomes by facilitating rapid and accurate diagnosis is the impetus behind the decision to carry out the inquiry that is the subject of this paper. The research project includes the creation, teaching, and evaluation of the CNN model, with the primary goal of achieving a remarkable degree of accuracy in the diagnosis of blood cancer [2].

This study aims to make a scholarly contribution not only to the field of blood cancer diagnosis but also to the wider discussion on the incorporation of Artificial Intelligence (AI) in the healthcare industry. This will be accomplished as we investigate the complexities of the suggested Convolutional Neural Network (CNN) model and its implementation on the Acute Lymphoblastic Leukaemia dataset. Specifically, this study will focus on the Acute Lymphoblastic Leukaemia (ALL) dataset. The purpose of this study is to investigate the drawbacks of traditional diagnostic procedures and to suggest replacements that are more adapted to the rapidly evolving area of medical technology. This will hopefully result in improved accuracy and reliability of diagnostic procedures [3].

II. LITERATURE REVIEW

This section briefly reviews prior research on detecting Acute Lymphoblastic Leukaemia (ALL) using deep learning. This part also includes a comparison of the prior investigations.

The research by R. Khandekar et al. [4] presented a novel approach using artificial intelligence (AI) to identify cases of Acute Lymphoblastic Leukaemia (ALL) via the analysis of microscopic blood smear pictures. The used method in the system for both detection and classification is the You Only Look Once (YOLOv4) algorithm. The system underwent training using the ALL_IDB1 and C_NMC_2019 datasets, achieving mean average precision scores of 96.06% and 90.77% respectively. This supplementary tool has the potential to be used throughout the pre-screening process for the diagnosis of acute lymphoblastic leukaemia (ALL). The study by M. M. A. Eid et al. [5] introduced a novel sensor based on photonic crystal fibres (PCFs) for the effective detection of blood and skin cancer cells. The model demonstrates best performance at a frequency of 2.0 THz by using an asymmetrical configuration of rectangular apertures and Zeonex fibre. It exhibits sensitivities over 96% for the detection of blood and skin cancer cells. The practicality and convenience of manufacture of the sensor are emphasised by the low material and confinement losses. The study by S. Shafique et al. [6] presented a novel automated methodology for the detection of acute lymphoblastic leukaemia via the examination of microscopic blood images. With the ALL-IDB-1 dataset, the approach achieved a complete accuracy of 93.7%, with a sensitivity of 92% and a specificity of 91%. Additionally, the method demonstrated a specificity of 91%.

The research carried out by C. An automated method for the detection of acute lymphoblastic leukaemia (ALL) in microscopic cell images was described by Mondal et al. [7]. This method made use of deep convolutional neural networks (CNNs) to accomplish this task. With kappa values acting as weights, the weighted ensemble model was able to attain a weighted F1-score of 88.6%, a balanced accuracy of 86.2%, and an area under the curve (AUC) of 0.941, according to the findings that were obtained from the first test set. The suggested model exhibits a concentrated learnt area, surpassing ensemble models such as Xception, VGG-16, DenseNet-121, MobileNet, and InceptionResNet-V2. This methodology has the potential to be used in several additional medical diagnostic contexts. The study by S. Praveena and S. P. Singh [8] presented a novel methodology for the identification and assessment of acute lymphoblastic leukaemia (ALL) via the analysis of blood smear pictures.

The approach employs a Deep CNN that has been trained using the Grey Wolf-based Jaya Optimisation Algorithm (GreyJOA). The suggested methodology utilises sparse fuzzy C-Means clustering, Local Directional Patterns, and features based on colour histograms. The approach attained a peak level of accuracy, sensitivity, and specificity at 0.9350, 0.9528, and 0.9389, correspondingly. The study by K. S. Ananthu et al. [9] comparative comparison of transfer learning models used in the identification of acute lymphocytic leukaemia from blood smear cells. The results provide notable accuracy rates of 87.97%, 88.92%, 88.92%, 95.28%, and 97.88% for the relevant models.

The study by G. Vieira and M. Eduardo Valle [10] employed hypercomplex-valued convolutional neural networks (HvCNNs) for the purpose of lymphocyte classification in blood smear pictures, hence assisting in the identification of acute lymphoblastic leukaemia (ALL). The performance of HvCNNs is superior to that of models that use real-valued representations. HvCNNs demonstrate the highest degree of accuracy when Clifford algebras are used for the processing of images that are stored in the HSV colour space. The mean accuracy rate of the HvCNN model was 96.6% across the board. Deep convolutional neural networks were used in the research conducted by S. Shafique and S. Tehsin [11] in order to detect and classify acute lymphoblastic leukaemia into four unique subtypes. These subtypes were referred to as L1, L2, L3, and Normal among others. Training was performed on the network by using a pre-trained AlexNet model, and data augmentation techniques were used in order to address the problem of overfitting. A sensitivity rate of 96.74%, a specificity rate of 99.03%, and an accuracy rate of 96.06% were achieved by the technique when it was used to the classification of subtypes. The method displayed a remarkable degree of accuracy without the need of microscopic image segmentation, which is in contrast to the methodologies that are often used.

III. PROPOSED METHODOLOGY

An extensive and thorough description of the methods used throughout the investigation is provided in this section. We provide the dataset that our model was trained on and describe in detail the steps used to prepare it for analysis via preprocessing. The proposed research method is shown in Fig. 1 as a simplified flow diagram. An overview of the research's sequential methods and processes is what the visual guide is trying to accomplish. It provides a thorough synopsis of the experimental design and the data processing procedure.




Fig.1 Proposed methodology

A. Dataset

Acute lymphoblastic leukaemia (ALL) is a prevalent malignancy that demands precise diagnosis because of the invasive, expensive, and time-consuming character of the disease. Better patient prognosis and results are possible benefits of research into more efficient screening methods. There are a number of non-invasive methods for differentiating between cancerous and non-cancerous conditions; one of them is the analysis and interpretation of peripheral blood smear (PBS) images. Specifically, this research makes use of data collected from Taleqani Hospital's bone marrow unit in Tehran, Iran. For this dataset, the investigators culled 3242 pictures of peripheral blood smears from 89 people who were thought to be cases. The material for this is taken from the reference [12]. Figure 2 shows that the dataset divides malignant lymphoblasts into three different subgroups: Early Pre-B, Pre-B, and Pro-B Acute Lymphoblastic Leukaemia. The dataset is much more reliable because of the usage of a Zeiss camera and a specialised flow cytometry device. As a result of a lack of specificity in symptoms and indications, manual interpretation of PBS photos by laboratory personnel might induce mistakes. In light of this, it is clear that deep learning models and other cutting-edge computational approaches are required to enhance the diagnostic procedure. This would provide a methodical and unbiased examination of PBS pictures, reducing the probability of incorrect diagnosis.




Fig.2. Dataset Distribution

B. Preprocessing and data augmentation

Within the domain of machine learning, the preprocessing phase assumes a pivotal role since it involves the conversion of raw data into a structure that is conducive to the training of models. The first phase of preparation provides the fundamental basis for the precise and effective acquisition of patterns within the dataset. Within the domain of computer vision tasks, such as picture classification, the preprocessing of data encompasses a sequence of actions specifically designed to guarantee the utmost efficiency of the model [13].

Firstly, the dataset undergoes a deliberate process of splitting, which is a key practice in the field of ML. This process aims to differentiate between the training set and the validation set. In this particular case, the dataset is partitioned into a ratio of 9:1, with 90% of the samples being allocated to the training set and the remaining 10% being given to the validation set. The selection of this ratio is often made in order to achieve a trade-off between the availability of an adequate amount of data for training purposes and the retention of a substantial part for the purpose of verifying the performance of the model on samples that have not been previously seen. The use of the

random state parameter, specifically assigned a value of 88, guarantees the repeatability of results. This facilitates the constant production of identical data splits when the programmed is executed many times. Ensuring consistency in outcomes and enabling seamless comparison across several trials is of utmost importance. After the division, the subsequent procedure entails the adjustment of pictures to conform to a uniformed dimension. The decision to use a target size of 224x224 pixels is consistent with prevailing conventions in deep learning models that rely on picture data [14]. In such models, a square input shape is often favored due to its simplicity and compatibility with widely used architectures. The act of resizing guarantees consistency in the input data, enabling the model to handle pictures of uniform proportions throughout the training and assessment processes. The aforementioned approach not only optimizes the computational procedure but also improves the model's capacity to generalize across heterogeneous datasets. Following this, the dataset is subjected to a random shuffling process, which introduces an element of unpredictability in the arrangement of samples. The act of shuffling the data helps to reduce the potential for the model to learn patterns that are particular to the arrangement of the data. In the absence of shuffling, the model runs the risk of unintentionally acquiring associations linked to the sequence in which samples were introduced throughout the training process. This might possibly undermine its capacity to effectively apply learned knowledge to new, unfamiliar data. The technique of random shuffling disrupts any underlying order within the dataset, hence facilitating a learning process that is more resilient and impartial [15].

C. Model

The use of a 14-layer Convolutional Neural Network model is a deliberate selection for the purpose of blood cancer diagnosis, owing to its inherent capacity to autonomously acquire and extract hierarchical features from intricate datasets (fig.3.). The design of the model integrates convolutional and separable convolutional layers, which serve as hierarchical feature extractors. This enables the model to effectively identify subtle patterns and anomalies present in blood cell pictures [16]. Convolutional neural networks (CNNs) are renowned for their ability to extract hierarchical features, making them indispensable in the field of blood cancer diagnosis. This is particularly important since even little alterations in cell shape may serve as indicators of illness. The positive characteristics of the model in medical image analysis include spatial invariance and flexibility, which are particularly beneficial for analysing blood cell pictures that may display alterations in the size, orientation, and location of malignant cells. The transfer learning capability of the model has considerable promise in the field of medical picture analysis, particularly in scenarios where the availability of annotated datasets is limited. Pre-existing convolutional neural network (CNN) models have shown their efficacy as initial frameworks for medical imaging tasks, therefore augmenting their capacity to generalise to the complexities inherent in blood cell pictures, without necessitating lengthy training particular to the job at hand [17]. Batch normalisation and stability are crucial factors in the training process of a model, as they

effectively mitigate the issue of internal covariate shift and promote efficient training. Fully linked layers play a crucial role in enabling the extraction of high-level features and subsequent classification, hence establishing a solid framework for categorising blood cell pictures into unique and separate groups. Dropout layers are strategically included into the model's design to reduce the problem of overfitting, hence improving the model's capacity to effectively generalise on unfamiliar and unexplored data. [18].




Fig.3. Model Architecture

IV. RESULTS

This study centers on assessing the performance and efficacy of a deep learning model. The paper thoroughly examines the process involved in training and evaluating the model.

The CNN model was subjected to a rigorous training protocol, consisting of 30 epochs, where each epoch corresponds to a full iteration over the whole dataset. The decision to choose a certain number of epochs is a conscious one, aimed at striking a delicate equilibrium between enabling the model to acquire complex patterns inherent in the training data and minimising the potential for overfitting. The learning rate, which is established at a value of 0.0001, assumes a pivotal function in guiding the optimisation procedure during the training phase. The selection of a low learning rate is motivated by the desire to achieve gradual convergence of the model, hence mitigating the risks of overshooting and oscillation in the optimisation landscape. The use of a cautious approach is especially relevant in the arena of medical image analysis, as the dataset often presents complexities that need a more refined and subtle convergence. The careful training procedure yields outcomes that are reflected in the attained accuracies. These accuracies serve as measures that indicate the model's capability to accurately categories both the training and validation datasets. The model's capacity to learn from the training data and comprehend the intricate connections within the blood cell pictures is shown by the remarkable training accuracy of 94.55% (Fig.4.). The observed high training accuracy suggests that the model has effectively adjusted to the many details and complexities included in the training dataset, demonstrating its ability to distinguish between benign and malignant cells. Of equal significance is the validation accuracy, which reached a peak of 92.81% after the completion of 30 epochs. The aforementioned statistic serves as a crucial indication of the model's skill to generalise its performance on data that it has not been previously exposed to. The validation dataset serves as a means of evaluating the model's ability to apply the acquired information from training to unfamiliar circumstances. The model's validation accuracy of 92.81% (Fig.5.) indicates its proficiency in both learning from the training data and exhibiting strong performance when presented with novel blood cell pictures. The achieved degree of validation accuracy has significant promise within the field of medical image analysis, since the precise classification of unseen instances is crucial for practical implementation in real-world scenarios. The observed equilibrium between the accuracies of the training and validation sets also serves as a positive indication. Differences seen between these two measures may indicate the possibility of overfitting, a condition in which the model gets too specialised to the unique characteristics of the training data and has difficulties in generalising to novel instances. The model's training accuracy of 94.55% and validation accuracy of 92.81% demonstrate a notable alignment, indicating that the model has successfully balanced the task of learning from the training set while also being able to generalise well to new cases. The presence of this harmony indicates a positive outlook for the model's potential for being applied to real-world situations, where the likelihood of seeing a variety of

blood cell pictures that have not been seen before is unavoidable [19]. Following the training phase, the CNN model was subjected to stringent testing using a specific test dataset. There, it achieved an outstanding accuracy of 97%, demonstrating excellent performance as shown in table I confirming its resilience and effectiveness in Acute Lymphoblastic Leukaemia classification.




Fig.4. loss graphs.




Fig.5. Accuracy graphs.

Table I. Performance Matrix

Classes	Precision (%)	Recall (%)	F1-Score (%)	Accuracy (%)
Benign	98	93	95	97
Malignant Pre-B	98	100	99	
Malignant Pro-B	100	100	100	
Malignant early Pre-B	85	93	89	

A confusion matrix is a crucial tool in machine learning and classification tasks, providing a detailed breakdown of a model's predictions and their comparison to actual

outcomes. It helps evaluate model performance, class imbalance, error analysis, threshold adjustment, model selection and comparison, medical or anomaly detection, business strategy adjustment, and hyperparameter optimization. It aids stakeholders in making informed decisions, optimizing models, and assessing their suitability for real-world applications [20]. The confusion matrix is shown in Fig.6.




Fig.6. Confusion Matrix

V. CONCLUSION

In this study, a 14-layer Convolutional Neural Network model that is specifically designed for the detection of blood cancer was presented. This model was shown to be extremely successful. After 30 epochs of painstaking training at a learning rate of 0.0001, the model displayed excellent performance. It achieved a training accuracy of 94.55% and a validation accuracy of 92.81%. Both of these percentages are much higher than chance. The fact that the model is able to acquire detailed patterns while yet preserving its capacity to generalise to new, unexplored situations is reflected in the model's ability to achieve a harmonic alignment between the accuracy of its training and its validation. The model showed a remarkable accuracy of 97% throughout rigorous testing on a dedicated dataset, which affirms its resilience when applied to real-world scenarios. The effectiveness of the model in distinguishing between benign and malignant blood cells may be attributed, in part, to the use of convolutional and separable convolutional layers, as well as batch normalisation, dropout mechanisms, and careful hyperparameter tuning. This study highlights the potential of advanced CNN architectures in increasing diagnostic capabilities in the area of blood cancer finding and adds to the expanding body of research that utilises DL for medical image analysis. The encouraging findings that have been provided here open the way for future development and implementation of such models in clinical settings. This will provide medical professionals with a helpful resource that will aid them in their efforts to identify cancer accurately and in a timely manner.

REFERENCES

- [1] S. M. Sasubilli, A. Kumar, and V. Dutt, "Machine learning implementation on medical domain to identify disease insights using TMS," in 2020 International Conference on Advances in Computing and Communication Engineering (ICACCE), 2020.
- [2] A. Kumar, J. M. Chatterjee, and V. G. Díaz, "A novel hybrid approach of SVM combined with NLP and probabilistic neural network for email phishing," *Int. J. Electr. Comput. Eng. (IJECE)*, vol. 10, no. 1, p. 486, 2020.
- [3] K. Guleria, S. Sharma, S. Kumar, and S. Tiwari, "Early prediction of hypothyroidism and multiclass classification using predictive machine learning and deep learning," *Measur. Sens.*, vol. 24, no. 100482, p. 100482, 2022.
- [4] R. Khandekar, P. Shastry, S. Jaishankar, O. Faust, and N. Sampathila, "Automated blast cell detection for Acute Lymphoblastic Leukemia diagnosis," *Biomed. Signal Process. Control*, vol. 68, no. 102690, p. 102690, 2021.
- [5] M. M. A. Eid, A. N. Z. Rashed, A. A.-M. Bulbul, and E. Podder, "Mono-rectangular core photonic crystal fiber (MRC-PCF) for skin and blood cancer detection," *Plasmonics*, vol. 16, no. 3, pp. 717–727, 2021.
- [6] S. Shafique, S. Tehsin, S. Anas, and F. Masud, "Computer-assisted Acute Lymphoblastic Leukemia detection and diagnosis," in 2019 2nd International Conference on Communication, Computing and Digital systems (C-CODE), 2019.
- [7] C. Mondal et al., "Acute Lymphoblastic Leukemia detection from microscopic images using weighted ensemble of Convolutional Neural Networks," 2021.
- [8] S. Praveena and S. P. Singh, "Sparse-FCM and Deep Convolutional Neural Network for the segmentation and classification of acute lymphoblastic leukaemia," *Biomed. Tech. (Berl.)*, vol. 65, no. 6, pp. 759–773, 2020.
- [9] K. S. Ananthu, P. Krishna Prasad, S. Nagarajan, and E. R. Vimina, "Acute lymphoblastic leukemia detection using transfer learning techniques," in *Intelligent Sustainable Systems*, Singapore: Springer Singapore, 2022, pp. 679–692.
- [10] G. Vieira and M. Eduardo Valle, "Acute lymphoblastic leukemia detection using hypercomplex-valued convolutional neural networks," in 2022 International Joint Conference on Neural Networks (IJCNN), 2022.
- [11] S. Shafique and S. Tehsin, "Acute lymphoblastic leukemia detection and classification of its subtypes using pretrained deep convolutional neural networks," *Technol. Cancer Res. Treat.*, vol. 17, p. 153303381880278, 2018.
- [12] M. Amir Eshraghi, "Blood Cells Cancer (ALL) dataset." 30-Oct-2021.
- [13] D. Koundal, S. Gupta, and S. Singh, "Computer aided thyroid nodule detection system using medical ultrasound images," *Biomed. Signal Process. Control*, vol. 40, pp. 117–130, 2018.
- [14] S. Rani, S. H. Ahmed, and R. Rastogi, "Dynamic clustering approach based on wireless sensor networks genetic algorithm for IoT applications," *Wirel. Netw.*, vol. 26, no. 4, pp. 2307–2316, 2020.
- [15] N. K. Trivedi et al., "Early detection and classification of tomato leaf disease using high-performance deep neural network," *Sensors (Basel)*, vol. 21, no. 23, p. 7987, 2021.
- [16] N. Khattar, J. Sidhu, and J. Singh, "Toward energy-efficient cloud computing: a survey of dynamic power management and heuristics-based optimization techniques," *J. Supercomput.*, vol. 75, no. 8, pp. 4750–4810, 2019.
- [17] P. K. Shukla, J. K. Sandhu, A. Ahirwar, D. Ghai, P. Maheshwary, and P. K. Shukla, "Multiobjective genetic algorithm and convolutional neural network based COVID-19 identification in chest X-ray images," *Math. Probl. Eng.*, vol. 2021, pp. 1–9, 2021.
- [18] K. Sood, B. Kaur, and S. Grima, "Revamping Indian non-life insurance industry with a trusted network: Blockchain technology," in *Big Data: A Game Changer for Insurance Industry*, Emerald Publishing Limited, 2022, pp. 213–228.
- [19] V. Anand, S. Gupta, D. Koundal, and K. Singh, "Fusion of U-Net and CNN model for segmentation and classification of skin lesion from dermoscopy images," *Expert Syst. Appl.*, vol. 213, no. 119230, p. 119230, 2023.
- [20] M. Pundir and J. K. Sandhu, "A systematic review of quality of service in wireless sensor networks using machine learning: Recent trend and future vision," *J. Netw. Comput. Appl.*, vol. 188, no. 103084, p. 103084, 2021.