

COMPSCI 250: Introduction to Computation

Lecture #30: Properties of the Regular Languages
David Mix Barrington and Ghazaleh Parvini
13 November 2023

Properties of Regular Languages

- Induction on Regular Expressions
- The One's Complement Operation
- Proving Our Function Correct
- The Pseudo-Java RegExp Class
- The One's Complement Method
- Reversal of Languages
- Testing for the Empty Language

Induction on Regular Expressions

- Because the regular languages have an inductive definition, we can prove propositions for all of them by induction.
- Let $P(R)$ be a predicate with one free variable of type “regular expression”. We can prove that $P(R)$ holds for any regular expression R by proving *two* base cases and *three* inductive cases.

Induction on Expressions

- These five cases are:
- $P(\emptyset)$,
- $P(a)$ for all $a \in \Sigma$,
- $(P(R) \wedge P(S)) \rightarrow P(R + S)$,
- $(P(R) \wedge P(S)) \rightarrow P(RS)$, and
- $P(R) \rightarrow P(R^*)$

Induction on Expressions

- For example, we will define two operations on languages and show that the regular languages are **closed** under these operations.
- That is, if R is a regular expression, the result of applying the operation to $L(R)$ gives us another regular language. We'll demonstrate an algorithm to compute this expression.
- We'll also show that we can test properties of R , such as whether $L(R) = \emptyset$.

One's Complement

- The **one's complement** of a binary string w , denoted $oc(w)$, is the string of the same length obtained by replacing all 0's with 1's and all 1's with 0's. For example, $oc(011001) = 100110$.
- We can define $oc(w)$ inductively, of course:
- $oc(\lambda) = \lambda$,
- $oc(w0) = oc(w)1$, and
- $oc(w1) = oc(w)0$.

One's Complement

- The one's complement of a *language* X is the language $\{oc(w) : w \in X\}$ -- the set of strings whose one's complements are in X .
- We will prove that for any regular expression R , the language $oc(L(R))$ is a regular language.
- It's not hard to see how to convert R into a regular expression for $oc(L(R))$. We just replace 0's with 1's and 1's with 0's in R itself.

One's Complement

- Formally this is a recursive algorithm:
- $oc(\emptyset) = \emptyset,$
- $oc(0) = 1,$
- $oc(1) = 0,$
- $oc(R + S) = oc(R) + oc(S),$
- $oc(RS) = oc(R)oc(S),$ and
- $oc(R^*) = oc(R)^*.$

Proving Our Function Correct

- We'll use induction to prove that this function f , from regular expressions to regular expressions, satisfies the property “ $L(f(R)) = \text{oc}(L(R))$ ”.
We write this property as “ $P(R)$ ”.
- $P(\emptyset)$ says that $L(\emptyset) = \text{oc}(L(\emptyset))$, which is true because $\{\text{oc}(w) : w \in \emptyset\} = \emptyset$.
- $P(0)$ says “ $L(1) = \text{oc}(L(0))$ ” and $P(1)$ says “ $L(0) = \text{oc}(L(1))$ ”. Both are true.

Proving Our Function Correct

- Assume that $P(R)$ and $P(S)$ are true, so that $L(f(R)) = \text{oc}(L(R))$ and $L(f(S)) = \text{oc}(L(S))$.
- We must show
that $L(f(R)) \cup L(f(S)) = \text{oc}(L(R+S))$,
that $L(f(R))L(f(S)) = \text{oc}(L(RS))$,
and that $L(f(R))^* = \text{oc}(L(R^*))$.
- Each of these three facts follow pretty directly from the definitions -- details are in the textbook.

Clicker Question #1

- To formally prove the statement “ $\text{oc}(S^*) = \text{oc}(S)^*$ ”, I am trying to prove that “ $\text{oc}(S^*)$ is a subset of $\text{oc}(S)^*$ ”. Which *would* be a good inductive step of my proof?
- (a) $((u \in \text{oc}(S)^*) \wedge (v \in \text{oc}(S)^*)) \rightarrow uv \in \text{oc}(S)^*$
- (b) $((u \in S^*) \wedge (v \in S)) \rightarrow uv \in \text{oc}(S)^*$
- (c) $((u \in \text{oc}(S^*)) \wedge (v \in \text{oc}(S))) \rightarrow uv \in \text{oc}(S^*)$
- (d) $((u \in \text{oc}(S^*)) \wedge (v \in \text{oc}(S))) \rightarrow uv \in \text{oc}(S)^*$

Not the Answer

Clicker Answer #1

- To formally prove the statement “ $\text{oc}(S^*) = \text{oc}(S)^*$ ”, I am trying to prove that “ $\text{oc}(S^*)$ is a subset of $\text{oc}(S)^*$ ”. Which *would* be a good inductive step of my proof?
- (a) $((u \in \text{oc}(S)^*) \wedge (v \in \text{oc}(S)^*)) \rightarrow uv \in \text{oc}(S)^*$
- (b) $((u \in S^*) \wedge (v \in S)) \rightarrow uv \in \text{oc}(S)^*$
- (c) $((u \in \text{oc}(S^*)) \wedge (v \in \text{oc}(S))) \rightarrow uv \in \text{oc}(S^*)$
- (d) $((u \in \text{oc}(S^*)) \wedge (v \in \text{oc}(S))) \rightarrow uv \in \text{oc}(S)^*$

More Answer #1

- Goal is to prove “ $\text{oc}(S^*) \subseteq \text{oc}(S)^*$ ”.
- (a) $((u \in \text{oc}(S)^*) \wedge (v \in \text{oc}(S)^*) \rightarrow uv \in \text{oc}(S)^*$
This is true, but says nothing about $\text{oc}(S^*)$
- (b) $((u \in S^*) \wedge (v \in S)) \rightarrow uv \in \text{oc}(S)^*$ no
reason to think that this is true
- (c) $((u \in \text{oc}(S^*)) \wedge (v \in \text{oc}(S))) \rightarrow uv \in \text{oc}(S^*)$
this gets the wrong conclusion for our goal
- (d) $((u \in \text{oc}(S^*)) \wedge (v \in \text{oc}(S))) \rightarrow uv \in \text{oc}(S)^*$

A Java RegExp Class

- Just as boolean or arithmetic expressions can be implemented by tree structures, we can define a real Java class RegExp whose objects are regular expressions.
- We will need methods to **parse** these objects, which means that they must determine their structure and component parts.

A Java RegExp Class

- ```
public class RegExp {
 public RegExp();
 // returns RegExp equal to emptyset
 public RegExp(String w);
 // returns RegExp denoted by w
 public boolean isEmptySet();
 // is it the empty set?
 public boolean isZero();
 // is it "0"?
 public boolean isOne();
 // is it "1"?
 public boolean isUnion();
 // is it "S + T"?
```



# A Java RegExp Class

```
public boolean isCat();
 // is it "ST"?
public boolean isStar();
 // is it "S*"?
public RegExp firstArg();
public RegExp secondArg();
public static RegExp
 plus (RegExp r, RegExp s);
public static RegExp
 cat (RegExp r, RegExp s);
public static RegExp
 star (RegExp r);
```

# Computing One's Complement

- This definition lets us write code for the one's complement algorithm. The next slide has a recursive method that creates a RegExp object with the same structure as the method's argument, but with 0's and 1's switched.
- We've essentially proved this method correct by our usual method for recursive code -- we prove the base cases correct and then prove the rest correct assuming that the recursive calls are correct.

# Computing One's Complement

```
public static RegExp f (RegExp s) {
 if (s.isEmptySet())
 return new RegExp();
 if (s.isZero())
 return new RegExp("1");
 if (s.isOne())
 return new RegExp("0");
 RegExp oc1 = f (s.firstArg());
 if (s.isStar()) return star(oc1);
 RegExp oc2 = f (s.secondArg());
 if (s.isPlus())
 return plus (oc1, oc2);
 else return cat (oc1, oc2);
 // s.isCat() must be true here
```

# Reversal of Languages

- A similar function from languages to languages is reversal, based on the familiar reversal operation on strings:  
for any language  $X$ ,  $X^R = \{w^R: w \in X\}$ .
- The regular languages are closed under reversal -- we can easily see that  $\emptyset^R = \emptyset$  and that  $a^R = a$  for any letter  $a$ . The string rule  $(xy)^R = y^R x^R$  yields a language rule  $(TU)^R = U^R T^R$ , and we have  $(T+U)^R = T^R + U^R$  and  $(T^*)^R = (T^R)^*$ .

# Computing Reversal

```
public static RegExp rev (RegExp s) {
 if (s.isEmptySet())
 return new RegExp();
 if (s.isZero())
 return new RegExp("0");
 if (s.isOne())
 return new RegExp("1");
 RegExp rev1 = rev (s.firstArg());
 if (s.isStar()) return star (rev1);
 RegExp rev2 = rev (s.secondArg());
 if (s.isPlus())
 return plus (rev1, rev2);
 else return cat (rev2, rev1);}
 // s.isCat() is true in this case
```

# Clicker Question #2

- For the case where `s` is a union, `rev` contains the line `return plus (rev1, rev2);`  
What would happen if we changed this line to `return plus (rev2, rev1);`?
- (a) `rev` would return a different expression, but equivalent to the one it returned before
- (b) `rev` would become the identity function
- (c) `rev` would return exactly the same expression
- (d) `rev` would return something not equivalent to the correct reversal, and also not the identity

Not the Answer

# Clicker Question #2

- For the case where  $s$  is a union,  $rev$  contains the line `return plus (rev1, rev2);`  
What would happen if we changed this line to `return plus (rev2, rev1);`?
- *(a)  $rev$  would return a different expression, but equivalent to the one it returned before* **for example**  
**we'd return "S+R" instead of "R+S"**
- (b)  $rev$  would become the identity function
- (c)  $rev$  would return exactly the same expression
- (d)  $rev$  would return something not equivalent to the correct reversal, and also not the identity



# Testing for the Empty Language

- The regular expression “ $\emptyset$ ” denotes the empty language, but so do other regular expressions like  $a(b+a)^*(\emptyset + a^*\emptyset)(bb)^*$ .
- Exercise 5.5.4 asks you to write a method that takes a `RegExp` object `R` and returns a boolean that is true if and only if  $L(R) = \emptyset$ .

# Testing for the Empty Language

- We solve the problem recursively.
- For the base cases, we should return `true` on  $\emptyset$  and return `false` on any letter `a`.
- If `R` and `S` are two regular expressions,  $L(R + S)$  is empty if and only if *both*  $L(R)$  and  $L(S)$  are empty, and  $L(RS)$  is empty if and only if *either*  $L(R)$  or  $L(S)$  is empty.
- And of course  $L(R^*)$  is never empty.

# Testing Properties of Expressions

- A similar problem is to tell whether  $L(R) = \{\lambda\}$ , or whether  $\lambda \in L(R)$ . Each of these may be solved by a recursive algorithm, because we know whether the property holds in the base cases, and how it behaves with respect to the three operations.
- But telling whether  $L(R) = \Sigma^*$  is much harder, because  $L(R + S)$  could equal  $\Sigma^*$  in so many *different* ways.

# Clicker Question #3

- Given a regular expression  $R$  over  $\{a, b\}$ , I would like to compute whether  $L(R) = \{\lambda\}$ . Which of these potential steps in an inductive definition of this property is *valid*?
- (a)  $L(R^*) = \{\lambda\} \Leftrightarrow L(R) = \emptyset$
- (b)  $L(RS) = \{\lambda\} \Leftrightarrow (L(R) = \{\lambda\}) \wedge (L(S) = \{\lambda\})$
- (c)  $L(R+S) = \{\lambda\} \Leftrightarrow (L(R) = \{\lambda\}) \wedge (L(S) = \{\lambda\})$
- (d)  $L(R+S) = \{\lambda\} \Leftrightarrow (L(R) = \{\lambda\}) \vee (L(S) = \{\lambda\})$

Not the Answer

# Clicker Question #3

- Given a regular expression  $R$  over  $\{a, b\}$ , I would like to compute whether  $L(R) = \{\lambda\}$ . Which of these potential steps in an inductive definition of this property is *valid*?
- (a)  $L(R^*) = \{\lambda\} \Leftrightarrow L(R) = \emptyset$
- (b)  $L(RS) = \{\lambda\} \Leftrightarrow (L(R) = \{\lambda\}) \wedge (L(S) = \{\lambda\})$
- (c)  $L(R+S) = \{\lambda\} \Leftrightarrow (L(R) = \{\lambda\}) \wedge (L(S) = \{\lambda\})$
- (d)  $L(R+S) = \{\lambda\} \Leftrightarrow (L(R) = \{\lambda\}) \vee (L(S) = \{\lambda\})$   
for  $L(R+S) = \{\lambda\}$  we need one of  $L(R)$  or  $L(S)$  to be  $\{\lambda\}$ , and the other to be  $\{\lambda\}$  or  $\emptyset$