



Report-ZAP-Full-Scan.pdf

Site: <http://localhost:8080>

Generated on Sun, 24 May 2026 22:52:14

ZAP Version: 2.17.0

ZAP by [Checkmarx](#)

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	5
Low	6
Informational	9

Insights

Level	Reason	Site	Description	Statistic
Low	Warning		ZAP errors logged - see the zap. log file for details	4
Low	Warning		ZAP warnings logged - see the zap. log file for details	86
Info	Informational	http://localhost:8080	Percentage of responses with status code 2xx	90 %
Info	Informational	http://localhost:8080	Percentage of responses with status code 3xx	3 %
Info	Exceeded Low	http://localhost:8080	Percentage of responses with status code 4xx	5 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content	1 %

			type application /javascript	
Info	Informational	http://localhost:8080	Percentage of endpoints with content type application /pdf	10 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content type application /x-trash	3 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content type application /xml	1 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content type image /gif	9 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content type image /jpeg	7 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content type image /png	21 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content type image /vnd. microsoft. icon	3 %
Info	Informational	http://localhost:8080	Percentage of endpoints with	1 %

			content type text /css	
Info	Informational	http://localhost:8080	Percentage of endpoints with content type text /html	37 %
Info	Informational	http://localhost:8080	Percentage of endpoints with content type text /plain	1 %
Info	Informational	http://localhost:8080	Percentage of endpoints with method GET	96 %
Info	Informational	http://localhost:8080	Percentage of endpoints with method POST	3 %
Info	Informational	http://localhost:8080	Count of total endpoints	64

Alerts

Name	Risk Level	Number of Instances
Absence of Anti-CSRF Tokens	Medium	5
Application Error Disclosure	Medium	6
Content Security Policy (CSP) Header Not Set	Medium	Systemic
Directory Browsing	Medium	Systemic
Missing Anti-clickjacking Header	Medium	Systemic
Cookie No HttpOnly Flag	Low	1
Cookie without SameSite Attribute	Low	1
In Page Banner Information Leak	Low	1
Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	Low	Systemic
Server Leaks Version Information via "Server" HTTP Response Header Field	Low	Systemic
X-Content-Type-Options Header Missing	Low	Systemic
Authentication Request Identified	Informational	2
GET for POST	Informational	2
Session Management Response Identified	Informational	2
Tech Detected - Apache HTTP Server	Informational	1

Tech Detected - PHP	Informational	1
Tech Detected - Ubuntu	Informational	1
Tech Detected - bun	Informational	1
User Agent Fuzzer	Informational	Systemic
User Controllable HTML Element Attribute (Potential XSS)	Informational	2

Alert Detail

Medium	Absence of Anti-CSRF Tokens
Description	No Anti-CSRF tokens were found in a HTML submission form. A cross-site request forgery is an attack that involves forcing a victim to send an HTTP request to a target destination without their knowledge or intent in order to perform an action as the victim. The underlying cause is application functionality using predictable URL /form actions in a repeatable way. The nature of the attack is that CSRF exploits the trust that a web site has for a user. By contrast, cross-site scripting (XSS) exploits the trust that a user has for a web site. Like XSS, CSRF attacks are not necessarily cross-site, but they can be. Cross-site request forgery is also known as CSRF, XSRF, one-click attack, session riding, confused deputy, and sea surf. CSRF attacks are effective in a number of situations, including: * The victim has an active session on the target site. * The victim is authenticated via HTTP auth on the target site. * The victim is on the same local network as the target site. CSRF has primarily been used to perform an action against a target site using the victim's privileges, but recent techniques have been discovered to disclose information by gaining access to the response. The risk of information disclosure is dramatically increased when the target site is vulnerable to XSS, because XSS can be used as a platform for CSRF, allowing the attack to operate within the bounds of the same-origin policy.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET
Attack	
Evidence	<form action="/login.php" method="POST">
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 1: "login" "password"].
URL	http://localhost:8080/login.php
Node Name	http://localhost:8080/login.php
Method	GET
Attack	
Evidence	<form action="/login.php" method="POST">
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 1: "login" "password"].

URL	http://localhost:8080/user_new.php
Node Name	http://localhost:8080/user_new.php
Method	GET
Attack	
Evidence	<form action="/user_new.php" method="POST">
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 1: "email" "login" "mail_activation" "password" "password_conf" "secret"].
URL	http://localhost:8080/login.php
Node Name	http://localhost:8080/login.php ()(form,login,password,security_level)
Method	POST
Attack	
Evidence	<form action="/login.php" method="POST">
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 1: "login" "password"].
URL	http://localhost:8080/user_new.php
Node Name	http://localhost:8080/user_new.php ()(action,email,login,mail_activation,password,password_conf,secret)
Method	POST
Attack	
Evidence	<form action="/user_new.php" method="POST">
Other Info	No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken] was found in the following HTML form: [Form 1: "email" "login" "mail_activation" "password" "password_conf" "secret"].
Instances	5
Solution	Phase: Architecture and Design Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, use anti-CSRF packages such as the OWASP CSRFGuard. Phase: Implementation Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script. Phase: Architecture and Design Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330). Note that this can be bypassed using XSS. Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation.

	Note that this can be bypassed using XSS. Use the ESAPI Session Management control. This control includes a component for CSRF. Do not use the GET method for any request that triggers a state change. Phase: Implementation Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.
Reference	https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html https://cwe.mitre.org/data/definitions/352.html
CWE Id	352
WASC Id	9
Plugin Id	10202

Medium	Application Error Disclosure
Description	This page contains an error/warning message that may disclose sensitive information like the location of the file that produced the unhandled exception. This information can be used to launch further attacks against the web application. The alert could be a false positive if the error message is found inside a documentation page.
URL	http://localhost:8080/documents/
Node Name	http://localhost:8080/documents/
Method	GET
Attack	
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/documents/?C=N;O=D
Node Name	http://localhost:8080/documents/ (C)
Method	GET
Attack	
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/images/
Node Name	http://localhost:8080/images/
Method	GET
Attack	
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/images/?C=N;O=D
Node	

Name	http://localhost:8080/images/ (C)
Method	GET
Attack	
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/passwords/
Node Name	http://localhost:8080/passwords/
Method	GET
Attack	
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/passwords/?C=M;O=A
Node Name	http://localhost:8080/passwords/ (C)
Method	GET
Attack	
Evidence	Parent Directory
Other Info	
Instances	6
Solution	Review the source code of this page. Implement custom error pages. Consider implementing a mechanism to provide a unique error reference/identifier to the client (browser) while logging the details on the server side and not exposing them to the user.
Reference	
CWE Id	550
WASC Id	13
Plugin Id	90022

Medium	Content Security Policy (CSP) Header Not Set
Description	Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks, including Cross Site Scripting (XSS) and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/admin/

Node Name	http://localhost:8080/admin/
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/documents/?C=N;O=D
Node Name	http://localhost:8080/documents/ (C)
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/images/
Node Name	http://localhost:8080/images/
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/passwords/?C=M;O=A
Node Name	http://localhost:8080/passwords/ (C)
Method	GET
Attack	
Evidence	
Other Info	
Instances	Systemic
Solution	Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Guides/CSP https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html https://www.w3.org/TR/CSP/ https://w3c.github.io/webappsec-csp/ https://web.dev/articles/csp https://caniuse.com/#feat=contentsecuritypolicy https://content-security-policy.com/
CWE Id	693
WASC Id	15
Plugin Id	10038

Medium	Directory Browsing

Description	It is possible to view a listing of the directory contents. Directory listings may reveal hidden scripts, include files, backup source files, etc., which can be accessed to reveal sensitive information.
URL	http://localhost:8080/documents/
Node Name	http://localhost:8080/documents/
Method	GET
Attack	http://localhost:8080/documents/
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/images/
Node Name	http://localhost:8080/images/
Method	GET
Attack	http://localhost:8080/images/
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/js/
Node Name	http://localhost:8080/js/
Method	GET
Attack	http://localhost:8080/js/
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/passwords/
Node Name	http://localhost:8080/passwords/
Method	GET
Attack	http://localhost:8080/passwords/
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/stylesheets/
Node Name	http://localhost:8080/stylesheets/
Method	GET
Attack	http://localhost:8080/stylesheets/
Evidence	Parent Directory
Other Info	
URL	http://localhost:8080/documents/
Node Name	http://localhost:8080/documents/

Method	GET
Attack	
Evidence	<title>Index of /documents</title>
Other Info	Web server identified: Apache 2
URL	http://localhost:8080/documents/?C=N;O=D
Node Name	http://localhost:8080/documents/ (C)
Method	GET
Attack	
Evidence	<title>Index of /documents</title>
Other Info	Web server identified: Apache 2
URL	http://localhost:8080/images/
Node Name	http://localhost:8080/images/
Method	GET
Attack	
Evidence	<title>Index of /images</title>
Other Info	Web server identified: Apache 2
URL	http://localhost:8080/images/?C=N;O=D
Node Name	http://localhost:8080/images/ (C)
Method	GET
Attack	
Evidence	<title>Index of /images</title>
Other Info	Web server identified: Apache 2
URL	http://localhost:8080/passwords/?C=M;O=A
Node Name	http://localhost:8080/passwords/ (C)
Method	GET
Attack	
Evidence	<title>Index of /passwords</title>
Other Info	Web server identified: Apache 2
Instances	Systemic
Solution	Configure the web server to disable directory browsing.
Reference	https://cwe.mitre.org/data/definitions/548.html
CWE Id	548
WASC Id	16
Plugin Id	10033
Medium	Missing Anti-clickjacking Header

Description	The response does not protect against 'ClickJacking' attacks. It should include either Content-Security-Policy with 'frame-ancestors' directive or X-Frame-Options.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/admin/
Node Name	http://localhost:8080/admin/
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/documents/?C=N;O=D
Node Name	http://localhost:8080/documents/ (C)
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/images/
Node Name	http://localhost:8080/images/
Method	GET
Attack	
Evidence	
Other Info	
URL	http://localhost:8080/passwords/?C=M;O=A
Node Name	http://localhost:8080/passwords/ (C)
Method	GET
Attack	
Evidence	
Other Info	
Instances	Systemic
	Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers. Ensure one of them is set on all web pages returned by your site/app.

Solution	If you expect the page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should use DENY. Alternatively consider implementing Content Security Policy's "frame-ancestors" directive.
Reference	https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/X-Frame-Options
CWE Id	1021
WASC Id	15
Plugin Id	10020

Low	Cookie No HttpOnly Flag
Description	A cookie has been set without the HttpOnly flag, which means that the cookie can be accessed by JavaScript. If a malicious script can be run on this page then the cookie will be accessible and can be transmitted to another site. If this is a session cookie then session hijacking may be possible.
URL	http://localhost:8080/portal.php
Node Name	http://localhost:8080/portal.php
Method	GET
Attack	
Evidence	Set-Cookie: PHPSESSID
Other Info	
Instances	1
Solution	Ensure that the HttpOnly flag is set for all cookies.
Reference	https://owasp.org/www-community/HttpOnly
CWE Id	1004
WASC Id	13
Plugin Id	10010

Low	Cookie without SameSite Attribute
Description	A cookie has been set without the SameSite attribute, which means that the cookie can be sent as a result of a 'cross-site' request. The SameSite attribute is an effective counter measure to cross-site request forgery, cross-site script inclusion, and timing attacks.
URL	http://localhost:8080/portal.php
Node Name	http://localhost:8080/portal.php
Method	GET
Attack	
Evidence	Set-Cookie: PHPSESSID
Other Info	
Instances	1
Solution	Ensure that the SameSite attribute is set to either 'lax' or ideally 'strict' for all cookies.
Reference	https://datatracker.ietf.org/doc/html/draft-ietf-httpbis-cookie-same-site
CWE Id	1275
WASC Id	13
Plugin Id	10054

Low	In Page Banner Information Leak
------------	--

Description	The server returned a version banner string in the response content. Such information leaks may allow attackers to further target specific issues impacting the product and version in use.
URL	http://localhost:8080/sitemap.xml
Node Name	http://localhost:8080/sitemap.xml
Method	GET
Attack	
Evidence	Apache/2.4.7
Other Info	There is a chance that the highlight in the finding is on a value in the headers, versus the actual matched string in the response body.
Instances	1
Solution	Configure the server to prevent such information leaks. For example: Under Tomcat this is done via the "server" directive and implementation of custom error pages. Under Apache this is done via the "ServerSignature" and "ServerTokens" directives.
Reference	https://owasp.org/www-project-web-security-testing-guide/v41/4-Web_Application_Security_Testing/08-Testing_for_Error_Handling/
CWE Id	497
WASC Id	13
Plugin Id	10009

Low	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)
Description	The web/application server is leaking information via one or more "X-Powered-By" HTTP response headers. Access to such information may facilitate attackers identifying other frameworks/components your web application is reliant upon and the vulnerabilities such components may be subject to.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET
Attack	
Evidence	X-Powered-By: PHP/5.5.9-1ubuntu4.14
Other Info	
URL	http://localhost:8080/admin/
Node Name	http://localhost:8080/admin/
Method	GET
Attack	
Evidence	X-Powered-By: PHP/5.5.9-1ubuntu4.14
Other Info	
URL	http://localhost:8080/info.php
Node Name	http://localhost:8080/info.php
Method	GET

Attack	
Evidence	X-Powered-By: PHP/5.5.9-1ubuntu4.14
Other Info	
URL	http://localhost:8080/login.php
Node Name	http://localhost:8080/login.php
Method	GET
Attack	
Evidence	X-Powered-By: PHP/5.5.9-1ubuntu4.14
Other Info	
URL	http://localhost:8080/user_new.php
Node Name	http://localhost:8080/user_new.php
Method	GET
Attack	
Evidence	X-Powered-By: PHP/5.5.9-1ubuntu4.14
Other Info	
Instances	Systemic
Solution	Ensure that your web server, application server, load balancer, etc. is configured to suppress "X-Powered-By" headers.
Reference	https://owasp.org/www-project-web-security-testing-guide/v42/4-Web_Application_Security_Testing/01-Information_Gathering/08-Fingerprint_Web_Application_Framework https://www.troyhunt.com/shhh-dont-let-your-response-headers/
CWE Id	497
WASC Id	13
Plugin Id	10037

Low	Server Leaks Version Information via "Server" HTTP Response Header Field
Description	The web/application server is leaking version information via the "Server" HTTP response header. Access to such information may facilitate attackers identifying other vulnerabilities your web/application server is subject to.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET
Attack	
Evidence	Apache/2.4.7 (Ubuntu)
Other Info	
URL	http://localhost:8080/admin/
Node Name	http://localhost:8080/admin/
Method	GET
Attack	

Evidence	Apache/2.4.7 (Ubuntu)
Other Info	
URL	http://localhost:8080/documents/?C=N;O=D
Node Name	http://localhost:8080/documents/ (C)
Method	GET
Attack	
Evidence	Apache/2.4.7 (Ubuntu)
Other Info	
URL	http://localhost:8080/images/
Node Name	http://localhost:8080/images/
Method	GET
Attack	
Evidence	Apache/2.4.7 (Ubuntu)
Other Info	
URL	http://localhost:8080/passwords/?C=M;O=A
Node Name	http://localhost:8080/passwords/ (C)
Method	GET
Attack	
Evidence	Apache/2.4.7 (Ubuntu)
Other Info	
Instances	Systemic
Solution	Ensure that your web server, application server, load balancer, etc. is configured to suppress the "Server" header or provide generic details.
Reference	https://httpd.apache.org/docs/current/mod/core.html#servertokens https://learn.microsoft.com/en-us/previous-versions/msp-n-p/ff648552(v=pandp.10) https://www.troyhunt.com/shhh-dont-let-your-response-headers/
CWE Id	497
WASC Id	13
Plugin Id	10036

Low	X-Content-Type-Options Header Missing
Description	The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET

Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://localhost:8080/admin/
Node Name	http://localhost:8080/admin/
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://localhost:8080/documents/?C=N;O=D
Node Name	http://localhost:8080/documents/ (C)
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://localhost:8080/images/
Node Name	http://localhost:8080/images/
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://localhost:8080/passwords/?C=M;O=A
Node Name	http://localhost:8080/passwords/ (C)
Method	GET
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.

Instances	Systemic
Solution	Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages. If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application /web server to not perform MIME-sniffing.
Reference	https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85) https://owasp.org/www-community/Security_Headers
CWE Id	693
WASC Id	15
Plugin Id	10021

Informational	Authentication Request Identified
Description	The given request has been identified as an authentication request. The 'Other Info' field contains a set of key=value lines which identify any relevant fields. If the request is in a context which has an Authentication Method set to "Auto-Detect" then this rule will change the authentication to match the request identified.
URL	http://localhost:8080/user_new.php
Node Name	http://localhost:8080/user_new.php ()(action,email,login,mail_activation,password,password_conf,secret)
Method	POST
Attack	
Evidence	password
Other Info	userParam=email userValue=zaproxy@example.com passwordParam=password referer=http://localhost:8080/user_new.php
URL	http://localhost:8080/login.php
Node Name	http://localhost:8080/login.php ()(form,login,password,security_level)
Method	POST
Attack	
Evidence	password
Other Info	userParam=login userValue=ZAP passwordParam=password referer=http://localhost:8080/login.php
Instances	2
Solution	This is an informational alert rather than a vulnerability and so there is nothing to fix.
Reference	https://www.zaproxy.org/docs/desktop/addons/authentication-helper/auth-req-id/
CWE Id	
WASC Id	
Plugin Id	10111

Informational	GET for POST
---------------	--------------

Description	A request that was originally observed as a POST was also accepted as a GET. This issue does not represent a security weakness unto itself, however, it may facilitate simplification of other attacks. For example if the original POST is subject to Cross-Site Scripting (XSS), then this finding may indicate that a simplified (GET based) XSS may also be possible.
URL	http://localhost:8080/login.php
Node Name	http://localhost:8080/login.php (form,login,password,security_level)
Method	GET
Attack	
Evidence	GET http://localhost:8080/login.php?form=submit&login=ZAP&password=ZAP&security_level=1 HTTP/1.1
Other Info	
URL	http://localhost:8080/user_new.php
Node Name	http://localhost:8080/user_new.php (action,email,login,mail_activation,password,password_conf,secret)
Method	GET
Attack	
Evidence	GET http://localhost:8080/user_new.php?action=create&email=zaproxy@example.com&login=ZAP&mail_activation=&password=ZAP&password_conf=ZAP&secret=ZAP HTTP/1.1
Other Info	
Instances	2
Solution	Ensure that only POST is accepted where POST is expected.
Reference	
CWE Id	16
WASC Id	20
Plugin Id	10058

Informational	Session Management Response Identified
Description	The given response has been identified as containing a session management token. The 'Other Info' field contains a set of header tokens that can be used in the Header Based Session Management Method. If the request is in a context which has a Session Management Method set to "Auto-Detect" then this rule will change the session management to use the tokens identified.
URL	http://localhost:8080/portal.php
Node Name	http://localhost:8080/portal.php
Method	GET
Attack	
Evidence	PHPSESSID
Other Info	cookie:PHPSESSID
URL	http://localhost:8080/portal.php
Node Name	http://localhost:8080/portal.php
Method	GET
Attack	

Evidence	PHPSESSID
Other Info	cookie:PHPSESSID
Instances	2
Solution	This is an informational alert rather than a vulnerability and so there is nothing to fix.
Reference	https://www.zaproxy.org/docs/desktop/addons/authentication-helper/session-mgmt-id/
CWE Id	
WASC Id	
Plugin Id	10112

Informational	Tech Detected - Apache HTTP Server
Description	The following "Web servers" technology was identified: Apache HTTP Server. Described as: Apache is a free and open-source cross-platform web server software.
URL	http://localhost:8080/admin/
Node Name	http://localhost:8080/admin/
Method	GET
Attack	
Evidence	Apache/2.4.7
Other Info	The following CPE is associated with the identified tech: cpe:2.3:a:apache:http_server:*:*:*:* The following version(s) is/are associated with the identified tech: 2.4.7
Instances	1
Solution	
Reference	https://httpd.apache.org/
CWE Id	
WASC Id	13
Plugin Id	10004

Informational	Tech Detected - PHP
Description	The following "Programming languages" technology was identified: PHP. Described as: PHP is a general-purpose scripting language used for web development.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET
Attack	
Evidence	PHP/5.5.9
Other Info	The following CPE is associated with the identified tech: cpe:2.3:a:php:php:*:*:*:*:* The following version(s) is/are associated with the identified tech: 5.5.9
Instances	1

Solution	
Reference	https://php.net
CWE Id	
WASC Id	13
Plugin Id	10004

Informational	Tech Detected - Ubuntu
Description	The following "Operating systems" technology was identified: Ubuntu. Described as: Ubuntu is a free and open-source operating system on Linux for the enterprise server, desktop, cloud, and IoT.
URL	http://localhost:8080/documents/?C=M;O=A
Node Name	http://localhost:8080/documents/ (C)
Method	GET
Attack	
Evidence	Ubuntu
Other Info	The following CPE is associated with the identified tech: cpe:2.3:o:canonical:ubuntu_linux:*:*:*:*:*
Instances	1
Solution	
Reference	https://www.ubuntu.com/server
CWE Id	
WASC Id	13
Plugin Id	10004

Informational	Tech Detected - bun
Description	The following "Programming languages" technology was identified: bun. Described as: Bun is a fast JavaScript runtime compatible with Node.js and Deno.
URL	http://localhost:8080
Node Name	http://localhost:8080
Method	GET
Attack	
Evidence	bun
Other Info	
Instances	1
Solution	
Reference	https://bun.sh
CWE Id	
WASC Id	13
Plugin Id	10004

--	--

Informational	User Agent Fuzzer
Description	Check for differences in response based on fuzzed User Agent (eg. mobile sites, access as a Search Engine Crawler). Compares the response statuscode and the hashcode of the response body with the original response.
URL	http://localhost:8080/
Node Name	http://localhost:8080/
Method	GET
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
URL	http://localhost:8080/admin
Node Name	http://localhost:8080/admin
Method	GET
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
URL	http://localhost:8080/documents
Node Name	http://localhost:8080/documents
Method	GET
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
URL	http://localhost:8080/login.php
Node Name	http://localhost:8080/login.php ()(form,login,password,security_level)
Method	POST
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
URL	http://localhost:8080/user_new.php
Node Name	http://localhost:8080/user_new.php ()(action,email,login,mail_activation,password,password_conf,secret)
Method	POST
Attack	Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)
Evidence	
Other Info	
Instances	Systemic
Solution	

Reference	https://owasp.org/wstg
CWE Id	
WASC Id	
Plugin Id	10104

Informational	User Controllable HTML Element Attribute (Potential XSS)
Description	This check looks at user-supplied input in query string parameters and POST data to identify where certain HTML attribute values might be controlled. This provides hot-spot detection for XSS (cross-site scripting) that will require further review by a security analyst to determine exploitability.
URL	http://localhost:8080/login.php
Node Name	http://localhost:8080/login.php ()(form,login,password,security_level)
Method	POST
Attack	
Evidence	
Other Info	User-controlled HTML attribute values were found. Try injecting special characters to see if XSS might be possible. The page at the following URL: http://localhost:8080/login.php appears to include user input in: a(n) [button] tag [type] attribute The user input found was: form=submit The user-controlled value was: submit
URL	http://localhost:8080/user_new.php
Node Name	http://localhost:8080/user_new.php ()(action,email,login,mail_activation,password,password_conf,secret)
Method	POST
Attack	
Evidence	
Other Info	User-controlled HTML attribute values were found. Try injecting special characters to see if XSS might be possible. The page at the following URL: http://localhost:8080/user_new.php appears to include user input in: a(n) [button] tag [value] attribute The user input found was: action=create The user-controlled value was: create
Instances	2
Solution	Validate all input and sanitize output it before writing to any HTML attributes.

Reference	https://cheatsheetseries.owasp.org/cheatsheets/Input_Validation_Cheat_Sheet.html
CWE Id	20
WASC Id	20
Plugin Id	10031