

JobKit - Playwright interview questions

98 questions for Playwright. Single-file download.

1. What is Playwright?

A Microsoft library to automate Chromium, Firefox, and WebKit.

2. Playwright vs Selenium?

Auto-wait, browsers included, and a single API across engines.

3. What is a browser context?

An isolated incognito-like session inside a browser.

4. What is a page?

A tab inside a context.

5. What is a locator?

A lazy handle to find elements, not a one-time query.

6. Why are locators better than element handles?

They re-query and wait; handles go stale.

7. What is getByRole?

Locate by accessible role and name.

8. What is getByTestId?

Locate by a test id attribute you control.

9. What is getByText?

Locate by visible text.

10. What is a strict mode violation?

Locator resolved to more than one element.

11. How do you pick one of many?

nth, filter, or a tighter locator.

12. What is auto-waiting?

Playwright waits for actionability before click or fill.

13. What is actionability?

Visible, enabled, stable, and receiving events.

14. What is a timeout in Playwright?

Default 30s for many actions; set per test or per action.

15. What is expect(locator).toBeVisible()?

An assertion that waits until the element is visible.

16. Web-first assertions?

Assertions that retry until they pass or time out.

17. What is a fixture?

Shared setup in Playwright Test, such as page.

18. What is test.extend?

Custom fixtures for login or data.

19. What is storageState?

Saved cookies/localStorage to skip login.

20. How do you reuse login?

Save storageState in a setup project.

JobKit - Playwright interview questions

21. What is a project in playwright.config?

A browser or setup target.

22. What is a worker?

A parallel process that runs tests.

23. What is fullyParallel?

Run tests in a file in parallel.

24. How do you stop test pollution?

Isolated contexts and no shared mutable files.

25. What is test.step?

A named chunk in the report.

26. What is a trace?

A recording you can open in Trace Viewer.

27. When do you keep traces?

On first retry or on failure in CI.

28. What is Trace Viewer?

UI to inspect DOM, network, and actions.

29. What is codegen?

Record actions into a test script.

30. Why not ship raw codegen?

It is a start; you still clean locators and asserts.

31. What is page.route?

Intercept and mock network requests.

32. How do you mock an API?

route fulfill with JSON.

33. How do you wait for a response?

page.waitForResponse with a URL predicate.

34. What is APIRequestContext?

HTTP requests without a browser, for setup or API tests.

35. How do you test downloads?

Wait for download event and save the file.

36. How do you test uploads?

setInputFiles on the file input.

37. Can Playwright set a file input?

Yes in tests; a Chrome extension cannot.

38. How do you handle a new tab?

Wait for a popup page event.

39. How do you handle a dialog?

page.on('dialog') accept or dismiss.

40. How do you run headed on a laptop?

headed: true or --headed.

41. How do you run in CI?

headless, HTML report, retries 1-2.

42. What is a flake retry?

JobKit - Playwright interview questions

Re-run a failed test; fix the flake, do not hide it forever.

43. What is a screenshot on failure?

Configured in use: screenshot: 'only-on-failure'.

44. What is video on failure?

use.video: 'retain-on-failure'.

45. What is a soft assertion?

expect.soft that does not stop the test immediately.

46. What is test.describe?

A group of tests.

47. What is test.beforeEach?

Runs before every test in the group.

48. What is a tag in Playwright?

test.info().annotations or grep @smoke.

49. How do you run only smoke?

npx playwright test --grep @smoke

50. What is a locator filter?

Narrow a locator by text or another locator.

51. What is getByLabel?

Find a control via its label text.

52. What is getByPlaceholder?

Find an input by placeholder.

53. What is a frame locator?

Enter an iframe without driver.switchTo.

54. How do you work with Shadow DOM?

Locators pierce open shadow roots.

55. What is fill vs type?

fill sets the value; type sends key events.

56. When do you use pressSequentially?

When the app listens to each key.

57. What is click force?

Bypasses some checks; use rarely.

58. What is hover?

Move the mouse for menus.

59. How do you select a dropdown?

selectOption on a select, or click options in a custom combo.

60. How do you check a checkbox?

locator.check().

61. How do you read text?

locator.innerText() or toHaveText.

62. How do you count rows?

locator.count() or toHaveCount.

63. What is a clock in Playwright?

Fake timers for time-dependent UI.

JobKit - Playwright interview questions

64. What is authentication setup project?

A project that logs in once and writes storageState.

65. How do you test localization?

A project per locale.

66. How do you test a mobile viewport?

Device descriptor in a project.

67. Does Playwright drive a real phone?

It emulates viewport and UA; real devices need another stack.

68. What is Playwright for Python vs Node?

Same browser engine; this kit uses Python in places and Node is common in web teams.

69. How do you install browsers?

playwright install.

70. What is a browserType.launch?

Lower-level API vs Playwright Test fixtures.

71. When do you use persistent context?

To keep a profile, as JobKit does for LinkedIn session.

72. What is CDP?

Chrome DevTools Protocol; Playwright can connect over it.

73. Why not click Submit in JobKit?

Sites forbid bots; you submit yourself after fill.

74. What is a POM?

Page Object Model: locators and actions in a class.

75. Playwright and POM?

Use fixtures plus small page objects; avoid huge base classes.

76. What is a component locator?

A locator root for a widget, then getByRole inside it.

77. How do you avoid xpath soup?

Prefer role, label, and test id.

78. What is an accessible name?

The name screen readers use; getByRole uses it.

79. How do you test file download names?

download.suggestedFilename().

80. How do you wait for URL?

expect(page).toHaveURL.

81. How do you wait for title?

expect(page).toHaveTitle.

82. What is networkidle?

Wait until no connections; often too brittle, prefer response waits.

83. What is domcontentloaded?

HTML parsed; assets may still load.

84. What is load?

Window load event.

85. Which wait is default for goto?

JobKit - Playwright interview questions

Usually load; you can pass waitUntil.

86. How do you debug a test?

PWDEBUG=1 or --debug and Trace Viewer.

87. What is UI mode?

playwright test --ui for watch and time travel.

88. How do you seed test data?

APIRequestContext in beforeEach or a factory.

89. How do you hide secrets in CI?

Env vars, not committed .env.

90. What is a visual snapshot?

Screenshot compare with toHaveScreenshot.

91. Why do visual tests flake?

Fonts, animation, and time; mask dynamic regions.

92. What is a mask in screenshots?

Hide volatile locators before compare.

93. How do you test accessibility?

axe via a Playwright plugin or extra library.

94. What is a console error test?

Listen to pageon console and fail on error if the team agrees.

95. How do you handle basic auth?

httpCredentials in context.

96. How do you set geolocation?

context.grantPermissions and setGeolocation.

97. How do you block ads?

route abort on ad hosts.

98. What is a har file?

Recorded network log you can replay.