

Swagger API Documentation

MyKanban Backend includes auto-generated Swagger/OpenAPI documentation powered by [Swagger](https://github.com/swagger-api/swagger-ui) (<https://github.com/swagger-api/swagger-ui>).

Accessing Swagger UI

Once the server is running, open your browser and navigate to:

```
http://localhost:8080/swagger/index.html
```

Replace `localhost:8080` with your actual host and port if different.

Authentication in Swagger UI

Most API endpoints require JWT authentication. Follow these steps:

1. Get a JWT Token

Use the **POST** `/api/v1/auth/login` endpoint in Swagger UI (under the **Auth** tag):

```
{
  "email": "admin@mykanban.local",
  "password": "admin123"
}
```

Copy the `token` value from the response.

2. Authorize

1. Click the  **Authorize** button at the top-right of Swagger UI.
2. In the **BearerAuth** field, enter:
`Bearer <your-jwt-token>`
For example:
`Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...`
3. Click **Authorize**, then **Close**.

All subsequent requests in Swagger UI will include the JWT token.

API Tags

The API is organized into the following groups:

Tag	Description
System	Health check
Auth	Login, password change, Google OAuth
Projects	CRUD operations for projects
Boards	CRUD operations for boards
Tasks	CRUD + PATCH operations for tasks
Schedulers	CRUD for recurring task schedulers
Resources	CRUD for resources (people/services)

Example Workflow in Swagger UI

1. **Health check** — GET /api/health (no auth needed)
2. **Login** — POST /api/v1/auth/login → copy token
3. **Authorize** — click  and paste Bearer <token>
4. **Create a project** — POST /api/v1/projects
5. **Create a board** — POST /api/v1/boards (provide project_id)
6. **Create a task** — POST /api/v1/tasks (provide board_id, valid swimlane, task_type)
7. **Move task** — PATCH /api/v1/tasks/{id} with {"swimlane": "Done"}

Regenerating Swagger Docs

If you modify handler annotations, regenerate the docs:

```
# Install swag CLI (one-time)
go install github.com/swaggo/swag/cmd/swag@latest

# Generate docs
swag init

# Or use the build script (runs swag init automatically)
bash scripts/build.sh
```

Generated files are in the docs/ folder:

- docs/docs.go — Go bindings for embedding
- docs/swagger.json — OpenAPI 2.0 spec (JSON)
- docs/swagger.yaml — OpenAPI 2.0 spec (YAML)

Downloading the OpenAPI Spec

The raw spec files are available at:

- **JSON:** <http://localhost:8080/swagger/doc.json>
- **YAML:** Download from the docs/swagger.yaml file

These can be imported into tools like Postman, Insomnia, or used for client code generation.