

Objective: The objective of this lab is to utilize a stored procedure, transactions, and conditionals to rollback a transaction if a certain value is found, if a certain value is not found, insert into the database table.

1.

a) Create a database and use the CREATE TABLE query for the orders table from the week 6 lecture.



b) Insert four rows of dummy data (the data can be whatever you like) into the orders table. Screenshot the result of a SELECT \* query to prove that this step was completed.



2. Using a stored procedure and a condition statement (if statement), start a transaction that inserts a new row into the orders table, the transaction should rollback if the orderNumber being inserted already exists. If the orderNumber does not exist, then it should insert into the table and commit. Include the stored procedure in the PDF that you submit for this lab. Prove that your stored procedure works by running it and screenshotting the result.

Stored procedure:

-- Creating the Procedure and setting the Delimiter to \$\$
DELIMITER \$\$
CREATE OR REPLACE PROCEDURE Trans\_Insert()
LANGUAGE SQL
DETERMINISTIC
SQL SECURITY DEFINER
COMMENT 'Using Transactions with Stored procedures'

#### **BEGIN**

-- Declaring Variables 'torder' and 'torderNumber' to store the count of order numbers and the latest value of order number

DECLARE torder DECIMAL(10,2) DEFAULT 0; DECLARE torderNumber DECIMAL(10,2) DEFAULT 0;

-- Starting the Transaction START TRANSACTION;

-- Getting the latest order number to our variable 'torderNumber' SELECT MAX(orderNumber) + 1 INTO torderNumber FROM orders:

-- Finding the Count of Ordernumber and storing the value in our variable 'torder' SELECT COUNT(orderNumber)
INTO torder
FROM orders

WHERE orderNumber = torderNumber;

-- Checking for condition to evaluate if ordernumber already exists

IF (torder>0) THEN

-- Transaction rolls back if condition is true ROLLBACK;

**ELSE** 

er)

-- Inserting new values

INSERT INTO orders(orderNumber,orderDate,requiredDate,shippedDate,status,comments,customerNumb

VALUES(torderNumber,'2022-07-01','2022-07-03','2022-07-02','No Comment','At a hub near you',369);

```
-- Committing changes to the database
COMMIT;
End IF;
END;
$$
-- End of Procedure
```

## Calling the Stored procedure to show the result:


## Call Trans\_Insert();



As we can see the output below, changes are committed only when an order is assigned a unique order number every time the stored procedure is run, otherwise the transaction will be rolled back.

(I have run the stored procedure twice before taking the screenshot, hence the row is inserted twice.)

# SELECT \* from orders;



#### **Attribution:**

These assignments were completed by **Ravi Chandan Pandi**, and they represent his original work completed for academic purposes during his studies and self-learning purposes.

Please note that the documents shared here are intended for educational and informational purposes only. Any unauthorized use or reproduction is strictly prohibited. If you have any questions or would like to reach out to Ravi, you can contact him on LinkedIn. [https://www.linkedin.com/in/ravichandan/].