QuickLifeNow

OFFICIAL SETUP GUIDE

Internal Enterprise Task Management & Audit System • Complete Laptop Installation Manual

Architecture: Laravel 12 + React 19 + MySQL 8.0

Target OS: Windows 10/11 / macOS / Linux

Date: October 2026

> **Welcome to QuickLifeNow!** Follow this step-by-step guide to run both the Laravel API backend and React Vite frontend seamlessly on your local laptop from scratch.

1 Laptop Prerequisites

Before starting, verify you have the following standard development tools installed on your laptop:

Required Software	Recommended Version	Verification Command
PHP (with pdo_mysql, gd, fileinfo)	8.2, 8.3, or 8.4	`php -v`
Composer (PHP Package Manager)	2.5+	`composer -V`
Node.js & npm	Node 18.x, 20.x, or 24.x	`node -v` & `npm -v`
MySQL Server	8.0+ (or MariaDB / XAMPP)	`mysql --version`
Git	2.30+	`git --version`

> **Tip for Windows Users:** If using standalone PHP on Windows, make sure the following extensions are enabled in your `php.ini` file: `extension=pdo_mysql`, `extension=fileinfo`, `extension=gd`, `extension=curl`, `extension=mbstring`, `extension=openssl`.

2 Database Setup (MySQL)

Start your MySQL service (via Windows Services, XAMPP, or Terminal) and create the project database:

```
-- Log into MySQL in your command prompt:
mysql -u root -p

-- Run the SQL query to create the database:
CREATE DATABASE task_management CHARACTER SET utf8mb4 COLLATE utf8mb4_unicode_ci;

-- Confirm creation:
```

```
SHOW DATABASES;
EXIT;
```

3 Backend Setup (Laravel 12 API)

Open your command line (PowerShell or Terminal) and navigate to the project directory:

```
cd c:\Users\ADMIN\Desktop\TaskManagement\backend
```

Step 3.1: Environment Configuration

Ensure your `.env` file exists (copy from `.env.example` if creating a fresh clone):

```
copy .env.example .env
```

Confirm the database settings in `backend/.env` match your local MySQL configuration:

```
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=task_management
DB_USERNAME=root
DB_PASSWORD=your_mysql_password_here

APP_URL=http://127.0.0.1:8000
SANCTUM_STATEFUL_DOMAINS=localhost:5173
```

Step 3.2: Install Dependencies & Generate Application Key

```
composer install
php artisan key:generate
```

Step 3.3: Run Database Migrations & Initial Seed Data

This creates all required tables (users, departments, tasks, branches, reviews, work logs, avatars):

```
php artisan migrate --seed
```

Step 3.4: Create Public Storage Link (Crucial for Avatars & Files)

Connects `backend/storage/app/public` to `backend/public/storage` to prevent 403 download errors:

```
php artisan storage:link
```

Step 3.5: Start the Laravel API Server

```
php artisan serve --host=127.0.0.1 --port=8000
```

Your backend API is now running live at **http://127.0.0.1:8000**

4 Frontend Setup (React 19 + Vite)

Open a **second, separate Terminal window** (keep the Laravel server running in the first):

```
cd c:\Users\ADMIN\Desktop\TaskManagement\frontend
```

Step 4.1: Install Node Dependencies

```
npm install
```

Step 4.2: Start Vite Development Server

```
npm run dev
```

> **Ready!** Open your web browser (Chrome, Edge, Firefox) and navigate to:
> **http://localhost:5173**

5 Default Login Credentials

Use any of the seeded accounts to log in and explore different role perspectives:

Role	Email Address	Password	Special Capabilities
ADMINISTRATOR	`ravi@company.com`	`password`	Company Work Logs, Audit Dossier, Departments, Users, All Task Management
SUB-ADMIN	`priya@company.com`	`password`	Operations Management, Review Queue, Handover Approvals, Work Logs Review
EMPLOYEE	`karan@gmail.com`	`password`	Personal Tasks, Deliverable Submissions, My Collaborations, Stage Handover

6 Key Feature Highlights & Testing

- **Avatar & Photo Customizer:** Click the 3D character avatar on the Dashboard Welcome Banner or Sidebar profile card to toggle between 3D Female ♀ / Male ♂ characters, or upload your personal photo.
- **Task Creation & Unique Codes:** Tasks automatically generate unique sequential codes (e.g., `T-001`, `T-017`).
- **Single & Multi-Assignee:** Assign tasks to single or multiple employees without unnecessary self-assignment restrictions.
- **Deliverables & Secure Downloads:** Upload attachments (PDF, DOCX, PNG) and download directly without 403 Forbidden errors.

- **Admin Work Logs Separation Page:** Inspect company-wide communications, stage history, and end-to-end task journey dossiers at `/work-logs`.

7 Troubleshooting & FAQs

Q: MySQL Connection Refused (SQLSTATE[HY000] [2002])?

Solution: Ensure your MySQL service is running. On Windows, open `services.msc`, locate *MySQL80* (or start Apache/MySQL in XAMPP), and click Start.

Q: Attachment or Avatar gives 403 Forbidden / Not Found?

Solution: Run `php artisan storage:link` in the `backend/` folder. Confirm that `backend/public/storage` exists as a connected link.

Q: Port 8000 or 5173 is already in use?

Solution: You can start Laravel on another port: `php artisan serve --port=8080` and Vite with `npm run dev -- --port 3000`.