



Qdrant self-querying

Qdrant (read: quadrant) is a vector similarity search engine. It provides a production-ready service with a convenient API to store, search, and manage points - vectors with an additional payload. **Qdrant** is tailored to extended filtering support. It makes it useful

In the notebook we'll demo the `SelfQueryRetriever` wrapped around a Qdrant vector store.

Creating a Qdrant vectorstore

First we'll want to create a Qdrant VectorStore and seed it with some data. We've created a small demo set of documents that contain summaries of movies.

NOTE: The self-query retriever requires you to have `lark` installed (`pip install lark`). We also need the `qdrant-client` package.

```
#!pip install lark qdrant-client
```

We want to use `OpenAIEmbeddings` so we have to get the OpenAI API Key.

```
# import os
# import getpass

# os.environ['OPENAI_API_KEY'] = getpass.getpass('OpenAI API Key:')
```



```
from langchain.schema import Document
from langchain.embeddings.openai import OpenAIEmbeddings
from langchain.vectorstores import Qdrant

embeddings = OpenAIEmbeddings()
```

API Reference:

- `Document` from `langchain.schema`

- `OpenAIEmbeddings` from `langchain.embeddings.openai`
- `Qdrant` from `langchain.vectorstores`

```
docs = [
    Document(
        page_content="A bunch of scientists bring back dinosaurs and
mayhem breaks loose",
        metadata={"year": 1993, "rating": 7.7, "genre": "science
fiction"},
    ),
    Document(
        page_content="Leo DiCaprio gets lost in a dream within a dream
within a dream within a ...",
        metadata={"year": 2010, "director": "Christopher Nolan", "rating":
8.2},
    ),
    Document(
        page_content="A psychologist / detective gets lost in a series of
dreams within dreams within dreams and Inception reused the idea",
        metadata={"year": 2006, "director": "Satoshi Kon", "rating": 8.6},
    ),
    Document(
        page_content="A bunch of normal-sized women are supremely
wholesome and some men pine after them",
        metadata={"year": 2019, "director": "Greta Gerwig", "rating":
8.3},
    ),
    Document(
        page_content="Toys come alive and have a blast doing so",
        metadata={"year": 1995, "genre": "animated"},
    ),
    Document(
        page_content="Three men walk into the Zone, three men walk out of
the Zone",
        metadata={
            "year": 1979,
            "rating": 9.9,
            "director": "Andrei Tarkovsky",
            "genre": "science fiction",
        },
    ),
]
```

```
vectorstore = Qdrant.from_documents(
    docs,
    embeddings,
    location=":memory:", # Local mode with in-memory storage only
    collection_name="my_documents",
)
```

Creating our self-querying retriever

Now we can instantiate our retriever. To do this we'll need to provide some information upfront about the metadata fields that our documents support and a short description of the document contents.

```
from langchain.llms import OpenAI
from langchain.retrievers.self_query.base import SelfQueryRetriever
from langchain.chains.query_constructor.base import AttributeInfo

metadata_field_info = [
    AttributeInfo(
        name="genre",
        description="The genre of the movie",
        type="string or list[string]",
    ),
    AttributeInfo(
        name="year",
        description="The year the movie was released",
        type="integer",
    ),
    AttributeInfo(
        name="director",
        description="The name of the movie director",
        type="string",
    ),
    AttributeInfo(
        name="rating", description="A 1-10 rating for the movie",
    ),
]
document_content_description = "Brief summary of a movie"
llm = OpenAI(temperature=0)
retriever = SelfQueryRetriever.from_llm(
```

```
llm, vectorstore, document_content_description, metadata_field_info,
verbose=True
)
```

API Reference:

- `OpenAI` from `langchain.llms`
- `SelfQueryRetriever` from `langchain.retrievers.self_query.base`
- `AttributeInfo` from `langchain.chains.query_constructor.base`

Testing it out

And now we can try actually using our retriever!

```
# This example only specifies a relevant query
retriever.get_relevant_documents("What are some movies about dinosaurs")
```

```
query='dinosaur' filter=None limit=None
```

```
[Document(page_content='A bunch of scientists bring back dinosaurs and
mayhem breaks loose', metadata={'year': 1993, 'rating': 7.7, 'genre':
'science fiction'}),
 Document(page_content='Toys come alive and have a blast doing so',
metadata={'year': 1995, 'genre': 'animated'}),
 Document(page_content='Three men walk into the Zone, three men walk
out of the Zone', metadata={'year': 1979, 'rating': 9.9, 'director':
'Andrei Tarkovsky', 'genre': 'science fiction'}),
 Document(page_content='A psychologist / detective gets lost in a
series of dreams within dreams within dreams and Inception reused the
idea', metadata={'year': 2006, 'director': 'Satoshi Kon', 'rating': 8.6})]
```

```
# This example only specifies a filter
retriever.get_relevant_documents("I want to watch a movie rated higher
```

```
than 8.5")
```

```
query=' ' filter=Comparison(comparator=<Comparator.GT: 'gt'>,
attribute='rating', value=8.5) limit=None
```

```
[Document(page_content='Three men walk into the Zone, three men walk
out of the Zone', metadata={'year': 1979, 'rating': 9.9, 'director':
'Andrei Tarkovsky', 'genre': 'science fiction'}),
 Document(page_content='A psychologist / detective gets lost in a
series of dreams within dreams within dreams and Inception reused the
idea', metadata={'year': 2006, 'director': 'Satoshi Kon', 'rating': 8.6})]
```

```
# This example specifies a query and a filter
retriever.get_relevant_documents("Has Greta Gerwig directed any movies
about women")
```

```
query='women' filter=Comparison(comparator=<Comparator.EQ: 'eq'>,
attribute='director', value='Greta Gerwig') limit=None
```

```
[Document(page_content='A bunch of normal-sized women are supremely
wholesome and some men pine after them', metadata={'year': 2019,
'director': 'Greta Gerwig', 'rating': 8.3})]
```

```
# This example specifies a composite filter
retriever.get_relevant_documents(
    "What's a highly rated (above 8.5) science fiction film?"
)
```

```
query=' ' filter=Operation(operator=<Operator.AND: 'and'>, arguments=
[Comparison(comparator=<Comparator.GT: 'gt'>, attribute='rating',
value=8.5), Comparison(comparator=<Comparator.EQ: 'eq'>,
attribute='genre', value='science fiction')]) limit=None
```

```
[Document(page_content='Three men walk into the Zone, three men walk
out of the Zone', metadata={'year': 1979, 'rating': 9.9, 'director':
'Andrei Tarkovsky', 'genre': 'science fiction'})]
```

This example specifies a query and composite filter

```
retriever.get_relevant_documents(
    "What's a movie after 1990 but before 2005 that's all about toys, and
preferably is animated"
)
```

```
query='toys' filter=Operation(operator=<Operator.AND: 'and'>,
arguments=[Comparison(comparator=<Comparator.GT: 'gt'>, attribute='year',
value=1990), Comparison(comparator=<Comparator.LT: 'lt'>,
attribute='year', value=2005), Comparison(comparator=<Comparator.EQ:
'eq'>, attribute='genre', value='animated')]) limit=None
```

```
[Document(page_content='Toys come alive and have a blast doing so',
metadata={'year': 1995, 'genre': 'animated'})]
```

Filter k

We can also use the self query retriever to specify `k`: the number of documents to fetch.

We can do this by passing `enable_limit=True` to the constructor.

```
retriever = SelfQueryRetriever.from_llm(
    llm,
    vectorstore,
    document_content_description,
    metadata_field_info,
    enable_limit=True,
    verbose=True,
)
```

```
# This example only specifies a relevant query
retriever.get_relevant_documents("what are two movies about dinosaurs")
```

```
query='dinosaur' filter=None limit=2
```

```
[Document(page_content='A bunch of scientists bring back dinosaurs and
mayhem breaks loose', metadata={'year': 1993, 'rating': 7.7, 'genre':
'science fiction'}),
 Document(page_content='Toys come alive and have a blast doing so',
 metadata={'year': 1995, 'genre': 'animated'})]
```