Modules

Agents

Tools

Tools as OpenAl Functions

## **Tools as OpenAl Functions**

This notebook goes over how to use LangChain tools as OpenAl functions.

```
from langchain.chat_models import ChatOpenAI
from langchain.schema import HumanMessage
```

## **API Reference:**

- ChatOpenAI from langchain.chat\_models
- HumanMessage from langchain.schema

```
model = ChatOpenAI(model="gpt-3.5-turbo-0613")
```

from langchain.tools import MoveFileTool, format\_tool\_to\_openai\_function

## **API Reference:**

- MoveFileTool from langchain.tools
- format\_tool\_to\_openai\_function from (langchain.tools)

```
tools = [MoveFileTool()]
functions = [format_tool_to_openai_function(t) for t in tools]
```

```
message = model.predict_messages(
    [HumanMessage(content="move file foo to bar")], functions=functions
)
```

## message

```
AIMessage(content='', additional_kwargs={'function_call': {'name': 'move_file', 'arguments': '{\n "source_path": "foo",\n "destination_path": "bar"\n}'}}, example=False)

message.additional_kwargs["function_call"]
```

```
{'name': 'move_file',
    'arguments': '{\n "source_path": "foo",\n "destination_path":
"bar"\n}'}
```