

```
Select *from Virtusa;
```

1	Ravi Kumar Singh	Java Full Stack Developer	50000	A
2	Karan Bansal	Java Full Stack Developer	50000	A
3	Sonu Jha	Java Full Stack Developer	50000	A
4	Rohit Bisen	Java Full Stack Developer	50000	A
5	Yuvan Hanwat	Java Full Stack Developer	50000	A
6	Shivendra Patel	Java Full Stack Developer	50000	A
7	Venus Garg	Java Full Stack Developer	50000	A
8	Dhirendra Kewat	Java Full Stack Developer	50000	A
9	Kahkasa	Java Full Stack Developer	50000	A
10	Kajal	Java Full Stack	50000	A

```
Select EmpName, label, bonus From Virtusa;
```

Output

EmpName	label	Bonus
Ravi Kumar Singh	A	50000
Karan Bansal	A	50000
Sonu Jha	A	50000
Rohit Bisen	A	50000
Yuvan Hanwat	A	50000
Shivendra Patel	A	50000

Venus Garg	A	50000
Dhirendra Kewat	A	50000
Kahkasa	A	50000
Kajal	A	50000

```
select *from newjoinee;
```

## Output

emp_no	student_name	college_name	training_status	bonus
	a	ies	90	50000
2	a	ies	90	50000
3	b	ies	70	0
4	e	ies	40	0

```
select *from newjoinee  
where training_status=(select max(training_status)from newjoinee);
```

## Output

emp_no	student_name	college_name	training_status	bonus
	a	ies	90	50000
2	a	ies	90	50000

```
update virtusa  
set emp_name='venus garg'  
where emp_name='venus kumar garg';
```

## Output

SQL query successfully executed. However, the result set is empty.

```
select * from newjoinee  
where training_status < 50;
```

## Output

emp_no	student_name	college_name	training_status	bonus
4	e	ies	40	0