

NAME

EStateIndicesFingerprints

SYNOPSIS

```
use Fingerprints::EStateIndicesFingerprints;

use Fingerprints::EStateIndicesFingerprints qw(:all);
```

DESCRIPTION

EStateIndicesFingerprints [Ref 75-78] class provides the following methods:

new, GenerateFingerprints, GetDescription, SetEStateAtomTypesSetToUse, SetValuesPrecision, StringifyEStateIndicesFingerprints

EStateIndicesFingerprints is derived from Fingerprints class which in turn is derived from ObjectProperty base class that provides methods not explicitly defined in AtomNeighborhoodsFingerprints, Fingerprints or ObjectProperty classes using Perl's AUTOLOAD functionality. These methods are generated on-the-fly for a specified object property:

```
Set<PropertyName>(<PropertyValue>);
$PropertyValue = Get<PropertyName>();
Delete<PropertyName>();
```

E-state atom types are assigned to all non-hydrogen atoms in a molecule using module AtomTypes::EStateAtomTypes.pm and E-state values are calculated using module AtomicDescriptors::EStateValues.pm. Using E-state atom types and E-state values, EStateIndicesFingerprints constituting sum of E-state values for E-state atom types are generated.

Two types of E-state atom types set size are allowed:

```
ArbitrarySize - Corresponds to only E-state atom types detected
                in molecule
FixedSize - Corresponds to fixed number of E-state atom types previously
                defined
```

Module AtomTypes::EStateAtomTypes.pm, used to assign E-state atom types to non-hydrogen atoms in the molecule, is able to assign atom types to any valid atom group. However, for *FixedSize* value of EStateAtomTypesSetToUse, only a fixed set of E-state atom types corresponding to specific atom groups [Appendix III in Ref 77] are used for fingerprints.

The fixed size E-state atom type set size used during generation of fingerprints contains 87 E-state non-hydrogen atom types in EStateAtomTypes.csv data file distributed with MayaChemTools.

Combination of Type and EStateAtomTypesSetToUse allow generation of 2 different types of E-state indices fingerprints:

Type	EStateAtomTypesSetToUse
EStateIndices	ArbitrarySize [default fingerprints]
EStateIndices	FixedSize

The current release of MayaChemTools generates the following types of E-state fingerprints vector strings:

```
FingerprintsVector;EStateIndices:ArbitrarySize;11;NumericalValues;IDs
AndValuesString;SaaCH SaasC SaasN SdO SdssC SsCH3 SsF SsOH SssCH2 SssN
H SsssCH;24.778 4.387 1.993 25.023 -1.435 3.975 14.006 29.759 -0.073 3
.024 -2.270
```

```
FingerprintsVector;EStateIndices:FixedSize;87;OrderedNumericalValues;
ValuesString;0 0 0 0 0 0 0 3.975 0 -0.073 0 0 24.778 -2.270 0 0 -1.435
4.387 0 0 0 0 0 0 3.024 0 0 0 0 0 0 1.993 0 29.759 25.023 0 0 0 0 1
4.006 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0
```

```
FingerprintsVector;EStateIndices:FixedSize;87;OrderedNumericalValues;
IDsAndValuesString;SsLi SssBe SssssBem SsBH2 SssBH SssssB SssssBm SsCH3
SdCH2 SssCH2 StCH SdsCH SaaCH SsssCH SddC StsC SdssC SaasC SaaaC Sssss
```


SEE ALSO

Fingerprints.pm, FingerprintsStringUtil.pm, AtomNeighborhoodsFingerprints.pm, AtomTypesFingerprints.pm, ExtendedConnectivityFingerprints.pm, MACCSKeys.pm, PathLengthFingerprints.pm, TopologicalAtomPairsFingerprints.pm, TopologicalAtomTripletsFingerprints.pm, TopologicalAtomTorsionsFingerprints.pm, TopologicalPharmacophoreAtomPairsFingerprints.pm, TopologicalPharmacophoreAtomTripletsFingerprints.pm

COPYRIGHT

Copyright (C) 2018 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.