

# Python Secrets and Advanced Concepts

---

A collection of useful Python tips and explanations for more advanced concepts.

---

## `__str__` vs. `__repr__`: How `print()` Behaves

---

A common point of confusion is how Python decides to represent an object as a string. The key is to understand the difference between `__str__` and `__repr__` and how `print()` uses them.

- `print(object)` will try to use the `__str__()` method of the object. This is meant to be a user-friendly, readable representation.
- If `__str__()` is not defined, it falls back to `__repr__()`.
- When you print a container like a list ( `print([object])` ), the list's `__repr__` method is called, which in turn calls the `__repr__()` method of each object inside it. `__repr__()` is meant to be an unambiguous, developer-friendly representation that could ideally be used to recreate the object.

### Example

```
class MyObject:
    def __init__(self, value):
        self.value = value

    def __str__(self):
        return f"A user-friendly string: {self.value}"

    def __repr__(self):
        return f"MyObject(value={self.value!r})"

obj = MyObject(10)

# print(object) uses __str__
print(obj)

# print([object]) uses __repr__ for the object inside the list
print([obj])
```

#### Output:

```
A user-friendly string: 10
[MyObject(value=10)]
```

---

## Generators and Coroutines

---

### Understanding the `TypeError: can't send non-None value to a just-started generator`

This error is a classic "rite of passage" when working with generator-based coroutines.

**The Problem:** A generator function's code does not run until you "prime" it. You cannot send a value ( `.send(value)` ) to a generator that hasn't started executing and paused at its first `yield` expression.

**The Solution:** You must first call `next(g)` or `g.send(None)` to advance the generator to its first `yield` point. Only then can it accept a non-`None` value.

### Example

```
def my_coroutine():
    print("-> Coroutine started")
    value = yield
    print(f"-> Coroutine received: {value}")
    yield

co = my_coroutine()

# This will cause the TypeError:
# co.send("Hello")

# Correct way: Prime the coroutine first
print("Priming the coroutine...")
next(co) # or co.send(None)
print("Coroutine is primed and waiting at the first yield.")

# Now we can send a value
print("Sending value to coroutine...")
co.send("Hello")
```

#### Output:

```
Priming the coroutine...
-> Coroutine started
Coroutine is primed and waiting at the first yield.
Sending value to coroutine...
-> Coroutine received: Hello
```

## What is a Coroutine?

📖 **In Simple Terms:** Think of a coroutine as a "function that can take a break." While normal functions run from start to finish without stopping, coroutines can pause (using `yield`), let other code run, and then pick up exactly where they left off when a value is sent back to them.

📖 **Why Use Coroutines?** They are incredibly efficient for handling asynchronous tasks, such as:

- Making API calls
- Reading from files or network sockets
- Waiting for user input

They help you write non-blocking code that can handle many operations concurrently.

## A Classic Coroutine Example

Here is a simple coroutine that yields a value and then waits to receive a value back.

```
def simple_coroutine():
    print("Coroutine started")
    x = yield 42 # Pauses here, returns 42, and waits for a value to be sent
    print(f"Received: {x}")

# 1. Create the coroutine object
co = simple_coroutine()

# 2. Prime the coroutine
# - It runs up to the first yield.
# - It prints "Coroutine started".
# - It yields the value 42.
value_from_yield = next(co)
print(f"Value from first yield: {value_from_yield}")

# 3. Send a value back into the coroutine
# - The coroutine resumes.
# - The value 100 is assigned to 'x'.
# - It prints "Received: 100".
# - The function finishes, raising StopIteration.
try:
    co.send(100)
except StopIteration:
    print("Coroutine finished.")
```

## Key Coroutine Concepts

| Concept                  | Meaning                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------|
| <code>yield</code>       | In a coroutine, it pauses the function, returns a value, and waits for a value to be sent back.                   |
| <code>send(value)</code> | Resumes the coroutine from its last <code>yield</code> point and passes <code>value</code> into it.               |
| <code>next()</code>      | Starts or resumes the coroutine until the next <code>yield</code> . It's equivalent to <code>send(None)</code> .  |
| <code>await</code>       | Used in modern Python (3.5+) with <code>async def</code> functions to pause execution on other awaitable objects. |

1. Can a coroutine accept and return data at the same time? Yes, this is the core feature of a classic generator-based coroutine! However, it's not happening in the exact same instant. It's a two-step sequence that happens at a single point in your code: the yield expression.

**Returning Data:** When a coroutine's execution reaches a `yield` statement, it yields (returns) a value to the caller and pauses its execution at that exact spot. **Accepting Data:** The caller can then use the `.send()` method to resume the coroutine. The value passed to `.send()` becomes the result of the yield expression inside the coroutine, effectively passing data into it. The `simple_coroutine` example from your `python_secrets.md` file is perfect for illustrating this:

```
def simple_coroutine():
    print("-> Coroutine started")
    # This is the key line:
    # 1. It yields the value 42 and pauses.
    # 2. When resumed, the value sent in is assigned to 'x'.
    x = yield 42
    print(f"-> Received: {x}")

# --- Execution Flow ---

# 1. Create the coroutine; no code has run yet.
co = simple_coroutine()

# 2. Prime the coroutine by calling next().
# - It runs until the `yield 42`.
# - It prints "-> Coroutine started".
# - It RETURNS the value 42 and pauses.
value_from_yield = next(co)
print(f"Caller received: {value_from_yield}")

# 3. Send data back into the paused coroutine.
# - The coroutine resumes.
# - The value 100 is ACCEPTED and assigned to 'x'.
# - It prints "-> Received: 100".
# - The function ends, raising StopIteration.
try:
    co.send(100)
except StopIteration:
    print("-> Coroutine finished.")
```

Output:

```
-> Coroutine started
Caller received: 42
-> Received: 100
-> Coroutine finished.
```

So, a single `x = yield 42` line both sends data out (42) and, upon resuming, receives data in (100).

2. Is a thread not better suited than a coroutine for handling user input? For handling a standard, blocking `input()` call, yes, a thread is almost always a better and more straightforward solution than a coroutine.

Here's why:

**The Threading Approach (Simpler and More Direct)** The `input()` function is a blocking operation. It halts the execution of its thread until the user types something and presses Enter.

By placing the `input()` call in a separate thread, you allow your main program to remain responsive and perform other computations while the dedicated input thread is blocked. This is a classic and highly effective use case for threading.

Your own example code in `1_threads.py` demonstrates this perfectly. The `complex_calculation` can run at the same time the program is waiting for user input.

```
# Based on /Users/ravikumarnayak/personal_projects/python/The-Complete-Python-Course/13_async_development/sample_code/1_threads.py
from threading import Thread
import time

def ask_user():
    user_input = input('Enter your name: ')
    print(f'Hello, {user_input}')

def complex_calculation():
    print('Started calculating...')
    [x**2 for x in range(20000000)]
    print('Finished calculating.')

thread1 = Thread(target=complex_calculation)
thread2 = Thread(target=ask_user)

start = time.time()
thread1.start()
thread2.start()

thread1.join()
thread2.join()
print(f'Two thread total time: {time.time() - start:.2f}s')
```

When you run this, the "Started calculating..." message appears immediately, and you can type your name while the calculation happens in the background. The total time will be that of the longest task, not the sum of both.

The Coroutine (asyncio) Approach (More Complex) Modern coroutines with `async/await` run on a single-threaded event loop. If you call a blocking function like `input()` inside an `async` function, it will block the entire event loop. No other coroutines can run, and your application will freeze, defeating the entire purpose of `asyncio`.

The Wrong Way (Don't do this!):

```
import asyncio

async def ask_user_badly():
    # This will freeze the event loop!
    user_input = input('Enter your name: ')
    print(f'Hello, {user_input}')

async def other_task():
    print("Other task starting...")
    await asyncio.sleep(2)
    print("Other task finished.")

# If you run these together, other_task will not start its sleep
# until AFTER the user has provided input.
# await asyncio.gather(ask_user_badly(), other_task())
```

The Correct (but more complex) Way:

To properly handle a blocking call in `asyncio`, you must run it in a separate thread managed by an executor, which prevents it from blocking the main event loop.

```

import asyncio
import time

def blocking_ask_user():
    """A standard function with a blocking call."""
    user_input = input('Enter your name: ')
    print(f'Hello, {user_input}')

async def main():
    loop = asyncio.get_running_loop()
    start = time.time()

    # Schedule the blocking function to run in the default thread pool executor
    input_task = loop.run_in_executor(
        None, blocking_ask_user
    )

    # Create another concurrent task
    calculation_task = asyncio.sleep(3) # Simulates a 3-second async operation

    print("Calculation and user input are running concurrently.")
    await asyncio.gather(input_task, calculation_task)
    print(f"Total time: {time.time() - start:.2f}s")

asyncio.run(main())

```

As you can see, while it's possible with asyncio, it requires the extra step of using `run_in_executor`. For the simple case of handling `input()`, the `threading` module provides a much more direct and readable solution.

#### If I ran a loop for a co routine, would it be able to accept data and return data at the same time? give me an example?

Yes, a coroutine running in a loop can absolutely accept data and return data in a continuous cycle. The key is the `yield` expression, which acts as a two-way communication channel.

When the caller uses `.send(value)`, it sends data into the coroutine. The `yield` expression inside the coroutine receives that value, processes it, and then yields a new value back to the caller. This creates a "ping-pong" effect where the caller's loop and the coroutine's loop are in sync, exchanging data on each iteration.

Example: A Running Average Coroutine Here is a practical example. We'll create a coroutine that runs in an infinite loop. On each iteration, it accepts a number, updates its internal state, and returns the new running average.

```

def running_averager():
    """
    A coroutine that maintains a running average.
    It accepts a number and yields the current average.
    """
    print("-> Coroutine started, ready to receive values.")
    # Initialize internal state
    total = 0.0
    count = 0
    average = None

    while True:
        # The magic happens here:
        # 1. The coroutine yields the `average` and PAUSES.
        # 2. When the caller .send()s a value, it RESUMES.
        # 3. The sent value is assigned to `term`.
        term = yield average

        # Process the received data and update state
        print(f"    -> Coroutine received: {term}")
        total += term
        count += 1
        average = total / count

# --- The Caller Code ---

# 1. Create the coroutine object.
averager = running_averager()

# 2. Prime the coroutine. This is essential!
# We call next() to run the code up to the first `yield`.
# It will yield its initial `average` (which is None) and then pause.
# The documentation in your `python_secrets.md` file explains this perfectly.
next(averager)

# 3. Now, loop and send data to the coroutine.
# The .send() call both sends a value and receives the next yielded value.
for number in [10, 20, 60, 30]:
    print(f"Caller: Sending {number}...")
    # Send the number in and get the calculated average back.
    current_average = averager.send(number)
    print(f"Caller: Current average is {current_average:.2f}\n")

# 4. Close the coroutine to clean up (good practice).
averager.close()
print("-> Coroutine closed.")

```

## Execution Breakdown

Let's trace the execution to see how the data flows:

`averager = running_averager()`: Creates the coroutine object, but no code inside it runs yet. `next(averager)`: Primes the coroutine. `-> Coroutine started...` is printed. The `while True` loop starts. It hits `term = yield average`. It yields the value of `average` (which is `None`) and pauses, waiting for data. `averager.send(10)`: The caller sends 10 into the paused coroutine. 10 is assigned to the `term` variable. `-> Coroutine received: 10` is printed. `total` becomes 10, `count` becomes 1, `average` becomes 10.0. The `while` loop repeats, hitting `yield average` again. It yields 10.0 back to the caller and pauses. The caller receives 10.0, assigns it to `current_average`, and prints it. `averager.send(20)`: The caller sends 20. 20 is assigned to `term`. `-> Coroutine received: 20` is printed. `total` becomes 30, `count` becomes 2, `average` becomes 15.0. The coroutine yields 15.0 back to the caller and pauses. The caller receives 15.0 and prints it. This cycle continues, with the coroutine maintaining its state (`total` and `count`) across multiple send calls, which is something a normal function cannot do.

```

-> Coroutine received: 20 is printed.
total becomes 30, count becomes 2, average becomes 15.0.
The coroutine yields 15.0 back to the caller and pauses.
The caller receives 15.0 and prints it. This cycle continues, with the coroutine maintaining its state (`total` and `count`) across
...

```

A function can be `async` and a generator at the same time

## Asynchronous Generators (`async def` + `yield`)

Since Python 3.6, a function **can** be both `async` and a generator. This powerful feature, called an **asynchronous generator**, allows you to `await` asynchronous operations and then `yield` a result in a sequence.

This is perfect for streaming data that requires an `async` call for each chunk (e.g., fetching pages from a web API).

### How It Works

- It is defined with `async def`.
- It uses `yield` to produce values.
- It can use `await` to pause for other coroutines.
- It is consumed using an `async for` loop.

### Example

Here is an asynchronous generator that counts down, waiting for one second between each number it yields.

```
import asyncio

async def async_countdown(n):
    """
    An asynchronous generator that counts down from n,
    waiting 1 second between each yield.
    """
    print("-> Countdown started!")
    while n > 0:
        await asyncio.sleep(1) # Pauses for an async operation
        yield n                # Yields a value
        n -= 1
    print("-> Countdown finished!")

async def main():
    # You consume an async generator with `async for`
    print("Starting the async for loop...")
    async for number in async_countdown(3):
        print(f"    Received number: {number}")
    print("Async for loop finished.")

# Run the main coroutine
asyncio.run(main())
```

**Output:**

```
Starting the async for loop...
-> Countdown started!
    Received number: 3
    Received number: 2
    Received number: 1
-> Countdown finished!
Async for loop finished.
```

### is a coroutine always defined using `async`?

Great question!

❌ No, a coroutine in Python is not always defined using `async def` — though that is the modern and preferred way.

There are two types of coroutines in Python:

❌

❌ 1. Modern Coroutines — using `async def` (Python 3.5+)

These are what most people mean when they say “coroutine” today.



```

async def say_hi():
    return "Hello"

coro = say_hi()
print(type(coro)) # <class 'coroutine'>

```

You can await these:

```

import asyncio
asyncio.run(say_hi())

```

## 2. Generator-based Coroutines — using @types.coroutine (Legacy Style)

Before `async def`, coroutines were built with `yield` + `@coroutine`.

```

from types import coroutine

@coroutine
def legacy_coro():
    yield
    return 42

c = legacy_coro()
print(type(c)) # <class 'generator'>

```

These behave like coroutines, but are actually generators with a special **`await()`** method under the hood.

They can be awaited too:

```

async def main():
    result = await legacy_coro()
    print(result)

import asyncio
asyncio.run(main())

```

## Summary Table

| Definition Style<br>-----                                          | Awaitable?<br>----- | Common Today?<br>-----      | Underlying Type<br>-----                |
|--------------------------------------------------------------------|---------------------|-----------------------------|-----------------------------------------|
| 1. <code>async def</code>                                          | ✅ Yes               | ✅ Yes                       | coroutine                               |
| 2. <code>def</code> + <code>yield</code> + <code>@coroutine</code> | ✅ Yes               | ⚠️ Rare                     | generator with <code>__await__()</code> |
| 3. <code>def</code> + <code>yield</code> (no decorator)            | ❌ No                | ✅ Yes (but not a coroutine) | generator                               |

## TL;DR

- A coroutine is not always defined with `async def`
- But in modern Python, you should always use `async def` unless you're writing low-level async libraries
- `@coroutine` is still useful for creating awaitable wrappers around generators, but it's mostly legacy

## What Is an Event Loop?

The event loop is a mechanism that waits for tasks (coroutines, I/O events, timers, etc.) to be ready, and then runs them one at a time in a loop — cooperatively, not in parallel.

Think of it like a scheduler that:

- Keeps track of what needs to run
- Runs whatever is ready without blocking
- Suspends tasks that are waiting (e.g., sleeping, I/O)
- Resumes tasks when their data is ready

🔗

## Analogy

Imagine a single-threaded robot that:

- Checks all its tasks in a list
- Runs each task until it hits an "await"
- Puts it aside and goes to the next ready task
- Comes

back later when the paused task can continue

🔗

🔗 Basic Event Loop Flow 1. You define one or more coroutines (async def) 2. You submit them to the event loop 3. The loop starts running and manages when each coroutine is allowed to run next 4. When a coroutine awaits, it's paused 5. The event loop resumes it later when it's ready

🔗

🔗 Example of Event Loop in Action

```
import asyncio

async def say_hello():
    await asyncio.sleep(1)
    print("Hello")

async def say_world():
    await asyncio.sleep(1)
    print("World")

async def main():
    await asyncio.gather(say_hello(), say_world())

asyncio.run(main()) # ← This starts the event loop
```

What Happens: • asyncio.run(main()) → starts the event loop • main() awaits two coroutines concurrently • Event loop sleeps for 1 second, then prints both

🔗

🔗 How to Think About It

| You Call...            | What It Does                                    |
|------------------------|-------------------------------------------------|
| -----                  | -----                                           |
| asyncio.run(...)       | Starts and manages the event loop automatically |
| await coro()           | Pauses until the result is ready                |
| asyncio.gather(...)    | Runs multiple coroutines concurrently           |
| await asyncio.sleep(n) | Suspends for n seconds without blocking         |

🔗 Behind the Scenes

Python uses selectors under the hood (e.g., epoll, kqueue) to: • Monitor file/network/socket events • Schedule future tasks (via call\_later, sleep) • Resume paused coroutines efficiently

The event loop is single-threaded and non-blocking — meaning it can handle thousands of tasks as long as none of them blocks.

🔗

🔗 What Blocks the Event Loop?

Any sync or blocking call — like: • time.sleep() • open().read() (for big files) • Long CPU work

Use: • await asyncio.sleep() • asyncio.to\_thread(...) • Or delegate CPU-heavy work to ProcessPoolExecutor

🔗

🔗 TL;DR — Event Loop Summary

| Concept         | Summary                                                         |
|-----------------|-----------------------------------------------------------------|
| -----           | -----                                                           |
| What it is      | A task scheduler that runs and suspends coroutines              |
| What it runs    | Coroutines, tasks, futures, callbacks                           |
| When it runs    | On asyncio.run(), or when manually started                      |
| How it switches | When a coroutine hits await, the loop picks the next ready task |
| Why it's useful | Efficient concurrency without threads or blocking               |

| Concept                                        | <code>await</code> ? | <code>next()</code> ?        | Notes              |
|------------------------------------------------|----------------------|------------------------------|--------------------|
| 1. <code>def</code> + <code>yield</code>       | ❌                    | ✅                            | Regular generators |
| 2. <code>async def</code> + <code>await</code> | ✅                    | ❌                            | Regular coroutines |
| 3. <code>async def</code> + <code>yield</code> | ❌                    | ✅ via <code>async for</code> | Async generators   |
| 4. <code>__await__()</code> object             | ✅                    | ✅ if it's a generator        | Custom awaitables  |

#### ❶ 1. `def` + `yield`

A regular generator (synchronous). You can `next()` it, but you can't `await` it.

```
def gen():
    yield "hello"
    yield "world"

g = gen()
print(next(g)) # ✅ "hello"
print(next(g)) # ✅ "world"

# await g ❌ TypeError: cannot 'await' a generator object
```

#### ❷ 2. `async def` + `await`

A coroutine function. You must use `await`, but you can't `next()` it.

```
import asyncio

async def say_hello():
    return "Hello Async"

async def main():
    result = await say_hello() # ✅ works
    print(result)

asyncio.run(main())

# say_hello() is a coroutine
# next(say_hello()) ❌ TypeError
```

#### ❸ 3. `async def` + `yield`

This defines an async generator. You can't `await` it, but you can iterate with `async for`.

```
import asyncio

async def async_gen():
    for i in range(3):
        yield i # ✅ allowed in async generators

async def main():
    async for val in async_gen(): # ✅ works
        print(val)

asyncio.run(main())

# await async_gen() ❌ TypeError: can't be awaited
# next(async_gen()) ❌ TypeError
```

#### ❹ 4. Object with `__await__()`

Custom object that is awaitable. This can be `await`-ed and sometimes also `next()`-ed.

```
class CustomAwaitable:
    def __await__(self):
        print("Inside __await__")
        yield # pause here
        return "Done!"

async def main():
    result = await CustomAwaitable() # ✅ Yes, works
    print(result)

asyncio.run(main())

# Technically, you could also do:
g = CustomAwaitable().__await__()
print(next(g)) # ✅ works because __await__ returns a generator
```

A coroutine is a special kind of function in Python that can: • pause its execution at a certain point, • wait for input or other events, • and then resume from where it left off.

They are used to write non-blocking, asynchronous, and cooperative multitasking code in a clean and readable way.

🔗

🔗 Simple Definition:

A coroutine is like a function that can pause, resume, and receive values, making it perfect for concurrent programming without threads.

🔗 Example 1: Basic Generator-as-Coroutine

```
def greeter():
    name = yield "What's your name?"
    yield f"Hello, {name}!"

g = greeter()
print(next(g)) # → "What's your name?"
print(g.send("Alice")) # → "Hello, Alice!"
```

Here: • yield pauses the function and optionally receives data back via .send(...). • This is a “generator-based coroutine”.

⚙️ Coroutine vs Generator

| Feature        | Generator (def + yield)        | Coroutine (async def)  |
|----------------|--------------------------------|------------------------|
| 1. Keyword     | yield                          | await, async def       |
| 2. Resume with | next(), .send()                | await, event loop      |
| 3. Use case    | Data pipelines, lazy iteration | Async I/O, concurrency |
| 4. Syntax      | Synchronous                    | Asynchronous           |

🔗 Example 2: Async Coroutine (Modern Python)

```
import asyncio

async def download():
    await asyncio.sleep(1)
    return "Download complete"

async def main():
    result = await download()
    print(result)

asyncio.run(main())
```

Here: • async def defines a coroutine function. • await pauses until the awaited task completes (e.g., network delay, file read).

🔗

🔗 Use Cases • Network I/O: HTTP requests, WebSocket handling • File I/O: reading large files asynchronously • Cooperative multitasking: doing many things without threads • Pipelines: coroutines that push/pull data

```
class CustomAwaitable:
    def __await__(self):
        print("Inside __await__")
        yield # pause here
        return "Done!"

async def main():
    result = await CustomAwaitable()
    print(result)

asyncio.run(main())
```

#### 🔗 Output

```
Inside __await__
Done!
```

#### 🔗 Why Does This Work?

\* Python allows any object with a **await()** method to be await-ed.

That's not an exception — it's part of the official awaitable protocol.

According to PEP 492 (async/await), an object is awaitable if: • It is a coroutine object, OR • It has a **await()** method that returns an iterator

🔗

#### 🔗 Let's Look at This Line:

```
await CustomAwaitable()
```

Here's what Python internally does: 1. Calls CustomAwaitable().**await()** → this returns a generator. 2. That generator is driven by the event loop (asyncio.run()), as if by repeated next() calls. 3. The yield inside the generator causes it to pause. 4. When the generator is complete, the return value ("Done!") is returned from await.

🔗

#### 🔗 What Makes This Legitimate?

Because the **await()** method returns a generator, and generators can be used in an async context if they're returned by **await**, it is completely legal to use this as a custom awaitable.

This allows developers to define their own awaitable behaviors — useful in async frameworks, mocking, or custom scheduling.

🔗

#### 🔗 Confirming the Type

```
obj = CustomAwaitable()
print(hasattr(obj, '__await__')) # True
print(type(obj.__await__()))     # <class 'generator'>
```

#### 🔗 Using It Manually

You can drive it manually too:

```
g = CustomAwaitable().__await__()
print(next(g)) # None (yielded)
# print(next(g)) # StopIteration: Done!
```

🔗 So Is This an Exception? • Yes, it's unusual: Most things you await are coroutine functions. • No, it's not a hack or unintended: Python intentionally supports this via the **await()** protocol.

🔗 TL;DR

| Question                                                           | Answer                                                                       |
|--------------------------------------------------------------------|------------------------------------------------------------------------------|
| -----                                                              | -----                                                                        |
| 1. Can we await this?                                              | ☑ Yes – because it defines <code>__await__()</code> that returns a generator |
| 2. Is this common?                                                 | ☑ Rare in real-world apps – mostly in advanced frameworks                    |
| 3. Is it an exception?                                             | ☑ No – it follows Python’s async protocol ( <code>__await__</code> )         |
| 4. What’s the output?                                              | Inside <code>__await__</code> , then Done!                                   |
| 5. Is the generator in <code>__await__()</code> automatically run? | ☑ Yes – by the event loop                                                    |

## These concepts – generator, iterator, and iterable – are closely related but not the same

### ☒ Short Summary

| Term         | Is it Iterable? | Is it Iterator?   | Can use for loop? | Can use next()?                     |
|--------------|-----------------|-------------------|-------------------|-------------------------------------|
| 1. Iterable  | ☑ Yes           | ☑ Not necessarily | ☑ Yes             | ☑ No (unless it’s also an iterator) |
| 2. Iterator  | ☑ Yes           | ☑ Yes             | ☑ Yes             | ☑ Yes                               |
| 3. Generator | ☑ Yes           | ☑ Yes             | ☑ Yes             | ☑ Yes                               |

### ☒ Definitions

#### 1. Iterable

An object that can be looped over (e.g., for x in obj). ☒ Must implement `iter()`, which returns an iterator.

☒ Examples: list, tuple, dict, str, generator, custom classes with `iter`.

```
lst = [1, 2, 3]
for i in lst:
    print(i)
```

You can get an iterator from it:

```
it = iter(lst) # calls lst.__iter__()
```

#### 2. Iterator

An object that produces values one at a time using `next()`.

☒ Must implement both: • `iter()` → returns self • `next()` → returns the next item (raises `StopIteration` at the end)

```
it = iter([1, 2, 3]) # this is an iterator
print(next(it)) # 1
print(next(it)) # 2
```

#### 3. Generator

A special kind of iterator created using a function with `yield`.

☒ Automatically: • Implements `iter()` and `next()` • Maintains internal state between calls

```
def my_gen():
    yield 1
    yield 2
    yield 3

g = my_gen() # g is a generator (and also an iterator)
print(next(g)) # 1
print(next(g)) # 2
```

### ☒ Key Differences

| Feature                        | Iterable                                                | Iterator                                          |
|--------------------------------|---------------------------------------------------------|---------------------------------------------------|
| 1. Used in for                 | <input checked="" type="checkbox"/> Yes                 | <input checked="" type="checkbox"/> Yes           |
| 2. Has <code>__iter__()</code> | <input checked="" type="checkbox"/> Yes                 | <input checked="" type="checkbox"/> Yes           |
| 3. Has <code>__next__()</code> | <input type="checkbox"/> Not required                   | <input checked="" type="checkbox"/> Yes           |
| 4. Can be reused               | <input checked="" type="checkbox"/> Usually (e.g. list) | <input type="checkbox"/> No – exhausted after use |
| 5. Needs <code>iter()</code>   | <input checked="" type="checkbox"/> Yes                 | <input checked="" type="checkbox"/> Already ready |

## 🔗 Examples to Compare

### A. Iterable but Not Iterator

```
lst = [1, 2, 3]          # list is iterable
it = iter(lst)           # this is now an iterator

print(hasattr(lst, '__next__')) # False
print(hasattr(it, '__next__'))  # True
```

### B. Generator is Iterator & Iterable

```
def gen():
    yield 1

g = gen()

print(hasattr(g, '__iter__')) # True
print(hasattr(g, '__next__')) # True
```

## 🔗 Summary

| Type           | Reusable?                               | Notes                     |
|----------------|-----------------------------------------|---------------------------|
| 1. List, Tuple | <input checked="" type="checkbox"/> Yes | Can re-iterate many times |
| 2. Generator   | <input type="checkbox"/> No             | One-shot, must recreate   |
| 3. Iterator    | <input type="checkbox"/> No             | Usually one-shot          |

## Explanation of the following Code which uses `await` with a generator object

```

from collections import deque
from types import coroutine

friends = deque(['Ram', 'Sita', 'Laxman', 'Shatrughan', 'Bharat', 'Hanuman'])

@coroutine
def friend_upper():
    while friends:
        friend = friends.popleft().upper()
        greeting = yield
        print(f'{greeting} {friend}')

async def greet(g):
    await g

greeter = greet(friend_upper())
greeter.send(None)
greeter.send('Hello')
greeter.send('Hi')
greeter.send('Hey')
greeter.send('What')
greeter.send('Why')

```

How is a generator (via `@coroutine`) being awaited in `await g`?

The short answer is:

Because `@coroutine` turns a generator into an awaitable coroutine — by giving it a **`await()`** method under the hood.

❏

❏ Let's unpack this step by step

❏ Code Recap:

```

from collections import deque
from types import coroutine

friends = deque(['Ram', 'Sita', 'Laxman', 'Shatrughan', 'Bharat', 'Hanuman'])

@coroutine
def friend_upper():
    while friends:
        friend = friends.popleft().upper()
        greeting = yield
        print(f'{greeting} {friend}')

```

You're using:

```
@coroutine
```

from:

```
from types import coroutine
```

from `types import coroutine`

```
This decorator transforms a generator-based coroutine into something that can be used with await.
```

❏

❏ What does `@coroutine` do?

It marks the generator function so that it behaves like an awaitable object — that is:

- It adds a **`await()`** method to the generator object.
- This makes it legal to use with `await`.

So this line:

```
await g
```



works, because:

- `g` is the generator returned by `friend_upper()`
- `@coroutine` makes `g.await()` available
- Python's event loop knows how to drive **`await()`** step-by-step

This is how `asyncio` used to work before `async def/await` syntax was introduced (i.e., Python 3.4 and earlier Python 3.5 styles).

❏

❏ Under the Hood: What's Happening

```
@coroutine
def friend_upper():
    ...
```

Becomes:

```
def friend_upper():
    ...
friend_upper = types.coroutine(friend_upper)
```

Internally, this creates a generator object with a `.await()` method that delegates to the generator itself using `yield from`.

❏

❏ What Happens During Execution?

```
greeter = greet(friend_upper())
```

- `friend_upper()` returns a generator (but marked as awaitable)
- `greet()` is a coroutine that awaits this generator

```
greeter.send('Hello') # greeting = 'Hello'
```

Causes:

```
print(f'{greeting} {friend}')
```

❏ No, you cannot use `await` in a function that is not declared with `async def`.

Trying to use `await` in a regular `def` function will result in a `SyntaxError`.

❏

```
def regular_function():
    await some_coroutine() # ❏ Invalid

# SyntaxError: 'await' outside async function
```

Python requires that any use of `await` must be inside an `async def` function — this is enforced at the syntax level by the parser.

❏

❏ Correct Usage

```
async def my_async_function():
    await some_coroutine()
```

And then you run it via:

```
import asyncio
asyncio.run(my_async_function())
```

❏ Why This Restriction Exists

- `await` only makes sense in the context of a coroutine.
- The event loop must manage the paused/resumed state of the function, which requires it to be `async def`.
- Regular `def` functions return values immediately and can't suspend execution.

❏

❏ TL;DR

| Question                                            | Answer                                                                                                |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| -----                                               | -----                                                                                                 |
| 1. Can you use await inside a regular def function? | ❌ No – it's a syntax error                                                                            |
| 2. What kind of function can use await?             | ❌ Only async def functions                                                                            |
| 3. Why?                                             | Because only async def functions are coroutines that can pause/resume under control of the event loop |

**without create\_task, can we run multiple coroutines at the same time, meaning if we simply await 2 co routines without creating tasks for them, will they run concurrently?**

Great question – you're digging into a key concept in Python's asyncio: what makes coroutines run concurrently?

❌

❌ Short Answer

❌ No, if you await two coroutines sequentially without using create\_task() or gather(), they will not run concurrently.

They will run one after the other, just like synchronous code – because await waits for the first to finish before moving to the next.

```
import asyncio

async def task1():
    print("Start task1")
    await asyncio.sleep(1)
    print("End task1")

async def task2():
    print("Start task2")
    await asyncio.sleep(1)
    print("End task2")

async def main():
    await task1() # ❌ waits until task1 is fully done
    await task2() # ❌ starts only after task1 is done

asyncio.run(main())
```

Output:

```
Start task1
End task1
Start task2
End task2
```

❌ Total time: ~2 seconds → Sequential execution

Concurrent Execution Without create\_task: Use asyncio.gather

```
async def main():
    await asyncio.gather(task1(), task2()) # ❌ runs concurrently

# OR, more explicitly:
# t1 = task1()
# t2 = task2()
# await asyncio.gather(t1, t2)
```

Output:

```
Start task1
Start task2
End task1
End task2
```

❌ Total time: ~1 second → Concurrent execution

❌ Or Use asyncio.create\_task (Explicit task scheduling)

```

async def main():
    t1 = asyncio.create_task(task1())
    t2 = asyncio.create_task(task2())
    await t1
    await t2

```

## TL;DR

| Pattern                                                | Concurrent?                             | Notes                                  |
|--------------------------------------------------------|-----------------------------------------|----------------------------------------|
| 1. <code>await task1(); await task2()</code>           | <input type="checkbox"/> No             | Runs one after the other               |
| 2. <code>await asyncio.gather(task1(), task2())</code> | <input checked="" type="checkbox"/> Yes | Best for launching coroutines together |
| 3. <code>create_task + await</code>                    | <input checked="" type="checkbox"/> Yes | Lower-level, used for long-lived tasks |

## Final Note:

`await` = wait for one thing

`asyncio.gather / create_task` = start multiple things, then await them together

## Let's walk through a complete, detailed example of using the `unsync` library to run:

- Synchronous functions
- Asynchronous coroutines
- CPU-bound functions (processes)
- All in parallel

We'll show: • How to declare each type • What each returns (`UnsyncFuture`) • How to access the results • What's happening under the hood

## Overview

| Type of Task              | Decorator Syntax                               | Backed by                        | Returns                   |
|---------------------------|------------------------------------------------|----------------------------------|---------------------------|
| Sync I/O-bound (default)  | <code>@unsync</code>                           | <code>ThreadPoolExecutor</code>  | <code>UnsyncFuture</code> |
| CPU-bound (heavy compute) | <code>@unsync(process=True)</code>             | <code>ProcessPoolExecutor</code> | <code>UnsyncFuture</code> |
| Async coroutine           | <code>@unsync</code> on <code>async def</code> | <code>asyncio</code> event loop  | <code>UnsyncFuture</code> |

## Step 2: Full Example

```

from unsync import unsync
import time
import asyncio
import math

# --- Threaded: I/O-style sleep ---
@unsync
def sleep_task(name):
    time.sleep(1)
    return f"Done sleeping: {name}"

# --- Async: asyncio-style task ---
@unsync
async def async_task(name):
    await asyncio.sleep(1)
    return f"Done async: {name}"

# --- Process: CPU-bound task ---
@unsync(process=True)
def cpu_task(x):
    # Simulate CPU-intensive operation
    return f"CPU result: sqrt({x}) = {math.sqrt(x)}"

# --- Run all tasks together ---
def main():
    futures = [
        sleep_task("Threaded"),      # Threaded function
        async_task("Async"),         # Async coroutine
        cpu_task(1000000),           # CPU-bound process
    ]

    # These are all UnsyncFuture objects
    for f in futures:
        print(f"Type: {type(f)}")    # Shows <class 'unsync.future.UnsyncFuture'>

    # Wait for all to complete and collect results
    results = [f.result() for f in futures]
    print("\nResults:")
    for r in results:
        print(r)

if __name__ == '__main__':
    main()

```

## Output

```

Type: <class 'unsync.future.UnsyncFuture'>
Type: <class 'unsync.future.UnsyncFuture'>
Type: <class 'unsync.future.UnsyncFuture'>

Results:
Done sleeping: Threaded
Done async: Async
CPU result: sqrt(1000000) = 1000.0

```

✓ Each task runs concurrently: • The `sleep_task` runs in a thread. • The `async_task` runs on the async event loop. • The `cpu_task` runs in a separate process.

They all return an `UnsyncFuture`, which supports:

| Method / Property                      | Meaning                               |
|----------------------------------------|---------------------------------------|
| 1. <code>.result()</code>              | Wait and return the result (blocking) |
| 2. <code>.done()</code>                | True if completed                     |
| 3. <code>.exception()</code>           | Returns exception if raised           |
| 4. <code>.add_done_callback(fn)</code> | Call when future completes            |

#### 🔍 Under the Hood

`@unsync` • On `def`: runs in `ThreadPoolExecutor` • On `async def`: runs on `asyncio` event loop • On `def` with `process=True`: runs in `ProcessPoolExecutor`

🔍 Bonus: Non-blocking Access with `.add_done_callback`

```
f = sleep_task("Ram")
f.add_done_callback(lambda fut: print("Callback:", fut.result()))
```

You can even use `fut.result(timeout=...)` to control blocking behavior.

#### 🔍 Summary Table of Unsync Usage

| What You Want                                          | Decorator                                      | Returns                   | Runs In                          |
|--------------------------------------------------------|------------------------------------------------|---------------------------|----------------------------------|
| 1. Async coroutine                                     | <code>@unsync</code> on <code>async def</code> | <code>UnsyncFuture</code> | <code>asyncio</code> event loop  |
| 2. I/O-style blocking (e.g., <code>time.sleep</code> ) | <code>@unsync</code> on <code>def</code>       | <code>UnsyncFuture</code> | <code>ThreadPoolExecutor</code>  |
| 3. Heavy computation                                   | <code>@unsync(process=True)</code>             | <code>UnsyncFuture</code> | <code>ProcessPoolExecutor</code> |

#### 🔍 TL;DR

• `unsync` simplifies concurrency without managing threads, event loops, or futures manually. • All functions return `UnsyncFuture` regardless of backend. • `.result()` blocks until completion and returns the result. • All tasks run concurrently, giving performance and simplicity.

## Can we prime a coroutine by using `next()`?

🔍 Yes — but only for regular generator-based coroutines, not `async def` coroutines.

Let's break it down very clearly, because it depends entirely on the kind of coroutine you're talking about:

#### 🔍 1. Generator-based coroutine (`@coroutine + yield`)

Yes, you can prime it using `next()` — because it's still a generator under the hood.

```
from types import coroutine

@coroutine
def gen_coro():
    print("Primed")
    yield "Paused here"

g = gen_coro()

print(next(g)) # 🔍 works: "Primed" then yields "Paused here"
```

🔍 Why this works: • `@coroutine` transforms a generator into an awaitable coroutine, but it's still a generator object. • So `next(g)` and `g.send(...)` still work. • `await g` also works.

#### 🔍 2. Native coroutine (`async def`)

🔍 No, you cannot use `next()` on a coroutine defined with `async def`.

```

async def native_coro():
    print("Inside")
    return 42

c = native_coro()

next(c) # ❌ TypeError: 'coroutine' object is not an iterator

```

❓ Why this fails: • Native coroutines (created with `async def`) are not iterators. • They must be awaited (`await c`) or wrapped in an `asyncio` task.

#### ❓ Summary Table

| Type of Function<br>-----                       | Can you <code>next()</code> it?<br>----- | Can you <code>await</code> it?<br>----- |
|-------------------------------------------------|------------------------------------------|-----------------------------------------|
| 1. <code>def</code> + <code>yield</code>        | ✅ Yes                                    | ❌ No                                    |
| 2. <code>@coroutine</code> + <code>yield</code> | ✅ Yes                                    | ✅ Yes                                   |
| 3. <code>async def</code>                       | ❌ No                                     | ✅ Yes                                   |
| 4. <code>async def</code> + <code>yield</code>  | ❌ No (not iterable)                      | ❌ No ( <code>async for</code> ) only    |

#### ❓ Final Verdict

You can prime a coroutine with `next()` only if it's a generator-based coroutine, such as one decorated with `@coroutine`. You cannot use `next()` on a coroutine created via `async def`.

### so for most generators, we can use next/send interchangeably ?

Excellent question — and the short answer is:

❓ Yes, for most generators, you can use `.next()` and `.send(None)` interchangeably — but there are important nuances you should know.

Let's break it down clearly and precisely:

❓

#### ❓ When `next()` and `send(None)` Are Equivalent

❓ Basic generator:

```

def my_gen():
    yield "step 1"
    yield "step 2"

g = my_gen()

print(next(g))      # ✅ "step 1"
print(g.send(None)) # ✅ "step 2" — works like next()

```

❓ `send(None)` is exactly the same as `next()` when: • The generator is waiting at a bare `yield` • You don't want to inject any actual data

❓

#### ❓ When `next()` and `send(None)` Are Not Interchangeable

❓ Case 1: First call to a generator with `yield = (expression)`

```

def my_gen():
    name = yield "What's your name?"
    yield f"Hello, {name}"

g = my_gen()

print(next(g))      # ✅ primes the generator, yields "What's your name?"
print(g.send("Alice")) # ✅ sends "Alice" into the generator

```

❓ But this will fail:

```
g = my_gen()
g.send("Alice") # ⚠ TypeError: can't send non-None value to a just-started generator
```

You must prime the generator first using next() or send(None).

⚠

⚠ Case 2: When you want to inject a value into the generator

Then send(...) is the only option:

```
def echo():
    while True:
        val = yield
        print(f"Received: {val}")

g = echo()
next(g) # ⚠ primes to first `yield`
g.send("Hello") # ⚠ sends "Hello" into the generator
```

Calling next(g) here again would just send None, which isn't useful if you're expecting real data.

⚠

⚠ Summary Table

| Use Case                          | Use next() | Use send(None) | Use send(value)         |
|-----------------------------------|------------|----------------|-------------------------|
| 1. Prime a new generator          | ⚠ Yes      | ⚠ Yes          | ⚠ No                    |
| 2. Resume at a bare yield         | ⚠ Yes      | ⚠ Yes          | ⚠ Only if value is None |
| 3. Pass value to yield expression | ⚠ No       | ⚠ No           | ⚠ Yes                   |

⚠ TL;DR • next() is shorthand for send(None) • You must use next() or send(None) to prime a generator (first step) • Use send(value) only after priming, when the generator is paused at name = yield • ⚠ Never use send(value) on a just-started generator – you'll get a TypeError

⚠ Summary Chart

| Task Type                   | Use asyncio ? | Use Threads?                                 | Notes                                           |
|-----------------------------|---------------|----------------------------------------------|-------------------------------------------------|
| Network requests            | ⚠ Yes         | ⚠ Not needed unless using blocking libraries |                                                 |
| File I/O                    | ⚠ No          | ⚠ Yes                                        | Use asyncio.to_thread() or ThreadPoolExecutor   |
| CPU-bound tasks             | ⚠ No          | ⚠ Use Process Pool                           | Use multiprocessing Or ProcessPoolExecutor      |
| Mixed I/O (files + network) | ⚠ with care   | ⚠ use threads for files                      | Use async for network, threads for blocking ops |

⚠ Final Recommendations

| Scenario                          | Tool                                      |
|-----------------------------------|-------------------------------------------|
| Web scraping, API calls           | asyncio + aiohttp                         |
| Read/write CSV, JSON, logs        | asyncio.to_thread() Or ThreadPoolExecutor |
| Heavy file parsing or computation | ProcessPoolExecutor (CPU-bound)           |
| Want simplicity and flexibility   | Use unsync to combine all styles          |